

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: CORELITE

Report Number: P995538

Luminaire Tested: 22D3X-LP-WD-50-L930.ies

Issue Date: 12/20/2023

Test Information

Test Method: LM-79-2019
Report Number: P995538
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2307-104-1)
Test Lab: INNOVATION CENTER
Issue Date: 12/20/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: 22D3X-LP-WD-50-L930.ies
Description: 2x2 D3X-LP AT 5000LM 3000K 90CRI
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3710.7 lumens
Efficiency: N/A
Efficacy: 88.6 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.18 / 1.29
Luminous Opening: Rectangular (W 2' x L: 2' x H: 0')
CIE Type: Direct

Input Watts (W): 41.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P995538

CATALOG NUMBER: 22D3X-LP-WD-50-L930.ies

Luminous Intensity Polar Plot



TEST NUMBER: P995538

CATALOG NUMBER: 22D3X-LP-WD-50-L930.ies

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		100
1	109	105	101	97	107	102	99	95	98	95	92	94	92	89	91	89	87	85		85
2	100	92	85	80	97	90	84	79	86	81	77	83	79	75	80	77	73	71		71
3	91	81	73	67	89	79	72	66	76	70	65	74	68	64	71	67	63	61		61
4	84	72	64	57	81	71	63	57	68	61	56	66	60	55	64	59	54	52		52
5	77	65	56	49	75	64	55	49	61	54	49	59	53	48	58	52	48	45		45
6	71	58	50	43	69	57	49	43	56	48	43	54	47	42	52	47	42	40		40
7	66	53	44	38	65	52	44	38	51	43	38	49	43	38	48	42	37	36		36
8	62	49	40	34	60	48	40	34	47	39	34	45	39	34	44	38	34	32		32
9	58	45	37	31	56	44	36	31	43	36	31	42	35	31	41	35	31	29		29
10	54	41	33	28	53	41	33	28	40	33	28	39	32	28	38	32	28	26		26

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	3996	3996	3996
5°	3999	3991	3999
10°	3977	3965	3973
15°	3939	3918	3918
20°	3871	3850	3842
25°	3798	3763	3750
30°	3709	3663	3640
35°	3610	3542	3518
40°	3476	3408	3382
45°	3343	3264	3236
50°	3213	3108	3083
55°	3067	2956	2914
60°	2913	2786	2746
65°	2713	2580	2552
70°	2478	2386	2327
75°	2260	2122	2138
80°	1948	1833	1857
85°	1507	1460	1371

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3343 cd/sqm

TEST NUMBER: P995538

CATALOG NUMBER: 22D3X-LP-WD-50-L930.ies

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	140.3	3.8
10°-20°	396.6	10.7
20°-30°	584.1	15.7
30°-40°	675.7	18.2
40°-50°	664.3	17.9
50°-60°	566.2	15.3
60°-70°	405.7	10.9
70°-80°	220.3	5.9
80°-90°	57.5	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1121.0	30.2
0°-40°	1796.8	48.4
0°-60°	3027.2	81.6
0°-90°	3710.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3710.7	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1485	1485	1485	1485	1485	
5°	1480	1478	1478	1478	1480	140
15°	1414	1408	1406	1405	1406	398
25°	1279	1273	1268	1265	1263	589
35°	1099	1090	1078	1072	1071	685
45°	878	873	858	850	850	679
55°	654	642	630	623	621	584
65°	426	417	405	401	401	422
75°	217	210	204	201	206	230
85°	49	49	47	46	44	59
90°	0	0	0	0	0	

TEST NUMBER: P995538

CATALOG NUMBER: 22D3X-LP-WD-50-L930.ies

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1484.9	1484.9	1484.9	1484.9	1484.9
2.5°	1484.9	1483.5	1482.0	1483.5	1486.4
5°	1480.5	1477.5	1477.5	1477.5	1480.5
7.5°	1470.1	1467.2	1465.7	1467.2	1468.7
10°	1455.3	1452.4	1450.9	1452.4	1453.9
12.5°	1434.6	1433.2	1431.7	1431.7	1433.2
15°	1413.9	1408.0	1406.5	1405.1	1406.5
17.5°	1384.4	1382.9	1377.0	1377.0	1377.0
20°	1351.8	1348.9	1344.4	1341.5	1341.5
22.5°	1317.8	1314.8	1307.4	1304.5	1306.0
25°	1279.3	1273.4	1267.5	1264.6	1263.1
27.5°	1237.9	1232.0	1223.1	1218.7	1218.7
30°	1193.6	1189.1	1178.8	1172.9	1171.4
32.5°	1144.8	1141.8	1127.0	1124.1	1124.1
35°	1098.9	1090.0	1078.2	1072.3	1070.8
37.5°	1044.2	1038.3	1026.4	1019.0	1017.6
40°	989.5	982.1	970.2	964.3	962.8
42.5°	934.7	927.3	915.5	908.1	906.6
45°	878.5	872.6	857.8	850.4	850.4
47.5°	825.3	813.5	800.1	794.2	792.8
50°	767.6	757.3	742.5	736.5	736.5
52.5°	709.9	702.5	686.3	683.3	680.3
55°	653.7	641.9	630.1	622.7	621.2
57.5°	593.1	582.7	570.9	565.0	565.0
60°	541.3	528.0	517.7	510.3	510.3
62.5°	482.2	470.3	460.0	455.5	454.1
65°	426.0	417.1	405.2	400.8	400.8
67.5°	369.8	362.4	352.0	347.6	349.0
70°	315.0	310.6	303.2	297.3	295.8
72.5°	264.7	258.8	251.4	250.0	250.0
75°	217.4	210.0	204.1	201.1	205.6
77.5°	168.6	164.2	161.2	159.7	161.2
80°	125.7	119.8	118.3	119.8	119.8
82.5°	87.3	84.3	82.8	82.8	82.8
85°	48.8	48.8	47.3	45.8	44.4
87.5°	19.2	19.2	20.7	20.7	22.2
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)