

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P1217176

Luminaire Tested: 14-ID2-20-CNV-L950-U

Issue Date: 12/5/2025

Test Information

Test Method: LM-79-2019
Report Number: P1217176
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2508-507-11)
Test Lab: INNOVATION CENTER
Issue Date: 12/5/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: 14-ID2-20-CNV-L950-U
Description: 1X4 IN DEPTH TROFFER WITH 2INCH CURVE DROP LENS
Light Source: 5000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1869.8 lumens
Efficiency: N/A
Efficacy: 106.2 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.33
Luminous Opening: Rectangular w/ Sides (W: 1' x L: 4' x H: 0.16')
CIE Type: Direct

Input Watts (W): 17.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P1217176
CATALOG NUMBER: 14-ID2-20-CNV-L950-U

Luminous Intensity Polar Plot



TEST NUMBER: P1217176

CATALOG NUMBER: 14-ID2-20-CNV-L950-U

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	0
RCR																				
0	118	118	118	118	115	115	115	115	110	110	110	105	105	105	100	100	100	100	100	98
1	107	102	98	94	104	100	96	92	95	92	88	91	88	85	87	84	82	80	80	80
2	98	89	82	76	95	87	80	75	83	77	73	79	75	71	76	72	69	66	66	66
3	89	78	70	63	86	76	69	62	73	66	61	70	64	60	67	62	58	56	56	56
4	81	69	60	54	79	68	59	53	65	58	52	62	56	51	60	54	50	48	48	48
5	75	62	53	46	73	61	52	46	58	51	45	56	49	44	54	48	44	41	41	41
6	69	56	47	40	67	55	46	40	53	45	39	51	44	39	49	43	38	36	36	36
7	64	51	42	36	62	50	41	35	48	40	35	46	40	35	45	39	34	32	32	32
8	60	46	38	32	58	45	37	32	44	37	31	42	36	31	41	35	31	29	29	29
9	56	42	34	29	54	42	34	29	40	33	28	39	33	28	38	32	28	26	26	26
10	52	39	31	26	51	39	31	26	37	30	26	36	30	25	35	29	25	23	23	23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1768	1768	1768
5°	1764	1742	1745
10°	1748	1714	1718
15°	1726	1679	1685
20°	1696	1639	1642
25°	1663	1591	1592
30°	1618	1539	1538
35°	1571	1481	1480
40°	1518	1418	1417
45°	1467	1352	1348
50°	1407	1279	1276
55°	1343	1200	1203
60°	1270	1121	1129
65°	1193	1038	1061
70°	1103	960	1005
75°	998	900	962
80°	861	857	942
85°	752	843	964

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1467 cd/sqm

TEST NUMBER: P1217176
 CATALOG NUMBER: 14-ID2-20-CNV-L950-U

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.1	3.3
10°-20°	176.8	9.5
20°-30°	263.4	14.1
30°-40°	310.0	16.6
40°-50°	312.7	16.7
50°-60°	275.7	14.7
60°-70°	211.2	11.3
70°-80°	138.3	7.4
80°-90°	74.0	4.0
90°-100°	31.4	1.7
100°-110°	10.0	0.5
110°-120°	2.4	0.1
120°-130°	1.1	0.1
130°-140°	0.5	0.0
140°-150°	0.2	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	502.3	26.9
0°-40°	812.2	43.4
0°-60°	1400.7	74.9
0°-90°	1824.2	97.6
90°-120°	43.8	2.3
90°-150°	45.6	2.4
90°-180°	46.0	2.5
0°-180°	1869.8	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	657	657	657	657	657	
5°	655	654	653	653	655	62
15°	626	626	626	628	631	177
25°	570	570	571	574	576	263
35°	492	492	495	500	501	307
45°	401	401	406	410	411	309
55°	303	303	307	314	315	271
65°	203	204	212	220	224	202
75°	110	115	132	144	148	117
85°	36	49	71	85	88	36
90°	13	28	48	61	64	8
95°	10	14	30	41	45	8
105°	7	6	6	13	15	8
115°	5	4	2	0	0	5
125°	3	2	1	0	0	3
135°	2	1	1	0	0	1
145°	1	1	0	0	0	1
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P1217176

CATALOG NUMBER: 14-ID2-20-CNV-L950-U

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	657.0	657.0	657.0	657.0	657.0
2.5°	658.2	657.3	655.1	655.7	656.7
5°	655.4	654.5	652.9	653.2	655.1
7.5°	651.3	650.1	648.8	649.7	651.9
10°	644.4	643.8	642.8	644.1	646.3
12.5°	636.2	635.6	635.3	636.9	639.4
15°	626.2	625.5	625.5	628.1	630.6
17.5°	614.5	614.2	614.9	617.7	619.6
20°	601.0	600.7	601.7	604.5	606.7
22.5°	586.9	586.3	587.2	589.7	591.9
25°	570.5	569.6	571.2	574.0	576.2
27.5°	552.9	551.4	553.9	557.0	558.9
30°	532.8	533.1	535.6	538.8	540.7
32.5°	513.0	512.7	515.8	519.6	521.5
35°	491.6	491.6	495.4	499.5	501.1
37.5°	469.3	470.3	474.0	477.8	479.7
40°	446.7	447.9	451.7	455.8	457.4
42.5°	423.4	424.7	428.8	433.2	434.4
45°	400.8	401.1	405.5	410.2	410.8
47.5°	376.3	376.6	381.3	386.0	387.0
50°	352.1	352.4	357.1	362.1	362.8
52.5°	327.5	327.9	331.9	337.9	339.2
55°	302.7	302.7	307.4	313.7	315.0
57.5°	277.9	277.9	282.9	289.5	291.1
60°	252.4	253.0	259.3	265.6	267.8
62.5°	227.9	228.5	235.4	242.0	244.9
65°	203.4	204.3	212.5	220.4	223.8
67.5°	179.5	180.7	190.2	200.2	203.4
70°	155.6	158.1	169.4	180.4	183.9
72.5°	132.7	135.5	150.6	162.2	165.3
75°	110.3	114.7	132.3	144.3	147.7
77.5°	88.6	95.2	115.4	128.3	131.4
80°	68.2	78.0	99.6	112.5	116.0
82.5°	50.9	61.9	85.2	98.4	101.5
85°	35.5	48.7	71.4	84.9	88.3
87.5°	22.9	37.4	59.1	72.3	76.1
90°	12.6	27.7	48.1	60.7	64.4
92.5°	11.3	20.1	38.3	50.3	54.1
95°	10.4	14.1	29.5	40.9	44.6
97.5°	9.4	9.4	22.0	32.4	35.8
100°	8.8	6.9	15.7	24.8	28.3
102.5°	7.9	6.3	10.4	18.2	21.4
105°	7.2	5.7	6.3	12.6	15.1
107.5°	6.6	5.0	3.1	7.9	10.1
110°	6.0	4.7	2.5	3.8	6.0

TEST NUMBER: P1217176

CATALOG NUMBER: 14-ID2-20-CNV-L950-U

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	5.3	4.1	2.2	0.9	2.2
115°	4.7	3.8	1.9	0.0	0.0
117.5°	4.1	3.5	1.6	0.0	0.0
120°	3.8	2.8	1.6	0.0	0.0
122.5°	3.5	2.5	1.3	0.0	0.0
125°	2.8	2.2	0.9	0.0	0.0
127.5°	2.5	1.9	0.9	0.0	0.0
130°	2.2	1.9	0.6	0.0	0.0
132.5°	1.9	1.6	0.6	0.0	0.0
135°	1.6	1.3	0.6	0.0	0.0
137.5°	1.6	1.3	0.3	0.0	0.0
140°	1.3	0.9	0.3	0.0	0.0
142.5°	0.9	0.6	0.3	0.0	0.0
145°	0.9	0.6	0.0	0.0	0.0
147.5°	0.6	0.6	0.0	0.0	0.0
150°	0.6	0.3	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P1217176

CATALOG NUMBER: 14-ID2-20-CNV-L950-U

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.04	13.64	12.45	14.00	14.38	12.69	14.28	13.09	14.65	15.02
	3H	13.64	15.09	14.06	15.47	15.89	14.66	16.11	15.08	16.49	16.91
	4H	14.21	15.58	14.65	15.97	16.41	15.56	16.92	15.99	17.32	17.75
	6H	14.61	15.88	15.06	16.29	16.74	16.43	17.70	16.88	18.11	18.56
	8H	14.73	15.94	15.19	16.38	16.84	16.85	18.07	17.32	18.50	18.96
	12H	14.81	15.97	15.28	16.40	16.89	17.29	18.46	17.76	18.89	19.38
4H	2H	12.69	14.05	13.12	14.45	14.88	13.20	14.56	13.64	14.96	15.40
	3H	14.51	15.66	14.96	16.11	16.56	15.41	16.56	15.86	17.01	17.46
	4H	15.20	16.25	15.67	16.71	17.20	16.46	17.51	16.93	17.97	18.46
	6H	15.72	16.64	16.21	17.13	17.64	17.51	18.44	18.00	18.92	19.43
	8H	15.89	16.76	16.39	17.24	17.77	18.03	18.90	18.52	19.38	19.90
	12H	16.02	16.80	16.53	17.32	17.85	18.57	19.36	19.09	19.88	20.40
8H	4H	15.62	16.49	16.12	16.98	17.50	16.73	17.60	17.23	18.09	18.61
	6H	16.30	17.03	16.82	17.56	18.09	17.95	18.69	18.48	19.22	19.74
	8H	16.55	17.21	17.09	17.75	18.29	18.60	19.26	19.14	19.80	20.34
	12H	16.76	17.34	17.30	17.88	18.49	19.31	19.90	19.86	20.43	21.04
12H	4H	15.72	16.50	16.23	17.02	17.54	16.76	17.54	17.27	18.06	18.58
	6H	16.45	17.11	16.99	17.66	18.20	18.01	18.67	18.56	19.22	19.76
	8H	16.78	17.37	17.33	17.90	18.51	18.73	19.32	19.28	19.85	20.46

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Corelite

Report Number: SP1-2506-458-13

Test Date: 08/27/2025

Luminaire Tested: 22ID2-55-CFR1-L950-U

Data in this report applies to families of products including 22ID2-55-CFR1-L950-U

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2506-458-13
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 08/27/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Corelite
 Catalog Number: **22ID2-55-CFR1-L950-U**
 Description: 2X2 CGTX WITH INDEPTH FRAME AND CFR1 LENS - 5500 LUMEN 5000K 90CRI

Spectral Parameters

CCT (K): 4919
 CIE u' : 0.2096
 CIE v' : 0.4901
 Duv: 0.0038
 CIE x: 0.3483
 CIE y: 0.3619
 CIE z: 0.2898
 Peak Wavelength (nm): 453
 Dominant Wavelength (nm): 570
 Purity: 13.10873
 R_f: 90.8
 R_g: 97.4

CRI (Ra): 94.0
 R1: 94.8
 R2: 97.7
 R3: 98.4
 R4: 90.8
 R5: 92.2
 R6: 94.3
 R7: 94.0
 R8: 90.0
 R9: 77.7
 R10: 93.1
 R11: 92.0
 R12: 65.9
 R13: 95.9
 R14: 99.0
 R15: 91.4



Test Conditions

Stabilization Time: M
 Operation Time: 1H 0M
 Sphere Temperature (°C): 25.0

REPORT NUMBER: SP1-2506-458-13

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	1/21/2025	1/21/2026
AC Power Source	CHROMA 61603 IN0063	10/22/2024	10/22/2025
DC Power Source	AGILENT E3634A IN0208	10/22/2024	10/22/2025
Sphere Thermometer	ONSET IN0085	10/22/2024	10/22/2025
Room Thermometer	ONSET IN0046	10/22/2024	10/22/2025

REPORT NUMBER: SP1-2506-458-13

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 5000K 4-step quadrangle

REPORT NUMBER: SP1-2506-458-13

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	419	NR	620	583	NR	750	44	NR	880	1	NR
365	0	NR	495	441	NR	625	580	NR	755	37	NR	885	1	NR
370	0	NR	500	472	NR	630	572	NR	760	32	NR	890	1	NR
375	0	NR	505	501	NR	635	559	NR	765	27	NR	895	0	NR
380	0	NR	510	524	NR	640	543	NR	770	23	NR	900	0	NR
385	0	NR	515	545	NR	645	522	NR	775	20	NR	905	0	NR
390	1	NR	520	559	NR	650	496	NR	780	17	NR	910	0	NR
395	3	NR	525	572	NR	655	468	NR	785	14	NR	915	0	NR
400	4	NR	530	581	NR	660	435	NR	790	12	NR	920	0	NR
405	7	NR	535	590	NR	665	403	NR	795	10	NR	925	0	NR
410	9	NR	540	595	NR	670	368	NR	800	9	NR	930	0	NR
415	14	NR	545	599	NR	675	335	NR	805	8	NR	935	0	NR
420	23	NR	550	599	NR	680	304	NR	810	6	NR	940	0	NR
425	40	NR	555	599	NR	685	271	NR	815	6	NR	945	0	NR
430	72	NR	560	595	NR	690	243	NR	820	5	NR	950	0	NR
435	132	NR	565	589	NR	695	215	NR	825	4	NR	955	0	NR
440	243	NR	570	581	NR	700	189	NR	830	3	NR	960	0	NR
445	488	NR	575	575	NR	705	165	NR	835	3	NR	965	0	NR
450	879	NR	580	573	NR	710	144	NR	840	3	NR	970	0	NR
455	974	NR	585	570	NR	715	124	NR	845	2	NR	975	0	NR
460	726	NR	590	572	NR	720	108	NR	850	2	NR	980	0	NR
465	627	NR	595	574	NR	725	93	NR	855	2	NR	985	0	NR
470	546	NR	600	576	NR	730	80	NR	860	1	NR	990	0	NR
475	434	NR	605	581	NR	735	69	NR	865	1	NR	995	0	NR
480	395	NR	610	582	NR	740	59	NR	870	1	NR	1000	0	NR
485	403	NR	615	586	NR	745	51	NR	875	1	NR			

REPORT NUMBER: SP1-2506-458-13

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR

S/P: 2.09

λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)	λ (nm)	Power W ^λ /nm	Lumens (Φ/nm)
360	0	NR	490	419	NR	620	583	NR	750	44	NR	880	1	NR
365	0	NR	495	441	NR	625	580	NR	755	37	NR	885	1	NR
370	0	NR	500	472	NR	630	572	NR	760	32	NR	890	1	NR
375	0	NR	505	501	NR	635	559	NR	765	27	NR	895	0	NR
380	0	NR	510	524	NR	640	543	NR	770	23	NR	900	0	NR
385	0	NR	515	545	NR	645	522	NR	775	20	NR	905	0	NR
390	1	NR	520	559	NR	650	496	NR	780	17	NR	910	0	NR
395	3	NR	525	572	NR	655	468	NR	785	14	NR	915	0	NR
400	4	NR	530	581	NR	660	435	NR	790	12	NR	920	0	NR
405	7	NR	535	590	NR	665	403	NR	795	10	NR	925	0	NR
410	9	NR	540	595	NR	670	368	NR	800	9	NR	930	0	NR
415	14	NR	545	599	NR	675	335	NR	805	8	NR	935	0	NR
420	23	NR	550	599	NR	680	304	NR	810	6	NR	940	0	NR
425	40	NR	555	599	NR	685	271	NR	815	6	NR	945	0	NR
430	72	NR	560	595	NR	690	243	NR	820	5	NR	950	0	NR
435	132	NR	565	589	NR	695	215	NR	825	4	NR	955	0	NR
440	243	NR	570	581	NR	700	189	NR	830	3	NR	960	0	NR
445	488	NR	575	575	NR	705	165	NR	835	3	NR	965	0	NR
450	879	NR	580	573	NR	710	144	NR	840	3	NR	970	0	NR
455	974	NR	585	570	NR	715	124	NR	845	2	NR	975	0	NR
460	726	NR	590	572	NR	720	108	NR	850	2	NR	980	0	NR
465	627	NR	595	574	NR	725	93	NR	855	2	NR	985	0	NR
470	546	NR	600	576	NR	730	80	NR	860	1	NR	990	0	NR
475	434	NR	605	581	NR	735	69	NR	865	1	NR	995	0	NR
480	395	NR	610	582	NR	740	59	NR	870	1	NR	1000	0	NR
485	403	NR	615	586	NR	745	51	NR	875	1	NR			

REPORT NUMBER: SP1-2506-458-13

Melanopic Flux vs. Wavelength


Melanopic Lumens: NR
M/P: 4.55


λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)	λ (nm)	Power $\text{W}^\wedge/\text{nm}$	Lumens (ϕ/nm)
360	0	NR	490	419	NR	620	583	NR	750	44	NR	880	1	NR
365	0	NR	495	441	NR	625	580	NR	755	37	NR	885	1	NR
370	0	NR	500	472	NR	630	572	NR	760	32	NR	890	1	NR
375	0	NR	505	501	NR	635	559	NR	765	27	NR	895	0	NR
380	0	NR	510	524	NR	640	543	NR	770	23	NR	900	0	NR
385	0	NR	515	545	NR	645	522	NR	775	20	NR	905	0	NR
390	1	NR	520	559	NR	650	496	NR	780	17	NR	910	0	NR
395	3	NR	525	572	NR	655	468	NR	785	14	NR	915	0	NR
400	4	NR	530	581	NR	660	435	NR	790	12	NR	920	0	NR
405	7	NR	535	590	NR	665	403	NR	795	10	NR	925	0	NR
410	9	NR	540	595	NR	670	368	NR	800	9	NR	930	0	NR
415	14	NR	545	599	NR	675	335	NR	805	8	NR	935	0	NR
420	23	NR	550	599	NR	680	304	NR	810	6	NR	940	0	NR
425	40	NR	555	599	NR	685	271	NR	815	6	NR	945	0	NR
430	72	NR	560	595	NR	690	243	NR	820	5	NR	950	0	NR
435	132	NR	565	589	NR	695	215	NR	825	4	NR	955	0	NR
440	243	NR	570	581	NR	700	189	NR	830	3	NR	960	0	NR
445	488	NR	575	575	NR	705	165	NR	835	3	NR	965	0	NR
450	879	NR	580	573	NR	710	144	NR	840	3	NR	970	0	NR
455	974	NR	585	570	NR	715	124	NR	845	2	NR	975	0	NR
460	726	NR	590	572	NR	720	108	NR	850	2	NR	980	0	NR
465	627	NR	595	574	NR	725	93	NR	855	2	NR	985	0	NR
470	546	NR	600	576	NR	730	80	NR	860	1	NR	990	0	NR
475	434	NR	605	581	NR	735	69	NR	865	1	NR	995	0	NR
480	395	NR	610	582	NR	740	59	NR	870	1	NR	1000	0	NR
485	403	NR	615	586	NR	745	51	NR	875	1	NR			

REPORT NUMBER: SP1-2506-458-13


TM-30-18

Summary

$R_f = 90.8$
 $R_g = 97.4$
 $CIE R_a = 94.0$
 $R_9 = 77.7$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 85	CES26 = 98	CES51 = 93	CES76 = 91
CES02 = 61	CES27 = 86	CES52 = 96	CES77 = 89
CES03 = 31	CES28 = 98	CES53 = 93	CES78 = 87
CES04 = 68	CES29 = 90	CES54 = 89	CES79 = 97
CES05 = 48	CES30 = 80	CES55 = 86	CES80 = 94
CES06 = 50	CES31 = 92	CES56 = 89	CES81 = 89
CES07 = 41	CES32 = 97	CES57 = 87	CES82 = 97
CES08 = 40	CES33 = 89	CES58 = 87	CES83 = 96
CES09 = 29	CES34 = 98	CES59 = 96	CES84 = 94
CES10 = 73	CES35 = 98	CES60 = 89	CES85 = 84
CES11 = 56	CES36 = 74	CES61 = 90	CES86 = 90
CES12 = 62	CES37 = 97	CES62 = 78	CES87 = 92
CES13 = 42	CES38 = 75	CES63 = 89	CES88 = 95
CES14 = 74	CES39 = 97	CES64 = 85	CES89 = 90
CES15 = 71	CES40 = 97	CES65 = 87	CES90 = 92
CES16 = 47	CES41 = 91	CES66 = 82	CES91 = 69
CES17 = 48	CES42 = 99	CES67 = 82	CES92 = 81
CES18 = 56	CES43 = 97	CES68 = 86	CES93 = 88
CES19 = 70	CES44 = 99	CES69 = 87	CES94 = 86
CES20 = 65	CES45 = 97	CES70 = 86	CES95 = 83
CES21 = 84	CES46 = 94	CES71 = 77	CES96 = 94
CES22 = 77	CES47 = 90	CES72 = 93	CES97 = 97
CES23 = 91	CES48 = 83	CES73 = 82	CES98 = 94
CES24 = 89	CES49 = 95	CES74 = 89	CES99 = 92
CES25 = 70	CES50 = 94	CES75 = 81	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)