

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P1057063

Luminaire Tested: CB3-055D-840-1D-UNV-STD-W-8

Issue Date: 7/31/2025

Test Information

Test Method: LM-79-2019
Report Number: P1057063
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2312-242-8)
Test Lab: INNOVATION CENTER
Issue Date: 7/31/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: CB3-055D-840-1D-UNV-STD-W-8
Description: CORELITE BASIC SLOT LED LUMINAIRE
3-INCH APERTURE
DOWNLIGHT 550 LUMENS PER FOOT
DIRECT ONLY
Light Source: 4000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4358.0 lumens
Efficiency: N/A
Efficacy: 133.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.13 / 1.26
Luminous Opening: Rectangular (W 0.24' x L: 8' x H: 0')
CIE Type: Direct


Input Watts (W): 32.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P1057063

CATALOG NUMBER: CB3-055D-840-1D-UNV-STD-W-8

Luminous Intensity Polar Plot



TEST NUMBER: P1057063

CATALOG NUMBER: CB3-055D-840-1D-UNV-STD-W-8

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	109	105	101	97	107	103	99	96	98	95	93		94	92	90		91
2	100	92	86	80	97	90	84	79	87	82	77		83	79	76		80
3	91	81	74	67	89	80	73	67	77	71	66		74	69	64		72
4	84	72	64	58	82	71	63	57	69	62	56		66	60	56		64
5	78	65	56	50	75	64	56	50	62	55	49		60	54	49		58
6	72	59	50	44	70	58	50	44	56	49	43		54	48	43		53
7	67	54	45	39	65	53	45	39	51	44	39		50	43	38		48
8	62	49	41	35	61	48	40	35	47	40	35		46	39	34		45
9	58	45	37	32	57	45	37	32	43	36	31		42	36	31		41
10	55	42	34	29	53	41	34	29	40	33	29		39	33	29		38

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	10298	10298	10298
5°	10249	10257	10315
10°	10204	10190	10190
15°	10048	10048	9987
20°	9885	9784	9698
25°	9635	9514	9345
30°	9400	9155	8935
35°	9152	8812	8500
40°	8822	8402	8039
45°	8523	8037	7541
50°	8215	7601	7055
55°	7881	7179	6593
60°	7519	6743	6070
65°	7096	6247	5521
70°	6608	5667	4918
75°	5991	4973	4380
80°	5222	4170	3874
85°	4031	3525	3525

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 8523 cd/sqm

TEST NUMBER: P1057063

CATALOG NUMBER: CB3-055D-840-1D-UNV-STD-W-8

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	171.7	3.9
10°-20°	482.5	11.1
20°-30°	701.0	16.1
30°-40°	797.0	18.3
40°-50°	773.7	17.8
50°-60°	653.3	15.0
60°-70°	464.8	10.7
70°-80°	248.3	5.7
80°-90°	65.6	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1355.3	31.1
0°-40°	2152.3	49.4
0°-60°	3579.3	82.1
0°-90°	4358.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4358.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1820	1820	1820	1820	1820	
5°	1805	1828	1806	1804	1816	171
15°	1716	1731	1716	1705	1705	483
25°	1544	1549	1524	1503	1497	711
35°	1325	1312	1276	1238	1231	826
45°	1065	1049	1004	956	942	822
55°	799	778	728	681	668	714
65°	530	511	467	425	412	525
75°	274	259	228	204	200	292
85°	62	57	54	54	54	76
90°	0	0	0	0	0	

TEST NUMBER: P1057063

CATALOG NUMBER: CB3-055D-840-1D-UNV-STD-W-8

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1820.3	1820.3	1820.3	1820.3	1820.3
2.5°	1811.0	1829.2	1813.1	1815.2	1819.3
5°	1804.8	1827.5	1806.1	1803.8	1816.4
7.5°	1790.8	1811.6	1789.3	1784.1	1795.5
10°	1776.3	1799.1	1773.8	1767.4	1773.8
12.5°	1750.5	1774.2	1754.1	1743.6	1748.9
15°	1715.6	1730.7	1715.6	1705.2	1705.2
17.5°	1672.9	1688.8	1660.2	1652.9	1650.2
20°	1641.9	1655.8	1625.1	1614.7	1610.9
22.5°	1600.5	1613.4	1587.8	1570.2	1565.4
25°	1543.6	1548.7	1524.2	1503.4	1497.1
27.5°	1486.5	1487.8	1454.2	1428.9	1420.6
30°	1438.9	1440.2	1401.4	1374.1	1367.8
32.5°	1391.3	1387.5	1350.7	1318.3	1314.0
35°	1325.1	1312.5	1276.0	1238.4	1230.8
37.5°	1245.2	1237.7	1194.6	1156.8	1145.4
40°	1194.6	1181.9	1137.7	1099.9	1088.6
42.5°	1143.9	1129.2	1083.9	1042.0	1029.6
45°	1065.3	1048.9	1004.5	956.4	942.5
47.5°	986.2	968.2	919.5	872.8	857.4
50°	933.4	914.5	863.6	818.0	801.6
52.5°	879.6	859.7	808.8	762.2	748.8
55°	799.0	777.5	727.9	681.0	668.4
57.5°	718.3	697.1	647.7	603.4	588.2
60°	664.5	644.3	596.0	551.7	536.5
62.5°	609.7	590.5	543.2	500.0	485.8
65°	530.1	511.1	466.7	425.1	412.4
67.5°	451.2	435.0	391.2	353.0	342.9
70°	399.5	384.3	342.6	307.5	297.3
72.5°	349.8	333.7	294.0	264.1	257.0
75°	274.1	258.9	227.5	204.2	200.4
77.5°	204.8	192.4	165.2	152.0	150.0
80°	160.3	148.9	128.0	118.9	118.9
82.5°	118.9	109.6	95.9	92.0	92.0
85°	62.1	57.0	54.3	54.3	54.3
87.5°	18.6	18.6	17.6	16.5	16.5
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)