

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P1057059

Luminaire Tested: CB3-0U-030D-835-1D-UNV-STD-W-8

Issue Date: 7/31/2025

Test Information

Test Method: LM-79-2019
Report Number: P1057059
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2312-242-8)
Test Lab: INNOVATION CENTER
Issue Date: 7/31/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: CB3-0U-030D-835-1D-UNV-STD-W-8
Description: CORELITE BASIC SLOT LED LUMINAIRE
3-INCH APERTURE
DOWNLIGHT 300 LUMENS PER FOOT
DIRECT ONLY
Light Source: 3500K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2312.1 lumens
Efficiency: N/A
Efficacy: 139.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.13 / 1.26
Luminous Opening: Rectangular (W 0.24' x L: 8' x H: 0')
CIE Type: Direct


Input Watts (W): 16.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P1057059

CATALOG NUMBER: CB3-0U-030D-835-1D-UNV-STD-W-8

Luminous Intensity Polar Plot



TEST NUMBER: P1057059

CATALOG NUMBER: CB3-OU-030D-835-1D-UNV-STD-W-8

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	109	105	101	97	107	103	99	96	98	95	93		94	92	90		91
2	100	92	86	80	97	90	84	79	87	82	77		83	79	76		80
3	91	81	74	67	89	80	73	67	77	71	66		74	69	64		72
4	84	72	64	58	82	71	63	57	69	62	56		66	60	56		64
5	78	65	56	50	75	64	56	50	62	55	49		60	54	49		58
6	72	59	50	44	70	58	50	44	56	49	43		54	48	43		53
7	67	54	45	39	65	53	45	39	51	44	39		50	43	38		48
8	62	49	41	35	61	48	40	35	47	40	35		46	39	34		45
9	58	45	37	32	57	45	37	32	43	36	31		42	36	31		41
10	55	42	34	29	53	41	34	29	40	33	29		39	33	29		38

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5463	5463	5463
5°	5438	5442	5473
10°	5414	5406	5406
15°	5331	5331	5299
20°	5244	5191	5145
25°	5112	5048	4958
30°	4987	4857	4741
35°	4855	4676	4510
40°	4681	4458	4265
45°	4522	4264	4000
50°	4358	4033	3742
55°	4181	3809	3497
60°	3988	3578	3220
65°	3764	3314	2929
70°	3505	3007	2610
75°	3178	2638	2324
80°	2769	2212	2056
85°	2136	1869	1869

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 4522 cd/sqm

TEST NUMBER: P1057059

CATALOG NUMBER: CB3-OU-030D-835-1D-UNV-STD-W-8

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	91.1	3.9
10°-20°	256.0	11.1
20°-30°	371.9	16.1
30°-40°	422.9	18.3
40°-50°	410.5	17.8
50°-60°	346.6	15.0
60°-70°	246.6	10.7
70°-80°	131.7	5.7
80°-90°	34.8	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	719.0	31.1
0°-40°	1141.9	49.4
0°-60°	1899.0	82.1
0°-90°	2312.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2312.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	966	966	966	966	966	
5°	958	970	958	957	964	91
15°	910	918	910	905	905	256
25°	819	822	809	798	794	377
35°	703	696	677	657	653	438
45°	565	556	533	507	500	436
55°	424	412	386	361	355	379
65°	281	271	248	226	219	279
75°	145	137	121	108	106	155
85°	33	30	29	29	29	40
90°	0	0	0	0	0	

TEST NUMBER: P1057059

CATALOG NUMBER: CB3-OU-030D-835-1D-UNV-STD-W-8

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	965.7	965.7	965.7	965.7	965.7
2.5°	960.8	970.4	961.9	963.0	965.2
5°	957.5	969.6	958.2	957.0	963.7
7.5°	950.1	961.1	949.3	946.5	952.6
10°	942.4	954.5	941.0	937.7	941.0
12.5°	928.7	941.3	930.6	925.0	927.9
15°	910.2	918.2	910.2	904.7	904.7
17.5°	887.5	896.0	880.8	876.9	875.5
20°	871.1	878.5	862.2	856.6	854.6
22.5°	849.1	856.0	842.4	833.0	830.5
25°	818.9	821.6	808.7	797.6	794.3
27.5°	788.6	789.3	771.5	758.1	753.7
30°	763.4	764.1	743.5	729.0	725.7
32.5°	738.2	736.1	716.6	699.4	697.1
35°	703.0	696.3	677.0	657.0	653.0
37.5°	660.6	656.6	633.8	613.7	607.7
40°	633.8	627.1	603.6	583.6	577.5
42.5°	606.9	599.1	575.0	552.8	546.2
45°	565.2	556.5	532.9	507.4	500.0
47.5°	523.2	513.7	487.8	463.1	454.9
50°	495.2	485.2	458.2	434.0	425.2
52.5°	466.7	456.1	429.1	404.4	397.3
55°	423.9	412.5	386.2	361.3	354.6
57.5°	381.1	369.8	343.6	320.1	312.1
60°	352.5	341.8	316.2	292.7	284.6
62.5°	323.5	313.3	288.2	265.3	257.8
65°	281.2	271.2	247.6	225.5	218.8
67.5°	239.4	230.8	207.5	187.3	181.9
70°	211.9	203.9	181.8	163.1	157.8
72.5°	185.6	177.0	156.0	140.1	136.4
75°	145.4	137.4	120.7	108.3	106.3
77.5°	108.6	102.1	87.7	80.6	79.6
80°	85.0	79.0	67.9	63.1	63.1
82.5°	63.1	58.1	50.9	48.8	48.8
85°	32.9	30.2	28.8	28.8	28.8
87.5°	9.9	9.9	9.3	8.8	8.8
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)