

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P1191234

Luminaire Tested: SQ2-FA-025U-075D-L835-UNV-STD-W-4

Issue Date: 9/23/2025

Test Information

Test Method: LM-79-2019
Report Number: P1191234
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2104-222-9, G2-2502-345-2)
Test Lab: INNOVATION CENTER
Issue Date: 9/23/2025
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2-FA-025U-075D-L835-UNV-STD-W-4
Description: CORELITE SQ2 LED LUMINAIRE
FROSTED CONTINUOUS ASYMMETRIC ROLL LENS
DOWNLIGHT 750 LUMENS PER FOOT
UPLIGHT 250 LUMENS PER FOOT
Light Source: 3500K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4300.9 lumens
Efficiency: N/A
Efficacy: 126.1 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.23 / 1.34
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Semi-Direct

Input Watts (W): 34.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

Luminous Intensity Polar Plot



TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	113	113	113	113	107	107	107	107	96	96	96	87	87	87	78	78	78
1	103	99	95	91	98	94	90	87	85	82	80	77	75	73	69	67	66
2	94	86	80	75	89	82	77	72	75	70	66	67	64	61	61	58	56
3	86	76	68	62	81	73	66	60	66	60	56	60	55	52	54	50	47
4	79	67	59	53	74	64	57	51	59	52	48	53	48	44	48	44	41
5	72	60	52	46	68	58	50	44	52	46	41	48	43	38	43	39	36
6	67	54	46	40	63	52	44	38	47	41	36	43	38	34	39	35	31
7	62	49	41	35	58	47	39	34	43	37	32	39	34	30	36	31	28
8	57	45	37	31	54	43	35	30	39	33	28	36	31	27	33	28	25
9	54	41	33	28	51	39	32	27	36	30	26	33	28	24	30	26	23
10	50	38	30	25	48	36	29	24	33	27	23	31	26	22	28	24	21

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	20518	20518	20518	20518
5°	20277	21235	20277	16924
10°	20189	21481	20189	15342
15°	19841	21653	19841	16959
20°	19295	21496	19295	17687
25°	18339	21323	18339	17900
30°	16897	20845	16897	18090
35°	14950	20386	14950	17767
40°	12874	19829	12874	17960
45°	12709	19119	12709	17995
50°	12125	18186	12125	18063
55°	12062	16777	12062	17886
60°	10814	14951	10814	17815
65°	9219	13173	9219	17310
70°	7440	11160	7440	16046
75°	6450	9220	6450	14747
80°	5495	6871	5495	11911
85°	3649	3649	3649	7299

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°

Vertical Angle: 45°

Luminance: 19795 cd/sqm

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.3	2.7
10°-20°	319.5	7.4
20°-30°	485.2	11.3
30°-40°	569.6	13.2
40°-50°	578.0	13.4
50°-60°	506.4	11.8
60°-70°	359.2	8.4
70°-80°	185.0	4.3
80°-90°	39.3	0.9
90°-100°	74.6	1.7
100°-110°	232.1	5.4
110°-120°	227.1	5.3
120°-130°	185.4	4.3
130°-140°	151.7	3.5
140°-150°	118.4	2.8
150°-160°	85.4	2.0
160°-170°	52.2	1.2
170°-180°	17.6	0.4
0°-30°	919.0	21.4
0°-40°	1488.7	34.6
0°-60°	2573.0	59.8
0°-90°	3156.5	73.4
90°-120°	533.8	12.4
90°-150°	989.2	23.0
90°-180°	1144.0	26.6
0°-180°	4300.9	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1271	1271	1271	1271	1271	
5°	1251	1310	1251	1044	1251	119
15°	1187	1295	1187	1015	1187	333
25°	1029	1197	1029	1005	1029	470
35°	758	1034	758	901	758	473
45°	557	837	557	788	557	426
55°	428	596	428	635	428	371
65°	241	345	241	453	241	241
75°	103	148	103	236	103	112
85°	20	20	20	39	20	25
90°	0	3	0	3	0	1
95°	10	33	10	33	10	12
105°	41	416	41	416	41	43
115°	72	448	72	448	72	71
125°	101	353	101	353	101	89
135°	121	292	121	292	121	94
145°	141	244	141	244	141	89
155°	162	208	162	208	162	75
165°	178	192	178	192	178	50
175°	184	184	184	184	184	17
180°	184	184	184	184	184	

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8
2.5°	1262.9	1282.2	1282.6	1282.6	1282.6	1282.6	1282.6	1282.2	1262.9	1262.9	1243.2
5°	1251.1	1284.8	1295.4	1300.5	1310.2	1300.5	1295.4	1284.8	1251.1	1236.6	1157.5
7.5°	1239.2	1284.5	1300.3	1309.3	1314.1	1309.3	1300.3	1284.5	1239.2	1174.7	1008.7
10°	1231.4	1284.3	1300.3	1305.4	1310.2	1305.4	1300.3	1284.3	1231.4	1101.3	965.4
12.5°	1219.5	1276.4	1296.4	1301.4	1306.2	1301.4	1296.4	1276.4	1219.5	1035.6	933.9
15°	1187.0	1264.1	1280.6	1290.6	1295.4	1290.6	1280.6	1264.1	1187.0	979.9	911.2
17.5°	1146.6	1240.1	1261.9	1270.9	1274.7	1270.9	1261.9	1240.1	1146.6	929.9	912.2
20°	1123.0	1224.1	1246.1	1251.1	1251.1	1251.1	1246.1	1224.1	1123.0	906.3	935.8
22.5°	1091.5	1204.2	1226.4	1227.5	1231.4	1227.5	1226.4	1204.2	1091.5	878.6	947.7
25°	1029.4	1159.5	1192.0	1187.3	1196.9	1187.3	1192.0	1159.5	1029.4	841.6	945.7
27.5°	953.6	1117.3	1140.7	1145.7	1145.7	1145.7	1140.7	1117.3	953.6	805.2	926.0
30°	906.3	1089.3	1113.2	1118.1	1118.1	1118.1	1113.2	1089.3	906.3	781.1	906.3
32.5°	847.2	1064.9	1085.6	1086.6	1086.6	1086.6	1085.6	1064.9	847.2	756.6	874.8
35°	758.5	1023.4	1039.3	1039.2	1034.3	1039.2	1039.3	1023.4	758.5	720.0	837.3
37.5°	669.9	970.4	992.0	985.0	980.2	985.0	992.0	970.4	669.9	682.4	805.8
40°	610.8	938.2	960.5	945.6	940.8	945.6	960.5	938.2	610.8	654.1	778.2
42.5°	579.2	902.9	925.0	906.2	901.4	906.2	925.0	902.9	579.2	626.4	754.6
45°	556.6	845.5	866.9	847.0	837.3	847.0	866.9	845.5	556.6	585.5	714.2
47.5°	522.1	776.4	806.8	777.0	767.4	777.0	806.8	776.4	522.1	543.3	677.7
50°	482.7	733.1	763.4	733.7	724.0	733.7	763.4	733.1	482.7	511.6	650.2
52.5°	455.1	690.1	716.2	682.4	672.8	682.4	716.2	690.1	455.1	472.4	626.5
55°	428.5	626.0	645.2	610.4	596.0	610.4	645.2	626.0	428.5	414.1	581.2
57.5°	366.5	554.3	574.3	534.5	518.2	534.5	574.3	554.3	366.5	353.9	533.9
60°	334.9	503.5	527.0	487.1	463.0	487.1	527.0	503.5	334.9	310.9	502.4
62.5°	299.5	448.8	479.7	439.8	415.7	439.8	479.7	448.8	299.5	283.1	466.9
65°	241.3	371.4	408.8	368.9	344.8	368.9	408.8	371.4	241.3	251.0	408.8
67.5°	189.1	300.9	342.8	299.0	279.8	299.0	342.8	300.9	189.1	220.9	355.6
70°	157.6	253.9	295.5	255.7	236.4	255.7	295.5	253.9	157.6	201.0	320.2
72.5°	137.9	211.1	256.1	212.4	197.0	212.4	256.1	211.1	137.9	181.3	276.8
75°	103.4	146.8	197.0	157.4	147.8	157.4	197.0	146.8	103.4	146.8	216.7
77.5°	74.9	95.1	138.9	105.3	101.5	105.3	138.9	95.1	74.9	110.5	157.6
80°	59.1	63.9	103.4	73.9	73.9	73.9	103.4	63.9	59.1	83.2	118.2
82.5°	39.4	44.2	71.9	50.2	46.3	50.2	71.9	44.2	39.4	59.6	82.7
85°	19.7	19.7	29.6	19.7	19.7	19.7	29.6	19.7	19.7	29.3	39.4
87.5°	3.9	4.2	8.6	4.6	4.6	4.6	8.6	4.2	3.9	8.0	8.6
90°	0.0	1.1	3.4	3.4	3.4	3.4	3.4	1.1	0.0	1.1	3.4
92.5°	3.6	12.7	43.2	14.2	11.5	14.2	43.2	12.7	3.6	12.7	43.2
95°	10.2	30.1	136.9	50.5	32.8	50.5	136.9	30.1	10.2	30.1	136.9
97.5°	18.6	39.1	226.7	141.1	88.9	141.1	226.7	39.1	18.6	39.1	226.7
100°	24.9	43.7	255.7	239.2	159.5	239.2	255.7	43.7	24.9	43.7	255.7
102.5°	31.2	49.1	250.2	341.6	268.1	341.6	250.2	49.1	31.2	49.1	250.2
105°	40.7	57.3	228.5	436.2	416.3	436.2	228.5	57.3	40.7	57.3	228.5
107.5°	50.2	65.7	207.7	443.5	465.4	443.5	207.7	65.7	50.2	65.7	207.7
110°	56.6	72.1	196.8	433.1	476.3	433.1	196.8	72.1	56.6	72.1	196.8

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
112.5°	62.9	77.5	191.4	414.4	469.0	414.4	191.4	77.5	62.9	77.5	191.4
115°	72.4	85.7	185.5	382.7	448.0	382.7	185.5	85.7	72.4	85.7	185.5
117.5°	81.7	93.8	183.0	352.4	419.3	352.4	183.0	93.8	81.7	93.8	183.0
120°	87.1	99.3	182.1	335.2	399.3	335.2	182.1	99.3	87.1	99.3	182.1
122.5°	92.5	104.7	183.0	320.6	379.4	320.6	183.0	104.7	92.5	104.7	183.0
125°	100.7	111.7	183.3	301.0	353.0	301.0	183.3	111.7	100.7	111.7	183.3
127.5°	107.2	118.5	183.3	286.3	330.6	286.3	183.3	118.5	107.2	118.5	183.3
130°	110.9	123.0	183.3	278.1	317.9	278.1	183.3	123.0	110.9	123.0	183.3
132.5°	115.4	127.6	182.4	270.8	307.9	270.8	182.4	127.6	115.4	127.6	182.4
135°	121.0	134.3	182.1	259.8	291.9	259.8	182.1	134.3	121.0	134.3	182.1
137.5°	127.6	139.8	182.1	248.9	278.1	248.9	182.1	139.8	127.6	139.8	182.1
140°	131.2	143.4	182.1	241.6	268.1	241.6	182.1	143.4	131.2	143.4	182.1
142.5°	135.8	147.0	182.1	234.3	258.2	234.3	182.1	147.0	135.8	147.0	182.1
145°	141.4	152.5	182.1	224.4	244.4	224.4	182.1	152.5	141.4	152.5	182.1
147.5°	148.2	157.7	183.3	215.3	231.0	215.3	183.3	157.7	148.2	157.7	183.3
150°	152.7	160.5	183.3	210.7	222.9	210.7	183.3	160.5	152.7	160.5	183.3
152.5°	156.3	163.2	183.3	206.1	216.5	206.1	183.3	163.2	156.3	163.2	183.3
155°	161.8	167.3	183.3	201.5	208.2	201.5	183.3	167.3	161.8	167.3	183.3
157.5°	167.2	171.4	183.3	197.4	201.6	197.4	183.3	171.4	167.2	171.4	183.3
160°	170.8	174.1	183.3	194.7	198.0	194.7	183.3	174.1	170.8	174.1	183.3
162.5°	173.5	176.0	183.3	192.8	195.3	192.8	183.3	176.0	173.5	176.0	183.3
165°	177.6	178.7	184.4	190.1	192.3	190.1	184.4	178.7	177.6	178.7	184.4
167.5°	180.1	180.3	183.3	188.5	189.6	188.5	183.3	180.3	180.1	180.3	183.3
170°	181.0	182.1	183.3	186.7	187.8	186.7	183.3	182.1	181.0	182.1	183.3
172.5°	182.8	183.0	184.2	185.8	186.0	185.8	184.2	183.0	182.8	183.0	184.2
175°	184.4	184.4	184.4	185.5	184.4	185.5	184.4	184.4	184.4	184.4	184.4
177.5°	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4
180°	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4	184.4

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	1270.8	1270.8	1270.8	1270.8	1270.8	1270.8
2.5°	1231.3	1227.4	1231.3	1243.2	1262.9	1262.9
5°	1068.3	1044.2	1068.3	1157.5	1236.6	1251.1
7.5°	971.1	963.4	971.1	1008.7	1174.7	1239.2
10°	935.8	935.8	935.8	965.4	1101.3	1231.4
12.5°	932.3	951.6	932.3	933.9	1035.6	1219.5
15°	990.6	1014.6	990.6	911.2	979.9	1187.0
17.5°	1010.2	1029.4	1010.2	912.2	929.9	1146.6
20°	1010.2	1029.4	1010.2	935.8	906.3	1123.0
22.5°	1006.2	1025.5	1006.2	947.7	878.6	1091.5
25°	995.2	1004.8	995.2	945.7	841.6	1029.4
27.5°	975.4	982.1	975.4	926.0	805.2	953.6
30°	955.9	970.3	955.9	906.3	781.1	906.3
32.5°	935.9	938.8	935.9	874.8	756.6	847.2
35°	906.2	901.4	906.2	837.3	720.0	758.5
37.5°	866.0	871.8	866.0	805.8	682.4	669.9
40°	842.5	852.1	842.5	778.2	654.1	610.8
42.5°	818.8	828.5	818.8	754.6	626.4	579.2
45°	783.3	788.1	783.3	714.2	585.5	556.6
47.5°	741.9	746.7	741.9	677.7	543.3	522.1
50°	714.3	719.1	714.3	650.2	511.6	482.7
52.5°	682.8	687.6	682.8	626.5	472.4	455.1
55°	635.4	635.4	635.4	581.2	414.1	428.5
57.5°	581.3	587.1	581.3	533.9	353.9	366.5
60°	542.0	551.7	542.0	502.4	310.9	334.9
62.5°	506.5	512.2	506.5	466.9	283.1	299.5
65°	448.3	453.1	448.3	408.8	251.0	241.3
67.5°	383.3	387.1	383.3	355.6	220.9	189.1
70°	339.9	339.9	339.9	320.2	201.0	157.6
72.5°	296.6	300.5	296.6	276.8	181.3	137.9
75°	231.6	236.4	231.6	216.7	146.8	103.4
77.5°	166.6	171.4	166.6	157.6	110.5	74.9
80°	123.2	128.1	123.2	118.2	83.2	59.1
82.5°	87.7	88.7	87.7	82.7	59.6	39.4
85°	39.4	39.4	39.4	39.4	29.3	19.7
87.5°	8.6	8.6	8.6	8.6	8.0	3.9
90°	3.4	3.4	3.4	3.4	1.1	0.0
92.5°	14.2	11.5	14.2	43.2	12.7	3.6
95°	50.5	32.8	50.5	136.9	30.1	10.2
97.5°	141.1	88.9	141.1	226.7	39.1	18.6
100°	239.2	159.5	239.2	255.7	43.7	24.9
102.5°	341.6	268.1	341.6	250.2	49.1	31.2
105°	436.2	416.3	436.2	228.5	57.3	40.7
107.5°	443.5	465.4	443.5	207.7	65.7	50.2
110°	433.1	476.3	433.1	196.8	72.1	56.6

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
112.5°	414.4	469.0	414.4	191.4	77.5	62.9
115°	382.7	448.0	382.7	185.5	85.7	72.4
117.5°	352.4	419.3	352.4	183.0	93.8	81.7
120°	335.2	399.3	335.2	182.1	99.3	87.1
122.5°	320.6	379.4	320.6	183.0	104.7	92.5
125°	301.0	353.0	301.0	183.3	111.7	100.7
127.5°	286.3	330.6	286.3	183.3	118.5	107.2
130°	278.1	317.9	278.1	183.3	123.0	110.9
132.5°	270.8	307.9	270.8	182.4	127.6	115.4
135°	259.8	291.9	259.8	182.1	134.3	121.0
137.5°	248.9	278.1	248.9	182.1	139.8	127.6
140°	241.6	268.1	241.6	182.1	143.4	131.2
142.5°	234.3	258.2	234.3	182.1	147.0	135.8
145°	224.4	244.4	224.4	182.1	152.5	141.4
147.5°	215.3	231.0	215.3	183.3	157.7	148.2
150°	210.7	222.9	210.7	183.3	160.5	152.7
152.5°	206.1	216.5	206.1	183.3	163.2	156.3
155°	201.5	208.2	201.5	183.3	167.3	161.8
157.5°	197.4	201.6	197.4	183.3	171.4	167.2
160°	194.7	198.0	194.7	183.3	174.1	170.8
162.5°	192.8	195.3	192.8	183.3	176.0	173.5
165°	190.1	192.3	190.1	184.4	178.7	177.6
167.5°	188.5	189.6	188.5	183.3	180.3	180.1
170°	186.7	187.8	186.7	183.3	182.1	181.0
172.5°	185.8	186.0	185.8	184.2	183.0	182.8
175°	185.5	184.4	185.5	184.4	184.4	184.4
177.5°	184.4	184.4	184.4	184.4	184.4	184.4
180°	184.4	184.4	184.4	184.4	184.4	184.4

TEST NUMBER: P1191234

CATALOG NUMBER: SQ2-FA-025U-075D-L835-UNV-STD-W-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	18.77	19.89	19.50	20.64	21.53	20.00	21.12	20.73	21.86	22.76
	3H	19.88	20.89	20.62	21.64	22.57	21.26	22.26	22.00	23.02	23.95
	4H	20.25	21.19	21.01	21.96	22.90	21.66	22.61	22.42	23.38	24.31
	6H	20.42	21.30	21.20	22.07	23.02	21.84	22.71	22.61	23.49	24.44
	8H	20.47	21.30	21.25	22.09	23.04	21.87	22.70	22.65	23.50	24.45
	12H	20.47	21.26	21.26	22.05	23.03	21.86	22.65	22.65	23.44	24.42
4H	2H	19.73	20.68	20.50	21.45	22.38	20.64	21.59	21.41	22.36	23.29
	3H	21.13	21.91	21.90	22.72	23.67	22.12	22.91	22.90	23.71	24.66
	4H	21.58	22.30	22.37	23.10	24.08	22.60	23.31	23.39	24.12	25.10
	6H	21.82	22.44	22.63	23.27	24.26	22.83	23.45	23.64	24.28	25.27
	8H	21.89	22.46	22.70	23.29	24.29	22.89	23.47	23.70	24.29	25.29
	12H	21.90	22.42	22.73	23.26	24.27	22.89	23.41	23.72	24.25	25.26
8H	4H	22.00	22.58	22.81	23.40	24.40	22.83	23.41	23.64	24.23	25.23
	6H	22.36	22.83	23.20	23.70	24.70	23.15	23.63	23.99	24.49	25.49
	8H	22.47	22.90	23.33	23.76	24.78	23.25	23.67	24.10	24.53	25.55
	12H	22.52	22.90	23.38	23.75	24.82	23.27	23.64	24.13	24.50	25.57
12H	4H	22.02	22.54	22.85	23.38	24.39	22.81	23.33	23.64	24.17	25.18
	6H	22.43	22.86	23.28	23.72	24.74	23.17	23.60	24.02	24.46	25.48
	8H	22.59	22.96	23.44	23.81	24.89	23.30	23.67	24.15	24.52	25.60