

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P935382

Luminaire Tested: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P935382
REPORT IS A COMBINATION OF REPORTS P933750 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Asymmetric Frosted Continuous I
Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8623.3 lumens
Efficiency: N/A
Efficacy: 125.3 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.26 / 1.36
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 68.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

Luminous Intensity Polar Plot



TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	108	108	108	108	100	100	100	100	85	85	85	72	72	72	59	59	59
1	99	94	90	87	91	88	84	81	75	73	70	63	62	60	53	51	50
2	90	82	76	71	83	77	71	67	66	62	58	56	53	50	46	44	42
3	82	72	65	59	76	67	61	56	58	53	49	49	46	42	41	38	36
4	75	64	56	50	69	60	53	47	51	46	42	44	40	36	37	34	31
5	69	57	49	43	64	53	46	41	46	40	36	39	35	31	33	30	27
6	63	51	43	37	59	48	41	35	41	36	31	35	31	28	30	26	24
7	59	46	38	33	54	43	36	31	38	32	28	32	28	24	27	24	21
8	54	42	34	29	50	39	32	27	34	29	24	29	25	22	25	22	19
9	51	38	31	26	47	36	29	24	31	26	22	27	23	19	23	20	17
10	47	35	28	23	44	33	26	22	29	23	20	25	21	18	21	18	15

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	16532	16532	16532	16532
5°	16637	16689	16637	13123
10°	16508	16439	16508	11753
15°	16309	16083	16309	13429
20°	15951	15661	15951	13457
25°	15233	15045	15233	13172
30°	14314	14535	14314	12547
35°	12742	13889	12742	11858
40°	10598	13127	10598	11339
45°	9451	12238	9451	10741
50°	10017	11175	10017	10140
55°	9400	10031	9400	9794
60°	9654	8520	9654	8970
65°	8711	7043	8711	7873
70°	5991	5613	5991	6598
75°	5198	4148	5198	4968
80°	4100	2743	4100	2985
85°	2236	1452	2236	1235

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 20°

Vertical Angle: 45°

Luminance: 14514 cd/sqm

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	160.8	1.9
10°-20°	456.6	5.3
20°-30°	705.9	8.2
30°-40°	842.6	9.8
40°-50°	847.6	9.8
50°-60°	737.5	8.6
60°-70°	522.9	6.1
70°-80°	276.6	3.2
80°-90°	71.2	0.8
90°-100°	300.9	3.5
100°-110°	791.1	9.2
110°-120°	820.2	9.5
120°-130°	657.9	7.6
130°-140°	516.2	6.0
140°-150°	396.2	4.6
150°-160°	285.4	3.3
160°-170°	174.6	2.0
170°-180°	59.0	0.7
0°-30°	1323.3	15.3
0°-40°	2165.9	25.1
0°-60°	3751.0	43.5
0°-90°	4621.8	53.6
90°-120°	1912.2	22.2
90°-150°	3482.6	40.4
90°-180°	4002.0	46.4
0°-180°	8623.3	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1782	1782	1782	1782	1782	
5°	1790	1846	1790	1451	1790	170
15°	1709	1829	1709	1527	1709	481
25°	1505	1706	1505	1493	1505	691
35°	1144	1522	1144	1300	1144	708
45°	738	1254	738	1101	738	591
55°	602	925	602	904	602	553
65°	418	558	418	624	418	399
75°	158	265	158	317	158	167
85°	27	67	27	57	27	36
90°	4	16	4	16	4	5
95°	40	182	40	182	40	44
105°	142	1239	142	1239	142	151
115°	253	1595	253	1595	253	250
125°	352	1270	352	1270	352	313
135°	420	986	420	986	420	325
145°	487	800	487	800	487	305
155°	550	688	550	688	550	253
165°	594	641	594	641	594	168
175°	617	621	617	621	617	59
180°	617	617	617	617	617	

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6
2.5°	1796.8	1796.8	1806.9	1810.3	1810.3	1805.2	1800.2	1805.2	1820.4	1825.5	1823.8
5°	1790.0	1803.6	1822.1	1825.5	1828.9	1827.2	1823.8	1827.2	1844.0	1847.4	1849.1
7.5°	1776.6	1801.9	1825.5	1830.5	1835.5	1830.5	1828.9	1832.2	1849.1	1852.5	1852.5
10°	1759.7	1795.1	1822.1	1825.5	1830.5	1825.5	1825.5	1832.2	1849.1	1852.5	1854.2
12.5°	1736.1	1785.0	1810.3	1813.6	1820.4	1818.7	1817.0	1823.8	1840.6	1844.0	1844.0
15°	1709.1	1766.5	1790.0	1793.4	1805.2	1801.9	1801.9	1808.6	1827.2	1832.2	1830.5
17.5°	1672.1	1742.9	1769.8	1774.9	1783.3	1781.6	1783.3	1790.0	1806.9	1810.3	1811.9
20°	1630.0	1710.8	1742.9	1747.9	1756.3	1756.3	1756.3	1764.8	1781.6	1788.4	1788.4
22.5°	1572.6	1677.2	1710.8	1714.2	1724.3	1724.3	1727.7	1739.5	1754.7	1756.3	1756.3
25°	1505.2	1640.0	1668.7	1678.9	1688.9	1694.0	1699.1	1705.7	1710.8	1709.1	1710.8
27.5°	1434.4	1592.8	1630.0	1636.6	1650.2	1655.3	1661.9	1663.6	1665.3	1670.4	1667.0
30°	1355.2	1527.1	1582.7	1589.5	1611.4	1614.7	1608.0	1611.4	1619.8	1623.2	1626.6
32.5°	1265.8	1429.4	1533.8	1549.0	1569.3	1559.1	1557.4	1562.5	1576.0	1576.0	1579.4
35°	1144.5	1353.5	1488.3	1501.9	1517.0	1505.2	1511.9	1513.6	1522.1	1527.1	1525.5
37.5°	1011.3	1287.7	1441.1	1451.3	1463.0	1447.9	1458.0	1463.0	1469.8	1466.4	1466.4
40°	893.3	1184.9	1385.5	1392.3	1402.4	1390.6	1400.7	1404.1	1407.4	1404.1	1402.4
42.5°	805.7	1072.0	1326.6	1334.9	1328.2	1336.6	1340.0	1346.8	1341.7	1334.9	1334.9
45°	738.2	1041.7	1262.4	1272.6	1262.4	1276.0	1281.1	1281.1	1265.8	1262.4	1260.8
47.5°	716.3	981.0	1198.4	1198.4	1193.4	1210.2	1218.6	1206.9	1191.7	1186.6	1186.6
50°	714.6	913.5	1110.7	1104.1	1127.7	1147.9	1139.4	1127.7	1115.8	1097.3	1097.3
52.5°	648.9	831.0	997.9	1023.1	1060.2	1072.0	1058.5	1046.7	1026.5	1018.1	1011.3
55°	601.8	745.0	895.0	945.6	984.3	999.5	974.3	962.4	932.2	927.1	923.7
57.5°	591.6	620.3	800.7	864.7	911.8	910.2	895.0	873.1	847.8	842.8	841.1
60°	542.7	448.4	699.5	775.4	824.2	819.2	805.7	785.4	761.8	758.5	755.2
62.5°	492.2	325.3	584.9	670.8	739.9	738.2	726.5	696.1	679.3	670.8	664.1
65°	418.0	273.1	416.3	558.0	657.4	660.7	635.4	613.5	595.0	584.9	583.2
67.5°	318.5	222.5	281.5	465.2	578.2	574.8	542.7	532.7	509.1	504.0	493.9
70°	236.0	148.3	195.5	377.6	500.6	492.2	466.9	455.1	433.2	421.4	414.6
72.5°	195.5	119.7	143.2	293.3	421.4	411.2	389.3	375.9	357.4	347.2	340.4
75°	158.5	126.4	109.6	217.4	342.1	335.5	315.2	301.7	286.5	273.1	274.7
77.5°	116.3	118.0	87.6	160.2	271.4	261.3	249.5	232.6	225.9	212.3	212.3
80°	87.6	92.7	65.7	109.6	195.5	195.5	185.5	173.6	161.8	155.1	155.1
82.5°	59.0	59.0	48.9	69.1	133.2	128.1	121.3	118.0	111.3	107.9	107.9
85°	27.0	33.7	30.4	42.1	72.5	75.9	75.9	72.5	70.8	67.4	69.1
87.5°	8.5	15.1	18.5	23.6	37.1	38.7	40.4	40.4	40.4	42.1	42.1
90°	4.2	7.5	10.8	11.6	18.2	27.1	31.5	28.0	21.0	15.7	15.7
92.5°	16.5	44.7	72.9	80.0	112.4	155.7	177.3	155.4	111.6	78.7	75.6
95°	39.7	91.3	142.9	155.8	276.6	437.6	518.2	462.4	350.9	267.2	257.8
97.5°	68.7	114.2	159.8	171.1	372.6	641.2	775.5	740.2	669.7	616.8	598.8
100°	91.1	132.4	173.6	184.0	407.6	705.7	854.7	857.3	862.3	866.2	844.7
102.5°	110.2	148.7	187.1	196.8	423.6	725.9	877.1	922.0	1011.8	1079.2	1060.7
105°	142.5	175.1	207.7	215.8	435.5	728.2	874.6	975.3	1176.7	1327.8	1317.9
107.5°	175.7	206.1	236.5	244.0	437.6	695.7	824.8	965.3	1246.3	1457.0	1459.4
110°	198.0	225.5	252.9	259.8	434.3	667.0	783.4	940.4	1254.6	1490.1	1500.5

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	220.0	246.1	272.2	278.8	434.5	641.9	745.7	906.5	1227.9	1469.0	1484.8
115°	253.1	277.2	301.3	307.4	438.4	613.2	700.6	855.5	1165.1	1397.4	1419.3
117.5°	285.9	307.8	329.7	335.2	446.6	595.2	669.5	809.2	1088.7	1298.4	1322.7
120°	304.9	325.5	346.1	351.3	453.2	589.1	657.1	784.7	1040.1	1231.7	1255.4
122.5°	323.6	344.4	365.2	370.4	462.7	585.9	647.5	762.4	992.4	1164.9	1188.2
125°	352.2	371.1	390.0	394.8	475.6	583.3	637.1	734.8	930.2	1076.7	1098.2
127.5°	375.3	394.4	413.6	418.4	488.4	581.8	628.5	712.3	880.1	1005.9	1024.0
130°	387.7	408.4	429.0	434.2	497.8	582.8	625.2	699.9	849.2	961.1	977.9
132.5°	400.6	421.2	441.8	447.0	505.4	583.3	622.2	689.0	822.7	923.0	938.0
135°	419.7	438.4	457.3	461.9	513.7	582.8	617.3	673.3	785.1	869.1	882.1
137.5°	439.1	457.8	476.3	481.0	526.1	586.3	616.4	663.7	758.4	829.4	839.9
140°	455.3	472.4	489.5	493.8	533.8	586.9	613.5	654.4	736.1	797.5	807.4
142.5°	467.7	483.6	499.4	503.4	540.1	589.0	613.5	649.4	721.2	775.1	783.7
145°	486.7	500.6	514.3	517.8	548.4	589.1	609.5	638.8	697.5	741.5	748.0
147.5°	505.9	519.3	532.7	536.0	560.5	593.1	609.5	632.6	678.8	713.4	718.8
150°	518.2	530.4	542.5	545.6	566.9	595.3	609.5	629.0	667.9	697.2	701.5
152.5°	531.1	540.2	549.5	551.8	571.0	596.6	609.5	626.1	659.4	684.4	687.6
155°	550.2	557.0	563.8	565.5	580.2	599.7	609.5	622.7	649.2	669.0	671.2
157.5°	564.2	570.9	577.5	579.2	589.2	602.7	609.5	619.7	640.3	655.8	657.3
160°	573.8	579.0	584.1	585.3	593.4	604.1	609.5	618.3	635.9	649.2	650.1
162.5°	583.3	587.1	591.0	592.0	597.8	605.6	609.5	616.9	631.8	642.9	643.7
165°	593.6	597.1	600.6	601.5	604.2	607.7	609.5	614.8	625.5	633.5	634.4
167.5°	603.2	604.9	606.6	607.0	609.2	612.0	613.5	617.0	624.0	629.3	629.7
170°	609.5	611.0	612.7	613.1	613.2	613.4	613.5	617.0	624.0	629.3	629.3
172.5°	612.7	613.1	613.4	613.5	613.5	613.5	613.5	616.3	621.8	626.0	625.7
175°	617.3	617.3	617.3	617.3	616.0	614.3	613.5	615.3	618.8	621.4	621.4
177.5°	617.3	617.3	617.3	617.3	616.3	615.0	614.3	615.7	618.5	620.6	620.2
180°	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
0°	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6
2.5°	1827.2	1822.1	1827.2	1823.8	1825.5	1820.4	1805.2	1800.2	1805.2	1810.3	1810.3
5°	1849.1	1845.7	1849.1	1849.1	1847.4	1844.0	1827.2	1823.8	1827.2	1828.9	1825.5
7.5°	1855.7	1850.8	1855.7	1852.5	1852.5	1849.1	1832.2	1828.9	1830.5	1835.5	1830.5
10°	1855.7	1850.8	1855.7	1854.2	1852.5	1849.1	1832.2	1825.5	1825.5	1830.5	1825.5
12.5°	1847.4	1844.0	1847.4	1844.0	1844.0	1840.6	1823.8	1817.0	1818.7	1820.4	1813.6
15°	1833.8	1828.9	1833.8	1830.5	1832.2	1827.2	1808.6	1801.9	1801.9	1805.2	1793.4
17.5°	1813.6	1806.9	1813.6	1811.9	1810.3	1806.9	1790.0	1783.3	1781.6	1783.3	1774.9
20°	1790.0	1785.0	1790.0	1788.4	1788.4	1781.6	1764.8	1756.3	1756.3	1756.3	1747.9
22.5°	1753.0	1747.9	1753.0	1756.3	1756.3	1754.7	1739.5	1727.7	1724.3	1724.3	1714.2
25°	1710.8	1705.7	1710.8	1710.8	1709.1	1710.8	1705.7	1699.1	1694.0	1688.9	1678.9
27.5°	1670.4	1667.0	1670.4	1667.0	1670.4	1665.3	1663.6	1661.9	1655.3	1650.2	1636.6
30°	1630.0	1626.6	1630.0	1626.6	1623.2	1619.8	1611.4	1608.0	1614.7	1611.4	1589.5
32.5°	1579.4	1576.0	1579.4	1579.4	1576.0	1576.0	1562.5	1557.4	1559.1	1569.3	1549.0
35°	1527.1	1522.1	1527.1	1525.5	1527.1	1522.1	1513.6	1511.9	1505.2	1517.0	1501.9
37.5°	1466.4	1461.3	1466.4	1466.4	1466.4	1469.8	1463.0	1458.0	1447.9	1463.0	1451.3
40°	1404.1	1397.3	1404.1	1402.4	1404.1	1407.4	1404.1	1400.7	1390.6	1402.4	1392.3
42.5°	1333.2	1331.6	1333.2	1334.9	1334.9	1341.7	1346.8	1340.0	1336.6	1328.2	1334.9
45°	1257.4	1254.1	1257.4	1260.8	1262.4	1265.8	1281.1	1281.1	1276.0	1262.4	1272.6
47.5°	1176.5	1168.1	1176.5	1186.6	1186.6	1191.7	1206.9	1218.6	1210.2	1193.4	1198.4
50°	1090.5	1092.2	1090.5	1097.3	1097.3	1115.8	1127.7	1139.4	1147.9	1127.7	1104.1
52.5°	1006.3	1004.6	1006.3	1011.3	1018.1	1026.5	1046.7	1058.5	1072.0	1060.2	1023.1
55°	922.0	925.4	922.0	923.7	927.1	932.2	962.4	974.3	999.5	984.3	945.6
57.5°	837.7	832.7	837.7	841.1	842.8	847.8	873.1	895.0	910.2	911.8	864.7
60°	739.9	733.3	739.9	755.2	758.5	761.8	785.4	805.7	819.2	824.2	775.4
62.5°	654.0	642.2	654.0	664.1	670.8	679.3	696.1	726.5	738.2	739.9	670.8
65°	562.9	558.0	562.9	583.2	584.9	595.0	613.5	635.4	660.7	657.4	558.0
67.5°	480.4	480.4	480.4	493.9	504.0	509.1	532.7	542.7	574.8	578.2	465.2
70°	404.6	402.9	404.6	414.6	421.4	433.2	455.1	466.9	492.2	500.6	377.6
72.5°	332.1	330.4	332.1	340.4	347.2	357.4	375.9	389.3	411.2	421.4	293.3
75°	268.0	264.6	268.0	274.7	273.1	286.5	301.7	315.2	335.5	342.1	217.4
77.5°	205.7	205.7	205.7	212.3	212.3	225.9	232.6	249.5	261.3	271.4	160.2
80°	153.4	151.7	153.4	155.1	155.1	161.8	173.6	185.5	195.5	195.5	109.6
82.5°	107.9	104.5	107.9	107.9	107.9	111.3	118.0	121.3	128.1	133.2	69.1
85°	67.4	67.4	67.4	69.1	67.4	70.8	72.5	75.9	75.9	72.5	42.1
87.5°	43.8	42.1	43.8	42.1	42.1	40.4	40.4	40.4	38.7	37.1	23.6
90°	15.7	15.7	15.7	15.7	15.7	21.0	28.0	31.5	27.1	18.2	11.6
92.5°	63.0	50.5	63.0	75.6	78.7	111.6	155.4	177.3	155.7	112.4	80.0
95°	219.8	181.9	219.8	257.8	267.2	350.9	462.4	518.2	437.6	276.6	155.8
97.5°	526.6	454.5	526.6	598.8	616.8	669.7	740.2	775.5	641.2	372.6	171.1
100°	758.8	672.8	758.8	844.7	866.2	862.3	857.3	854.7	705.7	407.6	184.0
102.5°	987.1	913.5	987.1	1060.7	1079.2	1011.8	922.0	877.1	725.9	423.6	196.8
105°	1278.3	1238.7	1278.3	1317.9	1327.8	1176.7	975.3	874.6	728.2	435.5	215.8
107.5°	1469.0	1478.6	1469.0	1459.4	1457.0	1246.3	965.3	824.8	695.7	437.6	244.0
110°	1541.7	1582.9	1541.7	1500.5	1490.1	1254.6	940.4	783.4	667.0	434.3	259.8

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
112.5°	1548.2	1611.5	1548.2	1484.8	1469.0	1227.9	906.5	745.7	641.9	434.5	278.8
115°	1507.1	1595.0	1507.1	1419.3	1397.4	1165.1	855.5	700.6	613.2	438.4	307.4
117.5°	1420.1	1517.5	1420.1	1322.7	1298.4	1088.7	809.2	669.5	595.2	446.6	335.2
120°	1350.0	1444.6	1350.0	1255.4	1231.7	1040.1	784.7	657.1	589.1	453.2	351.3
122.5°	1281.7	1375.0	1281.7	1188.2	1164.9	992.4	762.4	647.5	585.9	462.7	370.4
125°	1184.1	1270.2	1184.1	1098.2	1076.7	930.2	734.8	637.1	583.3	475.6	394.8
127.5°	1096.6	1169.1	1096.6	1024.0	1005.9	880.1	712.3	628.5	581.8	488.4	418.4
130°	1044.9	1111.9	1044.9	977.9	961.1	849.2	699.9	625.2	582.8	497.8	434.2
132.5°	998.0	1058.1	998.0	938.0	923.0	822.7	689.0	622.2	583.3	505.4	447.0
135°	933.8	985.5	933.8	882.1	869.1	785.1	673.3	617.3	582.8	513.7	461.9
137.5°	882.4	924.7	882.4	839.9	829.4	758.4	663.7	616.4	586.3	526.1	481.0
140°	847.0	886.5	847.0	807.4	797.5	736.1	654.4	613.5	586.9	533.8	493.8
142.5°	817.7	851.8	817.7	783.7	775.1	721.2	649.4	613.5	589.0	540.1	503.4
145°	773.8	799.6	773.8	748.0	741.5	697.5	638.8	609.5	589.1	548.4	517.8
147.5°	740.1	761.4	740.1	718.8	713.4	678.8	632.6	609.5	593.1	560.5	536.0
150°	718.8	736.1	718.8	701.5	697.2	667.9	629.0	609.5	595.3	566.9	545.6
152.5°	700.7	713.8	700.7	687.6	684.4	659.4	626.1	609.5	596.6	571.0	551.8
155°	679.9	688.5	679.9	671.2	669.0	649.2	622.7	609.5	599.7	580.2	565.5
157.5°	663.4	669.5	663.4	657.3	655.8	640.3	619.7	609.5	602.7	589.2	579.2
160°	653.6	657.1	653.6	650.1	649.2	635.9	618.3	609.5	604.1	593.4	585.3
162.5°	647.1	650.4	647.1	643.7	642.9	631.8	616.9	609.5	605.6	597.8	592.0
165°	637.8	641.3	637.8	634.4	633.5	625.5	614.8	609.5	607.7	604.2	601.5
167.5°	631.1	632.6	631.1	629.7	629.3	624.0	617.0	613.5	612.0	609.2	607.0
170°	629.3	629.3	629.3	629.3	629.3	624.0	617.0	613.5	613.4	613.2	613.1
172.5°	624.4	623.1	624.4	625.7	626.0	621.8	616.3	613.5	613.5	613.5	613.5
175°	621.4	621.4	621.4	621.4	621.4	618.8	615.3	613.5	614.3	616.0	617.3
177.5°	618.8	617.3	618.8	620.2	620.6	618.5	615.7	614.3	615.0	616.3	617.3
180°	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
0°	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6
2.5°	1806.9	1796.8	1796.8	1780.0	1773.2	1768.1	1759.7	1734.4	1727.7	1721.0	1731.0
5°	1822.1	1803.6	1790.0	1759.7	1734.4	1724.3	1692.3	1631.6	1591.2	1560.8	1544.0
7.5°	1825.5	1801.9	1776.6	1729.4	1668.7	1641.7	1544.0	1432.7	1402.4	1375.4	1358.5
10°	1822.1	1795.1	1759.7	1688.9	1545.7	1498.5	1400.7	1328.2	1309.6	1304.7	1309.6
12.5°	1810.3	1785.0	1736.1	1618.1	1417.5	1385.5	1328.2	1286.0	1282.7	1291.1	1336.6
15°	1790.0	1766.5	1709.1	1523.8	1346.8	1323.2	1282.7	1267.5	1286.0	1345.1	1481.6
17.5°	1769.8	1742.9	1672.1	1431.1	1292.8	1276.0	1247.3	1277.7	1382.1	1461.3	1506.8
20°	1742.9	1710.8	1630.0	1363.6	1254.1	1238.9	1225.4	1361.9	1441.1	1469.8	1495.1
22.5°	1710.8	1677.2	1572.6	1316.4	1213.6	1201.8	1210.2	1409.1	1441.1	1461.3	1483.2
25°	1668.7	1640.0	1505.2	1279.4	1181.6	1168.1	1200.1	1404.1	1422.6	1427.7	1471.5
27.5°	1630.0	1592.8	1434.4	1245.6	1142.8	1137.7	1208.5	1382.1	1395.6	1400.7	1447.9
30°	1582.7	1527.1	1355.2	1210.2	1102.4	1100.7	1210.2	1355.2	1351.8	1365.3	1412.5
32.5°	1533.8	1429.4	1265.8	1166.4	1063.6	1061.9	1198.4	1314.7	1311.3	1329.9	1365.3
35°	1488.3	1353.5	1144.5	1115.8	1014.7	1016.4	1169.8	1267.5	1269.2	1286.0	1307.9
37.5°	1441.1	1287.7	1011.3	1060.2	967.5	967.5	1131.0	1223.7	1220.3	1225.4	1255.8
40°	1385.5	1184.9	893.3	987.7	923.7	918.6	1083.8	1176.5	1164.7	1163.0	1205.2
42.5°	1326.6	1072.0	805.7	891.6	873.1	866.4	1026.5	1119.2	1097.3	1102.4	1156.3
45°	1262.4	1041.7	738.2	753.5	820.9	815.8	964.1	1053.5	1038.3	1051.8	1107.5
47.5°	1198.4	981.0	716.3	625.4	765.2	763.5	895.0	989.4	981.0	994.5	1053.5
50°	1110.7	913.5	714.6	536.0	702.9	709.6	812.4	927.1	927.1	938.8	1001.2
52.5°	997.9	831.0	648.9	485.5	630.4	650.6	739.9	873.1	876.5	888.3	943.9
55°	895.0	745.0	601.8	446.7	544.4	588.2	669.2	817.5	824.2	836.0	886.6
57.5°	800.7	620.3	591.6	401.2	465.2	507.4	606.8	763.5	766.9	777.1	825.9
60°	699.5	448.4	542.7	352.3	396.1	428.1	549.5	699.5	711.3	718.0	760.1
62.5°	584.9	325.3	492.2	318.5	362.3	369.1	502.3	638.8	654.0	659.1	684.4
65°	416.3	273.1	418.0	289.9	327.0	328.7	451.7	576.5	589.9	598.4	616.9
67.5°	281.5	222.5	318.5	262.9	300.0	301.7	402.9	504.0	522.5	529.3	541.0
70°	195.5	148.3	236.0	234.3	269.7	273.1	350.6	438.2	455.1	460.2	466.9
72.5°	143.2	119.7	195.5	210.7	237.6	241.0	296.6	364.0	381.0	386.0	389.3
75°	109.6	126.4	158.5	183.8	202.3	204.0	242.7	296.6	308.5	311.8	313.5
77.5°	87.6	118.0	116.3	148.3	165.1	161.8	190.4	229.3	239.3	239.3	239.3
80°	65.7	92.7	87.6	106.2	121.3	118.0	136.6	163.5	166.8	170.2	168.5
82.5°	48.9	59.0	59.0	67.4	80.9	77.5	91.0	106.2	106.2	106.2	109.6
85°	30.4	33.7	27.0	35.4	45.5	43.8	50.6	57.3	59.0	59.0	55.6
87.5°	18.5	15.1	8.5	13.4	20.2	20.2	23.6	25.3	23.6	23.6	23.6
90°	10.8	7.5	4.2	7.5	10.8	11.6	18.2	27.1	31.5	28.0	21.0
92.5°	72.9	44.7	16.5	44.7	72.9	80.0	112.4	155.7	177.3	155.4	111.6
95°	142.9	91.3	39.7	91.3	142.9	155.8	276.6	437.6	518.2	462.4	350.9
97.5°	159.8	114.2	68.7	114.2	159.8	171.1	372.6	641.2	775.5	740.2	669.7
100°	173.6	132.4	91.1	132.4	173.6	184.0	407.6	705.7	854.7	857.3	862.3
102.5°	187.1	148.7	110.2	148.7	187.1	196.8	423.6	725.9	877.1	922.0	1011.8
105°	207.7	175.1	142.5	175.1	207.7	215.8	435.5	728.2	874.6	975.3	1176.7
107.5°	236.5	206.1	175.7	206.1	236.5	244.0	437.6	695.7	824.8	965.3	1246.3
110°	252.9	225.5	198.0	225.5	252.9	259.8	434.3	667.0	783.4	940.4	1254.6

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
112.5°	272.2	246.1	220.0	246.1	272.2	278.8	434.5	641.9	745.7	906.5	1227.9
115°	301.3	277.2	253.1	277.2	301.3	307.4	438.4	613.2	700.6	855.5	1165.1
117.5°	329.7	307.8	285.9	307.8	329.7	335.2	446.6	595.2	669.5	809.2	1088.7
120°	346.1	325.5	304.9	325.5	346.1	351.3	453.2	589.1	657.1	784.7	1040.1
122.5°	365.2	344.4	323.6	344.4	365.2	370.4	462.7	585.9	647.5	762.4	992.4
125°	390.0	371.1	352.2	371.1	390.0	394.8	475.6	583.3	637.1	734.8	930.2
127.5°	413.6	394.4	375.3	394.4	413.6	418.4	488.4	581.8	628.5	712.3	880.1
130°	429.0	408.4	387.7	408.4	429.0	434.2	497.8	582.8	625.2	699.9	849.2
132.5°	441.8	421.2	400.6	421.2	441.8	447.0	505.4	583.3	622.2	689.0	822.7
135°	457.3	438.4	419.7	438.4	457.3	461.9	513.7	582.8	617.3	673.3	785.1
137.5°	476.3	457.8	439.1	457.8	476.3	481.0	526.1	586.3	616.4	663.7	758.4
140°	489.5	472.4	455.3	472.4	489.5	493.8	533.8	586.9	613.5	654.4	736.1
142.5°	499.4	483.6	467.7	483.6	499.4	503.4	540.1	589.0	613.5	649.4	721.2
145°	514.3	500.6	486.7	500.6	514.3	517.8	548.4	589.1	609.5	638.8	697.5
147.5°	532.7	519.3	505.9	519.3	532.7	536.0	560.5	593.1	609.5	632.6	678.8
150°	542.5	530.4	518.2	530.4	542.5	545.6	566.9	595.3	609.5	629.0	667.9
152.5°	549.5	540.2	531.1	540.2	549.5	551.8	571.0	596.6	609.5	626.1	659.4
155°	563.8	557.0	550.2	557.0	563.8	565.5	580.2	599.7	609.5	622.7	649.2
157.5°	577.5	570.9	564.2	570.9	577.5	579.2	589.2	602.7	609.5	619.7	640.3
160°	584.1	579.0	573.8	579.0	584.1	585.3	593.4	604.1	609.5	618.3	635.9
162.5°	591.0	587.1	583.3	587.1	591.0	592.0	597.8	605.6	609.5	616.9	631.8
165°	600.6	597.1	593.6	597.1	600.6	601.5	604.2	607.7	609.5	614.8	625.5
167.5°	606.6	604.9	603.2	604.9	606.6	607.0	609.2	612.0	613.5	617.0	624.0
170°	612.7	611.0	609.5	611.0	612.7	613.1	613.2	613.4	613.5	617.0	624.0
172.5°	613.4	613.1	612.7	613.1	613.4	613.5	613.5	613.5	613.5	616.3	621.8
175°	617.3	617.3	617.3	617.3	617.3	617.3	616.0	614.3	613.5	615.3	618.8
177.5°	617.3	617.3	617.3	617.3	617.3	617.3	616.3	615.0	614.3	615.7	618.5
180°	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
0°	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6	1781.6
2.5°	1719.3	1714.2	1721.0	1702.4	1721.0	1714.2	1719.3	1731.0	1721.0	1727.7	1734.4
5°	1508.5	1500.2	1473.2	1451.3	1473.2	1500.2	1508.5	1544.0	1560.8	1591.2	1631.6
7.5°	1348.5	1341.7	1334.9	1321.5	1334.9	1341.7	1348.5	1358.5	1375.4	1402.4	1432.7
10°	1313.0	1314.7	1324.9	1323.2	1324.9	1314.7	1313.0	1309.6	1304.7	1309.6	1328.2
12.5°	1404.1	1419.2	1474.9	1471.5	1474.9	1419.2	1404.1	1336.6	1291.1	1282.7	1286.0
15°	1508.5	1513.6	1525.5	1527.1	1525.5	1513.6	1508.5	1481.6	1345.1	1286.0	1267.5
17.5°	1518.7	1520.4	1528.8	1528.8	1528.8	1520.4	1518.7	1506.8	1461.3	1382.1	1277.7
20°	1510.2	1513.6	1530.5	1533.8	1530.5	1513.6	1510.2	1495.1	1469.8	1441.1	1361.9
22.5°	1506.8	1513.6	1527.1	1525.5	1527.1	1513.6	1506.8	1483.2	1461.3	1441.1	1409.1
25°	1490.0	1490.0	1491.7	1493.4	1491.7	1490.0	1490.0	1471.5	1427.7	1422.6	1404.1
27.5°	1454.7	1458.0	1468.1	1466.4	1468.1	1458.0	1454.7	1447.9	1400.7	1395.6	1382.1
30°	1422.6	1419.2	1410.8	1404.1	1410.8	1419.2	1422.6	1412.5	1365.3	1351.8	1355.2
32.5°	1368.7	1360.2	1351.8	1346.8	1351.8	1360.2	1368.7	1365.3	1329.9	1311.3	1314.7
35°	1304.7	1306.3	1304.7	1299.6	1304.7	1306.3	1304.7	1307.9	1286.0	1269.2	1267.5
37.5°	1259.1	1262.4	1260.8	1254.1	1260.8	1262.4	1259.1	1255.8	1225.4	1220.3	1223.7
40°	1211.9	1213.6	1211.9	1206.9	1211.9	1213.6	1211.9	1205.2	1163.0	1164.7	1176.5
42.5°	1166.4	1164.7	1159.6	1156.3	1159.6	1164.7	1166.4	1156.3	1102.4	1097.3	1119.2
45°	1114.1	1115.8	1105.8	1100.7	1105.8	1115.8	1114.1	1107.5	1051.8	1038.3	1053.5
47.5°	1061.9	1061.9	1053.5	1048.4	1053.5	1061.9	1061.9	1053.5	994.5	981.0	989.4
50°	1006.3	1004.6	992.8	991.1	992.8	1004.6	1006.3	1001.2	938.8	927.1	927.1
52.5°	942.2	942.2	943.9	947.3	943.9	942.2	942.2	943.9	888.3	876.5	873.1
55°	886.6	888.3	900.1	903.5	900.1	888.3	886.6	886.6	836.0	824.2	817.5
57.5°	829.3	829.3	837.7	837.7	837.7	829.3	829.3	825.9	777.1	766.9	763.5
60°	763.5	766.9	773.7	772.0	773.7	766.9	763.5	760.1	718.0	711.3	699.5
62.5°	694.4	697.8	699.5	696.1	699.5	697.8	694.4	684.4	659.1	654.0	638.8
65°	622.0	625.4	627.0	623.7	627.0	625.4	622.0	616.9	598.4	589.9	576.5
67.5°	547.8	546.1	544.4	551.2	544.4	546.1	547.8	541.0	529.3	522.5	504.0
70°	471.9	471.9	470.3	473.6	470.3	471.9	471.9	466.9	460.2	455.1	438.2
72.5°	391.0	389.3	396.1	391.0	396.1	389.3	391.0	389.3	386.0	381.0	364.0
75°	311.8	315.2	311.8	316.9	311.8	315.2	311.8	313.5	311.8	308.5	296.6
77.5°	237.6	241.0	237.6	237.6	237.6	241.0	237.6	239.3	239.3	239.3	229.3
80°	168.5	166.8	166.8	165.1	166.8	166.8	168.5	168.5	170.2	166.8	163.5
82.5°	107.9	106.2	106.2	109.6	106.2	106.2	107.9	109.6	106.2	106.2	106.2
85°	59.0	60.7	57.3	57.3	57.3	60.7	59.0	55.6	59.0	59.0	57.3
87.5°	21.9	20.2	20.2	20.2	20.2	20.2	21.9	23.6	23.6	23.6	25.3
90°	15.7	15.7	15.7	15.7	15.7	15.7	15.7	21.0	28.0	31.5	27.1
92.5°	78.7	75.6	63.0	50.5	63.0	75.6	78.7	111.6	155.4	177.3	155.7
95°	267.2	257.8	219.8	181.9	219.8	257.8	267.2	350.9	462.4	518.2	437.6
97.5°	616.8	598.8	526.6	454.5	526.6	598.8	616.8	669.7	740.2	775.5	641.2
100°	866.2	844.7	758.8	672.8	758.8	844.7	866.2	862.3	857.3	854.7	705.7
102.5°	1079.2	1060.7	987.1	913.5	987.1	1060.7	1079.2	1011.8	922.0	877.1	725.9
105°	1327.8	1317.9	1278.3	1238.7	1278.3	1317.9	1327.8	1176.7	975.3	874.6	728.2
107.5°	1457.0	1459.4	1469.0	1478.6	1469.0	1459.4	1457.0	1246.3	965.3	824.8	695.7
110°	1490.1	1500.5	1541.7	1582.9	1541.7	1500.5	1490.1	1254.6	940.4	783.4	667.0

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
112.5°	1469.0	1484.8	1548.2	1611.5	1548.2	1484.8	1469.0	1227.9	906.5	745.7	641.9
115°	1397.4	1419.3	1507.1	1595.0	1507.1	1419.3	1397.4	1165.1	855.5	700.6	613.2
117.5°	1298.4	1322.7	1420.1	1517.5	1420.1	1322.7	1298.4	1088.7	809.2	669.5	595.2
120°	1231.7	1255.4	1350.0	1444.6	1350.0	1255.4	1231.7	1040.1	784.7	657.1	589.1
122.5°	1164.9	1188.2	1281.7	1375.0	1281.7	1188.2	1164.9	992.4	762.4	647.5	585.9
125°	1076.7	1098.2	1184.1	1270.2	1184.1	1098.2	1076.7	930.2	734.8	637.1	583.3
127.5°	1005.9	1024.0	1096.6	1169.1	1096.6	1024.0	1005.9	880.1	712.3	628.5	581.8
130°	961.1	977.9	1044.9	1111.9	1044.9	977.9	961.1	849.2	699.9	625.2	582.8
132.5°	923.0	938.0	998.0	1058.1	998.0	938.0	923.0	822.7	689.0	622.2	583.3
135°	869.1	882.1	933.8	985.5	933.8	882.1	869.1	785.1	673.3	617.3	582.8
137.5°	829.4	839.9	882.4	924.7	882.4	839.9	829.4	758.4	663.7	616.4	586.3
140°	797.5	807.4	847.0	886.5	847.0	807.4	797.5	736.1	654.4	613.5	586.9
142.5°	775.1	783.7	817.7	851.8	817.7	783.7	775.1	721.2	649.4	613.5	589.0
145°	741.5	748.0	773.8	799.6	773.8	748.0	741.5	697.5	638.8	609.5	589.1
147.5°	713.4	718.8	740.1	761.4	740.1	718.8	713.4	678.8	632.6	609.5	593.1
150°	697.2	701.5	718.8	736.1	718.8	701.5	697.2	667.9	629.0	609.5	595.3
152.5°	684.4	687.6	700.7	713.8	700.7	687.6	684.4	659.4	626.1	609.5	596.6
155°	669.0	671.2	679.9	688.5	679.9	671.2	669.0	649.2	622.7	609.5	599.7
157.5°	655.8	657.3	663.4	669.5	663.4	657.3	655.8	640.3	619.7	609.5	602.7
160°	649.2	650.1	653.6	657.1	653.6	650.1	649.2	635.9	618.3	609.5	604.1
162.5°	642.9	643.7	647.1	650.4	647.1	643.7	642.9	631.8	616.9	609.5	605.6
165°	633.5	634.4	637.8	641.3	637.8	634.4	633.5	625.5	614.8	609.5	607.7
167.5°	629.3	629.7	631.1	632.6	631.1	629.7	629.3	624.0	617.0	613.5	612.0
170°	629.3	629.3	629.3	629.3	629.3	629.3	629.3	624.0	617.0	613.5	613.4
172.5°	626.0	625.7	624.4	623.1	624.4	625.7	626.0	621.8	616.3	613.5	613.5
175°	621.4	621.4	621.4	621.4	621.4	621.4	621.4	618.8	615.3	613.5	614.3
177.5°	620.6	620.2	618.8	617.3	618.8	620.2	620.6	618.5	615.7	614.3	615.0
180°	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3	617.3

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
0°	1781.6	1781.6	1781.6	1781.6	1781.6
2.5°	1759.7	1768.1	1773.2	1780.0	1796.8
5°	1692.3	1724.3	1734.4	1759.7	1790.0
7.5°	1544.0	1641.7	1668.7	1729.4	1776.6
10°	1400.7	1498.5	1545.7	1688.9	1759.7
12.5°	1328.2	1385.5	1417.5	1618.1	1736.1
15°	1282.7	1323.2	1346.8	1523.8	1709.1
17.5°	1247.3	1276.0	1292.8	1431.1	1672.1
20°	1225.4	1238.9	1254.1	1363.6	1630.0
22.5°	1210.2	1201.8	1213.6	1316.4	1572.6
25°	1200.1	1168.1	1181.6	1279.4	1505.2
27.5°	1208.5	1137.7	1142.8	1245.6	1434.4
30°	1210.2	1100.7	1102.4	1210.2	1355.2
32.5°	1198.4	1061.9	1063.6	1166.4	1265.8
35°	1169.8	1016.4	1014.7	1115.8	1144.5
37.5°	1131.0	967.5	967.5	1060.2	1011.3
40°	1083.8	918.6	923.7	987.7	893.3
42.5°	1026.5	866.4	873.1	891.6	805.7
45°	964.1	815.8	820.9	753.5	738.2
47.5°	895.0	763.5	765.2	625.4	716.3
50°	812.4	709.6	702.9	536.0	714.6
52.5°	739.9	650.6	630.4	485.5	648.9
55°	669.2	588.2	544.4	446.7	601.8
57.5°	606.8	507.4	465.2	401.2	591.6
60°	549.5	428.1	396.1	352.3	542.7
62.5°	502.3	369.1	362.3	318.5	492.2
65°	451.7	328.7	327.0	289.9	418.0
67.5°	402.9	301.7	300.0	262.9	318.5
70°	350.6	273.1	269.7	234.3	236.0
72.5°	296.6	241.0	237.6	210.7	195.5
75°	242.7	204.0	202.3	183.8	158.5
77.5°	190.4	161.8	165.1	148.3	116.3
80°	136.6	118.0	121.3	106.2	87.6
82.5°	91.0	77.5	80.9	67.4	59.0
85°	50.6	43.8	45.5	35.4	27.0
87.5°	23.6	20.2	20.2	13.4	8.5
90°	18.2	11.6	10.8	7.5	4.2
92.5°	112.4	80.0	72.9	44.7	16.5
95°	276.6	155.8	142.9	91.3	39.7
97.5°	372.6	171.1	159.8	114.2	68.7
100°	407.6	184.0	173.6	132.4	91.1
102.5°	423.6	196.8	187.1	148.7	110.2
105°	435.5	215.8	207.7	175.1	142.5
107.5°	437.6	244.0	236.5	206.1	175.7
110°	434.3	259.8	252.9	225.5	198.0

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
112.5°	434.5	278.8	272.2	246.1	220.0
115°	438.4	307.4	301.3	277.2	253.1
117.5°	446.6	335.2	329.7	307.8	285.9
120°	453.2	351.3	346.1	325.5	304.9
122.5°	462.7	370.4	365.2	344.4	323.6
125°	475.6	394.8	390.0	371.1	352.2
127.5°	488.4	418.4	413.6	394.4	375.3
130°	497.8	434.2	429.0	408.4	387.7
132.5°	505.4	447.0	441.8	421.2	400.6
135°	513.7	461.9	457.3	438.4	419.7
137.5°	526.1	481.0	476.3	457.8	439.1
140°	533.8	493.8	489.5	472.4	455.3
142.5°	540.1	503.4	499.4	483.6	467.7
145°	548.4	517.8	514.3	500.6	486.7
147.5°	560.5	536.0	532.7	519.3	505.9
150°	566.9	545.6	542.5	530.4	518.2
152.5°	571.0	551.8	549.5	540.2	531.1
155°	580.2	565.5	563.8	557.0	550.2
157.5°	589.2	579.2	577.5	570.9	564.2
160°	593.4	585.3	584.1	579.0	573.8
162.5°	597.8	592.0	591.0	587.1	583.3
165°	604.2	601.5	600.6	597.1	593.6
167.5°	609.2	607.0	606.6	604.9	603.2
170°	613.2	613.1	612.7	611.0	609.5
172.5°	613.5	613.5	613.4	613.1	612.7
175°	616.0	617.3	617.3	617.3	617.3
177.5°	616.3	617.3	617.3	617.3	617.3
180°	617.3	617.3	617.3	617.3	617.3

TEST NUMBER: P935382

CATALOG NUMBER: SQ4-FA-100U-125D-B2750-1D-UNV-W2A-W-4-2700K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.87	15.76	15.79	16.70	17.92	17.66	18.56	18.59	19.50	20.72
	3H	15.35	16.15	16.28	17.10	18.34	19.00	19.80	19.94	20.76	22.00
	4H	15.54	16.30	16.49	17.26	18.51	19.44	20.20	20.39	21.16	22.41
	6H	15.66	16.36	16.62	17.32	18.59	19.72	20.42	20.68	21.38	22.65
	8H	15.66	16.33	16.63	17.31	18.57	19.79	20.46	20.76	21.44	22.70
	12H	15.63	16.27	16.61	17.24	18.53	19.83	20.46	20.80	21.43	22.72
4H	2H	15.90	16.65	16.85	17.61	18.86	18.08	18.84	19.04	19.79	21.05
	3H	16.93	17.56	17.89	18.54	19.81	19.58	20.21	20.55	21.20	22.46
	4H	17.20	17.78	18.18	18.76	20.05	20.10	20.68	21.08	21.66	22.95
	6H	17.33	17.83	18.32	18.83	20.12	20.46	20.96	21.45	21.96	23.25
	8H	17.34	17.80	18.33	18.80	20.10	20.56	21.03	21.55	22.03	23.33
	12H	17.31	17.72	18.32	18.74	20.05	20.62	21.04	21.63	22.05	23.36
8H	4H	17.65	18.12	18.65	19.12	20.42	20.23	20.69	21.22	21.69	22.99
	6H	17.92	18.30	18.93	19.34	20.64	20.66	21.04	21.68	22.08	23.38
	8H	17.96	18.30	18.98	19.33	20.65	20.81	21.14	21.83	22.17	23.49
	12H	17.95	18.24	18.97	19.26	20.63	20.90	21.20	21.93	22.22	23.58
12H	4H	17.66	18.08	18.67	19.09	20.40	20.20	20.61	21.21	21.63	22.94
	6H	17.98	18.32	19.00	19.34	20.66	20.66	21.00	21.68	22.02	23.34
	8H	18.04	18.34	19.07	19.36	20.73	20.81	21.11	21.84	22.13	23.50

END OF REPORT