

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P936282

Luminaire Tested: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P936282
REPORT IS A COMBINATION OF REPORTS P933437 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Batwing Frosted Continuous Roll L
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2571.6 lumens
Efficiency: N/A
Efficacy: 116.9 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 2.69 / 2.33
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 22
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

Luminous Intensity Polar Plot



TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	110	110	110	110	103	103	103	103	90	90	90	78	78	78	68	68	68
1	100	95	91	87	93	89	86	82	78	75	73	68	66	64	59	57	56
2	90	82	76	70	84	77	71	66	68	63	59	59	55	52	51	48	46
3	82	72	64	57	76	67	60	55	59	53	49	51	47	43	44	41	38
4	75	63	54	48	69	59	52	46	52	46	41	45	40	37	39	35	32
5	68	56	47	41	64	52	45	39	46	40	35	40	35	31	35	31	28
6	63	50	41	35	58	47	39	33	41	35	30	36	31	27	31	27	24
7	58	45	36	30	54	42	34	29	37	31	26	33	27	23	28	24	21
8	53	40	32	26	50	38	31	25	34	27	23	30	24	21	26	22	18
9	50	37	29	23	46	35	27	22	31	25	20	27	22	18	24	19	16
10	46	34	26	21	43	32	25	20	28	22	18	25	20	16	22	18	15

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1928	1928	1928
5°	1882	2226	2591
10°	1705	3244	4297
15°	1448	4235	5188
20°	1177	4904	5288
25°	981	5128	5180
30°	826	5156	5171
35°	728	5067	5304
40°	635	4952	5442
45°	572	4865	5464
50°	524	4788	5374
55°	501	4675	5135
60°	511	4464	4759
65°	529	4144	4242
70°	559	3607	3585
75°	613	2934	2797
80°	655	2027	1886
85°	555	1070	963

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 45°

Luminance: 5464 cd/sqm

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	26.9	1.0
10°-20°	119.1	4.6
20°-30°	208.4	8.1
30°-40°	268.2	10.4
40°-50°	299.6	11.7
50°-60°	287.0	11.2
60°-70°	227.4	8.8
70°-80°	133.7	5.2
80°-90°	37.7	1.5
90°-100°	72.5	2.8
100°-110°	190.5	7.4
110°-120°	197.5	7.7
120°-130°	158.4	6.2
130°-140°	124.3	4.8
140°-150°	95.4	3.7
150°-160°	68.7	2.7
160°-170°	42.0	1.6
170°-180°	14.2	0.6
0°-30°	354.4	13.8
0°-40°	622.6	24.2
0°-60°	1209.2	47.0
0°-90°	1608.1	62.5
90°-120°	460.5	17.9
90°-150°	838.6	32.6
90°-180°	964.0	37.5
0°-180°	2571.6	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	208	208	208	208	208	
5°	202	217	244	277	287	19
15°	152	280	472	572	590	42
25°	97	317	562	587	587	45
35°	65	303	529	559	581	41
45°	45	242	468	536	560	35
55°	32	154	397	461	474	29
65°	25	82	295	331	336	25
75°	19	50	162	178	178	20
85°	7	15	40	44	45	7
90°	1	3	8	4	4	1
95°	10	38	125	64	44	11
105°	34	52	211	320	298	36
115°	61	74	169	336	384	60
125°	85	95	153	259	306	75
135°	101	111	149	209	237	78
145°	117	125	147	179	192	73
155°	132	136	147	161	166	61
165°	143	145	147	152	154	40
175°	149	149	148	150	150	14
180°	149	149	149	149	149	

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8	207.8
2.5°	207.8	207.8	209.2	209.8	211.2	211.8	213.1	214.4	218.5	219.1	220.5
5°	202.5	205.2	213.8	217.1	226.5	239.2	244.5	253.3	271.3	276.6	280.0
7.5°	194.4	200.5	221.8	227.2	250.6	284.0	298.0	316.7	345.4	359.5	370.8
10°	181.8	194.4	232.6	245.2	283.3	334.1	360.2	386.2	429.7	449.0	456.4
12.5°	167.7	188.4	243.9	261.3	316.0	390.2	421.6	450.4	499.8	525.9	529.9
15°	151.7	179.8	254.6	280.0	350.8	436.9	471.7	507.2	553.3	571.9	576.6
17.5°	137.6	173.1	264.6	291.3	377.5	479.1	514.5	543.9	581.3	594.0	597.3
20°	120.3	162.3	271.3	306.1	405.6	509.9	543.9	566.6	592.0	600.0	601.4
22.5°	107.6	151.0	275.3	311.3	424.3	528.5	557.3	575.3	592.6	595.3	596.0
25°	96.9	138.3	274.6	317.4	440.3	539.8	561.9	575.3	585.3	586.6	586.6
27.5°	86.9	124.3	271.9	318.7	452.4	542.5	560.0	569.3	574.0	576.6	576.6
30°	78.2	111.0	265.2	316.0	457.7	539.8	553.9	558.6	563.2	567.3	569.3
32.5°	71.5	98.2	255.3	310.7	458.4	533.2	543.2	545.9	552.6	561.9	565.2
35°	65.4	85.6	243.9	303.4	454.4	522.5	529.2	531.9	545.2	559.3	563.9
37.5°	59.5	76.2	229.2	290.6	448.3	509.9	514.5	519.2	539.8	556.6	561.9
40°	53.5	68.1	211.8	276.6	439.0	494.4	498.5	505.8	533.2	552.6	558.0
42.5°	48.8	61.5	193.1	261.9	427.0	477.1	483.1	493.8	525.2	545.9	551.9
45°	44.7	54.8	173.1	241.8	411.5	459.1	467.7	482.5	515.8	535.8	541.2
47.5°	40.7	50.1	152.4	221.2	394.9	441.0	452.4	469.0	503.2	522.5	527.2
50°	37.4	45.4	131.7	199.1	376.9	421.6	435.0	452.4	487.1	505.2	511.1
52.5°	34.8	41.4	112.2	177.1	356.2	401.6	416.9	435.0	467.7	485.1	489.1
55°	32.1	38.0	95.5	153.7	334.8	380.2	396.9	414.2	446.3	461.0	463.7
57.5°	30.8	35.5	81.5	131.7	312.0	356.2	374.8	390.8	420.9	432.3	435.0
60°	28.7	33.4	70.8	112.9	287.3	333.5	349.5	365.5	390.8	400.2	402.3
62.5°	26.7	32.1	62.8	94.9	261.9	306.7	322.7	337.4	358.8	365.5	368.1
65°	25.4	30.8	56.8	81.5	235.9	278.6	294.6	307.4	324.7	331.4	332.8
67.5°	24.1	29.4	52.1	70.1	209.8	250.6	262.5	274.6	287.9	294.6	295.3
70°	22.0	28.1	48.1	62.2	183.1	218.5	228.5	241.2	251.9	255.3	257.3
72.5°	20.7	26.1	45.4	56.2	155.7	187.7	197.1	204.5	213.8	217.1	217.1
75°	18.7	23.4	42.7	50.1	127.6	153.7	161.7	169.0	176.4	177.7	175.7
77.5°	16.7	20.7	36.8	42.1	99.6	121.6	128.3	132.3	138.3	139.6	140.3
80°	14.0	18.0	28.7	32.8	72.2	89.5	94.2	97.5	102.9	102.9	104.3
82.5°	10.7	14.0	20.7	23.4	48.8	61.5	65.4	67.5	70.8	70.8	70.8
85°	6.7	8.7	13.3	15.3	29.4	37.4	40.1	40.7	43.4	44.1	44.1
87.5°	3.4	4.7	8.7	9.4	15.3	19.4	19.4	20.7	20.7	20.0	19.4
90°	1.0	1.8	2.6	2.8	4.4	6.5	7.6	6.8	5.1	3.8	3.8
92.5°	4.0	10.8	17.5	19.2	27.1	37.5	42.7	37.4	26.9	18.9	18.1
95°	9.6	22.0	34.5	37.5	66.6	105.4	124.8	111.4	84.5	64.3	62.1
97.5°	16.5	27.5	38.4	41.2	89.7	154.4	186.8	178.3	161.3	148.5	144.1
100°	21.9	31.9	41.8	44.3	98.1	169.9	205.8	206.4	207.7	208.6	203.4
102.5°	26.5	35.8	45.1	47.4	102.0	174.8	211.2	222.0	243.6	259.9	255.4
105°	34.4	42.2	50.0	52.0	104.9	175.3	210.6	234.9	283.4	319.7	317.3
107.5°	42.3	49.6	57.0	58.8	105.4	167.5	198.6	232.5	300.1	350.9	351.5
110°	47.7	54.3	60.9	62.5	104.6	160.7	188.6	226.5	302.1	358.9	361.3

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	53.0	59.3	65.5	67.1	104.6	154.6	179.6	218.3	295.7	353.8	357.6
115°	61.0	66.7	72.5	74.0	105.6	147.7	168.7	206.0	280.6	336.4	341.7
117.5°	68.8	74.1	79.4	80.7	107.6	143.3	161.3	194.9	262.1	312.6	318.5
120°	73.4	78.4	83.4	84.6	109.1	141.8	158.2	188.9	250.5	296.6	302.3
122.5°	77.9	82.9	87.8	89.1	111.4	141.0	155.9	183.6	238.9	280.5	286.1
125°	84.8	89.3	93.9	95.1	114.5	140.4	153.4	176.9	224.0	259.3	264.4
127.5°	90.3	95.0	99.6	100.8	117.6	140.0	151.3	171.5	211.9	242.2	246.6
130°	93.3	98.3	103.3	104.6	119.9	140.3	150.5	168.5	204.5	231.5	235.5
132.5°	96.5	101.5	106.5	107.7	121.7	140.4	149.8	165.9	198.1	222.3	225.9
135°	101.1	105.6	110.2	111.3	123.7	140.3	148.6	162.0	189.0	209.3	212.3
137.5°	105.8	110.3	114.7	115.8	126.7	141.1	148.4	159.8	182.6	199.7	202.3
140°	109.7	113.7	117.9	118.9	128.5	141.3	147.7	157.6	177.3	192.0	194.4
142.5°	112.6	116.4	120.2	121.2	130.1	141.8	147.7	156.4	173.7	186.7	188.7
145°	117.2	120.5	123.9	124.7	132.1	141.8	146.7	153.8	167.9	178.6	180.2
147.5°	121.8	125.0	128.3	129.1	135.0	142.8	146.7	152.3	163.4	171.8	173.1
150°	124.8	127.7	130.7	131.4	136.5	143.3	146.7	151.4	160.9	167.9	168.9
152.5°	127.9	130.1	132.3	132.9	137.4	143.6	146.7	150.7	158.8	164.8	165.6
155°	132.5	134.1	135.8	136.2	139.6	144.3	146.7	149.9	156.4	161.2	161.7
157.5°	135.9	137.4	139.0	139.4	141.8	145.1	146.7	149.2	154.2	157.9	158.3
160°	138.1	139.3	140.6	140.9	142.8	145.4	146.7	148.8	153.1	156.3	156.5
162.5°	140.4	141.3	142.3	142.5	143.9	145.8	146.7	148.5	152.1	154.8	155.0
165°	142.9	143.7	144.6	144.8	145.4	146.3	146.7	148.0	150.6	152.5	152.7
167.5°	145.2	145.6	146.0	146.1	146.6	147.3	147.7	148.5	150.2	151.5	151.6
170°	146.7	147.1	147.5	147.6	147.6	147.7	147.7	148.5	150.2	151.5	151.5
172.5°	147.5	147.6	147.7	147.7	147.7	147.7	147.7	148.4	149.7	150.7	150.6
175°	148.6	148.6	148.6	148.6	148.3	147.9	147.7	148.1	149.0	149.6	149.6
177.5°	148.6	148.6	148.6	148.6	148.4	148.1	147.9	148.2	148.9	149.4	149.3
180°	148.6	148.6	148.6	148.6	148.6	148.6	148.6	148.6	148.6	148.6	148.6

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°
0°	207.8	207.8
2.5°	221.8	220.5
5°	285.4	286.6
7.5°	384.2	383.6
10°	477.8	483.8
12.5°	545.9	547.2
15°	587.3	590.0
17.5°	603.4	604.1
20°	604.1	602.7
22.5°	596.7	595.3
25°	588.0	587.3
27.5°	580.0	580.7
30°	576.6	578.7
32.5°	576.6	580.0
35°	578.0	581.3
37.5°	577.3	581.3
40°	574.6	579.3
42.5°	567.3	570.6
45°	555.9	560.0
47.5°	541.2	543.9
50°	522.5	525.2
52.5°	499.1	499.8
55°	471.1	473.7
57.5°	441.0	441.6
60°	407.6	409.6
62.5°	372.2	372.2
65°	334.8	336.1
67.5°	296.0	299.3
70°	256.6	257.3
72.5°	217.8	217.8
75°	177.7	178.4
77.5°	139.6	139.6
80°	103.6	104.3
82.5°	71.5	72.8
85°	44.7	44.7
87.5°	20.7	18.7
90°	3.8	3.8
92.5°	15.1	12.2
95°	53.0	43.8
97.5°	126.8	109.5
100°	182.8	162.0
102.5°	237.6	219.9
105°	307.9	298.3
107.5°	353.8	356.1
110°	371.2	381.2



TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

CANDELA DISTRIBUTION (continued):

	80°	90°
112.5°	372.8	388.0
115°	362.9	384.1
117.5°	341.9	365.4
120°	325.1	347.8
122.5°	308.6	331.1
125°	285.2	305.9
127.5°	264.0	281.5
130°	251.6	267.7
132.5°	240.3	254.8
135°	224.9	237.3
137.5°	212.4	222.7
140°	203.9	213.4
142.5°	196.9	205.1
145°	186.4	192.5
147.5°	178.2	183.4
150°	173.1	177.3
152.5°	168.7	171.9
155°	163.7	165.8
157.5°	159.8	161.3
160°	157.4	158.2
162.5°	155.8	156.6
165°	153.6	154.4
167.5°	151.9	152.3
170°	151.5	151.5
172.5°	150.3	150.0
175°	149.6	149.6
177.5°	149.0	148.6
180°	148.6	148.6

TEST NUMBER: P936282

CATALOG NUMBER: SQ4-FB-025U-050D-B2750-1D-UNV-W2A-W-4-2700K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	4.34	5.38	5.17	6.24	7.31	17.48	18.51	18.31	19.38	20.45
	3H	5.06	5.99	5.90	6.86	7.97	19.31	20.25	20.16	21.12	22.22
	4H	5.36	6.25	6.23	7.13	8.24	19.96	20.84	20.82	21.72	22.83
	6H	5.62	6.44	6.50	7.33	8.45	20.38	21.20	21.26	22.09	23.21
	8H	5.70	6.48	6.58	7.38	8.51	20.50	21.28	21.39	22.19	23.31
	12H	5.72	6.46	6.61	7.36	8.52	20.57	21.31	21.46	22.21	23.37
4H	2H	11.55	12.43	12.41	13.31	14.42	17.77	18.66	18.64	19.54	20.65
	3H	13.14	13.88	14.01	14.79	15.92	19.82	20.56	20.70	21.47	22.60
	4H	13.24	13.92	14.13	14.82	15.98	20.58	21.26	21.48	22.17	23.32
	6H	13.26	13.85	14.17	14.78	15.93	21.12	21.71	22.03	22.64	23.80
	8H	13.24	13.79	14.15	14.72	15.89	21.28	21.83	22.19	22.76	23.93
	12H	13.21	13.70	14.14	14.65	15.82	21.38	21.87	22.31	22.82	23.99
8H	4H	14.69	15.24	15.60	16.16	17.33	20.66	21.21	21.57	22.14	23.31
	6H	14.94	15.40	15.88	16.36	17.53	21.29	21.74	22.22	22.71	23.88
	8H	14.96	15.36	15.91	16.32	17.51	21.50	21.91	22.45	22.86	24.05
	12H	14.94	15.29	15.89	16.24	17.48	21.65	22.00	22.60	22.95	24.19
12H	4H	14.84	15.33	15.77	16.28	17.45	20.62	21.12	21.55	22.06	23.24
	6H	15.20	15.60	16.14	16.56	17.75	21.27	21.68	22.22	22.63	23.82
	8H	15.27	15.63	16.22	16.58	17.82	21.50	21.86	22.45	22.81	24.05