

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P935183

Luminaire Tested: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P935183
REPORT IS A COMBINATION OF REPORTS P933742 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Asymmetric Frosted Continuous I
Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6666.3 lumens
Efficiency: N/A
Efficacy: 135.5 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.26 / 1.36
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: General Diffuse

Input Watts (W): 49.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

Luminous Intensity Polar Plot



TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	105	105	105	105	96	96	96	96	78	78	78	62	62	62	47	47	47	41	41	41
1	96	91	88	84	87	83	80	77	68	66	64	55	53	52	42	41	40	34	34	34
2	87	80	74	69	79	73	68	63	60	56	53	48	45	43	37	35	34	29	29	29
3	79	70	63	57	72	64	58	53	53	48	45	42	39	37	33	31	29	24	24	24
4	73	62	54	48	66	57	50	45	47	42	38	38	34	31	29	27	25	21	21	21
5	67	55	47	41	60	51	44	38	42	37	33	34	30	27	26	24	22	18	18	18
6	61	49	41	36	56	45	38	33	38	32	28	31	27	24	24	21	19	16	16	16
7	57	45	37	31	51	41	34	29	34	29	25	28	24	21	22	19	17	14	14	14
8	52	40	33	27	48	37	30	26	31	26	22	25	21	18	20	17	15	13	13	13
9	49	37	29	24	44	34	27	23	28	23	20	23	19	17	18	16	13	11	11	11
10	46	34	26	22	41	31	25	20	26	21	18	21	18	15	17	14	12	10	10	10

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	9672	9672	9672	9672
5°	9733	9764	9733	7677
10°	9658	9618	9658	6876
15°	9542	9410	9542	7857
20°	9332	9162	9332	7873
25°	8912	8802	8912	7706
30°	8374	8503	8374	7340
35°	7455	8126	7455	6938
40°	6201	7680	6201	6634
45°	5531	7159	5531	6284
50°	5862	6538	5862	5933
55°	5500	5869	5500	5730
60°	5648	4985	5648	5248
65°	5095	4120	5095	4606
70°	3503	3284	3503	3860
75°	3040	2427	3040	2907
80°	2401	1604	2401	1747
85°	1308	849	1308	722

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 20°

Vertical Angle: 45°

Luminance: 8492 cd/sqm

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	94.1	1.4
10°-20°	267.1	4.0
20°-30°	413.0	6.2
30°-40°	493.0	7.4
40°-50°	495.9	7.4
50°-60°	431.5	6.5
60°-70°	305.9	4.6
70°-80°	161.8	2.4
80°-90°	42.6	0.6
90°-100°	297.9	4.5
100°-110°	783.1	11.7
110°-120°	812.0	12.2
120°-130°	651.3	9.8
130°-140°	511.1	7.7
140°-150°	392.3	5.9
150°-160°	282.5	4.2
160°-170°	172.8	2.6
170°-180°	58.4	0.9
0°-30°	774.2	11.6
0°-40°	1267.2	19.0
0°-60°	2194.5	32.9
0°-90°	2704.9	40.6
90°-120°	1893.0	28.4
90°-150°	3447.6	51.7
90°-180°	3961.0	59.4
0°-180°	6666.3	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1042	1042	1042	1042	1042	
5°	1047	1080	1047	849	1047	99
15°	1000	1070	1000	893	1000	281
25°	881	998	881	874	881	404
35°	670	890	670	760	670	414
45°	432	734	432	644	432	346
55°	352	541	352	529	352	324
65°	244	326	244	365	244	234
75°	93	155	93	185	93	97
85°	16	39	16	34	16	21
90°	4	16	4	16	4	4
95°	39	180	39	180	39	44
105°	141	1226	141	1226	141	150
115°	250	1579	250	1579	250	247
125°	349	1257	349	1257	349	309
135°	416	976	416	976	416	321
145°	482	792	482	792	482	302
155°	545	682	545	682	545	250
165°	588	635	588	635	588	166
175°	611	615	611	615	611	58
180°	611	611	611	611	611	

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3
2.5°	1051.2	1051.2	1057.2	1059.2	1059.2	1056.2	1053.2	1056.2	1065.1	1068.0	1067.0
5°	1047.2	1055.2	1066.1	1068.0	1070.0	1069.0	1067.0	1069.0	1078.9	1080.9	1081.8
7.5°	1039.3	1054.2	1068.0	1071.0	1074.0	1071.0	1070.0	1072.0	1081.8	1083.8	1083.8
10°	1029.5	1050.2	1066.1	1068.0	1071.0	1068.0	1068.0	1072.0	1081.8	1083.8	1084.8
12.5°	1015.7	1044.3	1059.2	1061.1	1065.1	1064.1	1063.1	1067.0	1076.9	1078.9	1078.9
15°	999.9	1033.4	1047.2	1049.2	1056.2	1054.2	1054.2	1058.2	1069.0	1072.0	1071.0
17.5°	978.2	1019.6	1035.4	1038.4	1043.3	1042.3	1043.3	1047.2	1057.2	1059.2	1060.1
20°	953.6	1000.9	1019.6	1022.6	1027.5	1027.5	1027.5	1032.4	1042.3	1046.2	1046.2
22.5°	920.0	981.2	1000.9	1002.9	1008.8	1008.8	1010.7	1017.7	1026.5	1027.5	1027.5
25°	880.6	959.5	976.2	982.2	988.1	991.0	994.0	997.9	1000.9	999.9	1000.9
27.5°	839.2	931.9	953.6	957.5	965.4	968.4	972.3	973.3	974.3	977.2	975.3
30°	792.8	893.4	926.0	929.9	942.7	944.7	940.7	942.7	947.6	949.6	951.6
32.5°	740.6	836.2	897.4	906.2	918.1	912.1	911.2	914.1	922.0	922.0	924.0
35°	669.6	791.9	870.7	878.6	887.5	880.6	884.5	885.5	890.5	893.4	892.4
37.5°	591.7	753.4	843.1	849.0	855.9	847.1	853.0	855.9	859.9	857.9	857.9
40°	522.7	693.3	810.6	814.5	820.5	813.5	819.5	821.4	823.4	821.4	820.5
42.5°	471.4	627.2	776.1	781.0	777.1	782.0	784.0	787.9	785.0	781.0	781.0
45°	432.0	609.4	738.6	744.5	738.6	746.5	749.5	749.5	740.6	738.6	737.6
47.5°	419.1	574.0	701.1	701.1	698.2	708.0	713.0	706.1	697.2	694.2	694.2
50°	418.2	534.5	649.9	645.9	659.7	671.6	666.6	659.7	652.8	642.0	642.0
52.5°	379.7	486.2	583.8	598.6	620.3	627.2	619.3	612.4	600.6	595.6	591.7
55°	352.1	435.9	523.7	553.2	575.9	584.8	570.0	563.1	545.4	542.4	540.4
57.5°	346.1	362.9	468.4	505.9	533.5	532.5	523.7	510.8	496.1	493.1	492.1
60°	317.5	262.3	409.3	453.7	482.3	479.3	471.4	459.6	445.8	443.8	441.8
62.5°	287.9	190.3	342.1	392.5	433.0	432.0	425.1	407.3	397.5	392.5	388.6
65°	244.5	159.7	243.5	326.4	384.6	386.6	371.8	359.0	348.1	342.1	341.2
67.5°	186.4	130.2	164.7	272.1	338.2	336.2	317.5	311.6	297.8	294.8	288.9
70°	138.0	86.8	114.4	220.9	292.8	287.9	273.1	266.2	253.4	246.5	242.6
72.5°	114.4	70.0	83.8	171.6	246.5	240.6	227.8	219.9	209.0	203.1	199.2
75°	92.7	74.0	64.1	127.2	200.2	196.2	184.4	176.5	167.6	159.7	160.7
77.5°	68.0	69.0	51.3	93.7	158.7	152.8	145.9	136.1	132.1	124.2	124.2
80°	51.3	54.2	38.5	64.1	114.4	114.4	108.5	101.6	94.7	90.7	90.7
82.5°	34.5	34.5	28.6	40.4	77.9	74.9	71.0	69.0	65.1	63.1	63.1
85°	15.8	19.7	17.7	24.6	42.4	44.4	44.4	42.4	41.4	39.4	40.4
87.5°	4.9	8.9	10.8	13.8	21.7	22.7	23.7	23.7	23.7	24.6	24.6
90°	4.1	7.4	10.6	11.4	18.0	26.8	31.2	27.7	20.8	15.6	15.6
92.5°	16.4	44.3	72.2	79.2	111.3	154.1	175.5	153.8	110.4	77.9	74.8
95°	39.3	90.4	141.5	154.2	273.8	433.2	513.0	457.8	347.4	264.5	255.2
97.5°	68.0	113.1	158.2	169.4	368.9	634.8	767.7	732.8	663.0	610.6	592.8
100°	90.2	131.0	171.9	182.1	403.5	698.6	846.1	848.7	853.7	857.5	836.2
102.5°	109.1	147.2	185.3	194.8	419.3	718.6	868.3	912.7	1001.7	1068.3	1050.1
105°	141.1	173.3	205.6	213.7	431.1	720.9	865.8	965.5	1164.9	1314.4	1304.7
107.5°	173.9	204.0	234.1	241.6	433.2	688.7	816.5	955.6	1233.8	1442.4	1444.8
110°	196.0	223.2	250.3	257.1	429.9	660.3	775.5	931.0	1242.0	1475.2	1485.4

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	217.8	243.6	269.5	276.0	430.1	635.5	738.2	897.4	1215.5	1454.3	1469.9
115°	250.5	274.4	298.3	304.3	434.0	607.1	693.6	846.9	1153.4	1383.4	1405.0
117.5°	283.0	304.7	326.4	331.8	442.1	589.2	662.8	801.1	1077.8	1285.3	1309.4
120°	301.8	322.2	342.6	347.8	448.6	583.2	650.5	776.9	1029.7	1219.3	1242.8
122.5°	320.4	341.0	361.6	366.7	458.1	580.1	641.0	754.8	982.5	1153.2	1176.3
125°	348.6	367.4	386.1	390.9	470.8	577.4	630.7	727.5	920.8	1065.9	1087.2
127.5°	371.5	390.5	409.5	414.2	483.5	575.9	622.2	705.2	871.2	995.8	1013.7
130°	383.8	404.3	424.7	429.8	492.8	576.9	618.9	692.9	840.7	951.5	968.1
132.5°	396.6	417.0	437.4	442.5	500.3	577.4	616.0	682.1	814.4	913.7	928.6
135°	415.5	434.0	452.7	457.3	508.6	576.9	611.1	666.5	777.3	860.4	873.2
137.5°	434.7	453.2	471.5	476.1	520.8	580.5	610.2	657.1	750.7	821.0	831.5
140°	450.7	467.7	484.6	488.9	528.4	581.0	607.4	647.8	728.8	789.5	799.3
142.5°	463.0	478.7	494.4	498.3	534.7	583.1	607.4	642.9	714.0	767.3	775.8
145°	481.9	495.6	509.2	512.6	542.9	583.2	603.3	632.4	690.5	734.1	740.5
147.5°	500.8	514.1	527.3	530.7	554.9	587.2	603.3	626.2	672.0	706.3	711.6
150°	513.0	525.0	537.1	540.1	561.2	589.3	603.3	622.7	661.2	690.2	694.4
152.5°	525.7	534.8	544.0	546.2	565.3	590.6	603.3	619.8	652.7	677.5	680.7
155°	544.7	551.4	558.2	559.9	574.3	593.7	603.3	616.4	642.7	662.3	664.5
157.5°	558.6	565.2	571.7	573.4	583.3	596.6	603.3	613.5	633.9	649.2	650.7
160°	568.0	573.2	578.2	579.5	587.5	598.0	603.3	612.1	629.6	642.7	643.6
162.5°	577.4	581.2	585.1	586.1	591.8	599.5	603.3	610.7	625.4	636.5	637.3
165°	587.7	591.1	594.6	595.4	598.1	601.6	603.3	608.7	619.2	627.1	628.0
167.5°	597.1	598.8	600.5	600.9	603.0	605.9	607.4	610.8	617.7	623.0	623.3
170°	603.3	604.9	606.6	607.0	607.1	607.3	607.4	610.8	617.7	623.0	623.0
172.5°	606.6	607.0	607.3	607.4	607.4	607.4	607.4	610.1	615.6	619.7	619.4
175°	611.1	611.1	611.1	611.1	609.8	608.2	607.4	609.2	612.6	615.2	615.2
177.5°	611.1	611.1	611.1	611.1	610.1	608.9	608.2	609.5	612.3	614.4	614.0
180°	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
0°	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3
2.5°	1069.0	1066.1	1069.0	1067.0	1068.0	1065.1	1056.2	1053.2	1056.2	1059.2	1059.2
5°	1081.8	1079.9	1081.8	1081.8	1080.9	1078.9	1069.0	1067.0	1069.0	1070.0	1068.0
7.5°	1085.8	1082.8	1085.8	1083.8	1083.8	1081.8	1072.0	1070.0	1071.0	1074.0	1071.0
10°	1085.8	1082.8	1085.8	1084.8	1083.8	1081.8	1072.0	1068.0	1068.0	1071.0	1068.0
12.5°	1080.9	1078.9	1080.9	1078.9	1078.9	1076.9	1067.0	1063.1	1064.1	1065.1	1061.1
15°	1073.0	1070.0	1073.0	1071.0	1072.0	1069.0	1058.2	1054.2	1054.2	1056.2	1049.2
17.5°	1061.1	1057.2	1061.1	1060.1	1059.2	1057.2	1047.2	1043.3	1042.3	1043.3	1038.4
20°	1047.2	1044.3	1047.2	1046.2	1046.2	1042.3	1032.4	1027.5	1027.5	1027.5	1022.6
22.5°	1025.5	1022.6	1025.5	1027.5	1027.5	1026.5	1017.7	1010.7	1008.8	1008.8	1002.9
25°	1000.9	997.9	1000.9	1000.9	999.9	1000.9	997.9	994.0	991.0	988.1	982.2
27.5°	977.2	975.3	977.2	975.3	977.2	974.3	973.3	972.3	968.4	965.4	957.5
30°	953.6	951.6	953.6	951.6	949.6	947.6	942.7	940.7	944.7	942.7	929.9
32.5°	924.0	922.0	924.0	924.0	922.0	922.0	914.1	911.2	912.1	918.1	906.2
35°	893.4	890.5	893.4	892.4	893.4	890.5	885.5	884.5	880.6	887.5	878.6
37.5°	857.9	855.0	857.9	857.9	857.9	859.9	855.9	853.0	847.1	855.9	849.0
40°	821.4	817.5	821.4	820.5	821.4	823.4	821.4	819.5	813.5	820.5	814.5
42.5°	780.0	779.0	780.0	781.0	781.0	785.0	787.9	784.0	782.0	777.1	781.0
45°	735.7	733.7	735.7	737.6	738.6	740.6	749.5	749.5	746.5	738.6	744.5
47.5°	688.3	683.4	688.3	694.2	694.2	697.2	706.1	713.0	708.0	698.2	701.1
50°	638.0	639.0	638.0	642.0	642.0	652.8	659.7	666.6	671.6	659.7	645.9
52.5°	588.7	587.8	588.7	591.7	595.6	600.6	612.4	619.3	627.2	620.3	598.6
55°	539.4	541.4	539.4	540.4	542.4	545.4	563.1	570.0	584.8	575.9	553.2
57.5°	490.1	487.2	490.1	492.1	493.1	496.1	510.8	523.7	532.5	533.5	505.9
60°	433.0	429.0	433.0	441.8	443.8	445.8	459.6	471.4	479.3	482.3	453.7
62.5°	382.7	375.8	382.7	388.6	392.5	397.5	407.3	425.1	432.0	433.0	392.5
65°	329.3	326.4	329.3	341.2	342.1	348.1	359.0	371.8	386.6	384.6	326.4
67.5°	281.0	281.0	281.0	288.9	294.8	297.8	311.6	317.5	336.2	338.2	272.1
70°	236.6	235.7	236.6	242.6	246.5	253.4	266.2	273.1	287.9	292.8	220.9
72.5°	194.2	193.3	194.2	199.2	203.1	209.0	219.9	227.8	240.6	246.5	171.6
75°	156.8	154.8	156.8	160.7	159.7	167.6	176.5	184.4	196.2	200.2	127.2
77.5°	120.3	120.3	120.3	124.2	124.2	132.1	136.1	145.9	152.8	158.7	93.7
80°	89.7	88.7	89.7	90.7	90.7	94.7	101.6	108.5	114.4	114.4	64.1
82.5°	63.1	61.1	63.1	63.1	63.1	65.1	69.0	71.0	74.9	77.9	40.4
85°	39.4	39.4	39.4	40.4	39.4	41.4	42.4	44.4	44.4	42.4	24.6
87.5°	25.6	24.6	25.6	24.6	24.6	23.7	23.7	23.7	22.7	21.7	13.8
90°	15.6	15.6	15.6	15.6	15.6	20.8	27.7	31.2	26.8	18.0	11.4
92.5°	62.4	50.0	62.4	74.8	77.9	110.4	153.8	175.5	154.1	111.3	79.2
95°	217.6	180.0	217.6	255.2	264.5	347.4	457.8	513.0	433.2	273.8	154.2
97.5°	521.3	449.9	521.3	592.8	610.6	663.0	732.8	767.7	634.8	368.9	169.4
100°	751.1	666.0	751.1	836.2	857.5	853.7	848.7	846.1	698.6	403.5	182.1
102.5°	977.2	904.4	977.2	1050.1	1068.3	1001.7	912.7	868.3	718.6	419.3	194.8
105°	1265.4	1226.3	1265.4	1304.7	1314.4	1164.9	965.5	865.8	720.9	431.1	213.7
107.5°	1454.3	1463.7	1454.3	1444.8	1442.4	1233.8	955.6	816.5	688.7	433.2	241.6
110°	1526.2	1567.0	1526.2	1485.4	1475.2	1242.0	931.0	775.5	660.3	429.9	257.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
112.5°	1532.6	1595.3	1532.6	1469.9	1454.3	1215.5	897.4	738.2	635.5	430.1	276.0
115°	1492.0	1579.0	1492.0	1405.0	1383.4	1153.4	846.9	693.6	607.1	434.0	304.3
117.5°	1405.8	1502.3	1405.8	1309.4	1285.3	1077.8	801.1	662.8	589.2	442.1	331.8
120°	1336.4	1430.1	1336.4	1242.8	1219.3	1029.7	776.9	650.5	583.2	448.6	347.8
122.5°	1268.8	1361.2	1268.8	1176.3	1153.2	982.5	754.8	641.0	580.1	458.1	366.7
125°	1172.3	1257.4	1172.3	1087.2	1065.9	920.8	727.5	630.7	577.4	470.8	390.9
127.5°	1085.6	1157.4	1085.6	1013.7	995.8	871.2	705.2	622.2	575.9	483.5	414.2
130°	1034.4	1100.8	1034.4	968.1	951.5	840.7	692.9	618.9	576.9	492.8	429.8
132.5°	988.0	1047.4	988.0	928.6	913.7	814.4	682.1	616.0	577.4	500.3	442.5
135°	924.4	975.6	924.4	873.2	860.4	777.3	666.5	611.1	576.9	508.6	457.3
137.5°	873.5	915.4	873.5	831.5	821.0	750.7	657.1	610.2	580.5	520.8	476.1
140°	838.5	877.6	838.5	799.3	789.5	728.8	647.8	607.4	581.0	528.4	488.9
142.5°	809.5	843.2	809.5	775.8	767.3	714.0	642.9	607.4	583.1	534.7	498.3
145°	766.0	791.6	766.0	740.5	734.1	690.5	632.4	603.3	583.2	542.9	512.6
147.5°	732.7	753.8	732.7	711.6	706.3	672.0	626.2	603.3	587.2	554.9	530.7
150°	711.6	728.8	711.6	694.4	690.2	661.2	622.7	603.3	589.3	561.2	540.1
152.5°	693.7	706.7	693.7	680.7	677.5	652.7	619.8	603.3	590.6	565.3	546.2
155°	673.0	681.6	673.0	664.5	662.3	642.7	616.4	603.3	593.7	574.3	559.9
157.5°	656.8	662.8	656.8	650.7	649.2	633.9	613.5	603.3	596.6	583.3	573.4
160°	647.0	650.5	647.0	643.6	642.7	629.6	612.1	603.3	598.0	587.5	579.5
162.5°	640.6	643.9	640.6	637.3	636.5	625.4	610.7	603.3	599.5	591.8	586.1
165°	631.4	634.9	631.4	628.0	627.1	619.2	608.7	603.3	601.6	598.1	595.4
167.5°	624.7	626.2	624.7	623.3	623.0	617.7	610.8	607.4	605.9	603.0	600.9
170°	623.0	623.0	623.0	623.0	623.0	617.7	610.8	607.4	607.3	607.1	607.0
172.5°	618.1	616.8	618.1	619.4	619.7	615.6	610.1	607.4	607.4	607.4	607.4
175°	615.2	615.2	615.2	615.2	615.2	612.6	609.2	607.4	608.2	609.8	611.1
177.5°	612.6	611.1	612.6	614.0	614.4	612.3	609.5	608.2	608.9	610.1	611.1
180°	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
0°	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3
2.5°	1057.2	1051.2	1051.2	1041.3	1037.4	1034.4	1029.5	1014.7	1010.7	1006.8	1012.7
5°	1066.1	1055.2	1047.2	1029.5	1014.7	1008.8	990.0	954.5	930.9	913.1	903.3
7.5°	1068.0	1054.2	1039.3	1011.7	976.2	960.5	903.3	838.2	820.5	804.7	794.8
10°	1066.1	1050.2	1029.5	988.1	904.3	876.7	819.5	777.1	766.2	763.3	766.2
12.5°	1059.2	1044.3	1015.7	946.7	829.3	810.6	777.1	752.4	750.4	755.4	782.0
15°	1047.2	1033.4	999.9	891.4	787.9	774.1	750.4	741.6	752.4	786.9	866.8
17.5°	1035.4	1019.6	978.2	837.2	756.4	746.5	729.7	747.5	808.6	855.0	881.6
20°	1019.6	1000.9	953.6	797.8	733.7	724.8	716.9	796.8	843.1	859.9	874.7
22.5°	1000.9	981.2	920.0	770.2	710.0	703.1	708.0	824.4	843.1	855.0	867.8
25°	976.2	959.5	880.6	748.5	691.3	683.4	702.1	821.4	832.3	835.2	860.9
27.5°	953.6	931.9	839.2	728.8	668.6	665.6	707.1	808.6	816.5	819.5	847.1
30°	926.0	893.4	792.8	708.0	644.9	644.0	708.0	792.8	790.9	798.8	826.4
32.5°	897.4	836.2	740.6	682.4	622.3	621.3	701.1	769.2	767.2	778.1	798.8
35°	870.7	791.9	669.6	652.8	593.7	594.7	684.4	741.6	742.6	752.4	765.2
37.5°	843.1	753.4	591.7	620.3	566.1	566.1	661.7	715.9	714.0	716.9	734.7
40°	810.6	693.3	522.7	577.9	540.4	537.5	634.1	688.3	681.4	680.4	705.1
42.5°	776.1	627.2	471.4	521.7	510.8	506.9	600.6	654.8	642.0	644.9	676.5
45°	738.6	609.4	432.0	440.8	480.3	477.3	564.1	616.3	607.5	615.4	647.9
47.5°	701.1	574.0	419.1	365.9	447.7	446.8	523.7	578.9	574.0	581.8	616.3
50°	649.9	534.5	418.2	313.5	411.3	415.2	475.4	542.4	542.4	549.3	585.8
52.5°	583.8	486.2	379.7	284.0	368.9	380.7	433.0	510.8	512.8	519.7	552.3
55°	523.7	435.9	352.1	261.3	318.5	344.1	391.5	478.3	482.3	489.2	518.7
57.5°	468.4	362.9	346.1	234.7	272.1	296.8	355.1	446.8	448.7	454.6	483.2
60°	409.3	262.3	317.5	206.1	231.7	250.4	321.4	409.3	416.2	420.1	444.8
62.5°	342.1	190.3	287.9	186.4	212.0	215.9	293.8	373.8	382.7	385.6	400.4
65°	243.5	159.7	244.5	169.6	191.3	192.3	264.2	337.2	345.1	350.0	361.0
67.5°	164.7	130.2	186.4	153.8	175.5	176.5	235.7	294.8	305.7	309.6	316.5
70°	114.4	86.8	138.0	137.1	157.8	159.7	205.1	256.4	266.2	269.2	273.1
72.5°	83.8	70.0	114.4	123.2	139.0	141.0	173.5	213.0	222.8	225.8	227.8
75°	64.1	74.0	92.7	107.5	118.3	119.3	142.0	173.5	180.4	182.4	183.4
77.5°	51.3	69.0	68.0	86.8	96.6	94.7	111.4	134.1	140.0	140.0	140.0
80°	38.5	54.2	51.3	62.1	71.0	69.0	79.9	95.6	97.6	99.6	98.6
82.5°	28.6	34.5	34.5	39.4	47.3	45.4	53.2	62.1	62.1	62.1	64.1
85°	17.7	19.7	15.8	20.7	26.6	25.6	29.6	33.5	34.5	34.5	32.5
87.5°	10.8	8.9	4.9	7.9	11.8	11.8	13.8	14.8	13.8	13.8	13.8
90°	10.6	7.4	4.1	7.4	10.6	11.4	18.0	26.8	31.2	27.7	20.8
92.5°	72.2	44.3	16.4	44.3	72.2	79.2	111.3	154.1	175.5	153.8	110.4
95°	141.5	90.4	39.3	90.4	141.5	154.2	273.8	433.2	513.0	457.8	347.4
97.5°	158.2	113.1	68.0	113.1	158.2	169.4	368.9	634.8	767.7	732.8	663.0
100°	171.9	131.0	90.2	131.0	171.9	182.1	403.5	698.6	846.1	848.7	853.7
102.5°	185.3	147.2	109.1	147.2	185.3	194.8	419.3	718.6	868.3	912.7	1001.7
105°	205.6	173.3	141.1	173.3	205.6	213.7	431.1	720.9	865.8	965.5	1164.9
107.5°	234.1	204.0	173.9	204.0	234.1	241.6	433.2	688.7	816.5	955.6	1233.8
110°	250.3	223.2	196.0	223.2	250.3	257.1	429.9	660.3	775.5	931.0	1242.0

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
112.5°	269.5	243.6	217.8	243.6	269.5	276.0	430.1	635.5	738.2	897.4	1215.5
115°	298.3	274.4	250.5	274.4	298.3	304.3	434.0	607.1	693.6	846.9	1153.4
117.5°	326.4	304.7	283.0	304.7	326.4	331.8	442.1	589.2	662.8	801.1	1077.8
120°	342.6	322.2	301.8	322.2	342.6	347.8	448.6	583.2	650.5	776.9	1029.7
122.5°	361.6	341.0	320.4	341.0	361.6	366.7	458.1	580.1	641.0	754.8	982.5
125°	386.1	367.4	348.6	367.4	386.1	390.9	470.8	577.4	630.7	727.5	920.8
127.5°	409.5	390.5	371.5	390.5	409.5	414.2	483.5	575.9	622.2	705.2	871.2
130°	424.7	404.3	383.8	404.3	424.7	429.8	492.8	576.9	618.9	692.9	840.7
132.5°	437.4	417.0	396.6	417.0	437.4	442.5	500.3	577.4	616.0	682.1	814.4
135°	452.7	434.0	415.5	434.0	452.7	457.3	508.6	576.9	611.1	666.5	777.3
137.5°	471.5	453.2	434.7	453.2	471.5	476.1	520.8	580.5	610.2	657.1	750.7
140°	484.6	467.7	450.7	467.7	484.6	488.9	528.4	581.0	607.4	647.8	728.8
142.5°	494.4	478.7	463.0	478.7	494.4	498.3	534.7	583.1	607.4	642.9	714.0
145°	509.2	495.6	481.9	495.6	509.2	512.6	542.9	583.2	603.3	632.4	690.5
147.5°	527.3	514.1	500.8	514.1	527.3	530.7	554.9	587.2	603.3	626.2	672.0
150°	537.1	525.0	513.0	525.0	537.1	540.1	561.2	589.3	603.3	622.7	661.2
152.5°	544.0	534.8	525.7	534.8	544.0	546.2	565.3	590.6	603.3	619.8	652.7
155°	558.2	551.4	544.7	551.4	558.2	559.9	574.3	593.7	603.3	616.4	642.7
157.5°	571.7	565.2	558.6	565.2	571.7	573.4	583.3	596.6	603.3	613.5	633.9
160°	578.2	573.2	568.0	573.2	578.2	579.5	587.5	598.0	603.3	612.1	629.6
162.5°	585.1	581.2	577.4	581.2	585.1	586.1	591.8	599.5	603.3	610.7	625.4
165°	594.6	591.1	587.7	591.1	594.6	595.4	598.1	601.6	603.3	608.7	619.2
167.5°	600.5	598.8	597.1	598.8	600.5	600.9	603.0	605.9	607.4	610.8	617.7
170°	606.6	604.9	603.3	604.9	606.6	607.0	607.1	607.3	607.4	610.8	617.7
172.5°	607.3	607.0	606.6	607.0	607.3	607.4	607.4	607.4	607.4	610.1	615.6
175°	611.1	611.1	611.1	611.1	611.1	611.1	609.8	608.2	607.4	609.2	612.6
177.5°	611.1	611.1	611.1	611.1	611.1	611.1	610.1	608.9	608.2	609.5	612.3
180°	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
0°	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3	1042.3
2.5°	1005.8	1002.9	1006.8	996.0	1006.8	1002.9	1005.8	1012.7	1006.8	1010.7	1014.7
5°	882.6	877.6	861.9	849.0	861.9	877.6	882.6	903.3	913.1	930.9	954.5
7.5°	788.9	785.0	781.0	773.1	781.0	785.0	788.9	794.8	804.7	820.5	838.2
10°	768.2	769.2	775.1	774.1	775.1	769.2	768.2	766.2	763.3	766.2	777.1
12.5°	821.4	830.3	862.8	860.9	862.8	830.3	821.4	782.0	755.4	750.4	752.4
15°	882.6	885.5	892.4	893.4	892.4	885.5	882.6	866.8	786.9	752.4	741.6
17.5°	888.5	889.5	894.4	894.4	894.4	889.5	888.5	881.6	855.0	808.6	747.5
20°	883.6	885.5	895.4	897.4	895.4	885.5	883.6	874.7	859.9	843.1	796.8
22.5°	881.6	885.5	893.4	892.4	893.4	885.5	881.6	867.8	855.0	843.1	824.4
25°	871.7	871.7	872.7	873.7	872.7	871.7	871.7	860.9	835.2	832.3	821.4
27.5°	851.0	853.0	858.9	857.9	858.9	853.0	851.0	847.1	819.5	816.5	808.6
30°	832.3	830.3	825.4	821.4	825.4	830.3	832.3	826.4	798.8	790.9	792.8
32.5°	800.7	795.8	790.9	787.9	790.9	795.8	800.7	798.8	778.1	767.2	769.2
35°	763.3	764.2	763.3	760.3	763.3	764.2	763.3	765.2	752.4	742.6	741.6
37.5°	736.6	738.6	737.6	733.7	737.6	738.6	736.6	734.7	716.9	714.0	715.9
40°	709.0	710.0	709.0	706.1	709.0	710.0	709.0	705.1	680.4	681.4	688.3
42.5°	682.4	681.4	678.5	676.5	678.5	681.4	682.4	676.5	644.9	642.0	654.8
45°	651.8	652.8	646.9	644.0	646.9	652.8	651.8	647.9	615.4	607.5	616.3
47.5°	621.3	621.3	616.3	613.4	616.3	621.3	621.3	616.3	581.8	574.0	578.9
50°	588.7	587.8	580.9	579.9	580.9	587.8	588.7	585.8	549.3	542.4	542.4
52.5°	551.3	551.3	552.3	554.2	552.3	551.3	551.3	552.3	519.7	512.8	510.8
55°	518.7	519.7	526.6	528.6	526.6	519.7	518.7	518.7	489.2	482.3	478.3
57.5°	485.2	485.2	490.1	490.1	490.1	485.2	485.2	483.2	454.6	448.7	446.8
60°	446.8	448.7	452.7	451.7	452.7	448.7	446.8	444.8	420.1	416.2	409.3
62.5°	406.3	408.3	409.3	407.3	409.3	408.3	406.3	400.4	385.6	382.7	373.8
65°	363.9	365.9	366.9	364.9	366.9	365.9	363.9	361.0	350.0	345.1	337.2
67.5°	320.4	319.5	318.5	322.4	318.5	319.5	320.4	316.5	309.6	305.7	294.8
70°	276.1	276.1	275.1	277.1	275.1	276.1	276.1	273.1	269.2	266.2	256.4
72.5°	228.8	227.8	231.7	228.8	231.7	227.8	228.8	227.8	225.8	222.8	213.0
75°	182.4	184.4	182.4	185.4	182.4	184.4	182.4	183.4	182.4	180.4	173.5
77.5°	139.0	141.0	139.0	139.0	139.0	141.0	139.0	140.0	140.0	140.0	134.1
80°	98.6	97.6	97.6	96.6	97.6	97.6	98.6	98.6	99.6	97.6	95.6
82.5°	63.1	62.1	62.1	64.1	62.1	62.1	63.1	64.1	62.1	62.1	62.1
85°	34.5	35.5	33.5	33.5	33.5	35.5	34.5	32.5	34.5	34.5	33.5
87.5°	12.8	11.8	11.8	11.8	11.8	11.8	12.8	13.8	13.8	13.8	14.8
90°	15.6	15.6	15.6	15.6	15.6	15.6	15.6	20.8	27.7	31.2	26.8
92.5°	77.9	74.8	62.4	50.0	62.4	74.8	77.9	110.4	153.8	175.5	154.1
95°	264.5	255.2	217.6	180.0	217.6	255.2	264.5	347.4	457.8	513.0	433.2
97.5°	610.6	592.8	521.3	449.9	521.3	592.8	610.6	663.0	732.8	767.7	634.8
100°	857.5	836.2	751.1	666.0	751.1	836.2	857.5	853.7	848.7	846.1	698.6
102.5°	1068.3	1050.1	977.2	904.4	977.2	1050.1	1068.3	1001.7	912.7	868.3	718.6
105°	1314.4	1304.7	1265.4	1226.3	1265.4	1304.7	1314.4	1164.9	965.5	865.8	720.9
107.5°	1442.4	1444.8	1454.3	1463.7	1454.3	1444.8	1442.4	1233.8	955.6	816.5	688.7
110°	1475.2	1485.4	1526.2	1567.0	1526.2	1485.4	1475.2	1242.0	931.0	775.5	660.3

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
112.5°	1454.3	1469.9	1532.6	1595.3	1532.6	1469.9	1454.3	1215.5	897.4	738.2	635.5
115°	1383.4	1405.0	1492.0	1579.0	1492.0	1405.0	1383.4	1153.4	846.9	693.6	607.1
117.5°	1285.3	1309.4	1405.8	1502.3	1405.8	1309.4	1285.3	1077.8	801.1	662.8	589.2
120°	1219.3	1242.8	1336.4	1430.1	1336.4	1242.8	1219.3	1029.7	776.9	650.5	583.2
122.5°	1153.2	1176.3	1268.8	1361.2	1268.8	1176.3	1153.2	982.5	754.8	641.0	580.1
125°	1065.9	1087.2	1172.3	1257.4	1172.3	1087.2	1065.9	920.8	727.5	630.7	577.4
127.5°	995.8	1013.7	1085.6	1157.4	1085.6	1013.7	995.8	871.2	705.2	622.2	575.9
130°	951.5	968.1	1034.4	1100.8	1034.4	968.1	951.5	840.7	692.9	618.9	576.9
132.5°	913.7	928.6	988.0	1047.4	988.0	928.6	913.7	814.4	682.1	616.0	577.4
135°	860.4	873.2	924.4	975.6	924.4	873.2	860.4	777.3	666.5	611.1	576.9
137.5°	821.0	831.5	873.5	915.4	873.5	831.5	821.0	750.7	657.1	610.2	580.5
140°	789.5	799.3	838.5	877.6	838.5	799.3	789.5	728.8	647.8	607.4	581.0
142.5°	767.3	775.8	809.5	843.2	809.5	775.8	767.3	714.0	642.9	607.4	583.1
145°	734.1	740.5	766.0	791.6	766.0	740.5	734.1	690.5	632.4	603.3	583.2
147.5°	706.3	711.6	732.7	753.8	732.7	711.6	706.3	672.0	626.2	603.3	587.2
150°	690.2	694.4	711.6	728.8	711.6	694.4	690.2	661.2	622.7	603.3	589.3
152.5°	677.5	680.7	693.7	706.7	693.7	680.7	677.5	652.7	619.8	603.3	590.6
155°	662.3	664.5	673.0	681.6	673.0	664.5	662.3	642.7	616.4	603.3	593.7
157.5°	649.2	650.7	656.8	662.8	656.8	650.7	649.2	633.9	613.5	603.3	596.6
160°	642.7	643.6	647.0	650.5	647.0	643.6	642.7	629.6	612.1	603.3	598.0
162.5°	636.5	637.3	640.6	643.9	640.6	637.3	636.5	625.4	610.7	603.3	599.5
165°	627.1	628.0	631.4	634.9	631.4	628.0	627.1	619.2	608.7	603.3	601.6
167.5°	623.0	623.3	624.7	626.2	624.7	623.3	623.0	617.7	610.8	607.4	605.9
170°	623.0	623.0	623.0	623.0	623.0	623.0	623.0	617.7	610.8	607.4	607.3
172.5°	619.7	619.4	618.1	616.8	618.1	619.4	619.7	615.6	610.1	607.4	607.4
175°	615.2	615.2	615.2	615.2	615.2	615.2	615.2	612.6	609.2	607.4	608.2
177.5°	614.4	614.0	612.6	611.1	612.6	614.0	614.4	612.3	609.5	608.2	608.9
180°	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1	611.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
0°	1042.3	1042.3	1042.3	1042.3	1042.3
2.5°	1029.5	1034.4	1037.4	1041.3	1051.2
5°	990.0	1008.8	1014.7	1029.5	1047.2
7.5°	903.3	960.5	976.2	1011.7	1039.3
10°	819.5	876.7	904.3	988.1	1029.5
12.5°	777.1	810.6	829.3	946.7	1015.7
15°	750.4	774.1	787.9	891.4	999.9
17.5°	729.7	746.5	756.4	837.2	978.2
20°	716.9	724.8	733.7	797.8	953.6
22.5°	708.0	703.1	710.0	770.2	920.0
25°	702.1	683.4	691.3	748.5	880.6
27.5°	707.1	665.6	668.6	728.8	839.2
30°	708.0	644.0	644.9	708.0	792.8
32.5°	701.1	621.3	622.3	682.4	740.6
35°	684.4	594.7	593.7	652.8	669.6
37.5°	661.7	566.1	566.1	620.3	591.7
40°	634.1	537.5	540.4	577.9	522.7
42.5°	600.6	506.9	510.8	521.7	471.4
45°	564.1	477.3	480.3	440.8	432.0
47.5°	523.7	446.8	447.7	365.9	419.1
50°	475.4	415.2	411.3	313.5	418.2
52.5°	433.0	380.7	368.9	284.0	379.7
55°	391.5	344.1	318.5	261.3	352.1
57.5°	355.1	296.8	272.1	234.7	346.1
60°	321.4	250.4	231.7	206.1	317.5
62.5°	293.8	215.9	212.0	186.4	287.9
65°	264.2	192.3	191.3	169.6	244.5
67.5°	235.7	176.5	175.5	153.8	186.4
70°	205.1	159.7	157.8	137.1	138.0
72.5°	173.5	141.0	139.0	123.2	114.4
75°	142.0	119.3	118.3	107.5	92.7
77.5°	111.4	94.7	96.6	86.8	68.0
80°	79.9	69.0	71.0	62.1	51.3
82.5°	53.2	45.4	47.3	39.4	34.5
85°	29.6	25.6	26.6	20.7	15.8
87.5°	13.8	11.8	11.8	7.9	4.9
90°	18.0	11.4	10.6	7.4	4.1
92.5°	111.3	79.2	72.2	44.3	16.4
95°	273.8	154.2	141.5	90.4	39.3
97.5°	368.9	169.4	158.2	113.1	68.0
100°	403.5	182.1	171.9	131.0	90.2
102.5°	419.3	194.8	185.3	147.2	109.1
105°	431.1	213.7	205.6	173.3	141.1
107.5°	433.2	241.6	234.1	204.0	173.9
110°	429.9	257.1	250.3	223.2	196.0

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
112.5°	430.1	276.0	269.5	243.6	217.8
115°	434.0	304.3	298.3	274.4	250.5
117.5°	442.1	331.8	326.4	304.7	283.0
120°	448.6	347.8	342.6	322.2	301.8
122.5°	458.1	366.7	361.6	341.0	320.4
125°	470.8	390.9	386.1	367.4	348.6
127.5°	483.5	414.2	409.5	390.5	371.5
130°	492.8	429.8	424.7	404.3	383.8
132.5°	500.3	442.5	437.4	417.0	396.6
135°	508.6	457.3	452.7	434.0	415.5
137.5°	520.8	476.1	471.5	453.2	434.7
140°	528.4	488.9	484.6	467.7	450.7
142.5°	534.7	498.3	494.4	478.7	463.0
145°	542.9	512.6	509.2	495.6	481.9
147.5°	554.9	530.7	527.3	514.1	500.8
150°	561.2	540.1	537.1	525.0	513.0
152.5°	565.3	546.2	544.0	534.8	525.7
155°	574.3	559.9	558.2	551.4	544.7
157.5°	583.3	573.4	571.7	565.2	558.6
160°	587.5	579.5	578.2	573.2	568.0
162.5°	591.8	586.1	585.1	581.2	577.4
165°	598.1	595.4	594.6	591.1	587.7
167.5°	603.0	600.9	600.5	598.8	597.1
170°	607.1	607.0	606.6	604.9	603.3
172.5°	607.4	607.4	607.3	607.0	606.6
175°	609.8	611.1	611.1	611.1	611.1
177.5°	610.1	611.1	611.1	611.1	611.1
180°	611.1	611.1	611.1	611.1	611.1

TEST NUMBER: P935183

CATALOG NUMBER: SQ4-FA-100U-075D-B2750-1D-UNV-W2A-W-4-3000K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.74	12.52	12.77	13.56	14.96	14.54	15.32	15.57	16.36	17.76
	3H	12.21	12.91	13.25	13.96	15.38	15.87	16.57	16.91	17.62	19.03
	4H	12.40	13.06	13.45	14.11	15.54	16.30	16.96	17.36	18.02	19.44
	6H	12.51	13.12	13.58	14.18	15.62	16.57	17.18	17.64	18.24	19.68
	8H	12.51	13.09	13.58	14.16	15.60	16.64	17.22	17.71	18.29	19.73
	12H	12.48	13.03	13.55	14.10	15.56	16.67	17.22	17.75	18.29	19.75
4H	2H	12.75	13.42	13.82	14.47	15.90	14.94	15.60	16.00	16.65	18.08
	3H	13.77	14.33	14.84	15.41	16.84	16.43	16.98	17.50	18.06	19.50
	4H	14.05	14.55	15.12	15.62	17.08	16.94	17.45	18.02	18.52	19.98
	6H	14.17	14.60	15.25	15.70	17.15	17.30	17.73	18.38	18.83	20.28
	8H	14.17	14.58	15.26	15.66	17.13	17.40	17.80	18.48	18.89	20.36
	12H	14.13	14.50	15.24	15.60	17.08	17.44	17.81	18.55	18.91	20.39
8H	4H	14.49	14.89	15.57	15.98	17.45	17.06	17.47	18.15	18.56	20.03
	6H	14.75	15.08	15.85	16.21	17.68	17.49	17.82	18.60	18.95	20.42
	8H	14.79	15.08	15.90	16.19	17.68	17.63	17.93	18.75	19.04	20.53
	12H	14.77	15.03	15.89	16.13	17.66	17.72	17.98	18.84	19.09	20.61
12H	4H	14.49	14.86	15.59	15.96	17.43	17.02	17.39	18.13	18.49	19.97
	6H	14.80	15.10	15.92	16.21	17.70	17.48	17.78	18.60	18.89	20.38
	8H	14.87	15.13	15.99	16.23	17.76	17.64	17.90	18.76	19.00	20.53

END OF REPORT