

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P933985

Luminaire Tested: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

Issue Date: 12/17/2024

Test Information

Test Method: LM-79-2019
Report Number: P933985
REPORT IS A COMBINATION OF REPORTS P933678 AND P933786
Test Lab: INNOVATION CENTER
Issue Date: 12/17/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K
Description: CORELITE SQ4 SUSPENDED INDIRECT LED LUMINAIRE WITH Asymmetric Frosted Continuous I
Lens
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3542.1 lumens
Efficiency: N/A
Efficacy: 118.1 lumens/watt
Spacing Criteria (0/90/45): 1.14 / 1.26 / 1.36
Luminous Opening: Rectangular w/ Sides (W: 0.29' x L: 4' x H: 0.1')
CIE Type: Semi-Direct

Input Watts (W): 30
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

Luminous Intensity Polar Plot



TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	113	113	113	113	107	107	107	107	97	97	97	87	87	87	78	78	78	74		
1	103	99	95	91	98	94	90	87	85	82	80	77	75	73	69	68	66	62		
2	94	86	80	75	89	82	77	72	75	70	66	68	64	61	61	58	56	52		
3	86	76	68	62	81	72	66	60	66	60	56	60	55	52	54	51	48	44		
4	79	67	59	53	74	64	57	51	59	52	48	53	48	44	48	44	41	38		
5	72	60	52	45	68	57	50	44	52	46	41	48	43	38	43	39	36	33		
6	67	54	46	39	63	52	44	38	47	41	36	43	38	34	39	35	31	29		
7	62	49	41	35	58	47	39	34	43	36	32	39	34	30	36	31	28	26		
8	57	44	36	31	54	43	35	30	39	33	28	36	31	27	33	28	25	23		
9	53	41	33	28	51	39	32	27	36	30	25	33	28	24	30	26	23	21		
10	50	37	30	25	48	36	29	24	33	27	23	31	25	22	28	24	20	19		

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	9367	9367	9367	9367
5°	9427	9457	9427	7436
10°	9354	9316	9354	6660
15°	9242	9114	9242	7609
20°	9038	8874	9038	7625
25°	8632	8526	8632	7464
30°	8111	8236	8111	7109
35°	7220	7870	7220	6719
40°	6006	7439	6006	6425
45°	5357	6934	5357	6086
50°	5677	6332	5677	5746
55°	5326	5684	5326	5550
60°	5470	4828	5470	5083
65°	4935	3990	4935	4461
70°	3394	3179	3394	3739
75°	2945	2350	2945	2814
80°	2326	1555	2326	1692
85°	1267	823	1267	700

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 20°

Vertical Angle: 45°

Luminance: 8225 cd/sqm

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	91.1	2.6
10°-20°	258.7	7.3
20°-30°	400.0	11.3
30°-40°	477.5	13.5
40°-50°	480.3	13.6
50°-60°	417.9	11.8
60°-70°	296.3	8.4
70°-80°	156.7	4.4
80°-90°	39.6	1.1
90°-100°	69.5	2.0
100°-110°	182.7	5.2
110°-120°	189.4	5.3
120°-130°	151.9	4.3
130°-140°	119.2	3.4
140°-150°	91.5	2.6
150°-160°	65.9	1.9
160°-170°	40.3	1.1
170°-180°	13.6	0.4
0°-30°	749.8	21.2
0°-40°	1227.3	34.7
0°-60°	2125.6	60.0
0°-90°	2618.2	73.9
90°-120°	441.5	12.5
90°-150°	804.1	22.7
90°-180°	924.0	26.1
0°-180°	3542.1	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1010	1010	1010	1010	1010	
5°	1014	1046	1014	822	1014	96
15°	968	1036	968	865	968	272
25°	853	967	853	846	853	392
35°	648	862	648	736	648	401
45°	418	711	418	624	418	335
55°	341	524	341	512	341	313
65°	237	316	237	353	237	226
75°	90	150	90	180	90	94
85°	15	38	15	32	15	21
90°	1	4	1	4	1	1
95°	9	42	9	42	9	10
105°	33	286	33	286	33	35
115°	58	368	58	368	58	58
125°	81	293	81	293	81	72
135°	97	228	97	228	97	75
145°	112	185	112	185	112	70
155°	127	159	127	159	127	58
165°	137	148	137	148	137	39
175°	142	143	142	143	142	14
180°	142	142	142	142	142	

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
0°	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5
2.5°	1018.1	1018.1	1024.0	1025.9	1025.9	1023.0	1020.1	1023.0	1031.6	1034.5	1033.5
5°	1014.3	1022.0	1032.5	1034.5	1036.4	1035.4	1033.5	1035.4	1045.0	1046.9	1047.8
7.5°	1006.7	1021.1	1034.5	1037.3	1040.2	1037.3	1036.4	1038.3	1047.8	1049.7	1049.7
10°	997.1	1017.2	1032.5	1034.5	1037.3	1034.5	1034.5	1038.3	1047.8	1049.7	1050.7
12.5°	983.7	1011.4	1025.9	1027.8	1031.6	1030.6	1029.7	1033.5	1043.1	1045.0	1045.0
15°	968.5	1000.9	1014.3	1016.2	1023.0	1021.1	1021.1	1024.9	1035.4	1038.3	1037.3
17.5°	947.5	987.6	1002.8	1005.7	1010.5	1009.5	1010.5	1014.3	1024.0	1025.9	1026.8
20°	923.6	969.4	987.6	990.4	995.2	995.2	995.2	1000.0	1009.5	1013.4	1013.4
22.5°	891.1	950.3	969.4	971.3	977.1	977.1	979.0	985.7	994.3	995.2	995.2
25°	852.9	929.3	945.5	951.3	957.0	959.9	962.7	966.6	969.4	968.5	969.4
27.5°	812.8	902.6	923.6	927.4	935.0	937.9	941.7	942.7	943.6	946.5	944.6
30°	767.9	865.3	896.8	900.7	913.1	915.0	911.2	913.1	917.9	919.8	921.7
32.5°	717.3	809.9	869.1	877.7	889.2	883.5	882.5	885.4	893.0	893.0	894.9
35°	648.5	767.0	843.4	851.0	859.6	852.9	856.7	857.7	862.5	865.3	864.4
37.5°	573.1	729.7	816.6	822.4	829.0	820.4	826.2	829.0	832.9	830.9	830.9
40°	506.2	671.5	785.1	788.9	794.7	788.0	793.7	795.6	797.5	795.6	794.7
42.5°	456.6	607.5	751.7	756.5	752.6	757.4	759.3	763.1	760.3	756.5	756.5
45°	418.4	590.3	715.4	721.1	715.4	723.0	725.9	725.9	717.3	715.4	714.4
47.5°	406.0	555.9	679.1	679.1	676.2	685.8	690.6	683.9	675.3	672.4	672.4
50°	405.0	517.7	629.4	625.6	639.0	650.5	645.7	639.0	632.3	621.8	621.8
52.5°	367.8	470.9	565.5	579.8	600.8	607.5	599.8	593.2	581.7	576.9	573.1
55°	341.0	422.2	507.2	535.9	557.8	566.4	552.1	545.4	528.2	525.3	523.4
57.5°	335.2	351.5	453.7	490.0	516.8	515.8	507.2	494.8	480.5	477.6	476.6
60°	307.5	254.0	396.4	439.4	467.1	464.2	456.6	445.1	431.8	429.8	427.9
62.5°	278.9	184.3	331.4	380.2	419.3	418.4	411.7	394.5	385.0	380.2	376.4
65°	236.8	154.7	235.9	316.1	372.5	374.5	360.1	347.7	337.1	331.4	330.4
67.5°	180.5	126.1	159.5	263.6	327.6	325.7	307.5	301.8	288.4	285.5	279.8
70°	133.7	84.0	110.8	213.9	283.6	278.9	264.5	257.8	245.4	238.8	234.9
72.5°	110.8	67.8	81.2	166.2	238.8	233.0	220.6	213.0	202.5	196.7	192.9
75°	89.8	71.6	62.1	123.2	193.9	190.0	178.6	170.9	162.4	154.7	155.7
77.5°	65.9	66.8	49.7	90.7	153.8	148.0	141.3	131.8	128.0	120.3	120.3
80°	49.7	52.5	37.2	62.1	110.8	110.8	105.0	98.4	91.7	87.9	87.9
82.5°	33.4	33.4	27.7	39.2	75.4	72.6	68.8	66.8	63.0	61.1	61.1
85°	15.3	19.1	17.2	23.9	41.1	43.0	43.0	41.1	40.1	38.2	39.2
87.5°	4.8	8.6	10.5	13.4	21.0	22.0	22.9	22.9	22.9	23.9	23.9
90°	1.0	1.7	2.5	2.7	4.2	6.2	7.3	6.5	4.9	3.6	3.6
92.5°	3.8	10.3	16.8	18.4	26.0	36.0	41.0	35.9	25.8	18.1	17.4
95°	9.2	21.1	33.0	36.0	63.9	101.0	119.7	106.8	81.0	61.7	59.5
97.5°	15.9	26.4	36.9	39.5	86.0	148.0	179.1	170.9	154.6	142.4	138.2
100°	21.0	30.6	40.1	42.5	94.1	162.9	197.3	197.9	199.1	200.0	195.0
102.5°	25.4	34.3	43.3	45.5	97.8	167.6	202.5	212.9	233.6	249.2	244.9
105°	32.9	40.5	47.9	49.9	100.6	168.1	201.9	225.2	271.7	306.6	304.3
107.5°	40.6	47.6	54.6	56.3	101.0	160.6	190.4	222.9	287.7	336.4	337.0
110°	45.7	52.0	58.4	60.0	100.3	154.0	180.9	217.2	289.7	344.1	346.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	22.5°	30°	40°	45°	50°	60°	67.5°	70°
112.5°	50.8	56.8	62.8	64.4	100.3	148.2	172.2	209.3	283.5	339.2	342.8
115°	58.4	64.0	69.5	71.0	101.2	141.6	161.8	197.5	269.0	322.6	327.7
117.5°	66.0	71.1	76.1	77.4	103.1	137.4	154.6	186.9	251.4	299.8	305.4
120°	70.4	75.2	79.9	81.1	104.6	136.0	151.7	181.2	240.2	284.4	289.8
122.5°	74.7	79.5	84.2	85.5	106.8	135.2	149.5	176.0	229.1	268.9	274.3
125°	81.3	85.7	90.1	91.2	109.8	134.7	147.1	169.6	214.8	248.6	253.6
127.5°	86.6	91.1	95.5	96.6	112.8	134.3	145.1	164.5	203.2	232.3	236.5
130°	89.5	94.3	99.0	100.3	115.0	134.6	144.3	161.6	196.1	221.9	225.8
132.5°	92.5	97.3	102.1	103.2	116.7	134.7	143.6	159.1	189.9	213.2	216.6
135°	96.9	101.2	105.6	106.7	118.6	134.6	142.5	155.4	181.3	200.6	203.6
137.5°	101.4	105.7	110.0	111.1	121.5	135.3	142.3	153.2	175.1	191.5	194.0
140°	105.1	109.1	113.1	114.0	123.2	135.5	141.6	151.1	170.0	184.1	186.4
142.5°	108.0	111.6	115.3	116.2	124.7	136.0	141.6	149.9	166.6	179.0	181.0
145°	112.4	115.6	118.8	119.6	126.6	136.0	140.7	147.5	161.0	171.2	172.8
147.5°	116.8	119.9	123.0	123.8	129.4	136.9	140.7	146.0	156.7	164.7	166.0
150°	119.7	122.4	125.3	126.0	130.8	137.4	140.7	145.2	154.2	161.0	162.0
152.5°	122.6	124.7	126.8	127.4	131.8	137.7	140.7	144.5	152.2	158.1	158.8
155°	127.0	128.5	130.2	130.5	133.9	138.4	140.7	143.7	149.9	154.5	155.0
157.5°	130.3	131.8	133.3	133.7	136.0	139.1	140.7	143.1	147.8	151.4	151.7
160°	132.5	133.6	134.8	135.1	136.9	139.4	140.7	142.7	146.8	149.8	150.0
162.5°	134.7	135.5	136.5	136.7	138.0	139.8	140.7	142.4	145.8	148.4	148.6
165°	137.0	137.8	138.7	138.9	139.4	140.3	140.7	141.9	144.4	146.2	146.4
167.5°	139.2	139.6	140.0	140.1	140.6	141.2	141.6	142.4	144.0	145.3	145.4
170°	140.7	141.1	141.4	141.5	141.5	141.6	141.6	142.4	144.0	145.3	145.3
172.5°	141.4	141.5	141.6	141.6	141.6	141.6	141.6	142.3	143.5	144.5	144.4
175°	142.5	142.5	142.5	142.5	142.2	141.8	141.6	142.0	142.9	143.4	143.4
177.5°	142.5	142.5	142.5	142.5	142.3	142.0	141.8	142.1	142.8	143.2	143.2
180°	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
0°	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5
2.5°	1035.4	1032.5	1035.4	1033.5	1034.5	1031.6	1023.0	1020.1	1023.0	1025.9	1025.9
5°	1047.8	1045.9	1047.8	1047.8	1046.9	1045.0	1035.4	1033.5	1035.4	1036.4	1034.5
7.5°	1051.6	1048.8	1051.6	1049.7	1049.7	1047.8	1038.3	1036.4	1037.3	1040.2	1037.3
10°	1051.6	1048.8	1051.6	1050.7	1049.7	1047.8	1038.3	1034.5	1034.5	1037.3	1034.5
12.5°	1046.9	1045.0	1046.9	1045.0	1045.0	1043.1	1033.5	1029.7	1030.6	1031.6	1027.8
15°	1039.2	1036.4	1039.2	1037.3	1038.3	1035.4	1024.9	1021.1	1021.1	1023.0	1016.2
17.5°	1027.8	1024.0	1027.8	1026.8	1025.9	1024.0	1014.3	1010.5	1009.5	1010.5	1005.7
20°	1014.3	1011.4	1014.3	1013.4	1013.4	1009.5	1000.0	995.2	995.2	995.2	990.4
22.5°	993.3	990.4	993.3	995.2	995.2	994.3	985.7	979.0	977.1	977.1	971.3
25°	969.4	966.6	969.4	969.4	968.5	969.4	966.6	962.7	959.9	957.0	951.3
27.5°	946.5	944.6	946.5	944.6	946.5	943.6	942.7	941.7	937.9	935.0	927.4
30°	923.6	921.7	923.6	921.7	919.8	917.9	913.1	911.2	915.0	913.1	900.7
32.5°	894.9	893.0	894.9	894.9	893.0	893.0	885.4	882.5	883.5	889.2	877.7
35°	865.3	862.5	865.3	864.4	865.3	862.5	857.7	856.7	852.9	859.6	851.0
37.5°	830.9	828.1	830.9	830.9	830.9	832.9	829.0	826.2	820.4	829.0	822.4
40°	795.6	791.8	795.6	794.7	795.6	797.5	795.6	793.7	788.0	794.7	788.9
42.5°	755.5	754.5	755.5	756.5	756.5	760.3	763.1	759.3	757.4	752.6	756.5
45°	712.5	710.6	712.5	714.4	715.4	717.3	725.9	725.9	723.0	715.4	721.1
47.5°	666.7	661.9	666.7	672.4	672.4	675.3	683.9	690.6	685.8	676.2	679.1
50°	618.0	618.9	618.0	621.8	621.8	632.3	639.0	645.7	650.5	639.0	625.6
52.5°	570.2	569.3	570.2	573.1	576.9	581.7	593.2	599.8	607.5	600.8	579.8
55°	522.5	524.4	522.5	523.4	525.3	528.2	545.4	552.1	566.4	557.8	535.9
57.5°	474.7	471.9	474.7	476.6	477.6	480.5	494.8	507.2	515.8	516.8	490.0
60°	419.3	415.5	419.3	427.9	429.8	431.8	445.1	456.6	464.2	467.1	439.4
62.5°	370.6	364.0	370.6	376.4	380.2	385.0	394.5	411.7	418.4	419.3	380.2
65°	319.0	316.1	319.0	330.4	331.4	337.1	347.7	360.1	374.5	372.5	316.1
67.5°	272.2	272.2	272.2	279.8	285.5	288.4	301.8	307.5	325.7	327.6	263.6
70°	229.2	228.2	229.2	234.9	238.8	245.4	257.8	264.5	278.9	283.6	213.9
72.5°	188.1	187.2	188.1	192.9	196.7	202.5	213.0	220.6	233.0	238.8	166.2
75°	151.8	149.9	151.8	155.7	154.7	162.4	170.9	178.6	190.0	193.9	123.2
77.5°	116.5	116.5	116.5	120.3	120.3	128.0	131.8	141.3	148.0	153.8	90.7
80°	86.9	86.0	86.9	87.9	87.9	91.7	98.4	105.0	110.8	110.8	62.1
82.5°	61.1	59.2	61.1	61.1	61.1	63.0	66.8	68.8	72.6	75.4	39.2
85°	38.2	38.2	38.2	39.2	38.2	40.1	41.1	43.0	43.0	41.1	23.9
87.5°	24.8	23.9	24.8	23.9	23.9	22.9	22.9	22.9	22.0	21.0	13.4
90°	3.6	3.6	3.6	3.6	3.6	4.9	6.5	7.3	6.2	4.2	2.7
92.5°	14.5	11.7	14.5	17.4	18.1	25.8	35.9	41.0	36.0	26.0	18.4
95°	50.8	42.0	50.8	59.5	61.7	81.0	106.8	119.7	101.0	63.9	36.0
97.5°	121.6	105.0	121.6	138.2	142.4	154.6	170.9	179.1	148.0	86.0	39.5
100°	175.2	155.4	175.2	195.0	200.0	199.1	197.9	197.3	162.9	94.1	42.5
102.5°	227.9	210.9	227.9	244.9	249.2	233.6	212.9	202.5	167.6	97.8	45.5
105°	295.2	286.0	295.2	304.3	306.6	271.7	225.2	201.9	168.1	100.6	49.9
107.5°	339.2	341.4	339.2	337.0	336.4	287.7	222.9	190.4	160.6	101.0	56.3
110°	355.9	365.5	355.9	346.5	344.1	289.7	217.2	180.9	154.0	100.3	60.0

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	80°	90°	100°	110°	112.5°	120°	130°	135°	140°	150°	157.5°
112.5°	357.5	372.1	357.5	342.8	339.2	283.5	209.3	172.2	148.2	100.3	64.4
115°	348.0	368.2	348.0	327.7	322.6	269.0	197.5	161.8	141.6	101.2	71.0
117.5°	327.9	350.4	327.9	305.4	299.8	251.4	186.9	154.6	137.4	103.1	77.4
120°	311.7	333.5	311.7	289.8	284.4	240.2	181.2	151.7	136.0	104.6	81.1
122.5°	295.9	317.4	295.9	274.3	268.9	229.1	176.0	149.5	135.2	106.8	85.5
125°	273.4	293.3	273.4	253.6	248.6	214.8	169.6	147.1	134.7	109.8	91.2
127.5°	253.2	269.9	253.2	236.5	232.3	203.2	164.5	145.1	134.3	112.8	96.6
130°	241.2	256.7	241.2	225.8	221.9	196.1	161.6	144.3	134.6	115.0	100.3
132.5°	230.4	244.3	230.4	216.6	213.2	189.9	159.1	143.6	134.7	116.7	103.2
135°	215.6	227.6	215.6	203.6	200.6	181.3	155.4	142.5	134.6	118.6	106.7
137.5°	203.7	213.5	203.7	194.0	191.5	175.1	153.2	142.3	135.3	121.5	111.1
140°	195.5	204.7	195.5	186.4	184.1	170.0	151.1	141.6	135.5	123.2	114.0
142.5°	188.8	196.6	188.8	181.0	179.0	166.6	149.9	141.6	136.0	124.7	116.2
145°	178.7	184.6	178.7	172.8	171.2	161.0	147.5	140.7	136.0	126.6	119.6
147.5°	170.8	175.8	170.8	166.0	164.7	156.7	146.0	140.7	136.9	129.4	123.8
150°	166.0	170.0	166.0	162.0	161.0	154.2	145.2	140.7	137.4	130.8	126.0
152.5°	161.8	164.8	161.8	158.8	158.1	152.2	144.5	140.7	137.7	131.8	127.4
155°	157.0	159.0	157.0	155.0	154.5	149.9	143.7	140.7	138.4	133.9	130.5
157.5°	153.2	154.6	153.2	151.7	151.4	147.8	143.1	140.7	139.1	136.0	133.7
160°	150.9	151.7	150.9	150.0	149.8	146.8	142.7	140.7	139.4	136.9	135.1
162.5°	149.4	150.1	149.4	148.6	148.4	145.8	142.4	140.7	139.8	138.0	136.7
165°	147.3	148.0	147.3	146.4	146.2	144.4	141.9	140.7	140.3	139.4	138.9
167.5°	145.6	146.0	145.6	145.4	145.3	144.0	142.4	141.6	141.2	140.6	140.1
170°	145.3	145.3	145.3	145.3	145.3	144.0	142.4	141.6	141.6	141.5	141.5
172.5°	144.1	143.8	144.1	144.4	144.5	143.5	142.3	141.6	141.6	141.6	141.6
175°	143.4	143.4	143.4	143.4	143.4	142.9	142.0	141.6	141.8	142.2	142.5
177.5°	142.9	142.5	142.9	143.2	143.2	142.8	142.1	141.8	142.0	142.3	142.5
180°	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
0°	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5
2.5°	1024.0	1018.1	1018.1	1008.6	1004.8	1001.9	997.1	982.8	979.0	975.2	980.9
5°	1032.5	1022.0	1014.3	997.1	982.8	977.1	958.9	924.5	901.6	884.4	874.9
7.5°	1034.5	1021.1	1006.7	979.9	945.5	930.3	874.9	811.8	794.7	779.4	769.8
10°	1032.5	1017.2	997.1	957.0	875.8	849.1	793.7	752.6	742.1	739.3	742.1
12.5°	1025.9	1011.4	983.7	916.9	803.3	785.1	752.6	728.8	726.9	731.6	757.4
15°	1014.3	1000.9	968.5	863.4	763.1	749.8	726.9	718.3	728.8	762.2	839.5
17.5°	1002.8	987.6	947.5	810.9	732.6	723.0	706.8	724.0	783.2	828.1	853.9
20°	987.6	969.4	923.6	772.7	710.6	702.0	694.4	771.7	816.6	832.9	847.2
22.5°	969.4	950.3	891.1	746.0	687.7	681.0	685.8	798.5	816.6	828.1	840.5
25°	945.5	929.3	852.9	724.9	669.6	661.9	680.1	795.6	806.1	809.0	833.8
27.5°	923.6	902.6	812.8	705.8	647.6	644.7	684.8	783.2	790.8	793.7	820.4
30°	896.8	865.3	767.9	685.8	624.7	623.7	685.8	767.9	766.0	773.6	800.4
32.5°	869.1	809.9	717.3	661.0	602.7	601.7	679.1	745.0	743.1	753.6	773.6
35°	843.4	767.0	648.5	632.3	575.0	576.0	662.9	718.3	719.2	728.8	741.2
37.5°	816.6	729.7	573.1	600.8	548.3	548.3	640.9	693.4	691.5	694.4	711.6
40°	785.1	671.5	506.2	559.7	523.4	520.6	614.2	666.7	660.0	659.0	682.9
42.5°	751.7	607.5	456.6	505.3	494.8	491.0	581.7	634.2	621.8	624.7	655.2
45°	715.4	590.3	418.4	427.0	465.2	462.3	546.4	597.0	588.4	596.0	627.5
47.5°	679.1	555.9	406.0	354.4	433.7	432.7	507.2	560.7	555.9	563.5	597.0
50°	629.4	517.7	405.0	303.7	398.3	402.2	460.4	525.3	525.3	532.0	567.4
52.5°	565.5	470.9	367.8	275.0	357.3	368.7	419.3	494.8	496.7	503.4	534.9
55°	507.2	422.2	341.0	253.1	308.5	333.3	379.2	463.3	467.1	473.8	502.4
57.5°	453.7	351.5	335.2	227.3	263.6	287.5	343.9	432.7	434.6	440.4	468.0
60°	396.4	254.0	307.5	199.6	224.4	242.6	311.3	396.4	403.1	406.9	430.8
62.5°	331.4	184.3	278.9	180.5	205.3	209.1	284.6	362.0	370.6	373.5	387.8
65°	235.9	154.7	236.8	164.3	185.3	186.2	255.9	326.6	334.2	339.0	349.6
67.5°	159.5	126.1	180.5	149.0	170.0	170.9	228.2	285.5	296.0	299.9	306.6
70°	110.8	84.0	133.7	132.7	152.8	154.7	198.6	248.3	257.8	260.7	264.5
72.5°	81.2	67.8	110.8	119.4	134.7	136.6	168.1	206.3	215.8	218.7	220.6
75°	62.1	71.6	89.8	104.1	114.6	115.6	137.5	168.1	174.8	176.7	177.6
77.5°	49.7	66.8	65.9	84.0	93.6	91.7	107.9	129.9	135.6	135.6	135.6
80°	37.2	52.5	49.7	60.2	68.8	66.8	77.4	92.6	94.5	96.5	95.5
82.5°	27.7	33.4	33.4	38.2	45.8	43.9	51.6	60.2	60.2	60.2	62.1
85°	17.2	19.1	15.3	20.1	25.8	24.8	28.6	32.5	33.4	33.4	31.5
87.5°	10.5	8.6	4.8	7.6	11.5	11.5	13.4	14.3	13.4	13.4	13.4
90°	2.5	1.7	1.0	1.7	2.5	2.7	4.2	6.2	7.3	6.5	4.9
92.5°	16.8	10.3	3.8	10.3	16.8	18.4	26.0	36.0	41.0	35.9	25.8
95°	33.0	21.1	9.2	21.1	33.0	36.0	63.9	101.0	119.7	106.8	81.0
97.5°	36.9	26.4	15.9	26.4	36.9	39.5	86.0	148.0	179.1	170.9	154.6
100°	40.1	30.6	21.0	30.6	40.1	42.5	94.1	162.9	197.3	197.9	199.1
102.5°	43.3	34.3	25.4	34.3	43.3	45.5	97.8	167.6	202.5	212.9	233.6
105°	47.9	40.5	32.9	40.5	47.9	49.9	100.6	168.1	201.9	225.2	271.7
107.5°	54.6	47.6	40.6	47.6	54.6	56.3	101.0	160.6	190.4	222.9	287.7
110°	58.4	52.0	45.7	52.0	58.4	60.0	100.3	154.0	180.9	217.2	289.7

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	160°	170°	180°	190°	200°	202.5°	210°	220°	225°	230°	240°
112.5°	62.8	56.8	50.8	56.8	62.8	64.4	100.3	148.2	172.2	209.3	283.5
115°	69.5	64.0	58.4	64.0	69.5	71.0	101.2	141.6	161.8	197.5	269.0
117.5°	76.1	71.1	66.0	71.1	76.1	77.4	103.1	137.4	154.6	186.9	251.4
120°	79.9	75.2	70.4	75.2	79.9	81.1	104.6	136.0	151.7	181.2	240.2
122.5°	84.2	79.5	74.7	79.5	84.2	85.5	106.8	135.2	149.5	176.0	229.1
125°	90.1	85.7	81.3	85.7	90.1	91.2	109.8	134.7	147.1	169.6	214.8
127.5°	95.5	91.1	86.6	91.1	95.5	96.6	112.8	134.3	145.1	164.5	203.2
130°	99.0	94.3	89.5	94.3	99.0	100.3	115.0	134.6	144.3	161.6	196.1
132.5°	102.1	97.3	92.5	97.3	102.1	103.2	116.7	134.7	143.6	159.1	189.9
135°	105.6	101.2	96.9	101.2	105.6	106.7	118.6	134.6	142.5	155.4	181.3
137.5°	110.0	105.7	101.4	105.7	110.0	111.1	121.5	135.3	142.3	153.2	175.1
140°	113.1	109.1	105.1	109.1	113.1	114.0	123.2	135.5	141.6	151.1	170.0
142.5°	115.3	111.6	108.0	111.6	115.3	116.2	124.7	136.0	141.6	149.9	166.6
145°	118.8	115.6	112.4	115.6	118.8	119.6	126.6	136.0	140.7	147.5	161.0
147.5°	123.0	119.9	116.8	119.9	123.0	123.8	129.4	136.9	140.7	146.0	156.7
150°	125.3	122.4	119.7	122.4	125.3	126.0	130.8	137.4	140.7	145.2	154.2
152.5°	126.8	124.7	122.6	124.7	126.8	127.4	131.8	137.7	140.7	144.5	152.2
155°	130.2	128.5	127.0	128.5	130.2	130.5	133.9	138.4	140.7	143.7	149.9
157.5°	133.3	131.8	130.3	131.8	133.3	133.7	136.0	139.1	140.7	143.1	147.8
160°	134.8	133.6	132.5	133.6	134.8	135.1	136.9	139.4	140.7	142.7	146.8
162.5°	136.5	135.5	134.7	135.5	136.5	136.7	138.0	139.8	140.7	142.4	145.8
165°	138.7	137.8	137.0	137.8	138.7	138.9	139.4	140.3	140.7	141.9	144.4
167.5°	140.0	139.6	139.2	139.6	140.0	140.1	140.6	141.2	141.6	142.4	144.0
170°	141.4	141.1	140.7	141.1	141.4	141.5	141.5	141.6	141.6	142.4	144.0
172.5°	141.6	141.5	141.4	141.5	141.6	141.6	141.6	141.6	141.6	142.3	143.5
175°	142.5	142.5	142.5	142.5	142.5	142.5	142.2	141.8	141.6	142.0	142.9
177.5°	142.5	142.5	142.5	142.5	142.5	142.5	142.3	142.0	141.8	142.1	142.8
180°	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
0°	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5	1009.5
2.5°	974.2	971.3	975.2	964.6	975.2	971.3	974.2	980.9	975.2	979.0	982.8
5°	854.8	850.0	834.8	822.4	834.8	850.0	854.8	874.9	884.4	901.6	924.5
7.5°	764.1	760.3	756.5	748.8	756.5	760.3	764.1	769.8	779.4	794.7	811.8
10°	744.0	745.0	750.7	749.8	750.7	745.0	744.0	742.1	739.3	742.1	752.6
12.5°	795.6	804.2	835.7	833.8	835.7	804.2	795.6	757.4	731.6	726.9	728.8
15°	854.8	857.7	864.4	865.3	864.4	857.7	854.8	839.5	762.2	728.8	718.3
17.5°	860.6	861.5	866.3	866.3	866.3	861.5	860.6	853.9	828.1	783.2	724.0
20°	855.8	857.7	867.2	869.1	867.2	857.7	855.8	847.2	832.9	816.6	771.7
22.5°	853.9	857.7	865.3	864.4	865.3	857.7	853.9	840.5	828.1	816.6	798.5
25°	844.3	844.3	845.3	846.2	845.3	844.3	844.3	833.8	809.0	806.1	795.6
27.5°	824.3	826.2	831.9	830.9	831.9	826.2	824.3	820.4	793.7	790.8	783.2
30°	806.1	804.2	799.4	795.6	799.4	804.2	806.1	800.4	773.6	766.0	767.9
32.5°	775.6	770.8	766.0	763.1	766.0	770.8	775.6	773.6	753.6	743.1	745.0
35°	739.3	740.2	739.3	736.4	739.3	740.2	739.3	741.2	728.8	719.2	718.3
37.5°	713.5	715.4	714.4	710.6	714.4	715.4	713.5	711.6	694.4	691.5	693.4
40°	686.7	687.7	686.7	683.9	686.7	687.7	686.7	682.9	659.0	660.0	666.7
42.5°	661.0	660.0	657.1	655.2	657.1	660.0	661.0	655.2	624.7	621.8	634.2
45°	631.4	632.3	626.6	623.7	626.6	632.3	631.4	627.5	596.0	588.4	597.0
47.5°	601.7	601.7	597.0	594.1	597.0	601.7	601.7	597.0	563.5	555.9	560.7
50°	570.2	569.3	562.6	561.6	562.6	569.3	570.2	567.4	532.0	525.3	525.3
52.5°	533.9	533.9	534.9	536.8	534.9	533.9	533.9	534.9	503.4	496.7	494.8
55°	502.4	503.4	510.1	512.0	510.1	503.4	502.4	502.4	473.8	467.1	463.3
57.5°	470.0	470.0	474.7	474.7	474.7	470.0	470.0	468.0	440.4	434.6	432.7
60°	432.7	434.6	438.4	437.5	438.4	434.6	432.7	430.8	406.9	403.1	396.4
62.5°	393.6	395.5	396.4	394.5	396.4	395.5	393.6	387.8	373.5	370.6	362.0
65°	352.5	354.4	355.4	353.4	355.4	354.4	352.5	349.6	339.0	334.2	326.6
67.5°	310.4	309.4	308.5	312.3	308.5	309.4	310.4	306.6	299.9	296.0	285.5
70°	267.4	267.4	266.4	268.4	266.4	267.4	267.4	264.5	260.7	257.8	248.3
72.5°	221.6	220.6	224.4	221.6	224.4	220.6	221.6	220.6	218.7	215.8	206.3
75°	176.7	178.6	176.7	179.5	176.7	178.6	176.7	177.6	176.7	174.8	168.1
77.5°	134.7	136.6	134.7	134.7	134.7	136.6	134.7	135.6	135.6	135.6	129.9
80°	95.5	94.5	94.5	93.6	94.5	94.5	95.5	95.5	96.5	94.5	92.6
82.5°	61.1	60.2	60.2	62.1	60.2	60.2	61.1	62.1	60.2	60.2	60.2
85°	33.4	34.4	32.5	32.5	32.5	34.4	33.4	31.5	33.4	33.4	32.5
87.5°	12.4	11.5	11.5	11.5	11.5	11.5	12.4	13.4	13.4	13.4	14.3
90°	3.6	3.6	3.6	3.6	3.6	3.6	3.6	4.9	6.5	7.3	6.2
92.5°	18.1	17.4	14.5	11.7	14.5	17.4	18.1	25.8	35.9	41.0	36.0
95°	61.7	59.5	50.8	42.0	50.8	59.5	61.7	81.0	106.8	119.7	101.0
97.5°	142.4	138.2	121.6	105.0	121.6	138.2	142.4	154.6	170.9	179.1	148.0
100°	200.0	195.0	175.2	155.4	175.2	195.0	200.0	199.1	197.9	197.3	162.9
102.5°	249.2	244.9	227.9	210.9	227.9	244.9	249.2	233.6	212.9	202.5	167.6
105°	306.6	304.3	295.2	286.0	295.2	304.3	306.6	271.7	225.2	201.9	168.1
107.5°	336.4	337.0	339.2	341.4	339.2	337.0	336.4	287.7	222.9	190.4	160.6
110°	344.1	346.5	355.9	365.5	355.9	346.5	344.1	289.7	217.2	180.9	154.0

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	247.5°	250°	260°	270°	280°	290°	292.5°	300°	310°	315°	320°
112.5°	339.2	342.8	357.5	372.1	357.5	342.8	339.2	283.5	209.3	172.2	148.2
115°	322.6	327.7	348.0	368.2	348.0	327.7	322.6	269.0	197.5	161.8	141.6
117.5°	299.8	305.4	327.9	350.4	327.9	305.4	299.8	251.4	186.9	154.6	137.4
120°	284.4	289.8	311.7	333.5	311.7	289.8	284.4	240.2	181.2	151.7	136.0
122.5°	268.9	274.3	295.9	317.4	295.9	274.3	268.9	229.1	176.0	149.5	135.2
125°	248.6	253.6	273.4	293.3	273.4	253.6	248.6	214.8	169.6	147.1	134.7
127.5°	232.3	236.5	253.2	269.9	253.2	236.5	232.3	203.2	164.5	145.1	134.3
130°	221.9	225.8	241.2	256.7	241.2	225.8	221.9	196.1	161.6	144.3	134.6
132.5°	213.2	216.6	230.4	244.3	230.4	216.6	213.2	189.9	159.1	143.6	134.7
135°	200.6	203.6	215.6	227.6	215.6	203.6	200.6	181.3	155.4	142.5	134.6
137.5°	191.5	194.0	203.7	213.5	203.7	194.0	191.5	175.1	153.2	142.3	135.3
140°	184.1	186.4	195.5	204.7	195.5	186.4	184.1	170.0	151.1	141.6	135.5
142.5°	179.0	181.0	188.8	196.6	188.8	181.0	179.0	166.6	149.9	141.6	136.0
145°	171.2	172.8	178.7	184.6	178.7	172.8	171.2	161.0	147.5	140.7	136.0
147.5°	164.7	166.0	170.8	175.8	170.8	166.0	164.7	156.7	146.0	140.7	136.9
150°	161.0	162.0	166.0	170.0	166.0	162.0	161.0	154.2	145.2	140.7	137.4
152.5°	158.1	158.8	161.8	164.8	161.8	158.8	158.1	152.2	144.5	140.7	137.7
155°	154.5	155.0	157.0	159.0	157.0	155.0	154.5	149.9	143.7	140.7	138.4
157.5°	151.4	151.7	153.2	154.6	153.2	151.7	151.4	147.8	143.1	140.7	139.1
160°	149.8	150.0	150.9	151.7	150.9	150.0	149.8	146.8	142.7	140.7	139.4
162.5°	148.4	148.6	149.4	150.1	149.4	148.6	148.4	145.8	142.4	140.7	139.8
165°	146.2	146.4	147.3	148.0	147.3	146.4	146.2	144.4	141.9	140.7	140.3
167.5°	145.3	145.4	145.6	146.0	145.6	145.4	145.3	144.0	142.4	141.6	141.2
170°	145.3	145.3	145.3	145.3	145.3	145.3	145.3	144.0	142.4	141.6	141.6
172.5°	144.5	144.4	144.1	143.8	144.1	144.4	144.5	143.5	142.3	141.6	141.6
175°	143.4	143.4	143.4	143.4	143.4	143.4	143.4	142.9	142.0	141.6	141.8
177.5°	143.2	143.2	142.9	142.5	142.9	143.2	143.2	142.8	142.1	141.8	142.0
180°	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5	142.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
0°	1009.5	1009.5	1009.5	1009.5	1009.5
2.5°	997.1	1001.9	1004.8	1008.6	1018.1
5°	958.9	977.1	982.8	997.1	1014.3
7.5°	874.9	930.3	945.5	979.9	1006.7
10°	793.7	849.1	875.8	957.0	997.1
12.5°	752.6	785.1	803.3	916.9	983.7
15°	726.9	749.8	763.1	863.4	968.5
17.5°	706.8	723.0	732.6	810.9	947.5
20°	694.4	702.0	710.6	772.7	923.6
22.5°	685.8	681.0	687.7	746.0	891.1
25°	680.1	661.9	669.6	724.9	852.9
27.5°	684.8	644.7	647.6	705.8	812.8
30°	685.8	623.7	624.7	685.8	767.9
32.5°	679.1	601.7	602.7	661.0	717.3
35°	662.9	576.0	575.0	632.3	648.5
37.5°	640.9	548.3	548.3	600.8	573.1
40°	614.2	520.6	523.4	559.7	506.2
42.5°	581.7	491.0	494.8	505.3	456.6
45°	546.4	462.3	465.2	427.0	418.4
47.5°	507.2	432.7	433.7	354.4	406.0
50°	460.4	402.2	398.3	303.7	405.0
52.5°	419.3	368.7	357.3	275.0	367.8
55°	379.2	333.3	308.5	253.1	341.0
57.5°	343.9	287.5	263.6	227.3	335.2
60°	311.3	242.6	224.4	199.6	307.5
62.5°	284.6	209.1	205.3	180.5	278.9
65°	255.9	186.2	185.3	164.3	236.8
67.5°	228.2	170.9	170.0	149.0	180.5
70°	198.6	154.7	152.8	132.7	133.7
72.5°	168.1	136.6	134.7	119.4	110.8
75°	137.5	115.6	114.6	104.1	89.8
77.5°	107.9	91.7	93.6	84.0	65.9
80°	77.4	66.8	68.8	60.2	49.7
82.5°	51.6	43.9	45.8	38.2	33.4
85°	28.6	24.8	25.8	20.1	15.3
87.5°	13.4	11.5	11.5	7.6	4.8
90°	4.2	2.7	2.5	1.7	1.0
92.5°	26.0	18.4	16.8	10.3	3.8
95°	63.9	36.0	33.0	21.1	9.2
97.5°	86.0	39.5	36.9	26.4	15.9
100°	94.1	42.5	40.1	30.6	21.0
102.5°	97.8	45.5	43.3	34.3	25.4
105°	100.6	49.9	47.9	40.5	32.9
107.5°	101.0	56.3	54.6	47.6	40.6
110°	100.3	60.0	58.4	52.0	45.7



TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CANDELA DISTRIBUTION (continued):

	330°	337.5°	340°	350°	360°
112.5°	100.3	64.4	62.8	56.8	50.8
115°	101.2	71.0	69.5	64.0	58.4
117.5°	103.1	77.4	76.1	71.1	66.0
120°	104.6	81.1	79.9	75.2	70.4
122.5°	106.8	85.5	84.2	79.5	74.7
125°	109.8	91.2	90.1	85.7	81.3
127.5°	112.8	96.6	95.5	91.1	86.6
130°	115.0	100.3	99.0	94.3	89.5
132.5°	116.7	103.2	102.1	97.3	92.5
135°	118.6	106.7	105.6	101.2	96.9
137.5°	121.5	111.1	110.0	105.7	101.4
140°	123.2	114.0	113.1	109.1	105.1
142.5°	124.7	116.2	115.3	111.6	108.0
145°	126.6	119.6	118.8	115.6	112.4
147.5°	129.4	123.8	123.0	119.9	116.8
150°	130.8	126.0	125.3	122.4	119.7
152.5°	131.8	127.4	126.8	124.7	122.6
155°	133.9	130.5	130.2	128.5	127.0
157.5°	136.0	133.7	133.3	131.8	130.3
160°	136.9	135.1	134.8	133.6	132.5
162.5°	138.0	136.7	136.5	135.5	134.7
165°	139.4	138.9	138.7	137.8	137.0
167.5°	140.6	140.1	140.0	139.6	139.2
170°	141.5	141.5	141.4	141.1	140.7
172.5°	141.6	141.6	141.6	141.5	141.4
175°	142.2	142.5	142.5	142.5	142.5
177.5°	142.3	142.5	142.5	142.5	142.5
180°	142.5	142.5	142.5	142.5	142.5

TEST NUMBER: P933985

CATALOG NUMBER: SQ4-FA-025U-075D-B2750-1D-UNV-W2A-W-4-4000K

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.53	15.66	15.25	16.40	17.28	17.33	18.46	18.05	19.20	20.08
	3H	15.03	16.04	15.76	16.79	17.71	18.68	19.70	19.42	20.45	21.36
	4H	15.23	16.19	15.99	16.95	17.87	19.13	20.09	19.89	20.85	21.78
	6H	15.37	16.25	16.13	17.02	17.96	19.42	20.31	20.19	21.08	22.02
	8H	15.37	16.21	16.15	17.00	17.95	19.50	20.34	20.28	21.13	22.07
	12H	15.35	16.15	16.14	16.94	17.91	19.55	20.35	20.33	21.13	22.10
4H	2H	15.59	16.54	16.35	17.30	18.23	17.77	18.73	18.53	19.49	20.41
	3H	16.64	17.43	17.41	18.23	19.18	19.29	20.09	20.06	20.88	21.83
	4H	16.93	17.65	17.71	18.45	19.42	19.82	20.55	20.61	21.34	22.32
	6H	17.07	17.69	17.87	18.51	19.49	20.20	20.82	21.00	21.64	22.62
	8H	17.08	17.66	17.88	18.48	19.47	20.30	20.89	21.11	21.71	22.70
	12H	17.06	17.59	17.89	18.42	19.42	20.37	20.90	21.20	21.73	22.73
8H	4H	17.40	17.98	18.20	18.80	19.79	19.97	20.56	20.78	21.37	22.36
	6H	17.67	18.15	18.50	19.01	20.01	20.41	20.89	21.25	21.75	22.75
	8H	17.71	18.14	18.56	19.00	20.01	20.56	20.99	21.41	21.85	22.86
	12H	17.71	18.09	18.56	18.94	20.00	20.66	21.04	21.51	21.89	22.96
12H	4H	17.41	17.94	18.24	18.78	19.78	19.95	20.47	20.77	21.31	22.31
	6H	17.73	18.16	18.58	19.02	20.03	20.41	20.84	21.26	21.70	22.71
	8H	17.81	18.19	18.66	19.04	20.10	20.58	20.96	21.43	21.80	22.87

END OF REPORT