

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P701267

Luminaire Tested: SQ4P-WB-0U-050D-B50-1D-UNV-

Issue Date: 8/14/2023

Test Information

Test Method: LM-79-2019
Report Number: P701267
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P519276)
Test Lab: INNOVATION CENTER
Issue Date: 8/14/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ4P-WB-0U-050D-B50-1D-UNV-
Description: CORELITE SQ4 SUSPENDED LED LUMINAIRE WITH, DIRECT ONLY 500 LUMENS PER FOOT DOV

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1580.4 lumens
Efficiency: N/A
Efficacy: 94.1 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 1 / 1.02
Luminous Opening: Rectangular (W 0.29' x L: 4' x H: 0')
CIE Type: Direct

Input Watts (W): 16.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P701267

CATALOG NUMBER: SQ4P-WB-0U-050D-B50-1D-UNV-

Luminous Intensity Polar Plot



TEST NUMBER: P701267

CATALOG NUMBER: SQ4P-WB-0U-050D-B50-1D-UNV-

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	111	107	104	101	109	105	102	99	101	99	96		97	95	93		94
2	103	97	91	87	101	95	90	86	92	87	84		88	85	82		85
3	96	87	81	75	94	86	80	75	83	78	73		80	76	72		78
4	89	79	72	66	87	78	71	66	76	70	65		74	68	64		71
5	83	72	65	59	81	71	64	59	69	63	58		67	62	58		66
6	78	66	59	53	76	65	58	53	64	57	53		62	56	52		61
7	73	61	53	48	71	60	53	48	59	52	48		58	52	47		56
8	68	57	49	44	67	56	49	44	55	48	44		53	48	43		52
9	64	53	45	40	63	52	45	40	51	45	40		50	44	40		49
10	61	49	42	37	60	48	42	37	48	41	37		47	41	37		46

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	10006	10006	10006
5°	9881	9846	9903
10°	9336	9420	9639
15°	8618	8819	9214
20°	7826	8120	8658
25°	7020	7403	8067
30°	6277	6687	7452
35°	5487	5885	6727
40°	4619	4986	5823
45°	3813	4141	4862
50°	3182	3469	4051
55°	2701	2977	3344
60°	2310	2581	2670
65°	1840	2170	1722
70°	1632	1694	1052
75°	1511	1376	645
80°	1392	1265	558
85°	1249	1154	455

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 45°

Luminance: 4862 cd/sqm

TEST NUMBER: P701267

CATALOG NUMBER: SQ4P-WB-0U-050D-B50-1D-UNV-

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	99.5	6.3
10°-20°	258.8	16.4
20°-30°	335.1	21.2
30°-40°	328.2	20.8
40°-50°	251.2	15.9
50°-60°	167.4	10.6
60°-70°	91.3	5.8
70°-80°	38.1	2.4
80°-90°	10.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	693.4	43.9
0°-40°	1021.6	64.6
0°-60°	1440.2	91.1
0°-90°	1580.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1580.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1084	1084	1084	1084	1084	
5°	1067	1056	1063	1066	1069	99
15°	902	899	923	948	965	252
25°	690	692	727	759	792	317
35°	487	490	522	558	597	303
45°	292	298	317	341	373	228
55°	168	175	185	192	208	152
65°	84	91	99	87	79	88
75°	42	42	39	26	18	45
85°	12	12	11	7	4	13
90°	0	0	0	0	0	

TEST NUMBER: P701267

CATALOG NUMBER: SQ4P-WB-0U-050D-B50-1D-UNV-

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1084.5	1084.5	1084.5	1084.5	1084.5
2.5°	1087.2	1077.5	1080.0	1079.9	1076.8
5°	1066.9	1056.2	1063.1	1065.6	1069.3
7.5°	1027.3	1019.2	1031.8	1041.1	1048.7
10°	996.5	989.5	1005.5	1019.1	1028.9
12.5°	960.8	954.8	974.8	992.9	1005.6
15°	902.2	899.0	923.3	948.3	964.6
17.5°	839.8	838.2	866.0	895.3	916.0
20°	797.1	796.7	827.0	857.7	881.8
22.5°	754.1	755.1	787.0	818.8	846.4
25°	689.6	691.5	727.2	758.9	792.4
27.5°	629.9	630.7	667.6	701.1	736.9
30°	589.2	591.4	627.7	662.3	699.5
32.5°	548.5	551.1	586.6	622.3	660.3
35°	487.2	489.6	522.5	557.7	597.3
37.5°	424.2	427.5	456.7	489.8	528.8
40°	383.5	388.2	414.0	445.4	483.5
42.5°	344.3	350.2	374.1	403.8	438.1
45°	292.2	297.8	317.4	341.4	372.6
47.5°	247.2	253.7	268.8	289.5	316.1
50°	221.7	227.8	241.7	257.0	282.2
52.5°	199.3	205.4	217.7	229.5	251.0
55°	167.9	175.0	185.1	192.2	207.9
57.5°	142.3	149.0	157.1	160.2	169.7
60°	125.2	132.6	139.9	139.5	144.7
62.5°	109.6	116.0	123.1	118.1	118.4
65°	84.3	91.2	99.4	86.9	78.9
67.5°	68.1	69.5	78.0	60.6	51.2
70°	60.5	60.5	62.8	46.9	39.0
72.5°	53.2	53.2	51.0	38.2	29.8
75°	42.4	42.4	38.6	26.5	18.1
77.5°	32.7	32.3	29.5	19.7	13.1
80°	26.2	26.2	23.8	15.6	10.5
82.5°	20.5	20.5	18.5	12.2	7.7
85°	11.8	11.8	10.9	7.1	4.3
87.5°	4.2	4.2	3.8	2.3	1.9
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)