

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: CORELITE

Report Number: P1428085

Luminaire Tested: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

Issue Date: 3/10/2026

Test Information

Test Method: LM-79-2019
Report Number: P1428085
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2303-941-3, G2-2308-131-7)
Test Lab: INNOVATION CENTER
Issue Date: 3/10/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: CORELITE
Catalog Number: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4
Description: CORELITE SQ2W WALL MOUNTED LED LUMINAIRE
DOWNLIGHT - PERCEIVE PRISM LENS
UPLIGHT - ASYMMETRIC ROLL LENS
DOWNLIGHT 500 LUMENS PER FOOT
UPLIGHT 1000 LUMENS PER FOOT
Light Source: 4000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 7288.8 lumens
Efficiency: N/A
Efficacy: 143.2 lumens/watt
Spacing Criteria (0/90/45): 1.26 / 1.41 / 1.4
Luminous Opening: Rectangular (W 0.17' x L: 4' x H: 0')
CIE Type: Semi-Indirect

Input Watts (W): 50.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

Luminous Intensity Polar Plot





TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	104	104	104	104	95	95	95	95	77	77	77	60	60	60	45	45	45	38
1	96	91	88	84	87	83	80	77	68	66	64	54	52	51	41	40	39	33
2	87	80	74	70	79	73	68	64	60	56	53	48	45	43	36	35	33	28
3	80	71	64	58	72	65	59	54	53	49	45	42	39	37	32	30	29	24
4	73	63	55	49	66	57	51	46	47	42	39	38	34	32	29	27	25	21
5	67	56	48	42	61	51	44	39	42	37	33	34	30	28	26	24	22	18
6	62	50	42	37	56	46	39	34	38	33	29	31	27	24	24	21	19	16
7	57	45	38	32	52	42	35	30	35	29	26	28	24	21	22	19	17	15
8	53	41	34	28	48	38	31	27	31	26	23	26	22	19	20	17	15	13
9	49	37	30	25	45	34	28	24	29	24	20	23	20	17	18	16	14	12
10	46	34	27	23	42	32	25	21	26	22	18	22	18	15	17	15	13	11

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	17800	17800	17800	17800
5°	17661	17982	17661	17982
10°	17750	18113	17750	18113
15°	17708	18156	17708	18156
20°	17580	18522	17580	18522
25°	17482	19495	17482	19495
30°	17381	19902	17381	19902
35°	17136	19939	17136	19939
40°	16678	18423	16678	18423
45°	16180	14024	16180	14024
50°	15543	11680	15543	11680
55°	14466	8397	14466	8397
60°	12458	6022	12458	6022
65°	10506	5922	10506	5922
70°	8747	5665	8747	5665
75°	7417	5309	7417	5309
80°	6285	4770	6285	4770
85°	4965	2593	4965	2593

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 40°
 Vertical Angle: 45°
 Luminance: 17698 cd/sqm



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	105.0	1.4
10°-20°	303.8	4.2
20°-30°	476.0	6.5
30°-40°	587.2	8.1
40°-50°	552.8	7.6
50°-60°	391.4	5.4
60°-70°	223.0	3.1
70°-80°	110.4	1.5
80°-90°	33.4	0.5
90°-100°	122.8	1.7
100°-110°	358.2	4.9
110°-120°	584.5	8.0
120°-130°	741.7	10.2
130°-140°	793.6	10.9
140°-150°	741.1	10.2
150°-160°	609.8	8.4
160°-170°	409.0	5.6
170°-180°	145.2	2.0
0°-30°	884.8	12.1
0°-40°	1471.9	20.2
0°-60°	2416.1	33.1
0°-90°	2783.0	38.2
90°-120°	1065.5	14.6
90°-150°	3341.8	45.8
90°-180°	4506.0	61.8
0°-180°	7288.8	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1102	1102	1102	1102	1102	
5°	1090	1110	1090	1110	1090	104
15°	1059	1086	1059	1086	1059	299
25°	981	1094	981	1094	981	452
35°	869	1012	869	1012	869	542
45°	709	614	709	614	709	545
55°	514	298	514	298	514	453
65°	275	155	275	155	275	276
75°	119	85	119	85	119	129
85°	27	14	27	14	27	32
90°	5	34	5	67	5	5
95°	48	36	48	210	48	58
105°	228	365	228	502	228	242
115°	436	605	436	745	436	430
125°	645	959	645	913	645	577
135°	878	1255	878	1012	878	678
145°	1121	1446	1121	1034	1121	701
155°	1331	1571	1331	1072	1331	612
165°	1472	1638	1472	1235	1472	414
175°	1538	1604	1538	1448	1538	146
180°	1543	1543	1543	1543	1543	



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (FULL):

	0°	10°	20°	30°	40°	50°	60°	70°	80°	90°	100°
0°	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5
2.5°	1094.1	1101.1	1108.2	1106.5	1102.0	1100.1	1100.9	1101.8	1102.6	1103.4	1102.6
5°	1089.7	1098.5	1107.3	1106.0	1101.3	1099.5	1100.5	1102.2	1105.8	1109.5	1105.8
7.5°	1085.5	1094.5	1103.5	1102.3	1097.8	1096.4	1098.1	1100.6	1105.0	1109.5	1105.0
10°	1082.7	1090.4	1098.2	1097.0	1092.9	1092.1	1094.7	1097.6	1101.2	1104.8	1101.2
12.5°	1074.3	1081.6	1089.0	1088.0	1084.3	1084.1	1087.6	1090.9	1094.1	1097.4	1094.1
15°	1059.4	1066.1	1072.8	1073.0	1070.9	1072.2	1076.8	1081.0	1083.6	1086.2	1083.6
17.5°	1039.1	1047.3	1055.4	1057.3	1057.1	1060.3	1067.0	1072.6	1075.3	1078.0	1075.3
20°	1023.2	1033.1	1042.9	1046.2	1047.2	1051.8	1060.1	1067.6	1072.8	1078.0	1072.8
22.5°	1006.4	1017.9	1029.4	1033.7	1035.6	1042.7	1055.2	1066.7	1075.6	1084.5	1075.6
25°	981.3	992.7	1004.1	1012.4	1019.6	1032.3	1050.4	1067.4	1080.9	1094.3	1080.9
27.5°	951.9	963.2	974.5	988.7	1004.0	1021.8	1042.2	1060.2	1070.8	1081.5	1070.8
30°	932.3	943.2	954.1	970.4	988.5	1008.2	1029.4	1047.8	1057.7	1067.5	1057.7
32.5°	908.1	919.4	930.7	948.0	967.4	988.5	1011.4	1030.8	1039.9	1048.9	1039.9
35°	869.4	880.3	891.2	911.4	934.7	958.2	982.1	1001.2	1006.4	1011.6	1006.4
37.5°	824.9	837.2	849.5	872.2	898.3	918.0	931.4	941.5	941.8	942.1	941.8
40°	791.3	807.4	823.4	846.1	871.0	884.7	887.3	887.5	880.8	874.1	880.8
42.5°	758.7	779.3	799.9	818.1	835.5	839.1	828.8	813.7	783.7	753.8	783.7
45°	708.6	732.9	757.3	768.4	775.1	752.3	700.0	655.6	634.9	614.2	634.9
47.5°	655.2	679.2	703.3	700.2	688.1	653.6	596.7	550.5	536.2	521.9	536.2
50°	618.8	641.6	664.4	648.0	618.4	579.6	531.4	491.9	478.5	465.0	478.5
52.5°	577.8	598.1	618.4	593.6	553.7	512.8	470.8	434.2	413.7	393.2	413.7
55°	513.9	527.9	541.9	514.7	473.8	428.7	379.5	337.7	318.0	298.3	318.0
57.5°	437.0	446.9	456.7	435.3	403.5	358.7	300.9	252.0	230.0	207.9	230.0
60°	385.8	393.5	401.3	381.9	353.4	310.6	253.7	208.2	197.3	186.5	197.3
62.5°	339.1	346.1	353.0	332.8	303.4	265.3	218.2	182.0	178.2	174.3	178.2
65°	275.0	281.8	288.5	267.3	236.7	206.9	177.9	156.0	155.5	155.0	155.5
67.5°	218.9	226.2	233.6	213.6	184.5	162.5	147.5	136.2	135.6	135.0	135.6
70°	185.3	193.1	200.8	182.2	154.7	136.9	128.6	122.1	121.1	120.0	121.1
72.5°	157.3	164.7	172.0	155.8	131.6	116.9	111.5	107.3	106.7	106.1	106.7
75°	118.9	124.6	130.3	118.5	100.9	90.8	88.2	86.1	85.6	85.1	85.6
77.5°	86.2	89.9	93.5	85.8	74.3	67.9	66.5	65.4	64.8	64.3	64.8
80°	67.6	69.1	70.7	65.3	57.5	53.3	52.8	52.3	51.8	51.3	51.8
82.5°	50.8	50.3	49.8	46.6	42.6	40.3	39.8	39.2	38.2	37.3	38.2
85°	26.8	25.8	24.7	23.7	22.7	21.1	19.0	17.1	15.5	14.0	15.5
87.5°	9.3	10.6	12.1	11.8	10.7	9.8	9.3	9.3	9.7	9.7	9.7
90°	4.7	10.9	18.7	24.9	29.6	31.2	31.2	32.7	34.3	34.3	34.3
92.5°	17.1	27.1	27.4	27.4	33.4	36.2	38.7	39.0	40.5	40.5	40.5
95°	48.3	53.0	79.5	77.9	53.0	42.1	35.9	35.9	35.9	35.9	35.9
97.5°	92.3	99.1	103.5	138.7	146.5	141.5	115.3	97.0	86.7	82.0	86.7
100°	130.9	134.1	143.4	145.0	183.9	221.3	202.6	179.3	171.5	166.8	171.5
102.5°	169.6	171.5	185.8	192.4	201.4	222.6	287.4	280.3	275.0	274.0	275.0
105°	227.6	229.1	255.6	268.1	274.3	274.3	272.8	304.0	353.8	364.8	353.8
107.5°	289.6	296.8	328.0	361.3	368.5	370.4	362.3	357.6	355.7	357.0	355.7
110°	332.0	342.9	380.3	422.4	433.3	436.5	433.3	428.7	425.5	425.5	425.5



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	0°	10°	20°	30°	40°	50°	60°	70°	80°	90°	100°
112.5°	373.2	389.1	431.5	479.8	498.2	507.5	500.7	497.2	494.1	496.6	494.1
115°	436.5	459.8	516.0	565.8	603.2	607.9	606.4	606.4	604.8	604.8	604.8
117.5°	495.1	532.5	595.5	653.4	696.8	709.2	715.5	713.6	711.7	714.9	711.7
120°	536.2	579.9	651.6	717.0	759.1	777.8	784.1	780.9	784.1	780.9	784.1
122.5°	579.9	633.5	703.9	771.9	821.5	842.7	850.2	850.8	851.4	849.5	851.4
125°	645.3	710.8	793.4	863.6	915.0	939.9	946.2	947.7	950.9	958.6	950.9
127.5°	711.4	785.6	876.3	944.0	996.7	1026.9	1036.6	1040.0	1046.6	1050.0	1046.6
130°	757.6	841.7	933.7	997.6	1049.1	1081.8	1098.9	1103.6	1111.4	1109.8	1111.4
132.5°	806.2	894.1	987.3	1053.7	1101.4	1136.7	1151.3	1164.7	1167.5	1169.7	1167.5
135°	877.6	972.7	1066.2	1131.7	1176.9	1211.2	1229.9	1242.3	1250.1	1254.8	1250.1
137.5°	952.7	1053.1	1142.9	1201.2	1246.7	1276.3	1297.5	1310.6	1318.7	1322.5	1318.7
140°	1003.9	1100.5	1187.8	1248.6	1289.1	1318.7	1337.4	1353.0	1362.4	1362.4	1362.4
142.5°	1052.5	1147.9	1232.7	1293.5	1329.0	1356.1	1376.1	1387.9	1398.5	1398.5	1398.5
145°	1120.8	1215.8	1293.8	1354.6	1384.2	1409.1	1431.0	1440.3	1446.5	1446.5	1446.5
147.5°	1192.2	1276.3	1347.4	1405.7	1430.6	1459.9	1477.1	1484.6	1492.4	1488.9	1492.4
150°	1234.6	1312.5	1381.1	1435.6	1460.6	1488.6	1505.8	1512.0	1519.8	1515.1	1519.8
152.5°	1275.7	1349.9	1412.3	1463.1	1484.3	1512.3	1532.0	1538.2	1543.5	1540.1	1543.5
155°	1331.2	1396.7	1454.3	1501.1	1519.8	1546.3	1565.0	1572.8	1579.0	1571.2	1579.0
157.5°	1380.8	1437.2	1487.4	1530.4	1550.4	1573.1	1590.6	1600.2	1606.5	1603.0	1606.5
160°	1410.7	1462.1	1507.3	1547.9	1566.6	1586.8	1605.5	1616.5	1622.7	1618.0	1622.7
162.5°	1435.6	1482.1	1524.8	1561.6	1577.8	1595.6	1618.0	1627.7	1633.9	1628.0	1633.9
165°	1471.5	1508.9	1546.3	1577.5	1591.5	1605.5	1628.9	1639.8	1644.5	1638.3	1644.5
167.5°	1498.6	1527.3	1557.5	1584.3	1594.6	1608.3	1631.7	1640.8	1646.7	1638.9	1646.7
170°	1513.6	1538.5	1565.0	1586.8	1594.6	1607.1	1630.5	1638.3	1643.0	1635.2	1643.0
172.5°	1526.0	1544.7	1566.3	1585.6	1589.6	1599.6	1621.8	1629.5	1633.0	1626.4	1633.0
175°	1538.5	1549.4	1565.0	1577.5	1575.9	1582.2	1600.9	1607.1	1613.3	1604.0	1613.3
177.5°	1544.4	1549.4	1554.4	1561.9	1556.9	1556.9	1570.6	1574.4	1575.6	1570.6	1575.6
180°	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	110°	120°	130°	140°	150°	160°	170°	180°	190°	200°	210°
0°	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5
2.5°	1101.8	1100.9	1100.1	1102.0	1106.5	1108.2	1101.1	1094.1	1101.1	1108.2	1106.5
5°	1102.2	1100.5	1099.5	1101.3	1106.0	1107.3	1098.5	1089.7	1098.5	1107.3	1106.0
7.5°	1100.6	1098.1	1096.4	1097.8	1102.3	1103.5	1094.5	1085.5	1094.5	1103.5	1102.3
10°	1097.6	1094.7	1092.1	1092.9	1097.0	1098.2	1090.4	1082.7	1090.4	1098.2	1097.0
12.5°	1090.9	1087.6	1084.1	1084.3	1088.0	1089.0	1081.6	1074.3	1081.6	1089.0	1088.0
15°	1081.0	1076.8	1072.2	1070.9	1073.0	1072.8	1066.1	1059.4	1066.1	1072.8	1073.0
17.5°	1072.6	1067.0	1060.3	1057.1	1057.3	1055.4	1047.3	1039.1	1047.3	1055.4	1057.3
20°	1067.6	1060.1	1051.8	1047.2	1046.2	1042.9	1033.1	1023.2	1033.1	1042.9	1046.2
22.5°	1066.7	1055.2	1042.7	1035.6	1033.7	1029.4	1017.9	1006.4	1017.9	1029.4	1033.7
25°	1067.4	1050.4	1032.3	1019.6	1012.4	1004.1	992.7	981.3	992.7	1004.1	1012.4
27.5°	1060.2	1042.2	1021.8	1004.0	988.7	974.5	963.2	951.9	963.2	974.5	988.7
30°	1047.8	1029.4	1008.2	988.5	970.4	954.1	943.2	932.3	943.2	954.1	970.4
32.5°	1030.8	1011.4	988.5	967.4	948.0	930.7	919.4	908.1	919.4	930.7	948.0
35°	1001.2	982.1	958.2	934.7	911.4	891.2	880.3	869.4	880.3	891.2	911.4
37.5°	941.5	931.4	918.0	898.3	872.2	849.5	837.2	824.9	837.2	849.5	872.2
40°	887.5	887.3	884.7	871.0	846.1	823.4	807.4	791.3	807.4	823.4	846.1
42.5°	813.7	828.8	839.1	835.5	818.1	799.9	779.3	758.7	779.3	799.9	818.1
45°	655.6	700.0	752.3	775.1	768.4	757.3	732.9	708.6	732.9	757.3	768.4
47.5°	550.5	596.7	653.6	688.1	700.2	703.3	679.2	655.2	679.2	703.3	700.2
50°	491.9	531.4	579.6	618.4	648.0	664.4	641.6	618.8	641.6	664.4	648.0
52.5°	434.2	470.8	512.8	553.7	593.6	618.4	598.1	577.8	598.1	618.4	593.6
55°	337.7	379.5	428.7	473.8	514.7	541.9	527.9	513.9	527.9	541.9	514.7
57.5°	252.0	300.9	358.7	403.5	435.3	456.7	446.9	437.0	446.9	456.7	435.3
60°	208.2	253.7	310.6	353.4	381.9	401.3	393.5	385.8	393.5	401.3	381.9
62.5°	182.0	218.2	265.3	303.4	332.8	353.0	346.1	339.1	346.1	353.0	332.8
65°	156.0	177.9	206.9	236.7	267.3	288.5	281.8	275.0	281.8	288.5	267.3
67.5°	136.2	147.5	162.5	184.5	213.6	233.6	226.2	218.9	226.2	233.6	213.6
70°	122.1	128.6	136.9	154.7	182.2	200.8	193.1	185.3	193.1	200.8	182.2
72.5°	107.3	111.5	116.9	131.6	155.8	172.0	164.7	157.3	164.7	172.0	155.8
75°	86.1	88.2	90.8	100.9	118.5	130.3	124.6	118.9	124.6	130.3	118.5
77.5°	65.4	66.5	67.9	74.3	85.8	93.5	89.9	86.2	89.9	93.5	85.8
80°	52.3	52.8	53.3	57.5	65.3	70.7	69.1	67.6	69.1	70.7	65.3
82.5°	39.2	39.8	40.3	42.6	46.6	49.8	50.3	50.8	50.3	49.8	46.6
85°	17.1	19.0	21.1	22.7	23.7	24.7	25.8	26.8	25.8	24.7	23.7
87.5°	9.3	9.3	9.8	10.7	11.8	12.1	10.6	9.3	10.6	11.8	12.4
90°	32.7	31.2	31.2	29.6	24.9	18.7	10.9	4.7	10.9	17.1	28.1
92.5°	39.0	38.7	36.2	33.4	27.4	27.4	27.1	17.1	29.6	42.1	60.5
95°	35.9	35.9	42.1	53.0	77.9	79.5	53.0	48.3	68.6	96.6	121.6
97.5°	97.0	115.3	141.5	146.5	138.7	103.5	99.1	92.3	125.6	153.4	193.6
100°	179.3	202.6	221.3	183.9	145.0	143.4	134.1	130.9	166.8	193.3	232.3
102.5°	280.3	287.4	222.6	201.4	192.4	185.8	171.5	169.6	205.4	241.9	274.7
105°	304.0	272.8	274.3	274.3	268.1	255.6	229.1	227.6	268.1	310.2	350.7
107.5°	357.6	362.3	370.4	368.5	361.3	328.0	296.8	289.6	326.1	376.6	421.2
110°	428.7	433.3	436.5	433.3	422.4	380.3	342.9	332.0	364.8	417.8	466.1



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	110°	120°	130°	140°	150°	160°	170°	180°	190°	200°	210°
112.5°	497.2	500.7	507.5	498.2	479.8	431.5	389.1	373.2	405.9	460.2	509.7
115°	606.4	606.4	607.9	603.2	565.8	516.0	459.8	436.5	464.5	514.4	569.0
117.5°	713.6	715.5	709.2	696.8	653.4	595.5	532.5	495.1	517.2	569.9	626.0
120°	780.9	784.1	777.8	759.1	717.0	651.6	579.9	536.2	553.4	604.8	660.9
122.5°	850.8	850.2	842.7	821.5	771.9	703.9	633.5	579.9	587.0	634.7	689.6
125°	947.7	946.2	939.9	915.0	863.6	793.4	710.8	645.3	636.0	676.5	732.6
127.5°	1040.0	1036.6	1026.9	996.7	944.0	876.3	785.6	711.4	690.5	716.1	767.5
130°	1103.6	1098.9	1081.8	1049.1	997.6	933.7	841.7	757.6	727.9	743.5	788.7
132.5°	1164.7	1151.3	1136.7	1101.4	1053.7	987.3	894.1	806.2	765.4	772.2	807.4
135°	1242.3	1229.9	1211.2	1176.9	1131.7	1066.2	972.7	877.6	821.5	815.2	835.5
137.5°	1310.6	1297.5	1276.3	1246.7	1201.2	1142.9	1053.1	952.7	882.0	861.1	868.9
140°	1353.0	1337.4	1318.7	1289.1	1248.6	1187.8	1100.5	1003.9	924.4	894.7	890.1
142.5°	1387.9	1376.1	1356.1	1329.0	1293.5	1232.7	1147.9	1052.5	968.0	929.7	918.7
145°	1440.3	1431.0	1409.1	1384.2	1354.6	1293.8	1215.8	1120.8	1036.6	986.7	963.3
147.5°	1484.6	1477.1	1459.9	1430.6	1405.7	1347.4	1276.3	1192.2	1105.8	1044.1	1013.8
150°	1512.0	1505.8	1488.6	1460.6	1435.6	1381.1	1312.5	1234.6	1151.9	1086.5	1047.5
152.5°	1538.2	1532.0	1512.3	1484.3	1463.1	1412.3	1349.9	1275.7	1191.8	1126.4	1086.2
155°	1572.8	1565.0	1546.3	1519.8	1501.1	1454.3	1396.7	1331.2	1259.5	1190.9	1145.7
157.5°	1600.2	1590.6	1573.1	1550.4	1530.4	1487.4	1437.2	1380.8	1318.1	1252.6	1206.5
160°	1616.5	1605.5	1586.8	1566.6	1547.9	1507.3	1462.1	1410.7	1353.0	1293.8	1243.9
162.5°	1627.7	1618.0	1595.6	1577.8	1561.6	1524.8	1482.1	1435.6	1384.2	1332.4	1286.3
165°	1639.8	1628.9	1605.5	1591.5	1577.5	1546.3	1508.9	1471.5	1427.8	1385.8	1348.3
167.5°	1640.8	1631.7	1608.3	1594.6	1584.3	1557.5	1527.3	1498.6	1464.6	1431.6	1400.4
170°	1638.3	1630.5	1607.1	1594.6	1586.8	1565.0	1538.5	1513.6	1487.1	1459.0	1434.1
172.5°	1629.5	1621.8	1599.6	1589.6	1585.6	1566.3	1544.7	1526.0	1503.3	1482.7	1462.8
175°	1607.1	1600.9	1582.2	1575.9	1577.5	1565.0	1549.4	1538.5	1524.5	1512.0	1501.1
177.5°	1574.4	1570.6	1556.9	1556.9	1561.9	1554.4	1549.4	1544.4	1538.2	1534.5	1530.7
180°	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	220°	230°	240°	250°	260°	270°	280°	290°	300°	310°	320°
0°	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5	1102.5
2.5°	1102.0	1100.1	1100.9	1101.8	1102.6	1103.4	1102.6	1101.8	1100.9	1100.1	1102.0
5°	1101.3	1099.5	1100.5	1102.2	1105.8	1109.5	1105.8	1102.2	1100.5	1099.5	1101.3
7.5°	1097.8	1096.4	1098.1	1100.6	1105.0	1109.5	1105.0	1100.6	1098.1	1096.4	1097.8
10°	1092.9	1092.1	1094.7	1097.6	1101.2	1104.8	1101.2	1097.6	1094.7	1092.1	1092.9
12.5°	1084.3	1084.1	1087.6	1090.9	1094.1	1097.4	1094.1	1090.9	1087.6	1084.1	1084.3
15°	1070.9	1072.2	1076.8	1081.0	1083.6	1086.2	1083.6	1081.0	1076.8	1072.2	1070.9
17.5°	1057.1	1060.3	1067.0	1072.6	1075.3	1078.0	1075.3	1072.6	1067.0	1060.3	1057.1
20°	1047.2	1051.8	1060.1	1067.6	1072.8	1078.0	1072.8	1067.6	1060.1	1051.8	1047.2
22.5°	1035.6	1042.7	1055.2	1066.7	1075.6	1084.5	1075.6	1066.7	1055.2	1042.7	1035.6
25°	1019.6	1032.3	1050.4	1067.4	1080.9	1094.3	1080.9	1067.4	1050.4	1032.3	1019.6
27.5°	1004.0	1021.8	1042.2	1060.2	1070.8	1081.5	1070.8	1060.2	1042.2	1021.8	1004.0
30°	988.5	1008.2	1029.4	1047.8	1057.7	1067.5	1057.7	1047.8	1029.4	1008.2	988.5
32.5°	967.4	988.5	1011.4	1030.8	1039.9	1048.9	1039.9	1030.8	1011.4	988.5	967.4
35°	934.7	958.2	982.1	1001.2	1006.4	1011.6	1006.4	1001.2	982.1	958.2	934.7
37.5°	898.3	918.0	931.4	941.5	941.8	942.1	941.8	941.5	931.4	918.0	898.3
40°	871.0	884.7	887.3	887.5	880.8	874.1	880.8	887.5	887.3	884.7	871.0
42.5°	835.5	839.1	828.8	813.7	783.7	753.8	783.7	813.7	828.8	839.1	835.5
45°	775.1	752.3	700.0	655.6	634.9	614.2	634.9	655.6	700.0	752.3	775.1
47.5°	688.1	653.6	596.7	550.5	536.2	521.9	536.2	550.5	596.7	653.6	688.1
50°	618.4	579.6	531.4	491.9	478.5	465.0	478.5	491.9	531.4	579.6	618.4
52.5°	553.7	512.8	470.8	434.2	413.7	393.2	413.7	434.2	470.8	512.8	553.7
55°	473.8	428.7	379.5	337.7	318.0	298.3	318.0	337.7	379.5	428.7	473.8
57.5°	403.5	358.7	300.9	252.0	230.0	207.9	230.0	252.0	300.9	358.7	403.5
60°	353.4	310.6	253.7	208.2	197.3	186.5	197.3	208.2	253.7	310.6	353.4
62.5°	303.4	265.3	218.2	182.0	178.2	174.3	178.2	182.0	218.2	265.3	303.4
65°	236.7	206.9	177.9	156.0	155.5	155.0	155.5	156.0	177.9	206.9	236.7
67.5°	184.5	162.5	147.5	136.2	135.6	135.0	135.6	136.2	147.5	162.5	184.5
70°	154.7	136.9	128.6	122.1	121.1	120.0	121.1	122.1	128.6	136.9	154.7
72.5°	131.6	116.9	111.5	107.3	106.7	106.1	106.7	107.3	111.5	116.9	131.6
75°	100.9	90.8	88.2	86.1	85.6	85.1	85.6	86.1	88.2	90.8	100.9
77.5°	74.3	67.9	66.5	65.4	64.8	64.3	64.8	65.4	66.5	67.9	74.3
80°	57.5	53.3	52.8	52.3	51.8	51.3	51.8	52.3	52.8	53.3	57.5
82.5°	42.6	40.3	39.8	39.2	38.2	37.3	38.2	39.2	39.8	40.3	42.6
85°	22.7	21.1	19.0	17.1	15.5	14.0	15.5	17.1	19.0	21.1	22.7
87.5°	11.9	12.9	14.6	15.6	16.8	16.2	16.8	15.6	14.6	12.9	11.9
90°	35.9	46.8	57.7	63.9	70.1	67.0	70.1	63.9	57.7	46.8	35.9
92.5°	72.0	90.4	103.8	115.0	120.0	119.4	120.0	115.0	103.8	90.4	72.0
95°	145.0	166.8	188.6	204.2	213.6	210.4	213.6	204.2	188.6	166.8	145.0
97.5°	223.5	252.8	277.2	291.8	301.2	307.4	301.2	291.8	277.2	252.8	223.5
100°	275.9	304.0	332.0	349.2	364.8	371.0	364.8	349.2	332.0	304.0	275.9
102.5°	318.3	355.1	385.6	404.0	417.1	423.4	417.1	404.0	385.6	355.1	318.3
105°	388.1	427.1	459.8	483.2	497.2	501.9	497.2	483.2	459.8	427.1	388.1
107.5°	458.0	498.2	528.4	554.3	571.4	581.4	571.4	554.3	528.4	498.2	458.0
110°	512.8	545.6	578.3	601.7	618.8	625.1	618.8	601.7	578.3	545.6	512.8



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	220°	230°	240°	250°	260°	270°	280°	290°	300°	310°	320°
112.5°	559.0	595.5	628.2	651.6	671.2	679.9	671.2	651.6	628.2	595.5	559.0
115°	623.5	671.8	701.4	723.3	737.3	745.1	737.3	723.3	701.4	671.8	623.5
117.5°	677.1	727.6	760.1	776.9	783.4	789.1	783.4	776.9	760.1	727.6	677.1
120°	710.8	757.6	795.0	816.8	824.6	827.7	824.6	816.8	795.0	757.6	710.8
122.5°	742.0	786.2	822.4	849.2	862.0	865.1	862.0	849.2	822.4	786.2	742.0
125°	785.6	827.7	865.1	891.6	905.6	913.4	905.6	891.6	865.1	827.7	785.6
127.5°	823.7	869.2	903.5	927.5	941.2	947.4	941.2	927.5	903.5	869.2	823.7
130°	844.9	891.6	925.9	952.4	964.9	971.1	964.9	952.4	925.9	891.6	844.9
132.5°	861.1	910.3	945.9	969.9	983.6	989.8	983.6	969.9	945.9	910.3	861.1
135°	880.7	932.1	969.6	992.9	1005.4	1011.6	1005.4	992.9	969.6	932.1	880.7
137.5°	897.9	944.6	983.6	1008.2	1019.4	1023.5	1019.4	1008.2	983.6	944.6	897.9
140°	910.3	950.9	989.8	1013.2	1025.7	1027.2	1025.7	1013.2	989.8	950.9	910.3
142.5°	926.5	958.3	992.3	1015.7	1028.2	1031.0	1028.2	1015.7	992.3	958.3	926.5
145°	955.5	974.2	997.6	1019.4	1030.4	1033.5	1030.4	1019.4	997.6	974.2	955.5
147.5°	992.0	997.9	1010.1	1024.4	1035.0	1037.2	1035.0	1024.4	1010.1	997.9	992.0
150°	1019.4	1017.9	1022.6	1031.9	1041.3	1039.7	1041.3	1031.9	1022.6	1017.9	1019.4
152.5°	1050.6	1041.6	1041.3	1045.6	1050.0	1049.7	1050.0	1045.6	1041.3	1041.6	1050.6
155°	1103.6	1086.5	1077.1	1074.0	1074.0	1072.4	1074.0	1074.0	1077.1	1086.5	1103.6
157.5°	1161.9	1137.9	1123.9	1116.4	1114.2	1110.8	1114.2	1116.4	1123.9	1137.9	1161.9
160°	1201.8	1175.3	1161.3	1148.8	1144.1	1139.5	1144.1	1148.8	1161.3	1175.3	1201.8
162.5°	1239.2	1214.0	1198.7	1187.5	1182.8	1175.6	1182.8	1187.5	1198.7	1214.0	1239.2
165°	1300.0	1273.5	1256.4	1247.0	1240.8	1234.6	1240.8	1247.0	1256.4	1273.5	1300.0
167.5°	1360.8	1331.8	1320.6	1310.0	1304.1	1292.8	1304.1	1310.0	1320.6	1331.8	1360.8
170°	1398.2	1371.7	1365.5	1356.1	1345.2	1332.8	1345.2	1356.1	1365.5	1371.7	1398.2
172.5°	1430.6	1412.9	1406.6	1397.3	1393.9	1383.9	1393.9	1397.3	1406.6	1412.9	1430.6
175°	1477.7	1463.7	1463.7	1462.1	1457.5	1448.1	1457.5	1462.1	1463.7	1463.7	1477.7
177.5°	1517.0	1509.5	1514.5	1514.5	1513.3	1504.5	1513.3	1514.5	1514.5	1509.5	1517.0
180°	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2	1543.2



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	330°	340°	350°	360°
0°	1102.5	1102.5	1102.5	1102.5
2.5°	1106.5	1108.2	1101.1	1094.1
5°	1106.0	1107.3	1098.5	1089.7
7.5°	1102.3	1103.5	1094.5	1085.5
10°	1097.0	1098.2	1090.4	1082.7
12.5°	1088.0	1089.0	1081.6	1074.3
15°	1073.0	1072.8	1066.1	1059.4
17.5°	1057.3	1055.4	1047.3	1039.1
20°	1046.2	1042.9	1033.1	1023.2
22.5°	1033.7	1029.4	1017.9	1006.4
25°	1012.4	1004.1	992.7	981.3
27.5°	988.7	974.5	963.2	951.9
30°	970.4	954.1	943.2	932.3
32.5°	948.0	930.7	919.4	908.1
35°	911.4	891.2	880.3	869.4
37.5°	872.2	849.5	837.2	824.9
40°	846.1	823.4	807.4	791.3
42.5°	818.1	799.9	779.3	758.7
45°	768.4	757.3	732.9	708.6
47.5°	700.2	703.3	679.2	655.2
50°	648.0	664.4	641.6	618.8
52.5°	593.6	618.4	598.1	577.8
55°	514.7	541.9	527.9	513.9
57.5°	435.3	456.7	446.9	437.0
60°	381.9	401.3	393.5	385.8
62.5°	332.8	353.0	346.1	339.1
65°	267.3	288.5	281.8	275.0
67.5°	213.6	233.6	226.2	218.9
70°	182.2	200.8	193.1	185.3
72.5°	155.8	172.0	164.7	157.3
75°	118.5	130.3	124.6	118.9
77.5°	85.8	93.5	89.9	86.2
80°	65.3	70.7	69.1	67.6
82.5°	46.6	49.8	50.3	50.8
85°	23.7	24.7	25.8	26.8
87.5°	12.4	11.8	10.6	9.3
90°	28.1	17.1	10.9	4.7
92.5°	60.5	42.1	29.6	17.1
95°	121.6	96.6	68.6	48.3
97.5°	193.6	153.4	125.6	92.3
100°	232.3	193.3	166.8	130.9
102.5°	274.7	241.9	205.4	169.6
105°	350.7	310.2	268.1	227.6
107.5°	421.2	376.6	326.1	289.6
110°	466.1	417.8	364.8	332.0



TEST NUMBER: P1428085

CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CANDELA DISTRIBUTION (continued):

	330°	340°	350°	360°
112.5°	509.7	460.2	405.9	373.2
115°	569.0	514.4	464.5	436.5
117.5°	626.0	569.9	517.2	495.1
120°	660.9	604.8	553.4	536.2
122.5°	689.6	634.7	587.0	579.9
125°	732.6	676.5	636.0	645.3
127.5°	767.5	716.1	690.5	711.4
130°	788.7	743.5	727.9	757.6
132.5°	807.4	772.2	765.4	806.2
135°	835.5	815.2	821.5	877.6
137.5°	868.9	861.1	882.0	952.7
140°	890.1	894.7	924.4	1003.9
142.5°	918.7	929.7	968.0	1052.5
145°	963.3	986.7	1036.6	1120.8
147.5°	1013.8	1044.1	1105.8	1192.2
150°	1047.5	1086.5	1151.9	1234.6
152.5°	1086.2	1126.4	1191.8	1275.7
155°	1145.7	1190.9	1259.5	1331.2
157.5°	1206.5	1252.6	1318.1	1380.8
160°	1243.9	1293.8	1353.0	1410.7
162.5°	1286.3	1332.4	1384.2	1435.6
165°	1348.3	1385.8	1427.8	1471.5
167.5°	1400.4	1431.6	1464.6	1498.6
170°	1434.1	1459.0	1487.1	1513.6
172.5°	1462.8	1482.7	1503.3	1526.0
175°	1501.1	1512.0	1524.5	1538.5
177.5°	1530.7	1534.5	1538.2	1544.4
180°	1543.2	1543.2	1543.2	1543.2



TEST NUMBER: P1428085
 CATALOG NUMBER: SQ2W-PP3-K-100U-050D-L840-UNV-STD-W-WM-4

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.24	16.98	17.30	18.04	19.47	12.01	12.75	13.07	13.81	15.24
	3H	17.29	17.95	18.36	19.02	20.47	13.31	13.97	14.38	15.04	16.49
	4H	17.65	18.28	18.73	19.35	20.81	13.86	14.49	14.94	15.56	17.02
	6H	17.84	18.42	18.93	19.49	20.96	14.22	14.80	15.31	15.87	17.34
	8H	17.90	18.45	18.99	19.54	21.00	14.35	14.90	15.44	15.98	17.45
	12H	17.92	18.44	19.01	19.52	21.01	14.38	14.90	15.47	15.98	17.47
4H	2H	16.34	16.97	17.43	18.04	19.50	12.90	13.53	13.99	14.60	16.06
	3H	17.63	18.15	18.72	19.24	20.71	14.32	14.84	15.41	15.93	17.40
	4H	18.13	18.61	19.23	19.69	21.19	14.93	15.41	16.03	16.50	17.99
	6H	18.44	18.85	19.54	19.96	21.44	15.37	15.78	16.48	16.89	18.38
	8H	18.55	18.93	19.65	20.03	21.53	15.54	15.92	16.65	17.02	18.52
	12H	18.59	18.93	19.71	20.05	21.55	15.59	15.93	16.71	17.04	18.55
8H	4H	18.14	18.52	19.25	19.62	21.12	15.23	15.62	16.34	16.72	18.22
	6H	18.55	18.86	19.68	20.01	21.51	15.79	16.10	16.92	17.25	18.75
	8H	18.73	19.01	19.86	20.13	21.65	16.04	16.31	17.17	17.44	18.96
	12H	18.82	19.07	19.96	20.19	21.74	16.13	16.38	17.27	17.50	19.05
12H	4H	18.10	18.44	19.22	19.55	21.06	15.24	15.59	16.36	16.70	18.21
	6H	18.54	18.82	19.67	19.94	21.46	15.85	16.13	16.99	17.26	18.77
	8H	18.73	18.98	19.87	20.10	21.65	16.13	16.37	17.26	17.49	19.04