

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P1356817

Luminaire Tested: 2ASL4-10HE-2-A59-UNV

Issue Date: 2/17/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1356817  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2511-597-7)  
Test Lab: INNOVATION CENTER  
Issue Date: 2/17/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: FAIL-SAFE  
Catalog Number: 2ASL4-10HE-2-A59-UNV  
Description: 2FT 1000 LUMEN PER FOOT 4ASL LED LUMINAIRE WITH OPL LENS AND A59 LEDS 2 ROW  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 415.0 lumens  
Efficiency: N/A  
Efficacy: 36.1 lumens/watt  
Spacing Criteria (0/90/45): 1.21 / 1.3 / 1.4  
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 1.98' x H: 0.1')  
CIE Type: Direct

Input Watts (W): 11.5  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P1356817  
CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

### Luminous Intensity Polar Plot





TEST NUMBER: P1356817  
 CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95	95	95	95	93
1	105	100	95	90	102	97	92	88	91	87	84	86	83	80	81	79	77	77	77	77	74
2	95	86	79	72	92	84	77	71	79	73	68	74	70	65	70	66	63	63	63	63	60
3	86	75	66	59	83	73	65	58	69	62	56	65	59	55	62	57	53	53	53	53	50
4	79	66	57	50	76	64	56	49	61	54	48	58	51	46	55	49	45	45	45	45	42
5	72	59	50	43	70	57	49	42	54	47	41	52	45	40	49	43	39	39	39	39	36
6	67	53	44	37	64	52	43	37	49	41	36	47	40	35	44	39	34	34	34	34	32
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30	30	30	30	28
8	58	44	35	29	56	43	34	29	41	33	28	39	32	28	37	31	27	27	27	27	25
9	54	40	32	26	52	39	31	26	37	30	25	36	29	25	34	29	24	24	24	24	22
10	50	37	29	24	49	36	28	23	35	28	23	33	27	22	32	26	22	22	22	22	20

**AVERAGE LUMINANCE (cd/sqm):**

	0°	45°	90°
0°	1973	1973	1973
5°	1951	1930	1927
10°	1934	1892	1880
15°	1912	1850	1842
20°	1884	1798	1790
25°	1843	1747	1744
30°	1794	1689	1698
35°	1752	1635	1646
40°	1705	1577	1591
45°	1657	1528	1551
50°	1598	1462	1491
55°	1540	1390	1444
60°	1465	1312	1393
65°	1360	1237	1352
70°	1238	1167	1317
75°	1059	1111	1307
80°	796	1060	1301
85°	444	1042	1339

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 1657 cd/sqm



TEST NUMBER: P1356817  
 CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	11.5	2.8
10°-20°	33.0	7.9
20°-30°	49.9	12.0
30°-40°	60.4	14.6
40°-50°	63.7	15.3
50°-60°	59.4	14.3
60°-70°	49.1	11.8
70°-80°	35.6	8.6
80°-90°	22.5	5.4
90°-100°	13.4	3.2
100°-110°	7.7	1.9
110°-120°	4.4	1.1
120°-130°	2.5	0.6
130°-140°	1.3	0.3
140°-150°	0.6	0.1
150°-160°	0.1	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	94.3	22.7
0°-40°	154.7	37.3
0°-60°	277.8	66.9
0°-90°	385.0	92.8
90°-120°	25.5	6.1
90°-150°	29.9	7.2
90°-180°	30.0	7.2
0°-180°	415.0	100.0

**CANDELA DISTRIBUTION:**

	0°	22.5°	45°	67.5°	90°	Flux
0°	121	121	121	121	121	
5°	120	121	120	120	121	11
15°	115	116	117	118	118	32
25°	105	106	109	110	111	48
35°	91	94	97	100	101	57
45°	76	79	83	87	88	58
55°	58	62	67	72	73	52
65°	39	43	50	56	58	39
75°	20	26	35	42	45	21
85°	4	12	22	30	33	5
90°	0	7	17	24	27	0
95°	0	5	13	20	22	0
105°	0	2	7	12	14	0
115°	0	1	4	8	9	0
125°	0	0	3	5	6	0
135°	0	0	2	3	4	0
145°	0	0	1	2	2	0
155°	0	0	0	0	1	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0



TEST NUMBER: P1356817

CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°
0°	120.9	120.9	120.9	120.9	120.9
2.5°	120.1	121.3	120.9	120.5	120.5
5°	119.7	120.9	120.5	120.5	120.9
7.5°	119.0	120.1	120.1	120.1	120.5
10°	117.8	119.4	119.4	119.4	119.7
12.5°	116.7	117.8	118.2	118.6	119.0
15°	114.8	116.3	117.1	117.5	118.2
17.5°	112.9	114.0	115.2	116.3	116.7
20°	110.6	112.1	113.3	114.4	114.8
22.5°	108.0	109.5	111.0	112.1	112.9
25°	104.9	106.4	108.7	110.2	111.0
27.5°	101.9	103.4	106.1	108.0	108.7
30°	98.1	100.4	103.0	105.3	106.4
32.5°	94.7	96.9	100.0	102.6	103.4
35°	91.2	93.5	96.9	99.6	100.7
37.5°	87.4	90.1	93.5	96.6	97.7
40°	83.6	86.3	90.1	93.5	94.3
42.5°	79.8	82.5	87.1	90.1	91.2
45°	75.6	78.7	83.3	86.7	88.2
47.5°	71.5	74.5	79.1	82.9	84.4
50°	66.9	70.3	75.3	79.1	80.6
52.5°	62.7	66.1	71.1	75.3	77.2
55°	58.2	61.6	66.9	71.5	73.4
57.5°	53.6	57.0	62.7	67.7	69.6
60°	49.0	52.5	58.2	63.9	65.8
62.5°	44.1	47.9	54.0	59.7	62.0
65°	39.2	43.3	49.8	55.9	58.5
67.5°	34.6	38.8	45.6	52.5	54.7
70°	29.7	34.2	41.8	48.7	51.3
72.5°	24.7	29.7	38.0	45.2	47.9
75°	20.1	25.5	34.6	41.8	44.9
77.5°	15.2	21.7	31.2	38.8	41.4
80°	11.0	17.9	27.8	35.7	38.4
82.5°	7.2	14.4	24.7	32.7	35.4
85°	3.8	11.8	22.0	29.7	32.7
87.5°	1.1	9.1	19.4	27.0	29.7
90°	0.0	7.2	17.1	24.3	27.4
92.5°	0.0	5.7	14.8	22.0	24.7
95°	0.0	4.6	12.9	19.8	22.4
97.5°	0.0	3.8	11.4	17.9	20.1
100°	0.0	3.0	9.9	16.0	18.2
102.5°	0.0	2.3	8.4	14.1	16.3
105°	0.0	1.5	7.2	12.5	14.4
107.5°	0.0	1.1	6.1	11.0	12.9
110°	0.0	1.1	5.7	9.5	11.4



TEST NUMBER: P1356817  
 CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°
112.5°	0.0	0.8	4.9	8.7	10.3
115°	0.0	0.8	4.2	7.6	9.1
117.5°	0.0	0.8	3.8	6.8	8.4
120°	0.0	0.8	3.4	6.1	7.2
122.5°	0.0	0.4	3.0	5.3	6.5
125°	0.0	0.4	2.7	4.9	5.7
127.5°	0.0	0.4	2.3	4.6	5.3
130°	0.0	0.4	2.3	4.2	4.9
132.5°	0.0	0.0	1.9	3.8	4.6
135°	0.0	0.0	1.5	3.0	3.8
137.5°	0.0	0.0	1.5	2.7	3.4
140°	0.0	0.0	1.1	2.7	3.0
142.5°	0.0	0.0	0.8	2.3	2.7
145°	0.0	0.0	0.8	1.9	2.3
147.5°	0.0	0.0	0.4	1.5	1.9
150°	0.0	0.0	0.4	1.1	1.5
152.5°	0.0	0.0	0.0	0.8	1.1
155°	0.0	0.0	0.0	0.4	0.8
157.5°	0.0	0.0	0.0	0.0	0.4
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1356817  
 CATALOG NUMBER: 2ASL4-10HE-2-A59-UNV

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.64	13.17	12.11	13.63	14.12	13.62	15.16	14.09	15.62	16.11
	3H	13.15	14.55	13.63	15.02	15.55	16.03	17.43	16.52	17.90	18.44
	4H	13.63	14.95	14.13	15.44	15.99	17.21	18.54	17.72	19.03	19.57
	6H	13.90	15.14	14.42	15.64	16.20	18.43	19.67	18.95	20.17	20.73
	8H	13.96	15.14	14.49	15.67	16.23	19.06	20.24	19.59	20.77	21.33
	12H	13.97	15.11	14.51	15.63	16.22	19.73	20.86	20.26	21.38	21.98
4H	2H	12.50	13.83	13.01	14.32	14.86	14.06	15.38	14.56	15.87	16.41
	3H	14.25	15.38	14.77	15.91	16.48	16.70	17.83	17.22	18.36	18.93
	4H	14.86	15.89	15.40	16.44	17.03	18.05	19.09	18.59	19.63	20.23
	6H	15.26	16.18	15.82	16.74	17.36	19.47	20.39	20.03	20.96	21.57
	8H	15.36	16.22	15.92	16.79	17.41	20.20	21.06	20.77	21.63	22.26
	12H	15.41	16.19	15.99	16.78	17.41	21.00	21.78	21.58	22.37	23.00
8H	4H	15.53	16.40	16.10	16.96	17.59	18.28	19.14	18.84	19.71	20.33
	6H	16.12	16.85	16.72	17.46	18.09	19.87	20.60	20.47	21.21	21.84
	8H	16.31	16.97	16.92	17.59	18.23	20.75	21.41	21.36	22.03	22.67
	12H	16.43	17.02	17.04	17.63	18.34	21.73	22.32	22.34	22.92	23.63
12H	4H	15.73	16.51	16.31	17.10	17.73	18.29	19.07	18.87	19.67	20.30
	6H	16.41	17.07	17.02	17.69	18.34	19.91	20.57	20.52	21.19	21.84
	8H	16.70	17.29	17.31	17.90	18.61	20.86	21.45	21.47	22.05	22.76

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Fail-Safe

Report Number: SP1-2511-597-9

Test Date: 01/22/2026

Luminaire Tested: 4ASL-2-A590-UNV-OPL-1\_600mA

Data in this report applies to families of products including 4ASL

**Test Information**

Test Method: LM-79-2019  
 Report Number: SP1-2511-597-9  
 Test Lab: COOPER LIGHTING SOLUTIONS  
 Photometer: SP1 - 76IN SPHERE  
 Measurement Geometry: 4π  
 Issue Date: 01/29/2026  
 Manufacturer: COOPER LIGHTING SOLUTIONS  
 Product Line: Fail-Safe  
 Catalog Number: **4ASL-2-A590-UNV-OPL-1\_600mA**  
 Description: 2foot 4ASL LED LUMINAIRE WITH OPL LENS AND AMBER 590 LEDS with 1 rows at 600mA

**Spectral Parameters**

CCT (K): 1535  
 CIE u': 0.3534  
 CIE v': 0.5468  
 Duv: 0.0117  
 CIE x: 0.5921  
 CIE y: 0.4072  
 CIE z: 0.0007  
 Peak Wavelength (nm): 598  
 Dominant Wavelength (nm): 592  
 Purity: 99.97894  
 R<sub>f</sub>: 1.3  
 R<sub>g</sub>: 0.1

CRI (Ra):	-20.0		
R1:	-32.1	R9:	-380.5
R2:	53.1	R10:	29.9
R3:	18.5	R11:	-92.0
R4:	-65.7	R12:	-8.5
R5:	-38.6	R13:	-13.5
R6:	42.8	R14:	47.1
R7:	-6.2	R15:	-65.4
R8:	-132.3		



**Test Conditions**


Stabilization Time: 77M  
 Operation Time: 2H 17M  
 Sphere Temperature (°C): 25.1

REPORT NUMBER: SP1-2511-597-9


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	12/16/2025	6/16/2026
Power Meter	XITRON INXT2011004	10/21/2025	10/21/2026
AC Power Source	CHROMA 61603 IN0063	10/21/2025	10/21/2026
DC Power Source	AGILENT E3634A IN0208	10/21/2025	10/21/2026
Sphere Thermometer	ONSET IN0085	10/21/2025	10/21/2026
Room Thermometer	ONSET IN0046	10/21/2025	10/21/2026

REPORT NUMBER: SP1-2511-597-9

**CIE 1931 Chromaticity Diagram**



**CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles**



Point lies outside the range

REPORT NUMBER: SP1-2511-597-9

**Photopic Flux vs. Wavelength**




**Photopic Lumens: NR**

λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	0	NR	620	35	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	17	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	9	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	5	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	2	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	1	NR	655	1	NR	785	0	NR	915	0	NR
400	0	NR	530	1	NR	660	1	NR	790	0	NR	920	0	NR
405	0	NR	535	1	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	2	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	4	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	7	NR	680	1	NR	810	0	NR	940	0	NR
425	0	NR	555	12	NR	685	0	NR	815	0	NR	945	0	NR
430	0	NR	560	22	NR	690	0	NR	820	0	NR	950	0	NR
435	0	NR	565	38	NR	695	0	NR	825	0	NR	955	0	NR
440	0	NR	570	66	NR	700	0	NR	830	0	NR	960	0	NR
445	0	NR	575	115	NR	705	0	NR	835	0	NR	965	0	NR
450	0	NR	580	203	NR	710	0	NR	840	0	NR	970	0	NR
455	0	NR	585	354	NR	715	0	NR	845	0	NR	975	0	NR
460	0	NR	590	596	NR	720	0	NR	850	0	NR	980	0	NR
465	0	NR	595	923	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	909	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	447	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	183	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	75	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-9

**Scotopic Flux vs. Wavelength**



**Scotopic Lumens: NR**

**S/P: 0.22**

λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	0	NR	620	35	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	17	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	9	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	5	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	2	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	1	NR	655	1	NR	785	0	NR	915	0	NR
400	0	NR	530	1	NR	660	1	NR	790	0	NR	920	0	NR
405	0	NR	535	1	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	2	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	4	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	7	NR	680	1	NR	810	0	NR	940	0	NR
425	0	NR	555	12	NR	685	0	NR	815	0	NR	945	0	NR
430	0	NR	560	22	NR	690	0	NR	820	0	NR	950	0	NR
435	0	NR	565	38	NR	695	0	NR	825	0	NR	955	0	NR
440	0	NR	570	66	NR	700	0	NR	830	0	NR	960	0	NR
445	0	NR	575	115	NR	705	0	NR	835	0	NR	965	0	NR
450	0	NR	580	203	NR	710	0	NR	840	0	NR	970	0	NR
455	0	NR	585	354	NR	715	0	NR	845	0	NR	975	0	NR
460	0	NR	590	596	NR	720	0	NR	850	0	NR	980	0	NR
465	0	NR	595	923	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	909	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	447	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	183	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	75	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-9

**Melanopic Flux vs. Wavelength**




**Melanopic Lumens: NR**

**M/P: 0.12**





λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)	λ (nm)	Power W <sup>^</sup> /nm	Lumens (φ/nm)
360	0	NR	490	0	NR	620	35	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	17	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	9	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	5	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	2	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	1	NR	655	1	NR	785	0	NR	915	0	NR
400	0	NR	530	1	NR	660	1	NR	790	0	NR	920	0	NR
405	0	NR	535	1	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	2	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	4	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	7	NR	680	1	NR	810	0	NR	940	0	NR
425	0	NR	555	12	NR	685	0	NR	815	0	NR	945	0	NR
430	0	NR	560	22	NR	690	0	NR	820	0	NR	950	0	NR
435	0	NR	565	38	NR	695	0	NR	825	0	NR	955	0	NR
440	0	NR	570	66	NR	700	0	NR	830	0	NR	960	0	NR
445	0	NR	575	115	NR	705	0	NR	835	0	NR	965	0	NR
450	0	NR	580	203	NR	710	0	NR	840	0	NR	970	0	NR
455	0	NR	585	354	NR	715	0	NR	845	0	NR	975	0	NR
460	0	NR	590	596	NR	720	0	NR	850	0	NR	980	0	NR
465	0	NR	595	923	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	909	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	447	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	183	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	75	NR	745	0	NR	875	0	NR			

**Summary**

$R_f = 1.3$   
 $R_g = 0.1$   
 $CIE R_a = -20.0$   
 $R_g = -380.5$




**Color Vector Graphics**






**Individual Sample Fidelity Index ( $R_{f,i}$ )**


CES01 = 90	CES26 = 0	CES51 = 19	CES76 = 0
CES02 = 70	CES27 = 32	CES52 = 2	CES77 = 0
CES03 = 31	CES28 = 25	CES53 = 0	CES78 = 0
CES04 = 77	CES29 = 1	CES54 = 13	CES79 = 2
CES05 = 52	CES30 = 31	CES55 = 7	CES80 = 1
CES06 = 56	CES31 = 1	CES56 = 0	CES81 = 0
CES07 = 41	CES32 = 0	CES57 = 0	CES82 = 51
CES08 = 39	CES33 = 21	CES58 = 0	CES83 = 21
CES09 = 29	CES34 = 0	CES59 = 10	CES84 = 55
CES10 = 87	CES35 = 24	CES60 = 60	CES85 = 10
CES11 = 70	CES36 = 77	CES61 = 14	CES86 = 0
CES12 = 76	CES37 = 6	CES62 = 53	CES87 = 2
CES13 = 47	CES38 = 42	CES63 = 68	CES88 = 2
CES14 = 77	CES39 = 75	CES64 = 0	CES89 = 0
CES15 = 74	CES40 = 49	CES65 = 0	CES90 = 2
CES16 = 49	CES41 = 75	CES66 = 0	CES91 = 57
CES17 = 56	CES42 = 0	CES67 = 0	CES92 = 0
CES18 = 60	CES43 = 0	CES68 = 0	CES93 = 3
CES19 = 80	CES44 = 95	CES69 = 28	CES94 = 0
CES20 = 71	CES45 = 1	CES70 = 0	CES95 = 0
CES21 = 94	CES46 = 6	CES71 = 0	CES96 = 2
CES22 = 87	CES47 = 70	CES72 = 42	CES97 = 1
CES23 = 94	CES48 = 0	CES73 = 0	CES98 = 0
CES24 = 95	CES49 = 6	CES74 = 62	CES99 = 0
CES25 = 79	CES50 = 10	CES75 = 0	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)