

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P1356894

Luminaire Tested: 2ASL4-20VHE-3-R63-UNV

Issue Date: 2/17/2026

Test Information

Test Method: LM-79-2019
Report Number: P1356894
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2511-597-12)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: FAIL-SAFE
Catalog Number: 2ASL4-20VHE-3-R63-UNV
Description: 2FT 2000 LUMEN PER FOOT 4ASL LED LUMINAIRE WITH OPL LENS AND R63 LEDS 3 ROW
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1044.0 lumens
Efficiency: N/A
Efficacy: 41.9 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.3 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 1.98' x H: 0.1')
CIE Type: Direct

Input Watts (W): 24.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1356894
CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P1356894

CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	96	96	96	96	96	96	93
1	105	100	95	91	102	97	92	88	91	88	84	86	83	80	81	79	77	77	77	77	74
2	95	86	79	72	92	84	77	71	79	73	68	75	70	66	71	67	63	63	63	63	61
3	86	75	67	60	83	73	65	59	69	62	57	65	60	55	62	57	53	53	53	53	50
4	79	66	57	50	76	65	56	49	61	54	48	58	52	47	55	50	45	45	45	45	43
5	73	59	50	43	70	58	49	42	55	47	41	52	45	40	49	44	39	39	39	39	37
6	67	53	44	37	64	52	43	37	49	42	36	47	40	35	45	39	34	34	34	34	32
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30	30	30	30	28
8	58	44	35	29	56	43	35	29	41	34	28	39	32	28	37	32	27	27	27	27	25
9	54	40	32	26	52	39	31	26	38	30	25	36	30	25	35	29	24	24	24	24	22
10	50	37	29	24	49	36	29	23	35	28	23	33	27	23	32	26	22	22	22	22	20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5011	5011	5011
5°	4955	4907	4896
10°	4915	4805	4772
15°	4849	4680	4667
20°	4763	4560	4548
25°	4667	4411	4414
30°	4564	4281	4300
35°	4439	4134	4172
40°	4322	4000	4040
45°	4198	3840	3906
50°	4056	3669	3766
55°	3902	3502	3641
60°	3702	3310	3515
65°	3455	3126	3410
70°	3138	2939	3326
75°	2692	2767	3271
80°	2033	2627	3247
85°	1122	2573	3292

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4198 cd/sqm



TEST NUMBER: P1356894
 CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.1	2.8
10°-20°	83.6	8.0
20°-30°	126.4	12.1
30°-40°	153.0	14.7
40°-50°	160.7	15.4
50°-60°	150.0	14.4
60°-70°	123.9	11.9
70°-80°	89.2	8.5
80°-90°	55.4	5.3
90°-100°	32.5	3.1
100°-110°	18.6	1.8
110°-120°	10.5	1.0
120°-130°	6.0	0.6
130°-140°	3.3	0.3
140°-150°	1.4	0.1
150°-160°	0.3	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	239.1	22.9
0°-40°	392.2	37.6
0°-60°	702.9	67.3
0°-90°	971.5	93.1
90°-120°	61.6	5.9
90°-150°	72.2	6.9
90°-180°	72.0	6.9
0°-180°	1044.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	307	307	307	307	307	
5°	304	306	306	306	307	29
15°	291	295	296	298	299	82
25°	266	270	274	278	281	122
35°	231	238	245	252	255	145
45°	192	198	209	218	222	148
55°	148	156	168	181	185	132
65°	100	109	126	142	148	99
75°	51	64	86	105	112	54
85°	10	29	54	73	80	12
90°	0	17	42	59	67	0
95°	0	11	31	48	55	0
105°	0	4	17	30	35	0
115°	0	2	10	18	22	0
125°	0	1	6	12	14	0
135°	0	0	4	8	10	0
145°	0	0	2	4	5	0
155°	0	0	0	1	2	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0



TEST NUMBER: P1356894

CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	307.1	307.1	307.1	307.1	307.1
2.5°	305.8	307.7	307.7	305.8	305.8
5°	303.9	306.4	306.4	306.4	307.1
7.5°	301.9	305.1	305.1	305.1	306.4
10°	299.4	302.6	303.2	303.2	303.9
12.5°	295.6	299.4	300.0	300.7	301.3
15°	291.1	294.9	296.2	298.1	299.4
17.5°	286.0	290.5	293.0	294.9	296.2
20°	279.6	284.1	287.3	289.8	291.7
22.5°	273.2	277.1	280.9	284.1	286.0
25°	265.6	270.0	274.5	278.3	280.9
27.5°	257.3	262.4	268.1	272.6	275.1
30°	249.6	254.7	261.1	266.8	269.4
32.5°	240.7	246.4	253.4	259.2	262.4
35°	231.1	237.5	245.1	252.2	255.3
37.5°	221.5	227.9	237.5	244.5	247.7
40°	211.9	218.3	228.5	236.2	239.4
42.5°	201.7	208.1	219.0	227.3	231.1
45°	191.5	198.5	209.4	218.3	222.2
47.5°	181.3	188.3	199.8	209.4	213.2
50°	169.8	177.5	189.0	199.8	203.6
52.5°	159.0	166.6	179.4	190.2	194.1
55°	147.5	155.8	168.5	180.7	185.1
57.5°	136.0	144.3	157.7	170.4	175.6
60°	123.8	132.8	146.8	160.2	166.0
62.5°	111.7	121.3	136.6	150.7	156.4
65°	99.6	109.2	125.8	141.7	147.5
67.5°	87.5	97.7	115.5	132.1	139.2
70°	75.3	86.2	105.3	122.6	129.6
72.5°	63.2	74.7	95.8	113.6	120.7
75°	51.1	63.8	86.2	104.7	112.4
77.5°	38.9	53.6	77.9	96.4	104.1
80°	28.1	44.7	68.9	88.1	95.8
82.5°	17.9	35.7	61.3	80.4	88.1
85°	9.6	28.7	54.3	73.4	80.4
87.5°	3.2	22.3	47.2	66.4	73.4
90°	0.0	17.2	41.5	59.4	67.0
92.5°	0.0	13.4	36.4	53.6	60.6
95°	0.0	10.9	31.3	47.9	54.9
97.5°	0.0	8.9	27.4	42.8	49.2
100°	0.0	7.0	23.6	38.3	44.0
102.5°	0.0	5.7	20.4	33.8	39.6
105°	0.0	3.8	17.2	30.0	35.1
107.5°	0.0	3.2	14.7	26.8	31.3
110°	0.0	2.6	13.4	23.0	27.4



TEST NUMBER: P1356894
 CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	0.0	1.9	12.1	20.4	24.9
115°	0.0	1.9	10.2	18.5	21.7
117.5°	0.0	1.9	8.9	16.6	19.8
120°	0.0	1.3	8.3	14.7	17.9
122.5°	0.0	1.3	7.0	13.4	16.0
125°	0.0	1.3	6.4	12.1	14.0
127.5°	0.0	0.6	5.7	10.9	12.8
130°	0.0	0.6	5.1	9.6	11.5
132.5°	0.0	0.6	4.5	8.9	10.9
135°	0.0	0.0	3.8	7.7	9.6
137.5°	0.0	0.0	3.2	7.0	8.3
140°	0.0	0.0	2.6	5.7	7.7
142.5°	0.0	0.0	1.9	5.1	6.4
145°	0.0	0.0	1.9	4.5	5.1
147.5°	0.0	0.0	1.3	3.2	4.5
150°	0.0	0.0	0.6	2.6	3.2
152.5°	0.0	0.0	0.0	1.9	2.6
155°	0.0	0.0	0.0	1.3	1.9
157.5°	0.0	0.0	0.0	0.0	0.6
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1356894
 CATALOG NUMBER: 2ASL4-20VHE-3-R63-UNV

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.90	16.44	15.37	16.90	17.38	16.84	18.38	17.31	18.84	19.32
	3H	16.40	17.81	16.88	18.27	18.79	19.27	20.68	19.75	21.14	21.66
	4H	16.88	18.21	17.38	18.70	19.23	20.44	21.77	20.94	22.25	22.79
	6H	17.16	18.40	17.67	18.89	19.45	21.64	22.88	22.16	23.38	23.93
	8H	17.21	18.40	17.74	18.92	19.48	22.25	23.44	22.78	23.96	24.52
	12H	17.22	18.36	17.76	18.88	19.47	22.90	24.04	23.44	24.55	25.15
4H	2H	15.76	17.09	16.27	17.58	18.11	17.28	18.61	17.79	19.10	19.63
	3H	17.50	18.63	18.01	19.16	19.72	19.94	21.07	20.45	21.60	22.16
	4H	18.10	19.14	18.64	19.68	20.27	21.28	22.31	21.81	22.85	23.44
	6H	18.50	19.42	19.06	19.98	20.59	22.67	23.59	23.23	24.15	24.76
	8H	18.60	19.46	19.16	20.02	20.64	23.39	24.25	23.95	24.81	25.43
	12H	18.64	19.43	19.22	20.02	20.64	24.16	24.94	24.74	25.53	26.16
8H	4H	18.77	19.63	19.33	20.19	20.81	21.50	22.36	22.06	22.92	23.54
	6H	19.34	20.08	19.94	20.68	21.30	23.06	23.79	23.66	24.40	25.02
	8H	19.53	20.19	20.13	20.80	21.44	23.92	24.58	24.52	25.19	25.83
	12H	19.64	20.23	20.25	20.83	21.54	24.88	25.47	25.48	26.07	26.77
12H	4H	18.95	19.73	19.53	20.32	20.95	21.50	22.29	22.09	22.88	23.50
	6H	19.63	20.29	20.23	20.90	21.54	23.10	23.76	23.71	24.38	25.01
	8H	19.90	20.49	20.51	21.10	21.80	24.03	24.62	24.63	25.22	25.92

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Fail-Safe

Report Number: SP1-2511-597-7

Test Date: 01/21/2026

Luminaire Tested: 4ASL-2-R630-UNV-OPL-1_600mA

Data in this report applies to families of products including 4ASL

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2511-597-7
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 01/29/2026
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Fail-Safe
 Catalog Number: **4ASL-2-R630-UNV-OPL-1_600mA**
 Description: 2foot 4ASL LED LUMINAIRE WITH OPL LENS AND RED 630NM LEDS with 1 rows at 600mA

Spectral Parameters

CCT (K): 0
 CIE u': 0.5395
 CIE v': 0.5190
 Duv: 0.0000
 CIE x: 0.7004
 CIE y: 0.2995
 CIE z: 0.0001
 Peak Wavelength (nm): 638
 Dominant Wavelength (nm): 624
 Purity: 99.9862
 Rf: NR
 Rg: NR

CRI (Ra): 0.0
 R1: 0.0
 R2: 0.0
 R3: 0.0
 R4: 0.0
 R5: 0.0
 R6: 0.0
 R7: 0.0
 R8: 0.0
 R9: 0.0
 R10: 0.0
 R11: 0.0
 R12: 0.0
 R13: 0.0
 R14: 0.0
 R15: 0.0



Test Conditions


Stabilization Time: 69M
 Operation Time: 2H 9M
 Sphere Temperature (°C): 25.1

REPORT NUMBER: SP1-2511-597-7


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	12/16/2025	6/16/2026
Power Meter	XITRON INXT2011004	10/21/2025	10/21/2026
AC Power Source	CHROMA 61603 IN0063	10/21/2025	10/21/2026
DC Power Source	AGILENT E3634A IN0208	10/21/2025	10/21/2026
Sphere Thermometer	ONSET IN0085	10/21/2025	10/21/2026
Room Thermometer	ONSET IN0046	10/21/2025	10/21/2026

REPORT NUMBER: SP1-2511-597-7

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies outside the range

REPORT NUMBER: SP1-2511-597-7

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)	λ (nm)	Power W [^] /nm	Lumens (ϕ /nm)
360	0	NR	490	0	NR	620	248	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	409	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	630	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	903	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	960	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	535	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	212	NR	780	0	NR	910	0	NR
395	0	NR	525	0	NR	655	88	NR	785	0	NR	915	0	NR
400	0	NR	530	0	NR	660	38	NR	790	0	NR	920	0	NR
405	0	NR	535	0	NR	665	19	NR	795	0	NR	925	0	NR
410	0	NR	540	0	NR	670	10	NR	800	0	NR	930	0	NR
415	0	NR	545	0	NR	675	6	NR	805	0	NR	935	0	NR
420	0	NR	550	0	NR	680	4	NR	810	0	NR	940	0	NR
425	0	NR	555	0	NR	685	2	NR	815	0	NR	945	0	NR
430	0	NR	560	0	NR	690	2	NR	820	0	NR	950	0	NR
435	0	NR	565	1	NR	695	1	NR	825	0	NR	955	0	NR
440	0	NR	570	2	NR	700	1	NR	830	0	NR	960	0	NR
445	0	NR	575	3	NR	705	1	NR	835	0	NR	965	0	NR
450	0	NR	580	4	NR	710	1	NR	840	0	NR	970	0	NR
455	0	NR	585	7	NR	715	1	NR	845	0	NR	975	0	NR
460	0	NR	590	12	NR	720	1	NR	850	0	NR	980	0	NR
465	0	NR	595	20	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	34	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	56	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	92	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	152	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-7

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 0.05

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	0	NR	620	248	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	409	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	630	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	903	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	960	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	535	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	212	NR	780	0	NR	910	0	NR
395	0	NR	525	0	NR	655	88	NR	785	0	NR	915	0	NR
400	0	NR	530	0	NR	660	38	NR	790	0	NR	920	0	NR
405	0	NR	535	0	NR	665	19	NR	795	0	NR	925	0	NR
410	0	NR	540	0	NR	670	10	NR	800	0	NR	930	0	NR
415	0	NR	545	0	NR	675	6	NR	805	0	NR	935	0	NR
420	0	NR	550	0	NR	680	4	NR	810	0	NR	940	0	NR
425	0	NR	555	0	NR	685	2	NR	815	0	NR	945	0	NR
430	0	NR	560	0	NR	690	2	NR	820	0	NR	950	0	NR
435	0	NR	565	1	NR	695	1	NR	825	0	NR	955	0	NR
440	0	NR	570	2	NR	700	1	NR	830	0	NR	960	0	NR
445	0	NR	575	3	NR	705	1	NR	835	0	NR	965	0	NR
450	0	NR	580	4	NR	710	1	NR	840	0	NR	970	0	NR
455	0	NR	585	7	NR	715	1	NR	845	0	NR	975	0	NR
460	0	NR	590	12	NR	720	1	NR	850	0	NR	980	0	NR
465	0	NR	595	20	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	34	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	56	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	92	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	152	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-7

Melanopic Flux vs. Wavelength




Melanopic Lumens: NR

M/P: 0.02



λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	0	NR	620	248	NR	750	0	NR	880	0	NR
365	0	NR	495	0	NR	625	409	NR	755	0	NR	885	0	NR
370	0	NR	500	0	NR	630	630	NR	760	0	NR	890	0	NR
375	0	NR	505	0	NR	635	903	NR	765	0	NR	895	0	NR
380	0	NR	510	0	NR	640	960	NR	770	0	NR	900	0	NR
385	0	NR	515	0	NR	645	535	NR	775	0	NR	905	0	NR
390	0	NR	520	0	NR	650	212	NR	780	0	NR	910	0	NR
395	0	NR	525	0	NR	655	88	NR	785	0	NR	915	0	NR
400	0	NR	530	0	NR	660	38	NR	790	0	NR	920	0	NR
405	0	NR	535	0	NR	665	19	NR	795	0	NR	925	0	NR
410	0	NR	540	0	NR	670	10	NR	800	0	NR	930	0	NR
415	0	NR	545	0	NR	675	6	NR	805	0	NR	935	0	NR
420	0	NR	550	0	NR	680	4	NR	810	0	NR	940	0	NR
425	0	NR	555	0	NR	685	2	NR	815	0	NR	945	0	NR
430	0	NR	560	0	NR	690	2	NR	820	0	NR	950	0	NR
435	0	NR	565	1	NR	695	1	NR	825	0	NR	955	0	NR
440	0	NR	570	2	NR	700	1	NR	830	0	NR	960	0	NR
445	0	NR	575	3	NR	705	1	NR	835	0	NR	965	0	NR
450	0	NR	580	4	NR	710	1	NR	840	0	NR	970	0	NR
455	0	NR	585	7	NR	715	1	NR	845	0	NR	975	0	NR
460	0	NR	590	12	NR	720	1	NR	850	0	NR	980	0	NR
465	0	NR	595	20	NR	725	0	NR	855	0	NR	985	0	NR
470	0	NR	600	34	NR	730	0	NR	860	0	NR	990	0	NR
475	0	NR	605	56	NR	735	0	NR	865	0	NR	995	0	NR
480	0	NR	610	92	NR	740	0	NR	870	0	NR	1000	0	NR
485	0	NR	615	152	NR	745	0	NR	875	0	NR			

Summary

$R_f = 0$
 $R_g = 0$
 CIE $R_a = 0.0$
 $R_9 = 0.0$



Color Vector Graphics



Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 0	CES26 = 0	CES51 = 0	CES76 = 0
CES02 = 0	CES27 = 0	CES52 = 0	CES77 = 0
CES03 = 0	CES28 = 0	CES53 = 0	CES78 = 0
CES04 = 0	CES29 = 0	CES54 = 0	CES79 = 0
CES05 = 0	CES30 = 0	CES55 = 0	CES80 = 0
CES06 = 0	CES31 = 0	CES56 = 0	CES81 = 0
CES07 = 0	CES32 = 0	CES57 = 0	CES82 = 0
CES08 = 0	CES33 = 0	CES58 = 0	CES83 = 0
CES09 = 0	CES34 = 0	CES59 = 0	CES84 = 0
CES10 = 0	CES35 = 0	CES60 = 0	CES85 = 0
CES11 = 0	CES36 = 0	CES61 = 0	CES86 = 0
CES12 = 0	CES37 = 0	CES62 = 0	CES87 = 0
CES13 = 0	CES38 = 0	CES63 = 0	CES88 = 0
CES14 = 0	CES39 = 0	CES64 = 0	CES89 = 0
CES15 = 0	CES40 = 0	CES65 = 0	CES90 = 0
CES16 = 0	CES41 = 0	CES66 = 0	CES91 = 0
CES17 = 0	CES42 = 0	CES67 = 0	CES92 = 0
CES18 = 0	CES43 = 0	CES68 = 0	CES93 = 0
CES19 = 0	CES44 = 0	CES69 = 0	CES94 = 0
CES20 = 0	CES45 = 0	CES70 = 0	CES95 = 0
CES21 = 0	CES46 = 0	CES71 = 0	CES96 = 0
CES22 = 0	CES47 = 0	CES72 = 0	CES97 = 0
CES23 = 0	CES48 = 0	CES73 = 0	CES98 = 0
CES24 = 0	CES49 = 0	CES74 = 0	CES99 = 0
CES25 = 0	CES50 = 0	CES75 = 0	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)