

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P1357358

Luminaire Tested: 6ASL4-30VHE-3-30-UNV

Issue Date: 2/17/2026

Test Information

Test Method: LM-79-2019
Report Number: P1357358
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2511-597-12)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: FAIL-SAFE
Catalog Number: 6ASL4-30VHE-3-30-UNV
Description: 6FT 3000 LUMEN PER FOOT 4ASL LED LUMINAIRE WITH OPL LENS AND 3000K LEDS 3 ROW
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 17310.0 lumens
Efficiency: N/A
Efficacy: 109.7 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.3 / 1.39
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 5.98' x H: 0.1')
CIE Type: Direct

Input Watts (W): 157.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

Luminous Intensity Polar Plot



TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	117	117	117	117	114	114	114	114	107	107	107		101	101	101		96
1	105	100	95	91	102	97	92	88	91	88	84		86	83	80		81
2	95	86	79	72	92	84	77	71	79	73	68		75	70	66		71
3	86	75	67	60	83	73	65	59	69	62	57		65	60	55		62
4	79	66	57	50	76	65	56	49	61	54	48		58	52	47		55
5	73	59	50	43	70	58	49	42	55	47	41		52	45	40		49
6	67	53	44	37	64	52	43	37	49	42	36		47	40	35		45
7	62	48	39	33	60	47	38	32	45	37	32		43	36	31		41
8	58	44	35	29	56	43	35	29	41	34	28		39	32	28		37
9	54	40	32	26	52	39	31	26	38	30	25		36	30	25		35
10	50	37	29	24	49	36	29	23	35	28	23		33	27	23		32

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	27496	27496	27496
5°	27272	26992	26866
10°	27140	26482	26187
15°	26861	25844	25611
20°	26477	25232	24961
25°	26027	24461	24222
30°	25552	23792	23597
35°	24958	23034	22902
40°	24417	22341	22170
45°	23837	21500	21435
50°	23175	20597	20671
55°	22463	19736	19984
60°	21530	18728	19286
65°	20341	17761	18708
70°	18822	16805	18255
75°	16591	15939	17945
80°	13182	15304	17812
85°	8206	15205	18075

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23837 cd/sqm

TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	482.8	2.8
10°-20°	1386.1	8.0
20°-30°	2095.7	12.1
30°-40°	2537.6	14.7
40°-50°	2665.2	15.4
50°-60°	2486.6	14.4
60°-70°	2055.0	11.9
70°-80°	1479.6	8.5
80°-90°	919.5	5.3
90°-100°	538.8	3.1
100°-110°	308.2	1.8
110°-120°	174.0	1.0
120°-130°	100.1	0.6
130°-140°	54.0	0.3
140°-150°	22.7	0.1
150°-160°	4.2	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3964.6	22.9
0°-40°	6502.2	37.6
0°-60°	11654.0	67.3
0°-90°	16108.0	93.1
90°-120°	1021.0	5.9
90°-150°	1197.8	6.9
90°-180°	1202.0	6.9
0°-180°	17310.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	5091	5091	5091	5091	5091	
5°	5038	5080	5080	5080	5091	479
15°	4826	4890	4911	4943	4964	1361
25°	4403	4477	4551	4615	4657	2028
35°	3832	3937	4064	4181	4234	2398
45°	3175	3292	3472	3620	3683	2450
55°	2445	2583	2794	2995	3070	2185
65°	1651	1810	2085	2350	2445	1634
75°	847	1058	1429	1736	1863	896
85°	159	476	900	1217	1334	194
90°	0	286	688	984	1111	7
95°	0	180	519	794	910	0
105°	0	64	286	498	582	0
115°	0	32	169	307	360	0
125°	0	21	106	201	233	0
135°	0	0	64	127	159	0
145°	0	0	32	74	85	0
155°	0	0	0	21	32	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	5091.1	5091.1	5091.1	5091.1	5091.1
2.5°	5069.9	5101.7	5101.7	5069.9	5069.9
5°	5038.2	5080.5	5080.5	5080.5	5091.1
7.5°	5006.4	5059.4	5059.4	5059.4	5080.5
10°	4964.1	5017.0	5027.6	5027.6	5038.2
12.5°	4900.6	4964.1	4974.7	4985.3	4995.8
15°	4826.5	4890.0	4911.2	4942.9	4964.1
17.5°	4741.8	4815.9	4858.2	4890.0	4911.2
20°	4636.0	4710.1	4763.0	4805.3	4837.1
22.5°	4530.1	4593.6	4657.1	4710.1	4741.8
25°	4403.1	4477.2	4551.3	4614.8	4657.1
27.5°	4265.5	4350.2	4445.5	4519.5	4561.9
30°	4138.5	4223.2	4329.0	4424.3	4466.6
32.5°	3990.3	4085.6	4202.0	4297.3	4350.2
35°	3831.6	3937.4	4064.4	4180.8	4233.8
37.5°	3672.8	3778.6	3937.4	4053.8	4106.8
40°	3514.0	3619.9	3789.2	3916.2	3969.2
42.5°	3344.7	3450.5	3630.5	3768.1	3831.6
45°	3175.3	3291.8	3471.7	3619.9	3683.4
47.5°	3006.0	3122.4	3312.9	3471.7	3535.2
50°	2815.5	2942.5	3133.0	3312.9	3376.4
52.5°	2635.5	2762.5	2974.2	3154.2	3217.7
55°	2445.0	2582.6	2794.3	2995.4	3069.5
57.5°	2254.5	2392.1	2614.4	2826.0	2910.7
60°	2053.4	2201.6	2434.4	2656.7	2751.9
62.5°	1852.3	2011.0	2265.1	2497.9	2593.2
65°	1651.2	1809.9	2085.1	2349.7	2445.0
67.5°	1450.1	1619.4	1915.8	2191.0	2307.4
70°	1249.0	1428.9	1746.4	2032.2	2148.6
72.5°	1047.9	1238.4	1587.7	1884.0	2000.5
75°	846.8	1058.4	1428.9	1735.8	1862.9
77.5°	645.6	889.1	1291.3	1598.2	1725.3
80°	465.7	740.9	1143.1	1460.6	1587.7
82.5°	296.4	592.7	1016.1	1333.6	1460.6
85°	158.8	476.3	899.7	1217.2	1333.6
87.5°	52.9	370.5	783.2	1100.8	1217.2
90°	0.0	285.8	688.0	984.4	1111.4
92.5°	0.0	222.3	603.3	889.1	1005.5
95°	0.0	179.9	518.6	793.8	910.3
97.5°	0.0	148.2	455.1	709.2	815.0
100°	0.0	116.4	391.6	635.1	730.3
102.5°	0.0	95.3	338.7	561.0	656.2
105°	0.0	63.5	285.8	497.5	582.1
107.5°	0.0	52.9	243.4	444.5	518.6
110°	0.0	42.3	222.3	381.0	455.1



TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	0.0	31.8	201.1	338.7	412.8
115°	0.0	31.8	169.4	306.9	359.9
117.5°	0.0	31.8	148.2	275.2	328.1
120°	0.0	21.2	137.6	243.4	296.4
122.5°	0.0	21.2	116.4	222.3	264.6
125°	0.0	21.2	105.8	201.1	232.9
127.5°	0.0	10.6	95.3	179.9	211.7
130°	0.0	10.6	84.7	158.8	190.5
132.5°	0.0	10.6	74.1	148.2	179.9
135°	0.0	0.0	63.5	127.0	158.8
137.5°	0.0	0.0	52.9	116.4	137.6
140°	0.0	0.0	42.3	95.3	127.0
142.5°	0.0	0.0	31.8	84.7	105.8
145°	0.0	0.0	31.8	74.1	84.7
147.5°	0.0	0.0	21.2	52.9	74.1
150°	0.0	0.0	10.6	42.3	52.9
152.5°	0.0	0.0	0.0	31.8	42.3
155°	0.0	0.0	0.0	21.2	31.8
157.5°	0.0	0.0	0.0	0.0	10.6
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

TEST NUMBER: P1357358

CATALOG NUMBER: 6ASL4-30VHE-3-30-UNV

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	20.86	22.40	21.33	22.85	23.34	22.91	24.45	23.38	24.91	25.39
	3H	22.35	23.76	22.83	24.22	24.75	25.39	26.79	25.87	27.26	27.78
	4H	22.83	24.17	23.34	24.65	25.19	26.60	27.93	27.10	28.41	28.95
	6H	23.11	24.35	23.62	24.84	25.40	27.87	29.11	28.38	29.60	30.16
	8H	23.16	24.35	23.69	24.87	25.43	28.53	29.72	29.06	30.24	30.80
	12H	23.17	24.31	23.71	24.83	25.42	29.26	30.40	29.80	30.91	31.50
4H	2H	21.74	23.07	22.24	23.55	24.09	23.34	24.68	23.85	25.16	25.70
	3H	23.47	24.61	23.99	25.13	25.69	26.05	27.18	26.56	27.71	28.27
	4H	24.08	25.12	24.61	25.65	26.25	27.42	28.46	27.96	29.00	29.59
	6H	24.48	25.39	25.03	25.95	26.56	28.89	29.80	29.44	30.37	30.97
	8H	24.57	25.43	25.13	25.99	26.61	29.65	30.52	30.21	31.08	31.70
	12H	24.61	25.40	25.20	25.99	26.61	30.51	31.30	31.10	31.89	32.51
8H	4H	24.77	25.63	25.33	26.19	26.81	27.64	28.50	28.20	29.07	29.68
	6H	25.34	26.08	25.94	26.68	27.31	29.27	30.00	29.86	30.61	31.23
	8H	25.53	26.19	26.13	26.80	27.44	30.18	30.84	30.78	31.45	32.09
	12H	25.64	26.23	26.25	26.83	27.54	31.22	31.81	31.83	32.42	33.12
12H	4H	24.96	25.75	25.54	26.34	26.96	27.65	28.43	28.23	29.02	29.65
	6H	25.64	26.30	26.25	26.92	27.56	29.31	29.97	29.91	30.58	31.22
	8H	25.92	26.51	26.53	27.12	27.82	30.29	30.87	30.89	31.48	32.18

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Fail-Safe

Report Number: SP1-2511-597-3

Test Date: 11/18/2025

Luminaire Tested: 4ASL-2-30-UNV-OPL-1_600mA

Data in this report applies to families of products including 4ASL


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2511-597-3
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 11/18/2025
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Fail-Safe
 Catalog Number: **4ASL-2-30-UNV-OPL-1_600mA**
 Description: 2foot 4ASL LED LUMINAIRE WITH OPL LENS AND 3000K LEDS with 1 rows at 600mA

Spectral Parameters

CCT (K): 3005
 CIE u' : 0.2513
 CIE v' : 0.5178
 Duv: -0.0025
 CIE x: 0.4330
 CIE y: 0.3966
 CIE z: 0.1704
 Peak Wavelength (nm): 630
 Dominant Wavelength (nm): 583
 Purity: 49.00645
 R_f: 90.1
 R_g: 103.3

CRI (Ra): 93.9
 R1: 96.5
 R2: 96.6
 R3: 95.5
 R4: 94.4
 R5: 96.0
 R6: 96.4
 R7: 91.7
 R8: 84.0
 R9: 62.0
 R10: 90.8
 R11: 94.1
 R12: 88.9
 R13: 96.4
 R14: 96.3
 R15: 91.9



Test Conditions


Stabilization Time: 32M
 Operation Time: 1H 32M
 Sphere Temperature (°C): 24.1

REPORT NUMBER: SP1-2511-597-3


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	6/16/2025	12/16/2025
Power Meter	XITRON INXT2011004	10/21/2025	10/21/2026
AC Power Source	CHROMA 61603 IN0063	10/21/2025	10/21/2026
DC Power Source	AGILENT E3634A IN0208	10/21/2025	10/21/2026
Sphere Thermometer	ONSET IN0085	10/21/2025	10/21/2026
Room Thermometer	ONSET IN0046	10/21/2025	10/21/2026

REPORT NUMBER: SP1-2511-597-3

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 3000K 4-step quadrangle

REPORT NUMBER: SP1-2511-597-3

Photopic Flux vs. Wavelength




Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	92	NR	620	304	NR	750	8	NR	880	0	NR
365	0	NR	495	114	NR	625	309	NR	755	7	NR	885	0	NR
370	0	NR	500	136	NR	630	1000	NR	760	6	NR	890	0	NR
375	0	NR	505	154	NR	635	582	NR	765	5	NR	895	0	NR
380	0	NR	510	169	NR	640	200	NR	770	4	NR	900	0	NR
385	0	NR	515	181	NR	645	207	NR	775	4	NR	905	0	NR
390	1	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	148	NR	785	3	NR	915	0	NR
400	2	NR	530	199	NR	660	127	NR	790	2	NR	920	0	NR
405	3	NR	535	203	NR	665	108	NR	795	2	NR	925	0	NR
410	5	NR	540	208	NR	670	100	NR	800	2	NR	930	0	NR
415	9	NR	545	214	NR	675	83	NR	805	2	NR	935	0	NR
420	16	NR	550	221	NR	680	71	NR	810	1	NR	940	0	NR
425	28	NR	555	228	NR	685	61	NR	815	1	NR	945	0	NR
430	48	NR	560	236	NR	690	53	NR	820	1	NR	950	0	NR
435	80	NR	565	244	NR	695	45	NR	825	1	NR	955	0	NR
440	135	NR	570	251	NR	700	38	NR	830	1	NR	960	0	NR
445	202	NR	575	259	NR	705	33	NR	835	1	NR	965	0	NR
450	195	NR	580	266	NR	710	28	NR	840	1	NR	970	0	NR
455	130	NR	585	274	NR	715	24	NR	845	1	NR	975	0	NR
460	101	NR	590	281	NR	720	20	NR	850	0	NR	980	0	NR
465	82	NR	595	286	NR	725	17	NR	855	0	NR	985	0	NR
470	62	NR	600	292	NR	730	15	NR	860	0	NR	990	0	NR
475	58	NR	605	298	NR	735	13	NR	865	0	NR	995	0	NR
480	62	NR	610	328	NR	740	11	NR	870	0	NR	1000	0	NR
485	74	NR	615	342	NR	745	9	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-3

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 1.42

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	92	NR	620	304	NR	750	8	NR	880	0	NR
365	0	NR	495	114	NR	625	309	NR	755	7	NR	885	0	NR
370	0	NR	500	136	NR	630	1000	NR	760	6	NR	890	0	NR
375	0	NR	505	154	NR	635	582	NR	765	5	NR	895	0	NR
380	0	NR	510	169	NR	640	200	NR	770	4	NR	900	0	NR
385	0	NR	515	181	NR	645	207	NR	775	4	NR	905	0	NR
390	1	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	148	NR	785	3	NR	915	0	NR
400	2	NR	530	199	NR	660	127	NR	790	2	NR	920	0	NR
405	3	NR	535	203	NR	665	108	NR	795	2	NR	925	0	NR
410	5	NR	540	208	NR	670	100	NR	800	2	NR	930	0	NR
415	9	NR	545	214	NR	675	83	NR	805	2	NR	935	0	NR
420	16	NR	550	221	NR	680	71	NR	810	1	NR	940	0	NR
425	28	NR	555	228	NR	685	61	NR	815	1	NR	945	0	NR
430	48	NR	560	236	NR	690	53	NR	820	1	NR	950	0	NR
435	80	NR	565	244	NR	695	45	NR	825	1	NR	955	0	NR
440	135	NR	570	251	NR	700	38	NR	830	1	NR	960	0	NR
445	202	NR	575	259	NR	705	33	NR	835	1	NR	965	0	NR
450	195	NR	580	266	NR	710	28	NR	840	1	NR	970	0	NR
455	130	NR	585	274	NR	715	24	NR	845	1	NR	975	0	NR
460	101	NR	590	281	NR	720	20	NR	850	0	NR	980	0	NR
465	82	NR	595	286	NR	725	17	NR	855	0	NR	985	0	NR
470	62	NR	600	292	NR	730	15	NR	860	0	NR	990	0	NR
475	58	NR	605	298	NR	735	13	NR	865	0	NR	995	0	NR
480	62	NR	610	328	NR	740	11	NR	870	0	NR	1000	0	NR
485	74	NR	615	342	NR	745	9	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-3

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 2.76


λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	92	NR	620	304	NR	750	8	NR	880	0	NR
365	0	NR	495	114	NR	625	309	NR	755	7	NR	885	0	NR
370	0	NR	500	136	NR	630	1000	NR	760	6	NR	890	0	NR
375	0	NR	505	154	NR	635	582	NR	765	5	NR	895	0	NR
380	0	NR	510	169	NR	640	200	NR	770	4	NR	900	0	NR
385	0	NR	515	181	NR	645	207	NR	775	4	NR	905	0	NR
390	1	NR	520	189	NR	650	174	NR	780	3	NR	910	0	NR
395	1	NR	525	194	NR	655	148	NR	785	3	NR	915	0	NR
400	2	NR	530	199	NR	660	127	NR	790	2	NR	920	0	NR
405	3	NR	535	203	NR	665	108	NR	795	2	NR	925	0	NR
410	5	NR	540	208	NR	670	100	NR	800	2	NR	930	0	NR
415	9	NR	545	214	NR	675	83	NR	805	2	NR	935	0	NR
420	16	NR	550	221	NR	680	71	NR	810	1	NR	940	0	NR
425	28	NR	555	228	NR	685	61	NR	815	1	NR	945	0	NR
430	48	NR	560	236	NR	690	53	NR	820	1	NR	950	0	NR
435	80	NR	565	244	NR	695	45	NR	825	1	NR	955	0	NR
440	135	NR	570	251	NR	700	38	NR	830	1	NR	960	0	NR
445	202	NR	575	259	NR	705	33	NR	835	1	NR	965	0	NR
450	195	NR	580	266	NR	710	28	NR	840	1	NR	970	0	NR
455	130	NR	585	274	NR	715	24	NR	845	1	NR	975	0	NR
460	101	NR	590	281	NR	720	20	NR	850	0	NR	980	0	NR
465	82	NR	595	286	NR	725	17	NR	855	0	NR	985	0	NR
470	62	NR	600	292	NR	730	15	NR	860	0	NR	990	0	NR
475	58	NR	605	298	NR	735	13	NR	865	0	NR	995	0	NR
480	62	NR	610	328	NR	740	11	NR	870	0	NR	1000	0	NR
485	74	NR	615	342	NR	745	9	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-3





TM-30-18

Summary

$R_f = 90.1$
 $R_g = 103.3$
 $CIE R_a = 93.9$
 $R_9 = 62.0$







Color Vector Graphics





Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 88	CES51 = 93	CES76 = 86
CES02 = 63	CES27 = 97	CES52 = 93	CES77 = 87
CES03 = 32	CES28 = 95	CES53 = 89	CES78 = 83
CES04 = 70	CES29 = 83	CES54 = 98	CES79 = 91
CES05 = 51	CES30 = 87	CES55 = 97	CES80 = 92
CES06 = 51	CES31 = 85	CES56 = 90	CES81 = 75
CES07 = 44	CES32 = 80	CES57 = 89	CES82 = 96
CES08 = 42	CES33 = 85	CES58 = 89	CES83 = 92
CES09 = 29	CES34 = 89	CES59 = 98	CES84 = 96
CES10 = 76	CES35 = 94	CES60 = 99	CES85 = 83
CES11 = 59	CES36 = 96	CES61 = 98	CES86 = 78
CES12 = 65	CES37 = 92	CES62 = 95	CES87 = 91
CES13 = 44	CES38 = 92	CES63 = 90	CES88 = 94
CES14 = 74	CES39 = 95	CES64 = 94	CES89 = 82
CES15 = 72	CES40 = 91	CES65 = 91	CES90 = 94
CES16 = 48	CES41 = 91	CES66 = 93	CES91 = 87
CES17 = 50	CES42 = 88	CES67 = 93	CES92 = 80
CES18 = 57	CES43 = 85	CES68 = 94	CES93 = 89
CES19 = 72	CES44 = 99	CES69 = 96	CES94 = 74
CES20 = 67	CES45 = 90	CES70 = 90	CES95 = 87
CES21 = 86	CES46 = 89	CES71 = 91	CES96 = 92
CES22 = 79	CES47 = 82	CES72 = 96	CES97 = 90
CES23 = 92	CES48 = 89	CES73 = 85	CES98 = 91
CES24 = 91	CES49 = 87	CES74 = 91	CES99 = 93
CES25 = 72	CES50 = 93	CES75 = 90	



Color Rendition by Hue-Angle Bin


Measure Comparisons



(END OF REPORT)