

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P1357430

Luminaire Tested: 8ASL4-10HE-2-G52-UNV

Issue Date: 2/17/2026

Test Information

Test Method: LM-79-2019
Report Number: P1357430
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2511-597-7)
Test Lab: INNOVATION CENTER
Issue Date: 2/17/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: FAIL-SAFE
Catalog Number: 8ASL4-10HE-2-G52-UNV
Description: 8FT 1000 LUMEN PER FOOT 4ASL LED LUMINAIRE WITH OPL LENS AND G52 LEDS 2 ROW
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4068.0 lumens
Efficiency: N/A
Efficacy: 53.2 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.3 / 1.4
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 7.98' x H: 0.1')
CIE Type: Direct

Input Watts (W): 76.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1357430
CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P1357430
 CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95	95	95	95	93
1	105	100	95	90	102	97	92	88	91	87	84	86	83	80	81	79	77	77	77	77	74
2	95	86	79	72	92	84	77	71	79	73	68	74	70	65	70	66	63	63	63	63	60
3	86	75	66	59	83	73	65	58	69	62	56	65	59	55	62	57	53	53	53	53	50
4	79	66	57	50	76	64	56	49	61	54	48	58	51	46	55	49	45	45	45	45	42
5	72	59	50	43	70	57	49	42	54	47	41	52	45	40	49	43	39	39	39	39	36
6	67	53	44	37	64	52	43	37	49	41	36	47	40	35	44	39	34	34	34	34	32
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30	30	30	30	28
8	58	44	35	29	56	43	34	29	41	33	28	39	32	28	37	31	27	27	27	27	25
9	54	40	32	26	52	39	31	26	37	30	25	36	29	25	34	29	24	24	24	24	22
10	50	37	29	24	49	36	28	23	35	28	23	33	27	22	32	26	22	22	22	22	20

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4796	4796	4796
5°	4763	4704	4686
10°	4736	4621	4572
15°	4698	4529	4480
20°	4648	4413	4351
25°	4565	4297	4241
30°	4459	4165	4131
35°	4378	4043	4003
40°	4284	3910	3868
45°	4189	3797	3770
50°	4066	3645	3624
55°	3949	3482	3509
60°	3805	3299	3386
65°	3575	3129	3291
70°	3321	2971	3203
75°	2945	2852	3174
80°	2346	2750	3164
85°	1507	2763	3255

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4189 cd/sqm



TEST NUMBER: P1357430
 CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	112.4	2.8
10°-20°	323.0	7.9
20°-30°	489.5	12.0
30°-40°	592.0	14.6
40°-50°	624.1	15.3
50°-60°	582.5	14.3
60°-70°	480.9	11.8
70°-80°	348.9	8.6
80°-90°	220.4	5.4
90°-100°	131.6	3.2
100°-110°	75.4	1.9
110°-120°	42.8	1.1
120°-130°	24.4	0.6
130°-140°	13.2	0.3
140°-150°	5.8	0.1
150°-160°	1.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	924.9	22.7
0°-40°	1516.9	37.3
0°-60°	2723.5	66.9
0°-90°	3773.7	92.8
90°-120°	249.9	6.1
90°-150°	293.3	7.2
90°-180°	294.0	7.2
0°-180°	4068.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1185	1185	1185	1185	1185	
5°	1174	1185	1181	1181	1185	111
15°	1125	1140	1148	1151	1159	318
25°	1028	1043	1066	1081	1088	474
35°	894	917	950	976	988	559
45°	742	771	816	850	864	572
55°	570	604	656	700	719	510
65°	384	425	488	548	574	381
75°	198	250	339	410	440	208
85°	37	116	216	291	320	46
90°	0	71	168	238	268	2
95°	0	45	127	194	220	0
105°	0	15	71	123	142	0
115°	0	8	41	74	89	0
125°	0	4	26	48	56	0
135°	0	0	15	30	37	0
145°	0	0	8	19	22	0
155°	0	0	0	4	8	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0



TEST NUMBER: P1357430
 CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1185.0	1185.0	1185.0	1185.0	1185.0
2.5°	1177.5	1188.7	1185.0	1181.2	1181.2
5°	1173.8	1185.0	1181.2	1181.2	1185.0
7.5°	1166.3	1177.5	1177.5	1177.5	1181.2
10°	1155.2	1170.1	1170.1	1170.1	1173.8
12.5°	1144.0	1155.2	1158.9	1162.6	1166.3
15°	1125.3	1140.3	1147.7	1151.4	1158.9
17.5°	1106.7	1117.9	1129.1	1140.3	1144.0
20°	1084.4	1099.3	1110.4	1121.6	1125.3
22.5°	1058.3	1073.2	1088.1	1099.3	1106.7
25°	1028.5	1043.4	1065.7	1080.6	1088.1
27.5°	998.7	1013.6	1039.6	1058.3	1065.7
30°	961.4	983.7	1009.8	1032.2	1043.4
32.5°	927.9	950.2	980.0	1006.1	1013.6
35°	894.3	916.7	950.2	976.3	987.5
37.5°	857.1	883.1	916.7	946.5	957.7
40°	819.8	845.9	883.1	916.7	924.1
42.5°	782.5	808.6	853.3	883.1	894.3
45°	741.5	771.3	816.1	849.6	864.5
47.5°	700.5	730.4	775.1	812.3	827.2
50°	655.8	689.4	737.8	775.1	790.0
52.5°	614.8	648.4	696.8	737.8	756.4
55°	570.1	603.7	655.8	700.5	719.2
57.5°	525.4	558.9	614.8	663.3	681.9
60°	480.7	514.2	570.1	626.0	644.7
62.5°	432.3	469.5	529.1	585.0	607.4
65°	383.8	424.8	488.1	547.8	573.9
67.5°	339.1	380.1	447.2	514.2	536.6
70°	290.7	335.4	409.9	477.0	503.1
72.5°	242.2	290.7	372.6	443.4	469.5
75°	197.5	249.7	339.1	409.9	439.7
77.5°	149.1	212.4	305.6	380.1	406.2
80°	108.1	175.1	272.0	350.3	376.4
82.5°	70.8	141.6	242.2	320.5	346.5
85°	37.3	115.5	216.1	290.7	320.5
87.5°	11.2	89.4	190.0	264.6	290.7
90°	0.0	70.8	167.7	238.5	268.3
92.5°	0.0	55.9	145.3	216.1	242.2
95°	0.0	44.7	126.7	193.8	219.9
97.5°	0.0	37.3	111.8	175.1	197.5
100°	0.0	29.8	96.9	156.5	178.9
102.5°	0.0	22.4	82.0	137.9	160.2
105°	0.0	14.9	70.8	123.0	141.6
107.5°	0.0	11.2	59.6	108.1	126.7
110°	0.0	11.2	55.9	93.2	111.8



TEST NUMBER: P1357430
 CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	0.0	7.5	48.4	85.7	100.6
115°	0.0	7.5	41.0	74.5	89.4
117.5°	0.0	7.5	37.3	67.1	82.0
120°	0.0	7.5	33.5	59.6	70.8
122.5°	0.0	3.7	29.8	52.2	63.3
125°	0.0	3.7	26.1	48.4	55.9
127.5°	0.0	3.7	22.4	44.7	52.2
130°	0.0	3.7	22.4	41.0	48.4
132.5°	0.0	0.0	18.6	37.3	44.7
135°	0.0	0.0	14.9	29.8	37.3
137.5°	0.0	0.0	14.9	26.1	33.5
140°	0.0	0.0	11.2	26.1	29.8
142.5°	0.0	0.0	7.5	22.4	26.1
145°	0.0	0.0	7.5	18.6	22.4
147.5°	0.0	0.0	3.7	14.9	18.6
150°	0.0	0.0	3.7	11.2	14.9
152.5°	0.0	0.0	0.0	7.5	11.2
155°	0.0	0.0	0.0	3.7	7.5
157.5°	0.0	0.0	0.0	0.0	3.7
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0



TEST NUMBER: P1357430
 CATALOG NUMBER: 8ASL4-10HE-2-G52-UNV

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.77	16.31	15.25	16.77	17.26	16.88	18.41	17.35	18.87	19.36
	3H	16.28	17.68	16.76	18.15	18.68	19.35	20.75	19.83	21.22	21.75
	4H	16.76	18.08	17.26	18.57	19.11	20.57	21.90	21.08	22.39	22.93
	6H	17.03	18.27	17.55	18.77	19.33	21.87	23.11	22.39	23.61	24.17
	8H	17.08	18.27	17.61	18.79	19.36	22.55	23.74	23.09	24.26	24.83
	12H	17.10	18.24	17.64	18.75	19.35	23.32	24.46	23.86	24.98	25.57
4H	2H	15.66	16.99	16.17	17.48	18.02	17.30	18.63	17.81	19.12	19.66
	3H	17.40	18.54	17.92	19.07	19.63	20.00	21.14	20.52	21.67	22.23
	4H	18.01	19.05	18.55	19.59	20.19	21.40	22.44	21.94	22.98	23.58
	6H	18.41	19.33	18.97	19.90	20.51	22.90	23.82	23.46	24.38	25.00
	8H	18.51	19.37	19.07	19.94	20.56	23.69	24.55	24.26	25.12	25.74
	12H	18.56	19.34	19.14	19.94	20.57	24.58	25.37	25.17	25.96	26.59
8H	4H	18.72	19.58	19.28	20.15	20.77	21.62	22.49	22.19	23.05	23.68
	6H	19.30	20.04	19.90	20.64	21.28	23.29	24.03	23.89	24.63	25.27
	8H	19.49	20.15	20.10	20.77	21.41	24.23	24.89	24.84	25.51	26.15
	12H	19.61	20.20	20.22	20.81	21.52	25.31	25.90	25.92	26.50	27.21
12H	4H	18.92	19.71	19.51	20.30	20.93	21.63	22.41	22.22	23.01	23.64
	6H	19.61	20.28	20.22	20.89	21.54	23.33	23.99	23.94	24.61	25.26
	8H	19.90	20.49	20.51	21.10	21.81	24.33	24.92	24.94	25.53	26.24

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Fail-Safe

Report Number: SP1-2511-597-8

Test Date: 01/22/2026

Luminaire Tested: 4ASL-2-G520-UNV-OPL-1_600mA

Data in this report applies to families of products including 4ASL


Test Information

Test Method: LM-79-2019
 Report Number: SP1-2511-597-8
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 01/29/2026
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Fail-Safe
 Catalog Number: **4ASL-2-G520-UNV-OPL-1_600mA**
 Description: 2foot 4ASL LED LUMINAIRE WITH OPL LENS AND GREEN 520NM LEDS with 1 rows at 600mA

Spectral Parameters

CCT (K): 7535
 CIE u': 0.0718
 CIE v': 0.5710
 Duv: 0.1461
 CIE x: 0.1962
 CIE y: 0.6931
 CIE z: 0.1107
 Peak Wavelength (nm): 524
 Dominant Wavelength (nm): 529
 Purity: 75.95236
 Rf: NR
 Rg: NR

CRI (Ra):	-11.7		
R1:	-30.6	R9:	-351.9
R2:	5.1	R10:	-75.5
R3:	5.6	R11:	-78.0
R4:	-51.7	R12:	-14.7
R5:	-6.4	R13:	-32.5
R6:	-0.6	R14:	52.7
R7:	10.9	R15:	-37.0
R8:	-25.8		



Test Conditions


Stabilization Time: 48M
 Operation Time: 1H 48M
 Sphere Temperature (°C): 25.1

REPORT NUMBER: SP1-2511-597-8

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	12/16/2025	6/16/2026
Power Meter	XITRON INXT2011004	10/21/2025	10/21/2026
AC Power Source	CHROMA 61603 IN0063	10/21/2025	10/21/2026
DC Power Source	AGILENT E3634A IN0208	10/21/2025	10/21/2026
Sphere Thermometer	ONSET IN0085	10/21/2025	10/21/2026
Room Thermometer	ONSET IN0046	10/21/2025	10/21/2026

REPORT NUMBER: SP1-2511-597-8

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles




CCT = 7535K
 CIE x = 0.1962
 CIE y = 0.6931
 Duv = 0.1461

Point lies outside the range

REPORT NUMBER: SP1-2511-597-8

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	169	NR	620	7	NR	750	0	NR	880	0	NR
365	0	NR	495	249	NR	625	6	NR	755	0	NR	885	0	NR
370	0	NR	500	356	NR	630	4	NR	760	0	NR	890	0	NR
375	0	NR	505	502	NR	635	4	NR	765	0	NR	895	0	NR
380	0	NR	510	674	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	853	NR	645	3	NR	775	0	NR	905	0	NR
390	0	NR	520	976	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	996	NR	655	2	NR	785	0	NR	915	0	NR
400	0	NR	530	920	NR	660	2	NR	790	0	NR	920	0	NR
405	0	NR	535	792	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	642	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	511	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	394	NR	680	1	NR	810	0	NR	940	0	NR
425	1	NR	555	300	NR	685	1	NR	815	0	NR	945	0	NR
430	1	NR	560	224	NR	690	1	NR	820	0	NR	950	0	NR
435	1	NR	565	166	NR	695	1	NR	825	0	NR	955	0	NR
440	2	NR	570	122	NR	700	1	NR	830	0	NR	960	0	NR
445	3	NR	575	90	NR	705	1	NR	835	0	NR	965	0	NR
450	4	NR	580	66	NR	710	1	NR	840	0	NR	970	0	NR
455	7	NR	585	48	NR	715	0	NR	845	0	NR	975	0	NR
460	12	NR	590	36	NR	720	0	NR	850	0	NR	980	0	NR
465	19	NR	595	27	NR	725	0	NR	855	0	NR	985	0	NR
470	31	NR	600	21	NR	730	0	NR	860	0	NR	990	0	NR
475	49	NR	605	16	NR	735	0	NR	865	0	NR	995	0	NR
480	75	NR	610	12	NR	740	0	NR	870	0	NR	1000	0	NR
485	115	NR	615	9	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-8

Scotopic Flux vs. Wavelength




Scotopic Lumens: NR

S/P: 2.63

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	169	NR	620	7	NR	750	0	NR	880	0	NR
365	0	NR	495	249	NR	625	6	NR	755	0	NR	885	0	NR
370	0	NR	500	356	NR	630	4	NR	760	0	NR	890	0	NR
375	0	NR	505	502	NR	635	4	NR	765	0	NR	895	0	NR
380	0	NR	510	674	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	853	NR	645	3	NR	775	0	NR	905	0	NR
390	0	NR	520	976	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	996	NR	655	2	NR	785	0	NR	915	0	NR
400	0	NR	530	920	NR	660	2	NR	790	0	NR	920	0	NR
405	0	NR	535	792	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	642	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	511	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	394	NR	680	1	NR	810	0	NR	940	0	NR
425	1	NR	555	300	NR	685	1	NR	815	0	NR	945	0	NR
430	1	NR	560	224	NR	690	1	NR	820	0	NR	950	0	NR
435	1	NR	565	166	NR	695	1	NR	825	0	NR	955	0	NR
440	2	NR	570	122	NR	700	1	NR	830	0	NR	960	0	NR
445	3	NR	575	90	NR	705	1	NR	835	0	NR	965	0	NR
450	4	NR	580	66	NR	710	1	NR	840	0	NR	970	0	NR
455	7	NR	585	48	NR	715	0	NR	845	0	NR	975	0	NR
460	12	NR	590	36	NR	720	0	NR	850	0	NR	980	0	NR
465	19	NR	595	27	NR	725	0	NR	855	0	NR	985	0	NR
470	31	NR	600	21	NR	730	0	NR	860	0	NR	990	0	NR
475	49	NR	605	16	NR	735	0	NR	865	0	NR	995	0	NR
480	75	NR	610	12	NR	740	0	NR	870	0	NR	1000	0	NR
485	115	NR	615	9	NR	745	0	NR	875	0	NR			

REPORT NUMBER: SP1-2511-597-8

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR


M/P: 4.87

λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)	λ (nm)	Power W [^] /nm	Lumens (φ/nm)
360	0	NR	490	169	NR	620	7	NR	750	0	NR	880	0	NR
365	0	NR	495	249	NR	625	6	NR	755	0	NR	885	0	NR
370	0	NR	500	356	NR	630	4	NR	760	0	NR	890	0	NR
375	0	NR	505	502	NR	635	4	NR	765	0	NR	895	0	NR
380	0	NR	510	674	NR	640	3	NR	770	0	NR	900	0	NR
385	0	NR	515	853	NR	645	3	NR	775	0	NR	905	0	NR
390	0	NR	520	976	NR	650	2	NR	780	0	NR	910	0	NR
395	0	NR	525	996	NR	655	2	NR	785	0	NR	915	0	NR
400	0	NR	530	920	NR	660	2	NR	790	0	NR	920	0	NR
405	0	NR	535	792	NR	665	1	NR	795	0	NR	925	0	NR
410	0	NR	540	642	NR	670	1	NR	800	0	NR	930	0	NR
415	0	NR	545	511	NR	675	1	NR	805	0	NR	935	0	NR
420	0	NR	550	394	NR	680	1	NR	810	0	NR	940	0	NR
425	1	NR	555	300	NR	685	1	NR	815	0	NR	945	0	NR
430	1	NR	560	224	NR	690	1	NR	820	0	NR	950	0	NR
435	1	NR	565	166	NR	695	1	NR	825	0	NR	955	0	NR
440	2	NR	570	122	NR	700	1	NR	830	0	NR	960	0	NR
445	3	NR	575	90	NR	705	1	NR	835	0	NR	965	0	NR
450	4	NR	580	66	NR	710	1	NR	840	0	NR	970	0	NR
455	7	NR	585	48	NR	715	0	NR	845	0	NR	975	0	NR
460	12	NR	590	36	NR	720	0	NR	850	0	NR	980	0	NR
465	19	NR	595	27	NR	725	0	NR	855	0	NR	985	0	NR
470	31	NR	600	21	NR	730	0	NR	860	0	NR	990	0	NR
475	49	NR	605	16	NR	735	0	NR	865	0	NR	995	0	NR
480	75	NR	610	12	NR	740	0	NR	870	0	NR	1000	0	NR
485	115	NR	615	9	NR	745	0	NR	875	0	NR			





Summary

$R_f = 0$
 $R_g = 0$
 $CIE R_a = -11.7$
 $R_g = -351.9$

Spectral Power Distribution Comparison



Color Vector Graphics




Individual Sample Fidelity Index ($R_{f,i}$)


CES01 = 0	CES26 = 0	CES51 = 0	CES76 = 0
CES02 = 0	CES27 = 0	CES52 = 0	CES77 = 0
CES03 = 0	CES28 = 0	CES53 = 0	CES78 = 0
CES04 = 0	CES29 = 0	CES54 = 0	CES79 = 0
CES05 = 0	CES30 = 0	CES55 = 0	CES80 = 0
CES06 = 0	CES31 = 0	CES56 = 0	CES81 = 0
CES07 = 0	CES32 = 0	CES57 = 0	CES82 = 0
CES08 = 0	CES33 = 0	CES58 = 0	CES83 = 0
CES09 = 0	CES34 = 0	CES59 = 0	CES84 = 0
CES10 = 0	CES35 = 0	CES60 = 0	CES85 = 0
CES11 = 0	CES36 = 0	CES61 = 0	CES86 = 0
CES12 = 0	CES37 = 0	CES62 = 0	CES87 = 0
CES13 = 0	CES38 = 0	CES63 = 0	CES88 = 0
CES14 = 0	CES39 = 0	CES64 = 0	CES89 = 0
CES15 = 0	CES40 = 0	CES65 = 0	CES90 = 0
CES16 = 0	CES41 = 0	CES66 = 0	CES91 = 0
CES17 = 0	CES42 = 0	CES67 = 0	CES92 = 0
CES18 = 0	CES43 = 0	CES68 = 0	CES93 = 0
CES19 = 0	CES44 = 0	CES69 = 0	CES94 = 0
CES20 = 0	CES45 = 0	CES70 = 0	CES95 = 0
CES21 = 0	CES46 = 0	CES71 = 0	CES96 = 0
CES22 = 0	CES47 = 0	CES72 = 0	CES97 = 0
CES23 = 0	CES48 = 0	CES73 = 0	CES98 = 0
CES24 = 0	CES49 = 0	CES74 = 0	CES99 = 0
CES25 = 0	CES50 = 0	CES75 = 0	



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)