

LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P517492

Luminaire Tested: HVL12-4-LD4-2HI-40-UNV-C-EDD

Issue Date: 4/27/2021

Tested By:

Approved By:



NVLAP Lab Code: 200050-0

Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-2019
Report Number: P517492
Test Lab: INNOVATION CENTER
Issue Date: 4/27/2021
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: FAIL-SAFE
Catalog Number: HVL12-4-LD4-2HI-40-UNV-C-EDD
Description: 4 FOOT, 12 INCH WIDE, HVL LED LUMINAIRE, WITH 4000K, 80 CRI LEDS
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9472.0 lumens
Efficiency: N/A
Efficacy: 107.0 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.32 / 1.37
Luminous Opening: Rectangular w/ Sides (W: 1' x L: 4' x H: 0.17')
CIE Type: Direct


Input Watts (W): 88.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	P3	10/30/2015	4/30/2016
Power Meter	IN0214	1/12/2016	1/12/2017
AC Power Source	IN0062	1/12/2016	1/12/2017
DC Power Supply	--	--	--
Room Thermometer	IN0145	1/13/2016	1/13/2017

TEST NUMBER: P517492

CATALOG NUMBER: HVL12-4-LD4-2HI-40-UNV-C-EDD

Luminous Intensity Polar Plot



TEST NUMBER: P517492

CATALOG NUMBER: HVL12-4-LD4-2HI-40-UNV-C-EDD

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101			99
1	108	103	98	94	105	100	96	92	96	92	89	91	89	86	87	85	83			81
2	98	89	82	76	95	87	80	75	83	78	73	80	75	71	76	72	69			67
3	89	78	69	63	86	76	68	62	73	66	61	70	64	59	67	62	58			56
4	81	69	60	53	79	67	59	52	65	57	51	62	56	51	60	54	50			47
5	75	61	52	45	72	60	51	45	58	50	44	56	49	44	54	48	43			41
6	69	55	46	39	67	54	46	39	52	45	39	50	44	38	49	43	38			36
7	64	50	41	35	62	49	41	35	47	40	34	46	39	34	44	38	34			32
8	59	46	37	31	58	45	37	31	43	36	31	42	35	30	41	35	30			28
9	55	42	34	28	54	41	33	28	40	33	28	39	32	27	38	32	27			25
10	52	39	31	25	51	38	30	25	37	30	25	36	29	25	35	29	25			23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	8461	8461	8461
5°	8442	8377	8480
10°	8331	8533	8593
15°	8179	8343	8031
20°	7995	7855	7735
25°	7800	7554	7840
30°	7504	7318	7986
35°	7292	7097	7908
40°	7065	6942	8026
45°	6821	6732	7956
50°	6524	6512	7979
55°	6089	6276	8073
60°	5755	5935	7840
65°	5088	5519	7724
70°	4151	4961	7082
75°	2962	4266	6659
80°	1662	3569	6235
85°	617	2852	5867

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 55°

Luminance: 8073 cd/sqm

TEST NUMBER: P517492

CATALOG NUMBER: HVL12-4-LD4-2HI-40-UNV-C-EDD

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	302.2	3.2
10°-20°	860.6	9.1
20°-30°	1280.4	13.5
30°-40°	1539.1	16.2
40°-50°	1620.0	17.1
50°-60°	1503.2	15.9
60°-70°	1188.5	12.5
70°-80°	726.0	7.7
80°-90°	316.3	3.3
90°-100°	98.5	1.0
100°-110°	22.1	0.2
110°-120°	8.9	0.1
120°-130°	5.0	0.1
130°-140°	1.4	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2443.2	25.8
0°-40°	3982.3	42.0
0°-60°	7105.4	75.0
0°-90°	9336.2	98.6
90°-120°	129.5	1.4
90°-150°	135.8	1.4
90°-180°	136.0	1.4
0°-180°	9472.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	3144	3144	3144	3144	3144	
5°	3136	3130	3141	3176	3185	297
15°	2969	3083	3113	3010	3012	836
25°	2678	2849	2719	2800	2846	1229
35°	2285	2348	2383	2600	2688	1428
45°	1867	1875	2030	2351	2439	1439
55°	1375	1398	1619	1973	2130	1236
65°	870	898	1141	1510	1647	862
75°	329	436	636	977	1039	359
85°	30	102	248	481	552	46
90°	1	31	130	305	359	1
95°	1	8	57	167	204	0
105°	1	4	12	33	46	1
115°	1	3	9	15	15	1
125°	1	1	4	10	14	1
135°	1	1	1	3	4	1
145°	0	0	0	0	0	0
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P517492

CATALOG NUMBER: HVL12-4-LD4-2HI-40-UNV-C-EDD

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	3144.2	3144.2	3144.2	3144.2	3144.2
2.5°	3148.0	3139.7	3122.4	3139.1	3143.5
5°	3136.5	3130.1	3141.0	3176.2	3185.2
7.5°	3110.2	3134.6	3163.4	3227.5	3247.9
10°	3071.2	3117.3	3203.8	3258.2	3237.1
12.5°	3023.8	3101.9	3217.8	3111.5	3062.2
15°	2968.7	3082.7	3112.8	3009.7	3011.6
17.5°	2904.0	3066.7	2973.8	2971.3	2952.7
20°	2834.2	3012.9	2889.9	2884.8	2864.9
22.5°	2759.3	2941.8	2815.6	2805.4	2859.2
25°	2677.9	2848.9	2718.9	2800.2	2845.7
27.5°	2576.1	2727.2	2638.2	2753.5	2810.5
30°	2473.0	2601.7	2555.6	2716.3	2817.5
32.5°	2376.2	2470.4	2487.7	2702.2	2718.9
35°	2284.6	2348.1	2383.3	2599.8	2688.2
37.5°	2184.1	2201.4	2294.9	2556.9	2642.0
40°	2081.6	2070.7	2220.6	2486.4	2604.3
42.5°	1971.4	1967.6	2141.8	2451.2	2510.1
45°	1867.0	1875.4	2029.7	2351.3	2439.0
47.5°	1760.1	1771.0	1923.4	2241.7	2350.6
50°	1635.8	1649.9	1828.6	2144.4	2284.6
52.5°	1501.3	1528.2	1736.4	2052.1	2193.7
55°	1375.1	1397.6	1619.2	1973.4	2130.3
57.5°	1259.9	1273.3	1498.1	1874.1	1992.6
60°	1146.5	1149.7	1384.1	1763.9	1877.3
62.5°	1016.5	1022.2	1266.9	1633.9	1785.7
65°	870.4	898.0	1140.7	1509.6	1646.7
67.5°	734.0	782.0	1012.0	1395.6	1467.4
70°	588.0	669.3	885.8	1261.8	1312.4
72.5°	454.1	549.5	756.4	1111.9	1183.0
75°	329.2	436.2	636.0	977.4	1038.9
77.5°	221.6	330.5	523.3	828.8	910.1
80°	132.6	241.5	422.7	691.1	782.7
82.5°	67.9	162.0	327.9	579.6	661.6
85°	29.5	102.5	247.9	481.0	552.1
87.5°	8.3	58.3	182.5	388.8	449.0
90°	0.6	30.7	130.0	304.9	359.3
92.5°	0.6	14.7	91.6	230.6	272.2
95°	0.6	7.7	57.0	167.2	204.3
97.5°	0.6	4.5	34.6	118.5	149.9
100°	0.6	3.8	20.5	78.8	107.0
102.5°	0.6	4.5	14.1	50.0	69.8
105°	0.6	4.5	11.5	32.7	46.1
107.5°	1.3	4.5	10.2	24.3	32.0
110°	0.6	3.8	10.9	18.6	25.0

TEST NUMBER: P517492

CATALOG NUMBER: HVL12-4-LD4-2HI-40-UNV-C-EDD

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	1.3	3.2	10.2	15.4	18.6
115°	0.6	2.6	9.0	14.7	15.4
117.5°	1.3	1.9	7.0	14.7	15.4
120°	1.3	1.3	5.8	14.1	16.0
122.5°	1.3	1.3	4.5	12.8	15.4
125°	0.6	1.3	3.8	9.6	13.5
127.5°	1.3	1.3	3.2	7.7	10.2
130°	1.3	1.3	2.6	5.8	7.7
132.5°	1.3	1.3	1.9	4.5	5.8
135°	1.3	1.3	1.3	3.2	4.5
137.5°	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)