

LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: FAIL-SAFE

Report Number: P518064

Luminaire Tested: HVL8-4-LD4-2HI-35-UNV-C-EDD

Issue Date: 4/27/2021

Tested By:

Approved By:



NVLAP Lab Code: 200050-0

Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

Test Information

Test Method: LM-79-2019
Report Number: P518064
Test Lab: INNOVATION CENTER
Issue Date: 4/27/2021
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: FAIL-SAFE
Catalog Number: HVL8-4-LD4-2HI-35-UNV-C-EDD
Description: 4 FOOT, 8 INCH WIDE, HVL LED LUMINAIRE, WITH 3500K, 80 CRI LEDS
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8982.0 lumens
Efficiency: N/A
Efficacy: 104.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.32 / 1.37
Luminous Opening: Rectangular w/ Sides (W: 0.67' x L: 4' x H: 0.17')
CIE Type: Direct


Input Watts (W): 86.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	P3	10/30/2015	4/30/2016
Power Meter	IN0214	1/12/2016	1/12/2017
AC Power Source	IN0062	1/12/2016	1/12/2017
DC Power Supply	--	--	--
Room Thermometer	IN0145	1/13/2016	1/13/2017

TEST NUMBER: P518064

CATALOG NUMBER: HVL8-4-LD4-2HI-35-UNV-C-EDD

Luminous Intensity Polar Plot



TEST NUMBER: P518064

CATALOG NUMBER: HVL8-4-LD4-2HI-35-UNV-C-EDD

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	101	101	101			99
1	108	103	98	94	105	100	96	92	96	92	89	91	89	86	87	85	83			81
2	98	89	82	76	95	87	80	75	83	78	73	80	75	71	76	72	69			67
3	89	78	69	63	86	76	68	62	73	66	61	70	64	59	67	62	58			56
4	81	69	60	53	79	67	59	52	65	57	51	62	56	51	60	54	50			47
5	75	61	52	45	72	60	51	45	58	50	44	56	49	44	54	48	43			41
6	69	55	46	39	67	54	46	39	52	45	39	50	44	38	49	43	38			36
7	64	50	41	35	62	49	41	35	47	40	34	46	39	34	44	38	34			32
8	59	46	37	31	58	45	37	31	43	36	31	42	35	30	41	35	30			28
9	55	42	34	28	54	41	33	28	40	33	28	39	32	27	38	32	27			25
10	52	39	31	25	51	38	30	25	37	30	25	36	29	25	35	29	25			23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	12035	12035	12035
5°	12007	11855	11976
10°	11850	12015	12050
15°	11634	11689	11185
20°	11372	10949	10696
25°	11094	10475	10763
30°	10673	10093	10882
35°	10373	9731	10689
40°	10050	9458	10756
45°	9702	9108	10562
50°	9280	8740	10481
55°	8661	8346	10475
60°	8186	7807	10028
65°	7237	7163	9708
70°	5905	6327	8706
75°	4214	5314	7947
80°	2363	4295	7135
85°	875	3241	6284

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 90°

Vertical Angle: 45°

Luminance: 10562 cd/sqm

TEST NUMBER: P518064

CATALOG NUMBER: HVL8-4-LD4-2HI-35-UNV-C-EDD

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	286.6	3.2
10°-20°	816.0	9.1
20°-30°	1214.2	13.5
30°-40°	1459.5	16.2
40°-50°	1536.2	17.1
50°-60°	1425.4	15.9
60°-70°	1127.0	12.5
70°-80°	688.4	7.7
80°-90°	299.9	3.3
90°-100°	93.4	1.0
100°-110°	21.0	0.2
110°-120°	8.4	0.1
120°-130°	4.7	0.1
130°-140°	1.3	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2316.8	25.8
0°-40°	3776.3	42.0
0°-60°	6737.8	75.0
0°-90°	8853.2	98.6
90°-120°	122.8	1.4
90°-150°	128.8	1.4
90°-180°	129.0	1.4
0°-180°	8982.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2982	2982	2982	2982	2982	
5°	2974	2968	2978	3012	3020	282
15°	2815	2923	2952	2854	2856	793
25°	2539	2702	2578	2655	2698	1166
35°	2166	2227	2260	2465	2549	1354
45°	1770	1778	1925	2230	2313	1365
55°	1304	1325	1535	1871	2020	1172
65°	825	852	1082	1432	1562	817
75°	312	414	603	927	985	341
85°	28	97	235	456	524	43
90°	1	29	123	289	341	1
95°	1	7	54	158	194	0
105°	1	4	11	31	44	1
115°	1	2	8	14	15	1
125°	1	1	4	9	13	1
135°	1	1	1	3	4	1
145°	0	0	0	0	0	0
155°	0	0	0	0	0	0
165°	0	0	0	0	0	0
175°	0	0	0	0	0	0
180°	0	0	0	0	0	0

TEST NUMBER: P518064

CATALOG NUMBER: HVL8-4-LD4-2HI-35-UNV-C-EDD

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2981.5	2981.5	2981.5	2981.5	2981.5
2.5°	2985.2	2977.3	2960.9	2976.7	2980.9
5°	2974.2	2968.2	2978.5	3011.9	3020.4
7.5°	2949.3	2972.4	2999.8	3060.5	3079.9
10°	2912.3	2956.0	3038.0	3089.6	3069.6
12.5°	2867.4	2941.4	3051.4	2950.6	2903.8
15°	2815.1	2923.2	2951.8	2854.0	2855.8
17.5°	2753.8	2908.0	2820.0	2817.5	2799.9
20°	2687.6	2857.0	2740.4	2735.6	2716.7
22.5°	2616.5	2789.6	2670.0	2660.2	2711.3
25°	2539.4	2701.5	2578.2	2655.4	2698.5
27.5°	2442.8	2586.1	2501.7	2611.0	2665.1
30°	2345.0	2467.1	2423.4	2575.8	2671.8
32.5°	2253.3	2342.6	2359.0	2562.5	2578.2
35°	2166.5	2226.6	2260.0	2465.3	2549.1
37.5°	2071.1	2087.5	2176.2	2424.6	2505.4
40°	1973.9	1963.6	2105.7	2357.8	2469.5
42.5°	1869.5	1865.8	2031.0	2324.4	2380.2
45°	1770.5	1778.4	1924.7	2229.6	2312.8
47.5°	1669.0	1679.4	1823.9	2125.8	2229.0
50°	1551.2	1564.6	1734.0	2033.4	2166.5
52.5°	1423.7	1449.2	1646.6	1946.0	2080.2
55°	1304.0	1325.3	1535.4	1871.3	2020.1
57.5°	1194.7	1207.4	1420.6	1777.1	1889.5
60°	1087.2	1090.2	1312.5	1672.7	1780.2
62.5°	963.9	969.3	1201.4	1549.4	1693.3
65°	825.4	851.5	1081.7	1431.6	1561.5
67.5°	696.0	741.6	959.6	1323.4	1391.5
70°	557.6	634.7	840.0	1196.5	1244.5
72.5°	430.6	521.1	717.3	1054.4	1121.8
75°	312.2	413.6	603.1	926.8	985.1
77.5°	210.1	313.4	496.2	785.9	863.1
80°	125.7	229.0	400.9	655.3	742.2
82.5°	64.4	153.7	311.0	549.7	627.4
85°	27.9	97.2	235.0	456.1	523.5
87.5°	7.9	55.3	173.1	368.7	425.8
90°	0.6	29.2	123.3	289.1	340.7
92.5°	0.6	14.0	86.9	218.6	258.1
95°	0.6	7.3	54.1	158.5	193.7
97.5°	0.6	4.3	32.8	112.4	142.1
100°	0.6	3.6	19.4	74.7	101.4
102.5°	0.6	4.3	13.4	47.4	66.2
105°	0.6	4.3	10.9	31.0	43.7
107.5°	1.2	4.3	9.7	23.1	30.4
110°	0.6	3.6	10.3	17.6	23.7

TEST NUMBER: P518064

CATALOG NUMBER: HVL8-4-LD4-2HI-35-UNV-C-EDD

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°
112.5°	1.2	3.0	9.7	14.6	17.6
115°	0.6	2.4	8.5	14.0	14.6
117.5°	1.2	1.8	6.7	14.0	14.6
120°	1.2	1.2	5.5	13.4	15.2
122.5°	1.2	1.2	4.3	12.1	14.6
125°	0.6	1.2	3.6	9.1	12.8
127.5°	1.2	1.2	3.0	7.3	9.7
130°	1.2	1.2	2.4	5.5	7.3
132.5°	1.2	1.2	1.8	4.3	5.5
135°	1.2	1.2	1.2	3.0	4.3
137.5°	0.0	0.0	0.0	0.0	0.0
140°	0.0	0.0	0.0	0.0	0.0
142.5°	0.0	0.0	0.0	0.0	0.0
145°	0.0	0.0	0.0	0.0	0.0
147.5°	0.0	0.0	0.0	0.0	0.0
150°	0.0	0.0	0.0	0.0	0.0
152.5°	0.0	0.0	0.0	0.0	0.0
155°	0.0	0.0	0.0	0.0	0.0
157.5°	0.0	0.0	0.0	0.0	0.0
160°	0.0	0.0	0.0	0.0	0.0
162.5°	0.0	0.0	0.0	0.0	0.0
165°	0.0	0.0	0.0	0.0	0.0
167.5°	0.0	0.0	0.0	0.0	0.0
170°	0.0	0.0	0.0	0.0	0.0
172.5°	0.0	0.0	0.0	0.0	0.0
175°	0.0	0.0	0.0	0.0	0.0
177.5°	0.0	0.0	0.0	0.0	0.0
180°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)