

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P861209

Luminaire Tested: **8APVTLD-SL3C3 LO POWER 4000K 120V**

Issue Date: 1/11/2023

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P861209
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (NTCLR22090026)
Test Lab: INNOVATION CENTER
Issue Date: 1/11/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: 8APVTLD-SL3C3 LO POWER 4000K 120V
Description: LOW POWER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER
Luminaire Equipment: Sample No. Condition Description

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 8590.9 lumens
Efficiency: N/A
Efficacy: 145.6 lumens/watt
Spacing Criteria (0/90/45): 1.22 / 1.28 / 1.38
Luminous Opening: Rectangular w/ Sides (W: 0.33' x L: 8' x H: 0.08')
CIE Type: Direct

Input Watts (W): 59
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

Luminous Intensity Polar Plot





TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10
RCR																	
0	117	117	117	117	114	114	114	114	107	107	107	101	101	101	95	95	95
1	105	100	95	91	102	97	92	88	91	88	84	86	83	80	81	79	77
2	95	86	79	73	92	84	77	71	79	73	68	74	70	66	70	66	63
3	86	75	67	60	83	73	65	59	69	62	57	65	59	55	62	57	53
4	79	66	57	50	76	65	56	49	61	54	48	58	52	46	55	49	45
5	72	59	50	43	70	58	49	42	55	47	41	52	45	40	49	43	39
6	67	53	44	37	64	52	43	37	49	42	36	47	40	35	44	39	34
7	62	48	39	33	60	47	38	32	45	37	32	43	36	31	41	35	30
8	58	44	35	29	56	43	35	29	41	33	28	39	32	28	37	31	27
9	54	40	32	26	52	39	31	26	38	30	25	36	29	25	34	29	24
10	50	37	29	24	49	36	29	23	35	28	23	33	27	22	32	26	22

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	10212	10212	10212	10212
5°	10180	9968	10179	9997
10°	10122	9732	10123	9797
15°	10038	9517	10024	9580
20°	9924	9289	9918	9363
25°	9781	9060	9753	9141
30°	9598	8823	9561	8955
35°	9398	8596	9387	8751
40°	9200	8390	9142	8584
45°	8983	8190	8905	8412
50°	8730	8014	8656	8262
55°	8471	7835	8372	8145
60°	8165	7661	8043	8026
65°	7793	7458	7655	7900
70°	7267	7269	7147	7770
75°	6580	7067	6373	7612
80°	5588	6847	5312	7416
85°	4317	6863	3882	7427



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	239.2	2.8
10°-20°	683.9	8.0
20°-30°	1034.5	12.0
30°-40°	1250.2	14.6
40°-50°	1315.9	15.3
50°-60°	1236.5	14.4
60°-70°	1031.0	12.0
70°-80°	735.5	8.6
80°-90°	430.7	5.0
90°-100°	268.1	3.1
100°-110°	176.1	2.0
110°-120°	103.4	1.2
120°-130°	52.6	0.6
130°-140°	20.2	0.2
140°-150°	6.4	0.1
150°-160°	3.6	0.0
160°-170°	2.3	0.0
170°-180°	0.8	0.0
0°-30°	1957.6	22.8
0°-40°	3207.8	37.3
0°-60°	5760.2	67.1
0°-90°	7957.4	92.6
90°-120°	547.6	6.4
90°-150°	626.7	7.3
90°-180°	633.0	7.4
0°-180°	8590.9	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	2530	2530	2530	2530	2530	
5°	2515	2514	2514	2521	2515	239
15°	2409	2430	2406	2446	2409	679
25°	2207	2271	2200	2292	2207	1016
35°	1921	2050	1919	2087	1921	1203
45°	1590	1793	1576	1842	1590	1225
55°	1222	1511	1207	1571	1222	1091
65°	834	1200	819	1271	834	824
75°	438	876	424	944	438	464
85°	104	572	94	619	104	116
90°	31	474	24	507	31	19
95°	27	407	22	438	27	22
105°	22	292	18	323	22	24
115°	19	194	16	216	19	18
125°	14	112	12	129	14	13
135°	11	50	8	61	11	8
145°	8	8	8	14	8	5
155°	7	6	6	10	7	3
165°	7	6	9	8	7	2
175°	9	7	11	7	9	1
180°	9	9	9	9	9	



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0
1°	2530.2	2530.4	2531.2	2528.2	2527.4	2531.5	2530.2	2528.2	2530.4	2527.2	2529.2
2°	2530.2	2530.2	2530.6	2525.2	2527.4	2525.6	2529.0	2527.0	2529.6	2527.2	2527.8
3°	2528.8	2529.4	2524.5	2523.5	2524.1	2524.3	2521.3	2523.1	2524.7	2526.4	2525.0
4°	2521.3	2524.9	2519.3	2523.3	2518.2	2520.3	2512.2	2520.7	2521.1	2523.3	2523.1
5°	2514.8	2520.9	2518.0	2518.4	2513.8	2512.6	2508.9	2511.1	2514.4	2517.0	2518.5
6°	2506.1	2512.6	2514.8	2513.8	2509.5	2510.7	2506.9	2504.8	2509.5	2512.4	2515.8
7°	2501.4	2506.3	2504.4	2509.1	2506.7	2501.2	2501.8	2498.5	2502.6	2507.1	2507.1
8°	2493.7	2497.7	2499.1	2497.9	2497.3	2492.4	2492.2	2489.4	2494.5	2495.7	2498.7
9°	2487.2	2488.4	2490.4	2495.7	2487.2	2486.8	2480.9	2480.4	2485.5	2489.4	2493.5
10°	2474.1	2479.4	2479.2	2481.9	2479.0	2474.6	2471.7	2471.5	2474.2	2480.0	2483.1
11°	2468.5	2469.5	2467.4	2472.3	2470.7	2467.0	2460.1	2459.5	2461.8	2468.9	2475.2
12°	2453.8	2457.3	2457.1	2462.2	2463.0	2458.7	2449.6	2446.9	2448.7	2457.5	2463.0
13°	2437.6	2444.7	2446.3	2451.0	2455.9	2449.2	2438.4	2435.9	2432.1	2445.9	2450.0
14°	2424.4	2434.1	2428.4	2439.0	2440.6	2433.5	2423.3	2421.3	2420.7	2430.1	2437.2
15°	2408.9	2417.3	2415.2	2425.0	2429.9	2423.3	2410.8	2405.3	2405.5	2414.4	2426.2
16°	2394.1	2397.7	2400.8	2410.1	2415.8	2410.3	2396.9	2385.4	2389.2	2400.0	2412.2
17°	2374.6	2378.4	2388.8	2400.4	2402.2	2396.7	2381.9	2368.7	2374.0	2384.9	2397.5
18°	2356.3	2369.5	2372.4	2380.5	2389.2	2380.7	2366.0	2352.6	2355.9	2366.0	2381.1
19°	2339.8	2344.1	2353.9	2367.1	2376.0	2363.8	2350.2	2336.2	2337.8	2347.8	2365.4
20°	2319.1	2326.8	2333.5	2352.6	2359.3	2351.4	2330.3	2313.2	2317.7	2327.4	2349.6
21°	2298.8	2304.3	2318.9	2337.4	2340.9	2332.9	2314.4	2294.3	2294.1	2307.3	2333.7
22°	2276.6	2283.1	2297.4	2315.9	2324.8	2313.0	2292.5	2273.0	2271.4	2285.0	2313.6
23°	2254.9	2265.1	2276.8	2298.2	2305.3	2294.9	2270.8	2252.3	2248.4	2264.7	2292.1
24°	2231.7	2242.9	2257.1	2280.3	2286.0	2275.4	2254.3	2229.3	2224.4	2242.9	2269.5
25°	2206.7	2217.9	2234.0	2259.4	2271.4	2255.5	2230.9	2205.3	2200.4	2221.2	2250.2
26°	2182.8	2193.7	2213.0	2240.3	2249.0	2236.4	2210.4	2181.3	2176.3	2196.6	2228.1
27°	2156.5	2171.0	2190.7	2221.4	2228.9	2217.1	2188.7	2155.7	2150.9	2168.9	2204.5
28°	2129.5	2144.6	2166.5	2197.8	2205.7	2193.7	2164.9	2129.3	2121.6	2144.6	2182.6
29°	2099.5	2111.2	2142.5	2176.9	2187.8	2171.2	2139.5	2098.6	2091.9	2119.0	2160.2
30°	2071.6	2089.1	2118.1	2152.7	2166.1	2149.4	2115.9	2072.8	2063.7	2092.5	2136.6
31°	2042.6	2063.1	2093.6	2128.9	2144.4	2125.5	2090.9	2047.6	2036.5	2061.5	2109.8
32°	2014.3	2031.0	2063.7	2104.9	2121.8	2103.7	2061.2	2018.6	2007.0	2034.2	2084.0
33°	1984.8	2004.4	2038.9	2081.2	2097.8	2078.1	2037.3	1991.1	1979.2	2005.6	2058.0
34°	1954.2	1973.9	2013.5	2057.4	2072.0	2054.7	2011.1	1961.9	1949.3	1976.7	2032.0
35°	1921.2	1944.5	1986.1	2034.0	2049.9	2030.8	1984.4	1927.8	1918.8	1949.4	2006.6
36°	1889.9	1915.8	1957.6	2009.8	2026.9	2002.3	1957.9	1898.5	1885.4	1919.8	1979.2
37°	1860.6	1882.1	1930.4	1984.2	2001.1	1977.7	1928.0	1867.7	1852.3	1889.8	1950.6
38°	1828.8	1849.4	1902.6	1954.3	1976.3	1951.0	1898.6	1835.0	1817.5	1856.6	1925.4
39°	1794.7	1819.2	1871.9	1928.6	1951.4	1926.8	1867.1	1802.1	1781.4	1826.5	1896.9
40°	1761.2	1786.8	1844.5	1904.1	1926.2	1899.2	1840.9	1770.3	1750.1	1792.6	1866.2
41°	1727.1	1753.5	1812.6	1878.4	1902.4	1873.6	1807.7	1741.5	1717.0	1763.9	1836.5
42°	1693.4	1722.9	1782.8	1852.9	1877.5	1849.0	1775.9	1702.8	1681.2	1729.7	1807.1



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
45°	1590.0	1620.5	1686.9	1770.0	1793.3	1764.3	1684.0	1602.0	1576.3	1633.5	1716.6
46°	1554.1	1585.6	1656.8	1741.1	1768.5	1737.1	1650.9	1567.5	1541.8	1595.8	1688.0
47°	1517.7	1550.0	1626.5	1713.4	1740.5	1706.2	1617.0	1531.3	1506.6	1561.0	1659.4
48°	1481.1	1517.0	1595.8	1684.5	1712.9	1678.6	1585.3	1496.8	1467.9	1525.6	1627.6
49°	1443.3	1479.4	1564.1	1654.7	1682.3	1649.8	1553.0	1459.4	1431.4	1494.5	1595.1
50°	1407.5	1444.3	1532.7	1627.2	1656.4	1621.0	1520.2	1425.5	1395.5	1459.5	1564.6
51°	1368.4	1409.5	1501.7	1595.6	1628.6	1591.2	1488.4	1389.2	1357.6	1423.7	1531.5
52°	1331.0	1372.6	1467.3	1567.2	1596.7	1559.0	1455.1	1350.9	1319.4	1386.2	1504.1
53°	1295.6	1335.8	1433.8	1536.5	1568.7	1528.9	1421.6	1316.9	1283.0	1352.5	1469.5
54°	1259.5	1299.0	1402.4	1508.9	1541.0	1498.8	1389.6	1281.8	1245.5	1316.4	1438.6
55°	1221.6	1262.0	1367.2	1478.5	1510.8	1468.2	1355.5	1244.4	1207.3	1281.3	1406.3
56°	1181.4	1227.3	1335.6	1445.1	1480.3	1435.4	1321.2	1206.2	1170.5	1245.2	1372.0
57°	1144.9	1190.0	1299.8	1414.0	1451.4	1405.8	1290.3	1170.0	1131.8	1203.5	1339.1
58°	1106.1	1153.8	1270.1	1380.6	1418.1	1373.3	1256.3	1132.5	1092.8	1172.5	1306.5
59°	1066.8	1117.2	1234.9	1350.6	1389.6	1340.2	1220.3	1094.2	1053.9	1133.9	1274.8
60°	1029.7	1079.5	1199.1	1318.8	1359.9	1309.1	1186.1	1057.3	1014.3	1097.4	1241.5
61°	988.8	1043.2	1166.6	1288.7	1327.9	1276.6	1154.4	1021.2	975.4	1056.5	1207.9
62°	951.7	1007.5	1132.4	1254.6	1297.4	1244.9	1120.4	982.7	937.0	1022.1	1175.6
63°	911.8	971.3	1099.5	1221.8	1263.5	1211.2	1084.3	945.7	897.5	987.2	1142.8
64°	872.2	932.9	1065.1	1188.9	1235.6	1180.3	1051.8	909.2	858.2	948.0	1109.6
65°	834.1	897.5	1031.3	1156.9	1199.5	1144.4	1016.3	871.8	819.4	914.0	1075.1
66°	794.5	859.5	997.9	1125.7	1172.7	1115.4	985.2	834.9	780.7	878.3	1043.2
67°	753.7	821.5	962.8	1095.1	1137.0	1082.6	949.1	797.1	740.4	840.4	1010.7
68°	713.3	784.8	930.0	1058.5	1104.0	1049.2	914.1	763.0	699.7	804.0	977.3
69°	673.4	747.6	895.8	1027.3	1070.6	1016.4	878.4	724.7	660.2	768.3	943.7
70°	633.4	711.8	861.8	992.7	1039.0	983.5	845.8	689.0	622.9	733.5	909.7
71°	594.2	676.6	828.9	959.6	1006.3	950.8	812.4	653.7	580.6	696.7	876.8
72°	555.4	640.0	796.0	924.7	973.3	918.1	778.1	617.8	543.1	662.6	842.7
73°	515.0	604.3	762.6	888.5	941.2	885.5	745.1	583.1	502.4	625.4	809.7
74°	476.0	569.4	729.9	856.7	906.4	850.6	711.4	547.0	463.6	591.3	776.9
75°	438.3	535.1	696.8	822.8	875.9	819.4	677.9	512.2	424.5	556.4	744.9
76°	399.7	501.0	663.9	791.9	840.0	786.0	644.5	477.8	386.6	523.5	711.5
77°	362.2	467.5	629.7	759.2	811.1	755.8	613.9	445.1	349.5	489.3	679.4
78°	324.6	435.0	598.4	727.4	775.1	720.6	579.4	411.0	312.9	455.1	643.9
79°	289.2	402.4	566.6	696.4	746.7	692.5	549.4	380.2	276.7	423.0	612.6
80°	254.6	371.4	534.8	664.8	712.2	657.5	518.0	349.4	242.0	390.6	581.9
81°	221.1	341.4	504.3	634.1	684.9	629.6	489.4	319.0	207.5	360.1	551.9
82°	188.8	312.9	475.0	604.1	652.4	598.9	458.8	290.5	175.9	329.5	519.6
83°	158.1	284.8	446.3	573.6	623.4	571.3	431.7	262.1	146.1	301.6	493.1
84°	129.9	257.8	420.5	546.4	597.0	544.2	406.4	238.1	117.6	274.0	466.0
85°	104.3	233.2	395.7	520.2	571.6	519.2	383.0	214.6	93.8	249.2	439.4
86°	81.0	210.0	371.9	495.4	548.4	495.8	360.0	193.7	72.5	226.4	416.4
87°	60.7	188.3	348.7	471.2	524.6	472.7	338.3	173.2	53.4	205.7	392.4



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
90°	30.8	146.8	302.3	421.5	473.5	423.9	293.3	131.9	23.6	159.0	338.7
91°	29.9	138.6	292.2	409.2	457.6	408.5	281.7	123.9	23.1	149.4	325.2
92°	29.2	130.7	281.7	397.1	446.2	397.7	272.0	117.0	22.8	141.2	314.4
93°	28.5	123.5	271.1	384.8	432.2	384.6	262.0	109.7	23.1	132.4	302.5
94°	27.5	116.6	261.5	373.1	420.0	373.4	253.2	102.8	22.6	124.1	291.6
95°	27.3	110.0	252.1	362.1	406.8	360.3	242.5	96.5	21.9	116.7	280.8
96°	26.4	103.2	242.0	350.9	394.4	350.7	233.7	90.8	21.0	109.5	270.3
97°	25.9	97.0	232.9	338.7	382.6	338.1	223.9	85.1	19.8	102.3	258.8
98°	25.4	91.8	223.8	328.6	369.6	327.4	215.7	79.6	19.3	96.2	248.6
99°	24.9	86.1	214.6	318.2	358.7	317.0	206.8	75.0	18.8	89.6	238.5
100°	24.5	80.7	206.1	307.6	345.2	306.3	197.8	70.7	18.8	83.6	228.4
101°	24.0	76.5	197.7	297.0	335.4	296.5	189.2	65.6	18.7	78.3	219.4
102°	24.0	72.2	188.7	287.1	321.6	284.8	181.9	61.1	18.7	73.6	209.7
103°	23.5	67.6	181.0	276.1	313.7	274.8	174.4	56.8	18.6	68.6	200.5
104°	23.0	63.4	173.0	265.8	300.4	263.4	166.1	52.6	18.5	63.9	192.2
105°	22.4	59.7	165.9	256.2	291.7	254.7	159.2	49.1	18.4	59.4	183.2
106°	22.1	55.7	157.9	246.4	278.6	244.2	151.0	45.1	18.3	55.3	174.6
107°	21.9	51.5	151.0	236.8	270.6	235.7	144.3	41.6	18.2	51.2	166.5
108°	21.4	48.4	143.4	227.1	257.3	225.7	136.0	38.3	18.1	46.9	158.5
109°	20.9	44.7	136.7	217.6	250.1	217.3	129.8	35.3	17.7	43.4	151.1
110°	20.5	41.3	129.9	208.3	238.4	208.2	122.4	32.4	17.0	39.4	142.8
111°	20.0	38.3	123.3	200.0	229.9	199.7	116.5	29.4	16.9	36.3	136.0
112°	19.5	35.2	117.1	190.9	219.3	190.1	109.8	26.4	16.5	33.0	128.4
113°	19.3	32.4	110.8	182.2	211.0	181.8	104.2	24.0	15.8	29.3	121.6
114°	19.1	29.8	104.7	173.9	201.5	172.2	97.7	21.7	16.0	26.4	115.1
115°	18.8	27.4	98.9	166.0	193.5	164.3	92.4	19.3	15.5	23.8	108.4
116°	18.1	24.8	93.3	157.9	184.1	155.3	86.6	17.9	15.1	21.7	101.9
117°	17.9	22.9	87.4	150.3	175.3	148.2	81.3	16.0	14.8	18.8	95.4
118°	17.2	21.0	81.9	142.7	167.1	140.1	76.0	14.8	14.6	17.0	89.9
119°	16.7	20.1	77.4	135.2	158.1	133.1	71.4	14.3	14.3	15.3	83.5
120°	16.5	19.1	72.2	128.0	151.1	126.0	66.0	14.3	14.0	14.4	78.1
121°	16.0	18.7	67.3	121.1	141.7	118.7	61.1	14.1	13.7	14.2	73.0
122°	15.5	18.2	62.6	114.2	135.5	111.7	56.1	13.9	13.5	14.2	67.5
123°	15.5	17.9	57.8	107.6	126.6	104.9	51.8	13.8	13.2	13.7	62.0
124°	14.8	17.7	53.0	101.1	120.5	98.2	46.6	13.6	12.3	13.4	56.9
125°	14.1	17.5	48.7	94.8	111.5	91.8	42.5	12.2	12.0	12.5	52.0
126°	13.6	17.0	44.1	88.3	105.7	85.3	37.9	12.2	11.3	12.5	46.9
127°	13.2	16.5	40.1	82.1	97.8	79.3	34.2	11.7	11.3	12.0	42.4
128°	12.9	16.1	35.7	76.7	92.2	73.9	30.5	11.5	10.9	11.8	38.0
129°	12.9	15.3	32.2	70.5	84.2	67.8	26.4	11.5	10.6	11.3	33.4
130°	12.2	15.1	28.4	65.3	79.5	62.5	23.0	11.3	10.2	11.1	29.3
131°	12.0	14.6	24.9	59.5	72.8	56.7	19.6	11.5	9.8	10.6	25.4
132°	11.5	14.4	21.5	54.2	67.5	51.3	16.6	11.0	9.4	10.9	21.5



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
135°	10.6	13.2	14.2	39.4	49.8	36.5	10.2	10.3	8.0	10.4	11.8
136°	10.6	12.8	13.3	34.9	44.9	32.0	9.5	9.4	8.0	9.4	10.7
137°	10.1	12.5	13.0	30.4	39.3	27.4	9.0	8.7	8.0	8.7	9.9
138°	10.1	12.1	12.8	26.6	34.4	23.6	8.5	8.0	7.9	8.5	9.0
139°	9.6	11.7	12.3	22.4	29.5	19.6	8.3	8.0	7.9	8.0	8.5
140°	9.4	11.3	12.1	18.8	25.4	16.0	8.1	7.5	7.9	8.0	8.3
141°	9.4	10.9	11.4	15.4	21.0	12.7	7.8	7.4	7.9	7.9	7.6
142°	8.9	10.4	11.1	13.0	16.6	10.5	7.8	7.2	7.8	7.9	7.3
143°	8.9	10.2	11.1	11.9	13.6	8.6	7.7	7.1	7.8	7.8	7.1
144°	8.5	9.9	10.7	11.4	10.0	8.4	7.6	7.0	7.8	7.7	6.9
145°	8.2	9.7	10.4	11.2	8.1	8.1	7.6	6.8	7.8	7.7	6.6
146°	8.0	9.2	10.1	10.9	7.6	7.9	7.5	6.7	7.3	7.6	6.7
147°	7.8	9.0	9.8	10.7	7.4	7.9	7.4	6.6	7.1	7.5	6.7
148°	7.5	9.0	9.4	10.4	7.2	7.8	7.4	6.5	7.3	7.4	6.7
149°	7.5	8.7	9.1	10.2	6.9	7.7	7.3	6.6	6.8	7.4	6.8
150°	7.3	8.3	9.0	9.7	7.2	7.6	7.3	6.6	6.8	7.3	6.8
151°	7.3	8.3	9.0	9.7	6.9	7.5	7.3	6.6	6.1	7.2	6.8
152°	6.8	8.0	8.9	9.5	6.7	7.4	7.2	6.6	6.1	7.3	6.8
153°	7.1	7.6	8.8	9.5	6.4	7.3	7.2	6.6	6.1	7.3	6.9
154°	7.0	7.6	8.8	8.8	6.4	7.2	7.2	6.7	6.1	7.4	6.9
155°	7.0	7.6	8.8	8.7	6.4	7.1	7.1	6.7	6.1	7.4	6.9
156°	7.0	7.6	8.8	8.6	6.4	7.0	7.1	6.7	6.1	7.5	7.0
157°	6.9	7.6	8.7	8.5	6.4	6.9	7.1	6.7	6.1	7.6	7.0
158°	6.9	7.6	8.7	8.4	6.3	6.9	7.0	6.7	6.1	7.6	7.0
159°	6.9	7.6	8.7	8.3	6.3	6.9	7.0	6.8	6.1	7.7	7.1
160°	6.9	7.7	8.7	8.3	6.3	6.8	7.0	6.8	6.1	7.7	7.1
161°	7.0	7.7	8.6	8.5	6.3	6.8	6.9	6.8	7.0	7.8	7.3
162°	7.0	7.7	8.6	8.1	6.3	6.8	6.9	7.3	7.8	8.3	8.1
163°	7.0	7.7	8.6	7.8	6.3	6.7	6.9	7.7	8.2	8.5	8.5
164°	7.1	7.7	8.6	7.8	6.3	6.7	7.1	8.0	8.7	8.7	8.8
165°	7.1	7.7	8.6	7.7	6.3	6.7	7.4	8.2	9.2	8.8	9.2
166°	7.3	7.8	8.5	7.6	6.3	6.7	7.6	8.4	9.4	8.8	9.7
167°	7.3	7.8	8.5	7.6	6.4	6.6	7.6	8.5	10.1	8.8	9.9
168°	8.0	7.8	8.5	7.5	6.4	6.6	7.6	8.5	10.6	8.8	10.0
169°	8.0	8.0	8.5	7.4	6.4	6.6	7.6	8.5	11.1	8.8	10.0
170°	8.2	8.5	8.4	7.3	6.5	6.5	7.6	8.5	11.5	8.8	10.1
171°	8.0	8.7	8.4	7.3	6.5	6.5	7.6	8.6	11.5	8.9	10.1
172°	8.2	9.2	8.4	7.3	6.6	6.5	7.6	8.6	11.5	8.9	10.2
173°	8.3	9.7	8.4	7.3	6.6	6.4	7.6	8.6	11.4	8.9	10.2
174°	8.5	9.9	8.4	7.3	6.7	6.9	7.6	8.6	11.4	8.9	10.3
175°	8.6	9.9	8.3	7.3	6.7	6.9	8.1	8.6	11.4	8.9	10.3
176°	8.8	9.9	8.3	7.3	7.2	7.2	7.8	8.7	11.3	8.9	10.4
177°	8.9	10.1	8.3	7.4	7.4	7.4	7.8	8.7	11.3	9.0	10.4



TEST NUMBER: P861209
CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
180°	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0	9.0



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	2530.0	2530.0	2530.0	2530.0	2530.0	2530.0
1°	2531.5	2530.8	2532.3	2527.6	2530.2	2530.2
2°	2532.3	2529.8	2533.3	2523.9	2528.0	2530.2
3°	2531.0	2524.9	2530.6	2526.8	2527.2	2528.8
4°	2526.4	2522.3	2528.0	2525.8	2517.4	2521.3
5°	2523.7	2521.1	2523.5	2521.5	2516.8	2514.8
6°	2517.6	2518.4	2518.5	2517.6	2512.8	2506.1
7°	2512.2	2513.4	2516.2	2514.6	2507.5	2501.4
8°	2506.7	2509.5	2512.4	2508.7	2499.6	2493.7
9°	2498.5	2501.8	2503.6	2504.0	2488.6	2487.2
10°	2492.6	2495.5	2495.9	2495.7	2480.4	2474.1
11°	2482.3	2487.0	2487.6	2487.6	2466.4	2468.5
12°	2474.2	2477.4	2476.0	2476.8	2457.5	2453.8
13°	2465.2	2463.8	2471.9	2465.2	2445.9	2437.6
14°	2452.0	2454.4	2463.4	2454.2	2427.8	2424.4
15°	2440.8	2446.1	2452.6	2443.9	2415.0	2408.9
16°	2428.6	2433.5	2437.6	2429.4	2401.6	2394.1
17°	2416.6	2419.7	2426.6	2413.8	2380.5	2374.6
18°	2402.0	2405.9	2410.3	2397.7	2364.4	2356.3
19°	2388.2	2392.1	2398.0	2381.7	2344.7	2339.8
20°	2372.8	2378.0	2385.1	2365.2	2327.4	2319.1
21°	2352.8	2361.0	2367.5	2346.7	2307.1	2298.8
22°	2338.4	2346.9	2351.0	2326.4	2285.0	2276.6
23°	2321.6	2329.3	2334.1	2308.5	2263.8	2254.9
24°	2302.9	2312.8	2316.3	2290.1	2241.3	2231.7
25°	2287.2	2291.7	2294.1	2270.8	2218.9	2206.7
26°	2265.3	2275.8	2275.4	2248.6	2195.2	2182.8
27°	2247.0	2257.3	2253.9	2224.8	2171.4	2156.5
28°	2226.2	2238.0	2235.2	2200.9	2147.6	2129.5
29°	2205.3	2216.3	2214.7	2177.7	2123.2	2099.5
30°	2183.8	2198.6	2193.3	2153.7	2097.2	2071.6
31°	2161.2	2176.1	2171.0	2126.5	2068.4	2042.6
32°	2137.9	2153.1	2149.2	2103.3	2041.9	2014.3
33°	2116.5	2130.7	2126.9	2079.5	2013.3	1984.8
34°	2092.1	2110.2	2105.1	2052.5	1983.2	1954.2
35°	2067.3	2086.9	2082.0	2024.5	1952.4	1921.2
36°	2043.2	2061.7	2055.6	1997.9	1923.8	1889.9
37°	2019.0	2040.1	2031.4	1969.2	1894.0	1860.6
38°	1994.4	2017.0	2006.6	1941.9	1859.9	1828.8
39°	1967.8	1994.4	1983.6	1915.2	1830.1	1794.7
40°	1941.7	1970.8	1957.2	1883.9	1797.6	1761.2
41°	1915.7	1944.0	1932.7	1852.9	1765.1	1727.1
42°	1891.5	1918.9	1904.7	1823.2	1733.1	1693.4



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
45°	1810.5	1842.0	1821.9	1729.6	1633.6	1590.0
46°	1784.1	1815.2	1794.2	1699.7	1598.7	1554.1
47°	1757.8	1789.6	1768.1	1668.3	1564.8	1517.7
48°	1729.7	1761.7	1738.6	1635.2	1529.9	1481.1
49°	1701.8	1734.4	1711.8	1604.5	1494.6	1443.3
50°	1673.9	1707.7	1680.9	1572.2	1461.0	1407.5
51°	1644.0	1681.5	1652.1	1541.9	1425.0	1368.4
52°	1613.0	1654.0	1619.8	1511.1	1389.1	1331.0
53°	1584.0	1625.1	1590.2	1476.6	1353.6	1295.6
54°	1554.0	1598.1	1560.2	1443.2	1317.6	1259.5
55°	1525.5	1570.7	1531.9	1409.0	1282.4	1221.6
56°	1495.2	1543.0	1504.5	1376.1	1246.3	1181.4
57°	1465.4	1513.4	1473.5	1345.3	1210.7	1144.9
58°	1433.2	1483.0	1440.9	1312.1	1173.5	1106.1
59°	1404.4	1454.7	1409.4	1278.9	1136.4	1066.8
60°	1373.1	1424.6	1377.7	1245.6	1100.7	1029.7
61°	1340.4	1391.9	1344.5	1212.4	1061.8	988.8
62°	1308.9	1364.1	1311.9	1178.0	1025.9	951.7
63°	1276.7	1332.6	1282.6	1147.0	989.3	911.8
64°	1247.0	1301.1	1250.1	1113.2	951.6	872.2
65°	1212.9	1270.6	1216.9	1079.0	915.8	834.1
66°	1184.3	1237.9	1185.4	1046.4	879.3	794.5
67°	1149.2	1205.9	1153.4	1011.9	841.1	753.7
68°	1116.2	1174.6	1120.1	975.7	804.3	713.3
69°	1085.0	1144.0	1088.5	944.9	769.6	673.4
70°	1050.6	1110.6	1055.4	909.2	735.0	633.4
71°	1019.5	1078.2	1024.2	875.2	698.3	594.2
72°	986.5	1045.6	990.7	841.3	663.0	555.4
73°	953.4	1011.5	956.5	807.8	626.5	515.0
74°	921.1	980.0	923.9	774.7	591.2	476.0
75°	889.0	943.5	892.6	739.1	556.7	438.3
76°	855.7	910.7	860.2	707.3	522.3	399.7
77°	825.5	874.8	826.1	674.8	488.5	362.2
78°	791.4	839.8	795.9	641.8	453.9	324.6
79°	762.2	805.7	762.9	610.9	422.1	289.2
80°	729.7	771.4	730.6	579.5	390.0	254.6
81°	699.2	738.8	698.3	551.0	358.5	221.1
82°	668.0	706.3	667.6	521.1	328.8	188.8
83°	639.0	676.2	637.7	492.2	301.1	158.1
84°	609.7	646.6	608.0	464.7	273.3	129.9
85°	582.2	618.6	581.3	438.5	248.3	104.3
86°	558.7	592.8	555.6	413.4	224.5	81.0
87°	535.2	568.3	530.2	389.3	200.9	60.7



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
90°	478.7	506.6	469.0	332.9	154.0	30.8
91°	462.2	491.4	454.3	321.1	145.2	29.9
92°	449.3	476.8	440.4	309.5	136.7	29.2
93°	435.1	464.3	427.1	298.3	128.8	28.5
94°	421.8	450.9	414.3	287.5	120.7	27.5
95°	407.5	438.1	401.7	275.7	113.9	27.3
96°	394.9	425.2	387.5	265.2	106.9	26.4
97°	380.6	412.8	375.4	255.3	100.2	25.9
98°	368.2	400.8	363.6	246.1	93.8	25.4
99°	356.0	388.8	351.7	235.9	87.9	24.9
100°	343.6	376.9	340.5	226.0	82.3	24.5
101°	331.5	365.6	328.4	216.7	78.0	24.0
102°	319.9	354.5	317.1	207.4	73.0	24.0
103°	308.8	343.2	305.4	198.6	68.5	23.5
104°	296.5	331.6	294.5	189.9	63.7	23.0
105°	285.5	322.7	282.7	181.6	59.7	22.4
106°	273.8	311.8	272.5	172.8	55.2	22.1
107°	263.4	300.8	262.7	164.6	51.1	21.9
108°	251.8	288.7	253.4	156.6	47.9	21.4
109°	242.9	278.7	243.5	149.1	44.3	20.9
110°	231.7	267.7	233.3	141.4	41.0	20.5
111°	223.0	256.7	223.5	134.0	37.8	20.0
112°	212.7	246.0	213.7	127.5	34.9	19.5
113°	204.1	235.7	204.1	120.6	32.1	19.3
114°	194.8	225.8	194.6	113.9	29.3	19.1
115°	185.9	216.1	185.8	106.9	27.0	18.8
116°	176.5	206.2	177.2	101.2	24.4	18.1
117°	168.0	197.1	168.7	95.0	22.5	17.9
118°	159.2	188.4	160.6	89.3	21.4	17.2
119°	151.3	179.0	152.5	83.7	20.6	16.7
120°	143.5	170.3	144.2	78.6	19.9	16.5
121°	135.1	161.8	136.4	73.2	19.7	16.0
122°	128.0	153.1	129.3	68.1	19.5	15.5
123°	120.0	144.9	121.2	62.9	19.0	15.5
124°	112.6	137.2	114.2	58.1	18.8	14.8
125°	105.8	129.4	106.9	53.2	18.5	14.1
126°	98.4	121.4	99.9	48.4	17.8	13.6
127°	92.1	113.9	93.3	44.1	17.6	13.2
128°	85.6	106.9	86.5	39.7	17.1	12.9
129°	78.8	99.6	80.4	35.3	16.7	12.9
130°	73.3	92.6	74.4	31.6	16.4	12.2
131°	67.3	86.1	68.3	27.7	15.9	12.0
132°	61.2	79.7	62.5	24.5	15.3	11.5



TEST NUMBER: P861209

CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
135°	44.4	61.0	45.6	15.9	14.1	10.6
136°	38.7	55.2	40.8	14.7	13.8	10.6
137°	33.7	49.6	36.0	14.5	13.4	10.1
138°	29.2	44.0	31.1	14.2	13.1	10.1
139°	24.5	38.8	26.6	13.8	12.4	9.6
140°	20.6	34.0	22.7	13.5	12.2	9.4
141°	15.9	29.2	18.9	12.8	12.0	9.4
142°	12.3	24.5	15.6	12.6	11.5	8.9
143°	10.9	20.4	13.6	12.1	11.0	8.9
144°	9.3	16.6	12.9	11.6	10.6	8.5
145°	8.5	13.9	12.6	11.4	10.3	8.2
146°	8.3	12.9	12.3	10.9	10.3	8.0
147°	7.8	12.0	12.0	10.7	9.9	7.8
148°	7.7	11.7	11.7	10.4	9.4	7.5
149°	7.7	11.2	11.5	10.0	9.4	7.5
150°	7.6	11.0	11.0	9.7	8.9	7.3
151°	7.5	10.8	10.7	9.5	9.2	7.3
152°	7.4	10.5	10.5	9.0	8.9	6.8
153°	7.3	10.5	10.5	9.0	8.9	7.1
154°	7.2	10.0	10.3	9.0	8.8	7.0
155°	7.1	9.6	10.1	9.0	8.8	7.0
156°	6.2	9.5	9.9	9.0	8.7	7.0
157°	6.4	9.4	9.7	8.9	8.6	6.9
158°	6.2	9.3	9.5	8.9	8.6	6.9
159°	6.2	9.2	9.4	8.9	8.5	6.9
160°	6.4	9.2	9.2	8.9	8.5	6.9
161°	6.6	9.1	9.1	8.9	8.4	7.0
162°	6.9	8.6	9.0	8.8	8.4	7.0
163°	7.1	8.8	8.9	8.8	8.3	7.0
164°	7.4	8.6	8.7	8.8	8.3	7.1
165°	7.6	8.5	8.6	8.8	8.2	7.1
166°	7.8	8.4	8.5	8.8	8.7	7.3
167°	8.1	8.3	8.4	8.7	9.2	7.3
168°	8.1	8.2	8.4	8.7	9.6	8.0
169°	8.1	8.1	8.3	8.7	9.9	8.0
170°	8.1	7.7	8.3	8.7	11.0	8.2
171°	8.2	7.9	8.2	8.7	10.8	8.0
172°	8.2	7.6	8.2	8.6	11.0	8.2
173°	8.2	7.6	8.1	8.6	11.0	8.3
174°	8.2	7.4	7.9	8.6	11.0	8.5
175°	8.3	7.2	7.9	8.6	11.0	8.6
176°	8.3	7.2	7.9	8.6	11.0	8.8
177°	8.3	7.4	7.9	8.6	11.0	8.9



TEST NUMBER: P861209
CATALOG NUMBER: 8APVTLD-SL3C3 LO POWER 4000K 120V

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
180°	9.0	9.0	9.0	9.0	9.0	9.0



Report Generated By 670246072 / DESKTOP-50001EG





— 0°-180° - - 45°-225° - - - - 90°-270° - · - 135°-315°







43°	1658.9	1687.6	1752.2	1826.0	1847.9	1819.6	1743.5	1672.3	1646.9	1696.8	1777.0
44°	1624.7	1654.4	1719.9	1797.9	1821.4	1792.4	1715.0	1637.5	1611.3	1665.4	1748.6



88°	45.8	171.9	330.0	451.9	506.2	454.9	321.3	156.1	38.6	187.6	372.0
89°	35.5	157.2	315.5	435.5	486.4	436.3	304.8	141.9	28.3	171.3	353.3



133°	11.3	13.9	18.5	49.2	61.3	46.4	14.1	10.6	8.5	10.9	18.3
134°	11.0	13.2	15.9	44.1	56.0	41.1	11.7	10.6	8.0	10.6	14.7



178°	8.9	10.1	8.3	7.4	7.4	7.6	7.8	8.7	11.3	9.0	10.4
179°	8.9	10.1	8.3	7.4	7.4	7.9	7.8	8.7	11.3	9.0	10.4





43°	1865.1	1893.6	1877.2	1794.0	1699.2	1658.9
44°	1837.2	1869.1	1849.8	1762.9	1666.3	1624.7



88°	515.2	544.7	506.9	367.7	182.4	45.8
89°	494.3	524.0	486.6	349.0	166.8	35.5



133°	56.1	73.4	56.7	20.9	15.0	11.3
134°	49.4	67.1	51.2	18.0	14.8	11.0



178°	8.3	7.4	7.9	8.6	11.0	8.9
179°	8.3	7.4	7.9	8.6	11.0	8.9



LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

METALUX

Report Number: SP1-2210-820-12

Test Date: 11/10/2022

Luminaire Tested: 4APVTLD-SL3C3

Data in this report applies to families of products including 4APVTLD-SL3C3.

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2210-820-12
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 11/10/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: METALUX
 Catalog Number: **4APVTLD-SL3C3**
 Description: METALUX

0.1699(@277V) [AT MAX POWER AND 5000K]


Spectral Parameters

CCT (K): 3876
 CIE u' : 0.2271
 CIE v' : 0.5046
 Duv: 0.0006
 CIE x: 0.3864
 CIE y: 0.3817
 CIE z: 0.2319
 Peak Wavelength (nm): 453
 Dominant Wavelength (nm): 579
 Purity: 30.7

CRI (Ra): 85.1
 R1: 84.0
 R2: 92.4
 R3: 96.5
 R4: 83.1
 R5: 83.9
 R6: 89.2
 R7: 86.0
 R8: 66.1

R9: 16.2
 R10: 81.7
 R11: 82.8
 R12: 65.5
 R13: 86.4
 R14: 98.7

Rf: 85.4
 Rg: 94.7



Test Conditions


Stabilization Time: 51M
 Operation Time: 12H
 Room Temperature (°C) / RH%: 24.0/40%
 Sphere Temperature (°C): 24.6

REPORT NUMBER: SP1-2210-820-12


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	8/8/2022	2/8/2023
Power Meter	XITRON 2801 IN0071	11/29/2021	11/29/2022
AC Power Source	CHROMA 61603 IN0063	11/29/2021	11/29/2022
DC Power Source	AGILENT E3634A IN0208	11/29/2021	11/29/2022
Sphere Thermometer	ONSET IN0085	11/29/2021	11/29/2022
Room Thermometer	ONSET IN0046	11/29/2021	11/29/2022

REPORT NUMBER: SP1-2210-820-12

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 4000K 4-step quadrangle

REPORT NUMBER: SP1-2210-820-12

Photopic Flux vs. Wavelength




#####

λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)
360	1947	NR	490	30170	NR	620	69440	NR	750	3331	NR	880	2112	NR
365	1674	NR	495	34118	NR	625	65415	NR	755	3046	NR	885	1588	NR
370	1805	NR	500	38463	NR	630	60773	NR	760	2809	NR	890	1766	NR
375	1851	NR	505	42724	NR	635	56746	NR	765	2547	NR	895	1779	NR
380	1831	NR	510	46310	NR	640	52045	NR	770	2181	NR	900	1381	NR
385	1846	NR	515	49050	NR	645	47246	NR	775	1960	NR	905	1679	NR
390	1484	NR	520	50932	NR	650	42768	NR	780	1873	NR	910	1446	NR
395	1354	NR	525	52361	NR	655	38663	NR	785	1666	NR	915	1701	NR
400	1264	NR	530	53844	NR	660	34619	NR	790	1747	NR	920	1395	NR
405	1149	NR	535	55134	NR	665	30494	NR	795	1563	NR	925	1892	NR
410	1194	NR	540	56888	NR	670	26724	NR	800	1631	NR	930	1940	NR
415	1603	NR	545	58422	NR	675	23315	NR	805	1543	NR	935	1652	NR
420	2323	NR	550	60239	NR	680	20244	NR	810	1652	NR	940	1415	NR
425	4025	NR	555	62462	NR	685	17427	NR	815	1601	NR	945	1691	NR
430	7375	NR	560	64721	NR	690	14880	NR	820	1646	NR	950	1630	NR
435	13538	NR	565	67424	NR	695	12818	NR	825	1575	NR	955	1775	NR
440	24620	NR	570	69684	NR	700	11158	NR	830	1604	NR	960	1691	NR
445	46624	NR	575	71962	NR	705	9622	NR	835	1470	NR	965	1501	NR
450	77306	NR	580	74253	NR	710	8505	NR	840	1426	NR	970	1931	NR
455	79561	NR	585	76606	NR	715	7565	NR	845	1386	NR	975	1781	NR
460	57072	NR	590	77663	NR	720	6660	NR	850	1770	NR	980	542	NR
465	45082	NR	595	78567	NR	725	5882	NR	855	1753	NR	985	1915	NR
470	37690	NR	600	79045	NR	730	5159	NR	860	1742	NR	990	1791	NR
475	29009	NR	605	78162	NR	735	4513	NR	865	1894	NR	995	2066	NR
480	26519	NR	610	76190	NR	740	4095	NR	870	1926	NR	1000	1597	NR
485	27641	NR	615	73307	NR	745	3585	NR	875	1426	NR			

REPORT NUMBER: SP1-2210-820-12

Scotopic Flux vs. Wavelength




Scotopic Lumens: 7601.5

S/P: 1.7

λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)
360	1947	NR	490	30170	NR	620	69440	NR	750	3331	NR	880	2112	NR
365	1674	NR	495	34118	NR	625	65415	NR	755	3046	NR	885	1588	NR
370	1805	NR	500	38463	NR	630	60773	NR	760	2809	NR	890	1766	NR
375	1851	NR	505	42724	NR	635	56746	NR	765	2547	NR	895	1779	NR
380	1831	NR	510	46310	NR	640	52045	NR	770	2181	NR	900	1381	NR
385	1846	NR	515	49050	NR	645	47246	NR	775	1960	NR	905	1679	NR
390	1484	NR	520	50932	NR	650	42768	NR	780	1873	NR	910	1446	NR
395	1354	NR	525	52361	NR	655	38663	NR	785	1666	NR	915	1701	NR
400	1264	NR	530	53844	NR	660	34619	NR	790	1747	NR	920	1395	NR
405	1149	NR	535	55134	NR	665	30494	NR	795	1563	NR	925	1892	NR
410	1194	NR	540	56888	NR	670	26724	NR	800	1631	NR	930	1940	NR
415	1603	NR	545	58422	NR	675	23315	NR	805	1543	NR	935	1652	NR
420	2323	NR	550	60239	NR	680	20244	NR	810	1652	NR	940	1415	NR
425	4025	NR	555	62462	NR	685	17427	NR	815	1601	NR	945	1691	NR
430	7375	NR	560	64721	NR	690	14880	NR	820	1646	NR	950	1630	NR
435	13538	NR	565	67424	NR	695	12818	NR	825	1575	NR	955	1775	NR
440	24620	NR	570	69684	NR	700	11158	NR	830	1604	NR	960	1691	NR
445	46624	NR	575	71962	NR	705	9622	NR	835	1470	NR	965	1501	NR
450	77306	NR	580	74253	NR	710	8505	NR	840	1426	NR	970	1931	NR
455	79561	NR	585	76606	NR	715	7565	NR	845	1386	NR	975	1781	NR
460	57072	NR	590	77663	NR	720	6660	NR	850	1770	NR	980	542	NR
465	45082	NR	595	78567	NR	725	5882	NR	855	1753	NR	985	1915	NR
470	37690	NR	600	79045	NR	730	5159	NR	860	1742	NR	990	1791	NR
475	29009	NR	605	78162	NR	735	4513	NR	865	1894	NR	995	2066	NR
480	26519	NR	610	76190	NR	740	4095	NR	870	1926	NR	1000	1597	NR
485	27641	NR	615	73307	NR	745	3585	NR	875	1426	NR			

REPORT NUMBER: SP1-2210-820-12

Melanopic Flux vs. Wavelength



Melanopic Lumens: 3097.7

S/P: 0.69


λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)	λ (nm)	Power (μW/nm)	Lumens (φ/nm)
360	1947	NR	490	30170	NR	620	69440	NR	750	3331	NR	880	2112	NR
365	1674	NR	495	34118	NR	625	65415	NR	755	3046	NR	885	1588	NR
370	1805	NR	500	38463	NR	630	60773	NR	760	2809	NR	890	1766	NR
375	1851	NR	505	42724	NR	635	56746	NR	765	2547	NR	895	1779	NR
380	1831	NR	510	46310	NR	640	52045	NR	770	2181	NR	900	1381	NR
385	1846	NR	515	49050	NR	645	47246	NR	775	1960	NR	905	1679	NR
390	1484	NR	520	50932	NR	650	42768	NR	780	1873	NR	910	1446	NR
395	1354	NR	525	52361	NR	655	38663	NR	785	1666	NR	915	1701	NR
400	1264	NR	530	53844	NR	660	34619	NR	790	1747	NR	920	1395	NR
405	1149	NR	535	55134	NR	665	30494	NR	795	1563	NR	925	1892	NR
410	1194	NR	540	56888	NR	670	26724	NR	800	1631	NR	930	1940	NR
415	1603	NR	545	58422	NR	675	23315	NR	805	1543	NR	935	1652	NR
420	2323	NR	550	60239	NR	680	20244	NR	810	1652	NR	940	1415	NR
425	4025	NR	555	62462	NR	685	17427	NR	815	1601	NR	945	1691	NR
430	7375	NR	560	64721	NR	690	14880	NR	820	1646	NR	950	1630	NR
435	13538	NR	565	67424	NR	695	12818	NR	825	1575	NR	955	1775	NR
440	24620	NR	570	69684	NR	700	11158	NR	830	1604	NR	960	1691	NR
445	46624	NR	575	71962	NR	705	9622	NR	835	1470	NR	965	1501	NR
450	77306	NR	580	74253	NR	710	8505	NR	840	1426	NR	970	1931	NR
455	79561	NR	585	76606	NR	715	7565	NR	845	1386	NR	975	1781	NR
460	57072	NR	590	77663	NR	720	6660	NR	850	1770	NR	980	542	NR
465	45082	NR	595	78567	NR	725	5882	NR	855	1753	NR	985	1915	NR
470	37690	NR	600	79045	NR	730	5159	NR	860	1742	NR	990	1791	NR
475	29009	NR	605	78162	NR	735	4513	NR	865	1894	NR	995	2066	NR
480	26519	NR	610	76190	NR	740	4095	NR	870	1926	NR	1000	1597	NR
485	27641	NR	615	73307	NR	745	3585	NR	875	1426	NR			

REPORT NUMBER: SP1-2210-820-12





TM-30-18

Summary

$R_f = 85.4$
 $R_g = 94.7$
 CIE $R_a = 85.1$
 $R_g = 16.2$



Color Vector Graphics




REPORT NUMBER: SP1-2210-820-12

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)




CES01 = 86	CES26 = 89	CES51 = 92	CES76 = 82
CES02 = 61	CES27 = 90	CES52 = 94	CES77 = 85
CES03 = 31	CES28 = 94	CES53 = 90	CES78 = 80
CES04 = 69	CES29 = 94	CES54 = 88	CES79 = 93
CES05 = 48	CES30 = 87	CES55 = 85	CES80 = 91
CES06 = 51	CES31 = 95	CES56 = 86	CES81 = 78
CES07 = 41	CES32 = 88	CES57 = 84	CES82 = 96
CES08 = 40	CES33 = 96	CES58 = 84	CES83 = 96
CES09 = 29	CES34 = 92	CES59 = 92	CES84 = 91
CES10 = 74	CES35 = 95	CES60 = 89	CES85 = 77
CES11 = 57	CES36 = 77	CES61 = 87	CES86 = 74
CES12 = 63	CES37 = 96	CES62 = 79	CES87 = 85
CES13 = 43	CES38 = 81	CES63 = 86	CES88 = 90
CES14 = 74	CES39 = 98	CES64 = 79	CES89 = 79
CES15 = 71	CES40 = 97	CES65 = 79	CES90 = 90
CES16 = 47	CES41 = 94	CES66 = 76	CES91 = 68
CES17 = 49	CES42 = 97	CES67 = 75	CES92 = 65
CES18 = 56	CES43 = 93	CES68 = 80	CES93 = 79
CES19 = 71	CES44 = 99	CES69 = 83	CES94 = 66
CES20 = 65	CES45 = 95	CES70 = 78	CES95 = 74
CES21 = 86	CES46 = 92	CES71 = 71	CES96 = 85
CES22 = 78	CES47 = 94	CES72 = 90	CES97 = 91
CES23 = 91	CES48 = 83	CES73 = 73	CES98 = 87
CES24 = 90	CES49 = 92	CES74 = 90	CES99 = 79
CES25 = 71	CES50 = 93	CES75 = 75	



REPORT NUMBER: SP1-2210-820-12

TM-30-18



Color Rendition by Hue-Angle Bin



REPORT NUMBER: SP1-2210-820-12

TM-30-18

Measure Comparisons



(END OF REPORT)