

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P572186

Luminaire Tested: **FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P572186
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205108)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 2700K, 90 CRI LEDS, 4LBMLI TRIM
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 802.0 lumens
Efficiency: N/A
Efficacy: 82.3 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.75
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P572186

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85

Luminous Intensity Polar Plot





TEST NUMBER: P572186

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			50
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			102
1	114	111	109	106		111	109	107	105		105	103	101			101	100	98			98
2	108	103	100	96		106	102	98	95		99	96	93			96	93	91			93
3	103	97	92	88		101	95	91	87		93	89	86			90	87	85			88
4	98	91	85	81		96	89	84	81		87	83	80			85	82	79			83
5	93	85	79	75		91	84	79	75		82	78	74			81	77	73			79
6	89	80	74	70		87	79	74	70		78	73	69			76	72	69			75
7	84	75	69	65		83	75	69	65		73	68	65			72	68	64			71
8	80	71	65	61		79	70	65	61		69	64	61			68	64	60			67
9	77	67	61	57		75	67	61	57		66	61	57			65	60	57			64
10	73	64	58	54		72	63	58	54		62	57	54			62	57	54			61

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	123308
5°	122127
10°	115729
15°	105069
20°	92850
25°	80275
30°	62744
35°	38484
40°	19758
45°	7853
50°	2542
55°	878
60°	762
65°	610
70°	359
75°	475
80°	0
85°	0



TEST NUMBER: P572186

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	92.5	11.5
10°-20°	230.2	28.7
20°-30°	267.6	33.4
30°-40°	163.9	20.4
40°-50°	40.7	5.1
50°-60°	4.8	0.6
60°-70°	1.8	0.2
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	590.2	73.6
0°-40°	754.1	94.0
0°-60°	799.6	99.7
0°-90°	802.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	802.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1004	
5°	990	92
15°	826	230
25°	592	268
35°	257	164
45°	45	41
55°	4	5
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P572186

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-27 F4X-M-X-LI-BL85

CANDELA DISTRIBUTION (FULL):

	0°
0°	1003.7
2.5°	1002.6
5°	990.3
7.5°	963.6
10°	927.7
12.5°	880.5
15°	826.1
17.5°	767.6
20°	710.2
22.5°	652.7
25°	592.2
27.5°	522.4
30°	442.3
32.5°	348.9
35°	256.6
37.5°	180.6
40°	123.2
42.5°	77.0
45°	45.2
47.5°	25.7
50°	13.3
52.5°	6.2
55°	4.1
57.5°	3.1
60°	3.1
62.5°	2.1
65°	2.1
67.5°	1.0
70°	1.0
72.5°	1.0
75°	1.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)