

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P572257

Luminaire Tested: **FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P572257
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205108)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 3500K, 90 CRI LEDS, 4LBMLI TRIM
AND BOTTOM LENS, 0.125" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 886.9 lumens
Efficiency: N/A
Efficacy: 91.0 lumens/watt
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 9.75
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P572257

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84

Luminous Intensity Polar Plot





TEST NUMBER: P572257

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	109	106		111	109	107	105		105	103	101		101	100	98		98	97	96
2	108	103	100	96		106	102	98	95		99	96	93		96	93	91		93	91	89
3	103	97	92	88		101	95	91	87		93	89	86		90	87	85		88	85	83
4	98	91	85	81		96	89	84	81		87	83	80		85	82	79		83	80	78
5	93	85	79	75		91	84	79	75		82	78	74		81	77	73		79	76	73
6	89	80	74	70		87	79	74	70		78	73	69		76	72	69		75	71	68
7	84	75	69	65		83	75	69	65		73	68	65		72	68	64		71	67	64
8	80	71	65	61		79	70	65	61		69	64	61		68	64	60		67	63	60
9	77	67	61	57		75	67	61	57		66	61	57		65	60	57		64	60	57
10	73	64	58	54		72	63	58	54		62	57	54		62	57	54		61	57	54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	136367
5°	135075
10°	127992
15°	116211
20°	102682
25°	88774
30°	69397
35°	42563
40°	21843
45°	8670
50°	2810
55°	964
60°	835
65°	669
70°	395
75°	522
80°	0
85°	0



TEST NUMBER: P572257

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	102.3	11.5
10°-20°	254.6	28.7
20°-30°	295.9	33.4
30°-40°	181.2	20.4
40°-50°	45.0	5.1
50°-60°	5.2	0.6
60°-70°	2.0	0.2
70°-80°	0.7	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	652.8	73.6
0°-40°	834.0	94.0
0°-60°	884.3	99.7
0°-90°	886.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	886.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1110	
5°	1095	102
15°	914	255
25°	655	296
35°	284	181
45°	50	45
55°	4	5
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P572257

CATALOG NUMBER: FLD4C-10-D010 FEU4C-X-90-35 F4X-M-X-LI-BL84

CANDELA DISTRIBUTION (FULL):

	0°
0°	1110.0
2.5°	1108.9
5°	1095.3
7.5°	1065.8
10°	1026.0
12.5°	973.8
15°	913.7
17.5°	849.0
20°	785.4
22.5°	721.9
25°	654.9
27.5°	577.7
30°	489.2
32.5°	385.9
35°	283.8
37.5°	199.7
40°	136.2
42.5°	85.1
45°	49.9
47.5°	28.4
50°	14.7
52.5°	6.8
55°	4.5
57.5°	3.4
60°	3.4
62.5°	2.3
65°	2.3
67.5°	1.1
70°	1.1
72.5°	1.1
75°	1.1
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)