

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P572805

Luminaire Tested: **FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P572805
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207666)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 3500K, 90 CRI LEDS, 4LBNH TRIM
AND BOTTOM LENS, 0.250" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1418.0 lumens
Efficiency: N/A
Efficacy: 45.0 lumens/watt
Spacing Criteria (0/90/45): 0.81 / 0.81 / 0.85
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P572805

CATALOG NUMBER: FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86

Luminous Intensity Polar Plot





TEST NUMBER: P572805

CATALOG NUMBER: FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	78		84	81	78		83
5	92	84	78	74	91	83	78	73	81	76	73		80	75	72		78
6	88	79	73	69	86	78	72	68	76	72	68		75	71	67		74
7	83	74	68	64	82	73	68	64	72	67	63		71	66	63		70
8	79	70	64	60	78	69	64	60	68	63	59		67	63	59		66
9	76	66	60	56	74	65	60	56	65	59	56		64	59	56		63
10	72	62	57	53	71	62	56	53	61	56	53		60	56	52		60

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	218728
5°	213854
10°	197727
15°	177426
20°	156180
25°	134415
30°	108238
35°	72064
40°	37479
45°	16975
50°	7358
55°	4948
60°	3170
65°	2238
70°	1868
75°	1234
80°	0
85°	0



TEST NUMBER: P572805

CATALOG NUMBER: FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	160.6	11.3
10°-20°	389.6	27.5
20°-30°	452.4	31.9
30°-40°	299.6	21.1
40°-50°	84.0	5.9
50°-60°	21.1	1.5
60°-70°	7.9	0.6
70°-80°	2.7	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1002.6	70.7
0°-40°	1302.2	91.8
0°-60°	1407.3	99.2
0°-90°	1418.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1418.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1780	
5°	1734	161
15°	1395	390
25°	992	452
35°	480	300
45°	98	84
55°	23	21
65°	8	8
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P572805

CATALOG NUMBER: FLD4C-25-D010 FEU4C-X-90-35 F4X-N-X-H-BL86

CANDELA DISTRIBUTION (FULL):

	0°
0°	1780.4
2.5°	1772.6
5°	1734.1
7.5°	1667.2
10°	1585.0
12.5°	1492.5
15°	1395.0
17.5°	1299.9
20°	1194.6
22.5°	1097.0
25°	991.6
27.5°	891.5
30°	763.0
32.5°	626.8
35°	480.5
37.5°	344.3
40°	233.7
42.5°	151.5
45°	97.7
47.5°	59.1
50°	38.5
52.5°	28.2
55°	23.1
57.5°	18.0
60°	12.9
62.5°	10.3
65°	7.7
67.5°	5.2
70°	5.2
72.5°	2.6
75°	2.6
77.5°	2.6
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)