

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P572923

Luminaire Tested: **FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P572923
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 2700K, 90 CRI LEDS, 4LBWH TRIM
AND BOTTOM LENS, 0.125" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2184.1 lumens
Efficiency: N/A
Efficacy: 69.1 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P572923

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84

Luminous Intensity Polar Plot





TEST NUMBER: P572923

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	112	109	106	104		110	107	104	102		103	101	99		99	97	96		96	94	93
2	105	100	95	91		103	98	93	90		95	91	88		91	88	86		89	86	84
3	99	91	85	80		97	90	84	80		87	82	78		84	80	77		82	79	76
4	92	83	77	72		90	82	76	71		80	75	70		78	73	70		76	72	69
5	87	77	70	65		85	76	69	64		74	68	64		72	67	63		70	66	62
6	81	71	64	58		80	70	63	58		68	62	58		67	61	57		65	61	57
7	76	65	58	53		75	65	58	53		63	57	53		62	56	52		61	56	52
8	72	60	53	49		70	60	53	49		59	53	48		58	52	48		57	52	48
9	68	56	49	45		66	56	49	45		55	49	44		54	48	44		53	48	44
10	64	52	46	41		63	52	46	41		51	45	41		50	45	41		49	44	41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	172941
5°	173601
10°	174137
15°	174145
20°	173189
25°	169130
30°	158073
35°	136883
40°	106937
45°	76724
50°	49846
55°	29836
60°	17470
65°	11221
70°	7471
75°	5649
80°	4174
85°	0



TEST NUMBER: P572923

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	134.1	6.1
10°-20°	386.3	17.7
20°-30°	570.0	26.1
30°-40°	562.5	25.8
40°-50°	344.2	15.8
50°-60°	132.0	6.0
60°-70°	41.3	1.9
70°-80°	12.1	0.6
80°-90°	1.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1090.3	49.9
0°-40°	1652.8	75.7
0°-60°	2129.1	97.5
0°-90°	2184.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2184.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1408	
5°	1408	134
15°	1369	386
25°	1248	570
35°	913	562
45°	442	344
55°	139	132
65°	39	41
75°	12	12
85°	0	2
90°	0	



TEST NUMBER: P572923

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-27 F4X-W-X-H-BL84

CANDELA DISTRIBUTION (FULL):

	0°
0°	1407.7
2.5°	1410.7
5°	1407.7
7.5°	1404.8
10°	1395.9
12.5°	1384.0
15°	1369.2
17.5°	1351.4
20°	1324.7
22.5°	1295.1
25°	1247.7
27.5°	1188.3
30°	1114.3
32.5°	1022.5
35°	912.7
37.5°	791.2
40°	666.8
42.5°	551.2
45°	441.6
47.5°	343.7
50°	260.8
52.5°	192.7
55°	139.3
57.5°	97.8
60°	71.1
62.5°	53.4
65°	38.6
67.5°	29.7
70°	20.8
72.5°	14.8
75°	11.9
77.5°	5.9
80°	5.9
82.5°	3.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)