

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573050

Luminaire Tested: **FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85**

Issue Date: 3/1/2023



**Test Information**

Test Method: LM-79-08  
Report Number: P573050  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P205108)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/1/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: FAIL-SAFE  
Catalog Number: FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85  
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 5000K, 90 CRI LEDS, 4LBMLI TRIM  
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE  
  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2518.9 lumens  
Efficiency: N/A  
Efficacy: 79.7 lumens/watt  
Spacing Criteria (0/90/45): 0.85 / 0.85 / 0.85  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 31.6  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P573050

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85

### Luminous Intensity Polar Plot





TEST NUMBER: P573050

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
|-----|-----|-----|-----|-----|--|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|
| RF  | 20  |     |     |     |  | 20  |     |     |     |  | 20  |     |     |  |     | 20  |     |  |     |     | 20  |
| RC  | 80  |     |     |     |  | 70  |     |     |     |  | 50  |     |     |  |     | 30  |     |  |     |     | 10  |
| RW  | 70  | 50  | 30  | 10  |  | 70  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  |
| RCR |     |     |     |     |  |     |     |     |     |  |     |     |     |  |     |     |     |  |     |     |     |
| 0   | 119 | 119 | 119 | 119 |  | 116 | 116 | 116 | 116 |  | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 |
| 1   | 114 | 111 | 109 | 106 |  | 111 | 109 | 107 | 105 |  | 105 | 103 | 101 |  | 101 | 100 | 98  |  | 98  | 97  | 96  |
| 2   | 108 | 103 | 100 | 96  |  | 106 | 102 | 98  | 95  |  | 99  | 96  | 93  |  | 96  | 93  | 91  |  | 93  | 91  | 89  |
| 3   | 103 | 97  | 92  | 88  |  | 101 | 95  | 91  | 87  |  | 93  | 89  | 86  |  | 90  | 87  | 85  |  | 88  | 85  | 83  |
| 4   | 98  | 91  | 85  | 81  |  | 96  | 89  | 84  | 81  |  | 87  | 83  | 80  |  | 85  | 82  | 79  |  | 83  | 80  | 78  |
| 5   | 93  | 85  | 79  | 75  |  | 91  | 84  | 79  | 75  |  | 82  | 78  | 74  |  | 81  | 77  | 73  |  | 79  | 76  | 73  |
| 6   | 89  | 80  | 74  | 70  |  | 87  | 79  | 74  | 70  |  | 78  | 73  | 69  |  | 76  | 72  | 69  |  | 75  | 71  | 68  |
| 7   | 84  | 75  | 69  | 65  |  | 83  | 75  | 69  | 65  |  | 73  | 68  | 65  |  | 72  | 68  | 64  |  | 71  | 67  | 64  |
| 8   | 80  | 71  | 65  | 61  |  | 79  | 70  | 65  | 61  |  | 69  | 64  | 61  |  | 68  | 64  | 60  |  | 67  | 63  | 60  |
| 9   | 77  | 67  | 61  | 57  |  | 75  | 67  | 61  | 57  |  | 66  | 61  | 57  |  | 65  | 60  | 57  |  | 64  | 60  | 57  |
| 10  | 73  | 64  | 58  | 54  |  | 72  | 63  | 58  | 54  |  | 62  | 57  | 54  |  | 62  | 57  | 54  |  | 61  | 57  | 54  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 387283 |
| 5°  | 383595 |
| 10° | 363493 |
| 15° | 330026 |
| 20° | 291624 |
| 25° | 252117 |
| 30° | 197070 |
| 35° | 120851 |
| 40° | 62033  |
| 45° | 24636  |
| 50° | 8008   |
| 55° | 2763   |
| 60° | 2359   |
| 65° | 1890   |
| 70° | 1149   |
| 75° | 1519   |
| 80° | 0      |
| 85° | 0      |



TEST NUMBER: P573050

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 290.4  | 11.5      |
| 10°-20°   | 723.0  | 28.7      |
| 20°-30°   | 840.5  | 33.4      |
| 30°-40°   | 514.7  | 20.4      |
| 40°-50°   | 127.8  | 5.1       |
| 50°-60°   | 14.9   | 0.6       |
| 60°-70°   | 5.6    | 0.2       |
| 70°-80°   | 2.1    | 0.1       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 1853.9 | 73.6      |
| 0°-40°    | 2368.5 | 94.0      |
| 0°-60°    | 2511.3 | 99.7      |
| 0°-90°    | 2518.9 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 2518.9 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 3152 |      |
| 5°  | 3110 | 290  |
| 15° | 2595 | 723  |
| 25° | 1860 | 840  |
| 35° | 806  | 515  |
| 45° | 142  | 128  |
| 55° | 13   | 15   |
| 65° | 6    | 6    |
| 75° | 3    | 2    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P573050

CATALOG NUMBER: FLD4C-30-D010 FEU4C-X-90-50 F4X-M-X-LI-BL85

**CANDELA DISTRIBUTION (FULL):**

|       | 0°     |
|-------|--------|
| 0°    | 3152.4 |
| 2.5°  | 3149.2 |
| 5°    | 3110.5 |
| 7.5°  | 3026.7 |
| 10°   | 2913.8 |
| 12.5° | 2765.6 |
| 15°   | 2594.8 |
| 17.5° | 2411.0 |
| 20°   | 2230.6 |
| 22.5° | 2050.0 |
| 25°   | 1859.9 |
| 27.5° | 1640.7 |
| 30°   | 1389.2 |
| 32.5° | 1095.9 |
| 35°   | 805.8  |
| 37.5° | 567.3  |
| 40°   | 386.8  |
| 42.5° | 241.7  |
| 45°   | 141.8  |
| 47.5° | 80.6   |
| 50°   | 41.9   |
| 52.5° | 19.4   |
| 55°   | 12.9   |
| 57.5° | 9.6    |
| 60°   | 9.6    |
| 62.5° | 6.5    |
| 65°   | 6.5    |
| 67.5° | 3.2    |
| 70°   | 3.2    |
| 72.5° | 3.2    |
| 75°   | 3.2    |
| 77.5° | 0.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |
| 85°   | 0.0    |
| 87.5° | 0.0    |
| 90°   | 0.0    |



Report Generated By 670246072 / DESKTOP-MV3F9LC







— 0°-180°







(END OF REPORT)