

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573104

Luminaire Tested: **FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573104
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 2700K, 90 CRI LEDS, 4LBWH TRIM
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2458.0 lumens
Efficiency: N/A
Efficacy: 60.8 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 40.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573104

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85

Luminous Intensity Polar Plot





TEST NUMBER: P573104

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10			50	30	10			0
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111			106	106	106			100
1	112	109	106	104		110	107	104	102		103	101	99			99	97	96			91
2	105	100	95	91		103	98	93	90		95	91	88			91	88	86			82
3	99	91	85	80		97	90	84	80		87	82	78			84	80	77			74
4	92	83	77	72		90	82	76	71		80	75	70			78	73	70			67
5	87	77	70	65		85	76	69	64		74	68	64			72	67	63			61
6	81	71	64	58		80	70	63	58		68	62	58			67	61	57			55
7	76	65	58	53		75	65	58	53		63	57	53			62	56	52			50
8	72	60	53	49		70	60	53	49		59	53	48			58	52	48			46
9	68	56	49	45		66	56	49	45		55	49	44			54	48	44			43
10	64	52	46	41		63	52	46	41		51	45	41			50	45	41			39

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	194637
5°	195380
10°	195980
15°	195983
20°	194904
25°	190345
30°	177905
35°	154056
40°	120345
45°	86349
50°	56096
55°	33585
60°	19657
65°	12616
70°	8405
75°	6361
80°	4740
85°	0



TEST NUMBER: P573104

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	150.9	6.1
10°-20°	434.7	17.7
20°-30°	641.5	26.1
30°-40°	633.1	25.8
40°-50°	387.4	15.8
50°-60°	148.5	6.0
60°-70°	46.5	1.9
70°-80°	13.6	0.6
80°-90°	1.8	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1227.1	49.9
0°-40°	1860.2	75.7
0°-60°	2396.1	97.5
0°-90°	2458.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2458.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1584	
5°	1584	151
15°	1541	435
25°	1404	642
35°	1027	633
45°	497	387
55°	157	149
65°	43	46
75°	13	14
85°	0	2
90°	0	



TEST NUMBER: P573104

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-27 F4X-W-X-H-BL85

CANDELA DISTRIBUTION (FULL):

0°	
0°	1584.3
2.5°	1587.7
5°	1584.3
7.5°	1581.0
10°	1571.0
12.5°	1557.6
15°	1540.9
17.5°	1520.9
20°	1490.8
22.5°	1457.6
25°	1404.2
27.5°	1337.4
30°	1254.1
32.5°	1150.8
35°	1027.2
37.5°	890.5
40°	750.4
42.5°	620.4
45°	497.0
47.5°	386.8
50°	293.5
52.5°	216.9
55°	156.8
57.5°	110.0
60°	80.0
62.5°	60.1
65°	43.4
67.5°	33.4
70°	23.4
72.5°	16.7
75°	13.4
77.5°	6.7
80°	6.7
82.5°	3.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)