

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573116

Luminaire Tested: **FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573116
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 3000K, 90 CRI LEDS, 4LBMH TRIM
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2298.0 lumens
Efficiency: N/A
Efficacy: 56.9 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 40.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573116

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85

Luminous Intensity Polar Plot





TEST NUMBER: P573116

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	279934
5°	275873
10°	264342
15°	249669
20°	233053
25°	211559
30°	176629
35°	127960
40°	80107
45°	45781
50°	23872
55°	13387
60°	8526
65°	5029
70°	3736
75°	1661
80°	2476
85°	0



TEST NUMBER: P573116

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	209.7	9.1
10°-20°	550.1	23.9
20°-30°	706.9	30.8
30°-40°	531.9	23.1
40°-50°	213.6	9.3
50°-60°	60.7	2.6
60°-70°	19.2	0.8
70°-80°	5.5	0.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1466.6	63.8
0°-40°	1998.5	87.0
0°-60°	2272.8	98.9
0°-90°	2298.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2298.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2279	
5°	2237	210
15°	1963	550
25°	1561	707
35°	853	532
45°	264	214
55°	62	61
65°	17	19
75°	4	5
85°	0	0
90°	0	



TEST NUMBER: P573116

CATALOG NUMBER: FLD4C-35-D010 FEU4C-X-90-30 F4X-M-X-H-BL85

CANDELA DISTRIBUTION (FULL):

0°	
0°	2278.6
2.5°	2264.7
5°	2237.0
7.5°	2184.9
10°	2119.0
12.5°	2039.4
15°	1963.0
17.5°	1876.3
20°	1782.6
22.5°	1682.1
25°	1560.7
27.5°	1415.0
30°	1245.1
32.5°	1054.3
35°	853.2
37.5°	665.9
40°	499.5
42.5°	367.6
45°	263.5
47.5°	180.4
50°	124.9
52.5°	86.7
55°	62.5
57.5°	45.1
60°	34.7
62.5°	24.3
65°	17.3
67.5°	13.9
70°	10.4
72.5°	6.9
75°	3.5
77.5°	3.5
80°	3.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)