

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573298

Luminaire Tested: **FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573298
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 3000K, 90 CRI LEDS, 4LBMH TRIM
AND BOTTOM LENS, 0.125" OPAL POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1213.0 lumens
Efficiency: N/A
Efficacy: 25.8 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573298

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM

Luminous Intensity Polar Plot





TEST NUMBER: P573298

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	110	108	105		111	108	106	104		104	102	100		100	99	97		97	96	95
2	107	102	98	94		105	100	96	93		97	94	91		94	91	89		91	89	87
3	101	94	89	85		99	93	88	84		90	86	83		88	84	82		86	83	80
4	96	88	82	77		94	86	81	77		84	80	76		82	78	75		80	77	74
5	90	82	75	71		89	81	75	70		79	74	70		77	73	69		75	72	69
6	86	76	70	65		84	75	69	65		74	68	64		72	68	64		71	67	64
7	81	71	65	60		80	70	64	60		69	64	60		68	63	59		67	62	59
8	77	67	60	56		75	66	60	56		65	59	56		64	59	55		63	58	55
9	73	63	56	52		72	62	56	52		61	56	52		60	55	52		59	55	52
10	69	59	53	49		68	59	53	49		58	52	49		57	52	48		56	52	48

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	147768
5°	145620
10°	139531
15°	131791
20°	123024
25°	111669
30°	93230
35°	67549
40°	42275
45°	24167
50°	12595
55°	7068
60°	4496
65°	2674
70°	1976
75°	854
80°	1273
85°	0



TEST NUMBER: P573298

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	110.7	9.1
10°-20°	290.4	23.9
20°-30°	373.1	30.8
30°-40°	280.7	23.1
40°-50°	112.7	9.3
50°-60°	32.1	2.6
60°-70°	10.1	0.8
70°-80°	2.9	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	774.2	63.8
0°-40°	1054.9	87.0
0°-60°	1199.7	98.9
0°-90°	1213.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1213.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1203	
5°	1181	111
15°	1036	290
25°	824	373
35°	450	281
45°	139	113
55°	33	32
65°	9	10
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P573298

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-M-X-H-BL89AM

CANDELA DISTRIBUTION (FULL):

	0°
0°	1202.8
2.5°	1195.4
5°	1180.8
7.5°	1153.3
10°	1118.5
12.5°	1076.5
15°	1036.2
17.5°	990.4
20°	941.0
22.5°	887.9
25°	823.8
27.5°	746.9
30°	657.2
32.5°	556.5
35°	450.4
37.5°	351.5
40°	263.6
42.5°	194.1
45°	139.1
47.5°	95.2
50°	65.9
52.5°	45.8
55°	33.0
57.5°	23.8
60°	18.3
62.5°	12.8
65°	9.2
67.5°	7.3
70°	5.5
72.5°	3.7
75°	1.8
77.5°	1.8
80°	1.8
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)