

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573320

Luminaire Tested: **FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573320
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 3000K, 90 CRI LEDS, 4LBWH TRIM
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2966.0 lumens
Efficiency: N/A
Efficacy: 63.1 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573320

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85

Luminous Intensity Polar Plot





TEST NUMBER: P573320

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	112	109	106	104		110	107	104	102		103	101	99		99	97	96		96	94	93
2	105	100	95	91		103	98	93	90		95	91	88		91	88	86		89	86	84
3	99	91	85	80		97	90	84	80		87	82	78		84	80	77		82	79	76
4	92	83	77	72		90	82	76	71		80	75	70		78	73	70		76	72	69
5	87	77	70	65		85	76	69	64		74	68	64		72	67	63		70	66	62
6	81	71	64	58		80	70	63	58		68	62	58		67	61	57		65	61	57
7	76	65	58	53		75	65	58	53		63	57	53		62	56	52		61	56	52
8	72	60	53	49		70	60	53	49		59	53	48		58	52	48		57	52	48
9	68	56	49	45		66	56	49	45		55	49	44		54	48	44		53	48	44
10	64	52	46	41		63	52	46	41		51	45	41		50	45	41		49	44	41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	234871
5°	235768
10°	236474
15°	236492
20°	235198
25°	229682
30°	214675
35°	185896
40°	145218
45°	104193
50°	67697
55°	40524
60°	23711
65°	15232
70°	10129
75°	7642
80°	5731
85°	0



TEST NUMBER: P573320

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	182.1	6.1
10°-20°	524.6	17.7
20°-30°	774.1	26.1
30°-40°	763.9	25.8
40°-50°	467.5	15.8
50°-60°	179.2	6.0
60°-70°	56.0	1.9
70°-80°	16.4	0.6
80°-90°	2.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1480.7	49.9
0°-40°	2244.6	75.7
0°-60°	2891.4	97.5
0°-90°	2966.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2966.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1912	
5°	1912	182
15°	1859	525
25°	1694	774
35°	1240	764
45°	600	467
55°	189	179
65°	52	56
75°	16	16
85°	0	2
90°	0	



TEST NUMBER: P573320

CATALOG NUMBER: FLD4C-40-D010 FEU4C-X-90-30 F4X-W-X-H-BL85

CANDELA DISTRIBUTION (FULL):

	0°
0°	1911.8
2.5°	1915.8
5°	1911.8
7.5°	1907.7
10°	1895.6
12.5°	1879.5
15°	1859.4
17.5°	1835.2
20°	1799.0
22.5°	1758.9
25°	1694.4
27.5°	1613.8
30°	1513.3
32.5°	1388.6
35°	1239.5
37.5°	1074.5
40°	905.5
42.5°	748.6
45°	599.7
47.5°	466.8
50°	354.2
52.5°	261.7
55°	189.2
57.5°	132.8
60°	96.5
62.5°	72.5
65°	52.4
67.5°	40.3
70°	28.2
72.5°	20.1
75°	16.1
77.5°	8.1
80°	8.1
82.5°	4.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)