

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573440

Luminaire Tested: **FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573440
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P207151)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 2700K, 90 CRI LEDS, 4LBMH TRIM
AND BOTTOM LENS, 0.187" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2971.0 lumens
Efficiency: N/A
Efficacy: 59.9 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.93
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 49.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573440

CATALOG NUMBER: FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85

Luminous Intensity Polar Plot





TEST NUMBER: P573440

CATALOG NUMBER: FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75
6	86	76	70	65	84	75	69	65	74	68	64		72	68	64		71
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59
10	69	59	53	49	68	59	53	49	58	52	49		57	52	48		56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	361914
5°	356662
10°	341762
15°	322789
20°	301312
25°	273520
30°	228365
35°	165439
40°	103553
45°	59194
50°	30867
55°	17285
60°	11032
65°	6512
70°	4849
75°	2136
80°	3184
85°	0



TEST NUMBER: P573440

CATALOG NUMBER: FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	271.1	9.1
10°-20°	711.1	23.9
20°-30°	913.9	30.8
30°-40°	687.6	23.1
40°-50°	276.2	9.3
50°-60°	78.5	2.6
60°-70°	24.8	0.8
70°-80°	7.1	0.2
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1896.2	63.8
0°-40°	2583.8	87.0
0°-60°	2938.5	98.9
0°-90°	2971.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2971.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2946	
5°	2892	271
15°	2538	711
25°	2018	914
35°	1103	688
45°	341	276
55°	81	78
65°	22	25
75°	4	7
85°	0	1
90°	0	



TEST NUMBER: P573440

CATALOG NUMBER: FLD4C-45-D010 FEU4C-X-90-27 F4X-M-X-H-BL85

CANDELA DISTRIBUTION (FULL):

0°	
0°	2945.9
2.5°	2928.0
5°	2892.1
7.5°	2824.8
10°	2739.6
12.5°	2636.6
15°	2537.9
17.5°	2425.8
20°	2304.7
22.5°	2174.8
25°	2017.8
27.5°	1829.4
30°	1609.8
32.5°	1363.1
35°	1103.1
37.5°	860.9
40°	645.7
42.5°	475.3
45°	340.7
47.5°	233.3
50°	161.5
52.5°	112.1
55°	80.7
57.5°	58.3
60°	44.9
62.5°	31.4
65°	22.4
67.5°	17.9
70°	13.5
72.5°	9.0
75°	4.5
77.5°	4.5
80°	4.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)