

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P573787

Luminaire Tested: **FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84**

Issue Date: 3/1/2023



Test Information

Test Method: LM-79-08
Report Number: P573787
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P206636)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/1/2023
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84
Description: 4 INCH FAIL-SAFE LED DOWNLIGHT WITH 5000K, 90 CRI LEDS, 4LBWH TRIM
AND BOTTOM LENS, 0.125" CLEAR POLYCARBONATE

Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4227.0 lumens
Efficiency: N/A
Efficacy: 72.4 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.13
Luminous Opening: Circular (Dia: 0.33' x H: 0')
CIE Type: Direct

Input Watts (W): 58.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P573787

CATALOG NUMBER: FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84

Luminous Intensity Polar Plot





TEST NUMBER: P573787

CATALOG NUMBER: FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	112	109	106	104		110	107	104	102		103	101	99		99	97	96		96	94	93
2	105	100	95	91		103	98	93	90		95	91	88		91	88	86		89	86	84
3	99	91	85	80		97	90	84	80		87	82	78		84	80	77		82	79	76
4	92	83	77	72		90	82	76	71		80	75	70		78	73	70		76	72	69
5	87	77	70	65		85	76	69	64		74	68	64		72	67	63		70	66	62
6	81	71	64	58		80	70	63	58		68	62	58		67	61	57		65	61	57
7	76	65	58	53		75	65	58	53		63	57	53		62	56	52		61	56	52
8	72	60	53	49		70	60	53	49		59	53	48		58	52	48		57	52	48
9	68	56	49	45		66	56	49	45		55	49	44		54	48	44		53	48	44
10	64	52	46	41		63	52	46	41		51	45	41		50	45	41		49	44	41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	334727
5°	336005
10°	337021
15°	337034
20°	335186
25°	327335
30°	305947
35°	264933
40°	206962
45°	148496
50°	96461
55°	57745
60°	33785
65°	21686
70°	14440
75°	10917
80°	8136
85°	0



TEST NUMBER: P573787

CATALOG NUMBER: FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	259.5	6.1
10°-20°	747.6	17.7
20°-30°	1103.2	26.1
30°-40°	1088.7	25.8
40°-50°	666.2	15.8
50°-60°	255.4	6.0
60°-70°	79.8	1.9
70°-80°	23.4	0.6
80°-90°	3.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2110.3	49.9
0°-40°	3199.0	75.7
0°-60°	4120.6	97.5
0°-90°	4227.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4227.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2725	
5°	2725	259
15°	2650	748
25°	2415	1103
35°	1766	1089
45°	855	666
55°	270	255
65°	75	80
75°	23	23
85°	0	3
90°	0	



TEST NUMBER: P573787

CATALOG NUMBER: FLD4C-50-D010 FEU4C-X-90-50 F4X-W-X-H-BL84

CANDELA DISTRIBUTION (FULL):

	0°
0°	2724.6
2.5°	2730.3
5°	2724.6
7.5°	2718.8
10°	2701.6
12.5°	2678.6
15°	2649.9
17.5°	2615.5
20°	2563.8
22.5°	2506.6
25°	2414.8
27.5°	2300.0
30°	2156.7
32.5°	1979.0
35°	1766.5
37.5°	1531.4
40°	1290.5
42.5°	1066.9
45°	854.7
47.5°	665.2
50°	504.7
52.5°	372.9
55°	269.6
57.5°	189.2
60°	137.5
62.5°	103.3
65°	74.6
67.5°	57.4
70°	40.2
72.5°	28.7
75°	23.0
77.5°	11.5
80°	11.5
82.5°	5.7
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670246072 / DESKTOP-MV3F9LC





— 0°-180°







(END OF REPORT)