

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P309362

Luminaire Tested: **24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K**

Issue Date: 3/3/2020

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Test Information

Test Method: LM-79-08
Report Number: P309362
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1808-918-20)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: 24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K
Description: 2'X4' TROFFER LED MODULE, HIGH EFFICIENCY RND PERF. LENS, 0.250"
POLYCARB SHEET
Light Source: (336) 5500K TUNABLE CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER
Luminaire Equipment:

<u>Sample No.</u>	<u>Condition</u>	<u>Description</u>
AS-5443-1	Good	WHITE TWIN R-EVOLVE FLOOD
AS-5443-2	Good	REFLECTOR
AS-5443-3	Good	DRIVER
AS-5443-4	Good	UPPER MODULE
AS-5443-5	Good	LENS
AS-5443-6	Good	DRIVER 2
AS-5443-7	Good	TRIM RING

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2726.0 lumens
Efficiency: N/A
Efficacy: 87.1 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.3 / 1.4
Luminous Opening: Rectangular (W 2' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 31.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P309362

CATALOG NUMBER: 24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K

Luminous Intensity Polar Plot





TEST NUMBER: P309362

CATALOG NUMBER: 24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	108	103	98	94	105	101	96	93	96	93	90		92	90	87		82
2	98	89	82	76	95	87	80	75	83	78	73		80	75	71		67
3	89	78	69	62	86	76	68	62	73	66	61		70	64	59		56
4	81	68	59	52	79	67	59	52	65	57	51		62	56	50		48
5	74	61	52	45	72	60	51	45	58	50	44		56	49	44		41
6	69	55	46	39	67	54	45	39	52	44	38		50	43	38		36
7	63	50	41	34	62	49	40	34	47	39	34		46	39	34		31
8	59	45	36	30	57	44	36	30	43	36	30		42	35	30		28
9	55	41	33	27	54	41	33	27	40	32	27		39	32	27		25
10	52	38	30	25	50	38	30	25	37	30	25		36	29	24		23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1190	1190	1190
5°	1192	1187	1192
10°	1188	1187	1194
15°	1181	1184	1195
20°	1173	1181	1198
25°	1159	1176	1200
30°	1145	1172	1204
35°	1127	1166	1205
40°	1107	1159	1217
45°	1081	1157	1236
50°	1046	1156	1268
55°	1009	1164	1314
60°	952	1182	1373
65°	879	1210	1450
70°	768	1253	1544
75°	623	1317	1596
80°	459	1291	1291
85°	352	951	1074



TEST NUMBER: P309362

CATALOG NUMBER: 24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	83.8	3.1
10°-20°	240.6	8.8
20°-30°	366.3	13.4
30°-40°	444.8	16.3
40°-50°	469.9	17.2
50°-60°	443.4	16.3
60°-70°	368.7	13.5
70°-80°	242.5	8.9
80°-90°	66.1	2.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	690.7	25.3
0°-40°	1135.4	41.7
0°-60°	2048.7	75.2
0°-90°	2726.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2726.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	884	884	884	884	884	
5°	882	882	879	882	882	84
15°	848	849	850	858	858	239
25°	781	785	792	806	808	360
35°	686	694	710	728	734	429
45°	568	580	608	638	649	438
55°	430	448	496	543	560	383
65°	276	308	380	436	455	273
75°	120	175	253	300	307	129
85°	23	50	62	68	70	28
90°	0	0	0	0	0	



TEST NUMBER: P309362

CATALOG NUMBER: 24FCZ2-40HE-UNV-L82765-HRP-CP250-W2A-U-5500K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	884.5	884.5	884.5	884.5	884.5
2.5°	885.6	884.5	879.9	884.5	884.5
5°	882.2	882.2	878.7	882.2	882.2
7.5°	876.5	876.5	874.2	878.7	878.7
10°	869.6	869.6	868.5	874.2	874.2
12.5°	859.3	860.5	859.3	866.2	866.2
15°	847.9	849.1	850.2	858.2	858.2
17.5°	833.1	835.4	837.7	846.8	847.9
20°	819.4	820.5	825.1	835.4	836.5
22.5°	801.1	804.6	810.3	820.5	824.0
25°	780.6	785.2	792.0	805.7	808.0
27.5°	761.2	764.6	773.8	788.6	793.2
30°	737.2	742.9	754.4	769.2	774.9
32.5°	714.4	720.1	733.8	749.8	754.4
35°	685.9	693.9	709.8	728.1	733.8
37.5°	658.5	666.5	685.9	706.4	713.3
40°	630.0	639.1	659.6	683.6	692.7
42.5°	599.1	611.7	634.5	660.8	671.0
45°	568.3	579.7	608.3	637.9	649.4
47.5°	535.2	548.9	579.7	615.1	628.8
50°	499.9	517.0	552.4	591.2	606.0
52.5°	464.5	483.9	523.8	567.2	583.2
55°	430.2	448.5	496.4	543.2	560.3
57.5°	392.6	415.4	467.9	518.1	535.2
60°	353.8	378.9	439.4	491.9	510.1
62.5°	315.0	343.5	412.0	464.5	483.9
65°	276.2	308.1	380.0	435.9	455.4
67.5°	238.5	273.9	350.4	406.3	425.7
70°	195.2	239.7	318.4	373.2	392.6
72.5°	155.2	206.6	287.6	338.9	356.1
75°	119.8	174.6	253.4	300.1	307.0
77.5°	87.9	142.7	218.0	234.0	235.1
80°	59.3	114.1	166.6	164.3	166.6
82.5°	38.8	85.6	105.0	117.5	118.7
85°	22.8	50.2	61.6	68.5	69.6
87.5°	11.4	17.1	21.7	22.8	25.1
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)