

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P309626

Luminaire Tested: **24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K**

Issue Date: 3/3/2020

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Test Information

Test Method: LM-79-08
Report Number: P309626
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1808-918-20)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: 24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K
Description: 2'X4' TROFFER LED MODULE, HIGH EFFICIENCY RND PERF. LENS, 0.250"
POLYCARB SHEET
Light Source: (336) 2700K TUNABLE CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER
Luminaire Equipment:

<u>Sample No.</u>	<u>Condition</u>	<u>Description</u>
AS-5443-1	Good	WHITE TWIN R-EVOLVE FLOOD
AS-5443-2	Good	REFLECTOR
AS-5443-3	Good	DRIVER
AS-5443-4	Good	UPPER MODULE
AS-5443-5	Good	LENS
AS-5443-6	Good	DRIVER 2
AS-5443-7	Good	TRIM RING

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3278.0 lumens
Efficiency: N/A
Efficacy: 76.1 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.3 / 1.4
Luminous Opening: Rectangular (W 2' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 43.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P309626

CATALOG NUMBER: 24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K

Luminous Intensity Polar Plot





TEST NUMBER: P309626

CATALOG NUMBER: 24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	108	103	98	94	105	101	96	93	96	93	90		92	90	87		82
2	98	89	82	76	95	87	80	75	83	78	73		80	75	71		67
3	89	78	69	62	86	76	68	62	73	66	61		70	64	59		56
4	81	68	59	52	79	67	59	52	65	57	51		62	56	50		48
5	74	61	52	45	72	60	51	45	58	50	44		56	49	44		41
6	69	55	46	39	67	54	45	39	52	44	38		50	43	38		36
7	63	50	41	34	62	49	40	34	47	39	34		46	39	34		31
8	59	45	36	30	57	44	36	30	43	36	30		42	35	30		28
9	55	41	33	27	54	41	33	27	40	32	27		39	32	27		25
10	52	38	30	25	50	38	30	25	37	30	25		36	29	24		23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1431	1431	1431
5°	1433	1427	1433
10°	1429	1427	1436
15°	1420	1424	1438
20°	1411	1421	1440
25°	1394	1414	1442
30°	1377	1409	1448
35°	1355	1402	1449
40°	1330	1393	1463
45°	1300	1392	1486
50°	1258	1390	1525
55°	1214	1400	1581
60°	1145	1422	1651
65°	1057	1455	1743
70°	923	1506	1857
75°	749	1584	1919
80°	553	1553	1553
85°	423	1144	1292



TEST NUMBER: P309626

CATALOG NUMBER: 24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	100.7	3.1
10°-20°	289.3	8.8
20°-30°	440.5	13.4
30°-40°	534.8	16.3
40°-50°	565.0	17.2
50°-60°	533.2	16.3
60°-70°	443.3	13.5
70°-80°	291.7	8.9
80°-90°	79.5	2.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	830.5	25.3
0°-40°	1365.3	41.7
0°-60°	2463.5	75.2
0°-90°	3278.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3278.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1064	1064	1064	1064	1064	
5°	1061	1061	1057	1061	1061	101
15°	1020	1021	1022	1032	1032	288
25°	939	944	952	969	972	433
35°	825	834	854	876	882	516
45°	683	697	731	767	781	526
55°	517	539	597	653	674	461
65°	332	370	457	524	548	328
75°	144	210	305	361	369	155
85°	27	60	74	82	84	34
90°	0	0	0	0	0	



TEST NUMBER: P309626

CATALOG NUMBER: 24FCZ2-55HE-UNV-L82765-HRP-CP250-W2A-U-2700K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1063.5	1063.5	1063.5	1063.5	1063.5
2.5°	1064.9	1063.5	1058.1	1063.5	1063.5
5°	1060.8	1060.8	1056.7	1060.8	1060.8
7.5°	1053.9	1053.9	1051.2	1056.7	1056.7
10°	1045.7	1045.7	1044.3	1051.2	1051.2
12.5°	1033.4	1034.7	1033.4	1041.6	1041.6
15°	1019.6	1021.0	1022.4	1032.0	1032.0
17.5°	1001.8	1004.5	1007.3	1018.3	1019.6
20°	985.3	986.7	992.2	1004.5	1005.9
22.5°	963.4	967.5	974.3	986.7	990.8
25°	938.7	944.2	952.4	968.9	971.6
27.5°	915.3	919.5	930.4	948.3	953.8
30°	886.5	893.4	907.1	924.9	931.8
32.5°	859.1	865.9	882.4	901.6	907.1
35°	824.8	834.4	853.6	875.5	882.4
37.5°	791.8	801.4	824.8	849.5	857.7
40°	757.5	768.5	793.2	822.0	833.0
42.5°	720.5	735.6	763.0	794.6	806.9
45°	683.4	697.1	731.4	767.1	780.9
47.5°	643.6	660.1	697.1	739.7	756.1
50°	601.1	621.7	664.2	710.9	728.7
52.5°	558.5	581.9	629.9	682.0	701.3
55°	517.4	539.3	597.0	653.2	673.8
57.5°	472.1	499.5	562.7	623.0	643.6
60°	425.4	455.6	528.3	591.5	613.4
62.5°	378.8	413.1	495.4	558.5	581.9
65°	332.1	370.5	457.0	524.2	547.6
67.5°	286.8	329.4	421.3	488.5	511.9
70°	234.7	288.2	382.9	448.7	472.1
72.5°	186.6	248.4	345.8	407.6	428.2
75°	144.1	210.0	304.7	360.9	369.2
77.5°	105.7	171.5	262.1	281.3	282.7
80°	71.4	137.2	200.4	197.6	200.4
82.5°	46.7	102.9	126.3	141.3	142.7
85°	27.4	60.4	74.1	82.3	83.7
87.5°	13.7	20.6	26.1	27.4	30.2
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)