

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P310235

Luminaire Tested: **24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K**

Issue Date: 3/3/2020

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Test Information

Test Method: LM-79-08
Report Number: P310235
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1808-918-19)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: 24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K
Description: 2'X4' TROFFER LED MODULE, SMOOTH LENS WITH INSERT, 0.125" ACRYLIC SHEET
Light Source: (168) 5500K TUNABLE CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER
Luminaire Equipment:

<u>Sample No.</u>	<u>Condition</u>	<u>Description</u>
AS-5443-1	Good	WHITE TWIN R-EVOLVE FLOOD
AS-5443-2	Good	REFLECTOR
AS-5443-3	Good	DRIVER
AS-5443-4	Good	UPPER MODULE
AS-5443-5	Good	LENS
AS-5443-6	Good	DRIVER 2
AS-5443-7	Good	TRIM RING

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3187.0 lumens
Efficiency: N/A
Efficacy: 72.6 lumens/watt
Spacing Criteria (0/90/45): 1.26 / 1.3 / 1.41
Luminous Opening: Rectangular (W 2' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 43.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P310235

CATALOG NUMBER: 24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K

Luminous Intensity Polar Plot





TEST NUMBER: P310235

CATALOG NUMBER: 24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	108	103	98	94	105	100	96	92	96	93	89	92	89	87	88	86	84	82		
2	97	89	81	75	95	87	80	74	83	77	72	80	75	71	77	73	69	67		
3	88	77	68	62	86	76	67	61	72	66	60	70	64	59	67	62	58	56		
4	81	68	59	52	78	67	58	51	64	57	51	62	55	50	59	54	49	47		
5	74	60	51	44	72	59	51	44	57	49	43	55	48	43	53	47	42	40		
6	68	54	45	38	66	53	45	38	51	44	38	50	43	37	48	42	37	35		
7	63	49	40	34	61	48	40	34	47	39	33	45	38	33	44	38	33	31		
8	59	45	36	30	57	44	36	30	43	35	30	41	34	29	40	34	29	27		
9	55	41	33	27	53	40	32	27	39	32	27	38	31	26	37	31	26	24		
10	51	38	30	24	50	37	29	24	36	29	24	35	29	24	34	28	24	22		

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1348	1348	1348
5°	1354	1345	1351
10°	1350	1345	1352
15°	1348	1345	1354
20°	1338	1344	1358
25°	1333	1347	1361
30°	1321	1343	1365
35°	1309	1340	1371
40°	1294	1338	1388
45°	1272	1339	1420
50°	1244	1347	1463
55°	1213	1368	1528
60°	1161	1395	1612
65°	1087	1444	1711
70°	989	1511	1841
75°	838	1594	1923
80°	662	1605	1556
85°	488	1220	1366



TEST NUMBER: P310235

CATALOG NUMBER: 24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	95.1	3.0
10°-20°	273.6	8.6
20°-30°	418.4	13.1
30°-40°	511.5	16.0
40°-50°	545.2	17.1
50°-60°	521.2	16.4
60°-70°	441.6	13.9
70°-80°	296.8	9.3
80°-90°	83.7	2.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	787.1	24.7
0°-40°	1298.6	40.7
0°-60°	2365.0	74.2
0°-90°	3187.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3187.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	1002	1002	1002	1002	1002	
5°	1002	1001	996	1001	1001	95
15°	967	967	966	974	972	273
25°	898	901	907	915	917	414
35°	797	803	816	832	835	499
45°	669	680	704	734	746	516
55°	517	536	583	629	651	460
65°	342	376	454	514	538	339
75°	161	220	307	359	370	173
85°	32	65	79	85	88	39
90°	0	0	0	0	0	



TEST NUMBER: P310235

CATALOG NUMBER: 24FCZ2-50-UNV-L82765-RDP-CA125-W2A-U-5500K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	1002.2	1002.2	1002.2	1002.2	1002.2
2.5°	1003.8	1003.8	999.1	1002.2	1002.2
5°	1002.2	1000.6	995.9	1000.6	1000.6
7.5°	997.5	995.9	992.7	997.5	995.9
10°	988.0	988.0	984.8	989.6	989.6
12.5°	980.1	978.5	976.9	983.3	981.7
15°	967.4	967.4	965.9	973.8	972.2
17.5°	951.6	953.2	954.8	961.1	962.7
20°	934.2	937.4	939.0	948.5	948.5
22.5°	918.4	920.0	923.2	932.7	932.7
25°	897.9	901.0	907.4	915.3	916.9
27.5°	877.3	878.9	886.8	897.9	899.5
30°	850.5	855.2	864.7	877.3	878.9
32.5°	826.8	831.5	842.6	855.2	858.4
35°	796.7	803.0	815.7	831.5	834.7
37.5°	769.8	774.6	790.4	807.8	812.5
40°	736.6	746.1	761.9	782.5	790.4
42.5°	703.5	712.9	731.9	758.8	768.3
45°	668.7	679.7	703.5	733.5	746.1
47.5°	633.9	646.5	673.4	708.2	722.4
50°	594.4	610.2	643.4	682.9	698.7
52.5°	556.4	575.4	611.8	656.0	676.6
55°	516.9	535.9	583.3	629.2	651.3
57.5°	472.7	497.9	550.1	602.3	626.0
60°	431.6	455.3	518.5	575.4	599.1
62.5°	387.3	418.9	486.9	547.0	570.7
65°	341.5	376.2	453.7	513.8	537.5
67.5°	300.3	338.3	420.5	480.6	504.3
70°	251.3	298.8	384.1	444.2	467.9
72.5°	205.5	257.7	346.2	404.7	426.8
75°	161.2	219.7	306.7	358.8	369.9
77.5°	120.1	181.8	265.6	287.7	279.8
80°	85.4	145.4	207.1	196.0	200.8
82.5°	55.3	110.7	128.0	145.4	150.2
85°	31.6	64.8	79.0	85.4	88.5
87.5°	14.2	23.7	31.6	31.6	30.0
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)