

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: FAIL-SAFE

Report Number: P311055

Luminaire Tested: **24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K**

Issue Date: 3/3/2020

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.

Test Information

Test Method: LM-79-08
Report Number: P311055
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1805-783-15)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: FAIL-SAFE
Catalog Number: 24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K
Description: 2'X4' TROFFER LED MODULE, RIBBED LENS, 0.125" POLYCARB SHEET
Light Source: (336) 5700K TUNABLE CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER
Luminaire Equipment:

<u>Sample No.</u>	<u>Condition</u>	<u>Description</u>
AS-5443-1	Good	WHITE TWIN R-EVOLVE FLOOD
AS-5443-2	Good	REFLECTOR
AS-5443-3	Good	DRIVER
AS-5443-4	Good	UPPER MODULE
AS-5443-5	Good	LENS
AS-5443-6	Good	DRIVER 2
AS-5443-7	Good	TRIM RING

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6087.0 lumens
Efficiency: N/A
Efficacy: 112.5 lumens/watt
Spacing Criteria (0/90/45): 1.22 / 1.29 / 1.38
Luminous Opening: Rectangular (W 2' x L: 4' x H: 0')
CIE Type: Direct


Input Watts (W): 54.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P311055

CATALOG NUMBER: 24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K

Luminous Intensity Polar Plot





TEST NUMBER: P311055

CATALOG NUMBER: 24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	108	103	98	94	105	100	96	92	96	92	89		92	89	87		82
2	98	89	81	75	95	87	80	74	83	78	73		80	75	71		67
3	89	77	69	62	86	76	68	61	73	66	60		70	64	59		56
4	81	68	59	52	79	67	58	52	64	57	51		62	56	50		47
5	74	61	52	45	72	60	51	44	58	50	44		56	49	43		41
6	69	55	46	39	67	54	45	39	52	44	38		50	43	38		36
7	64	50	41	34	62	49	40	34	47	39	34		46	39	34		31
8	59	45	37	31	57	45	36	30	43	36	30		42	35	30		28
9	55	41	33	27	54	41	33	27	40	32	27		39	32	27		25
10	52	38	30	25	50	38	30	25	37	30	25		36	29	25		23

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	2701	2701	2701
5°	2706	2690	2706
10°	2690	2682	2704
15°	2667	2673	2706
20°	2634	2655	2704
25°	2593	2635	2701
30°	2545	2614	2698
35°	2495	2587	2700
40°	2437	2568	2717
45°	2379	2552	2740
50°	2308	2545	2782
55°	2250	2549	2838
60°	2163	2571	2935
65°	2064	2598	3041
70°	1954	2677	3210
75°	1743	2793	3506
80°	1487	2958	3584
85°	1061	2930	3430



TEST NUMBER: P311055

CATALOG NUMBER: 24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	190.0	3.1
10°-20°	543.2	8.9
20°-30°	820.5	13.5
30°-40°	988.9	16.2
40°-50°	1038.2	17.1
50°-60°	971.3	16.0
60°-70°	802.1	13.2
70°-80°	546.6	9.0
80°-90°	186.4	3.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1553.7	25.5
0°-40°	2542.6	41.8
0°-60°	4552.0	74.8
0°-90°	6087.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6087.0	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	2007	2007	2007	2007	2007	
5°	2003	2001	1991	2003	2003	190
15°	1914	1917	1919	1939	1943	540
25°	1747	1755	1775	1810	1820	804
35°	1519	1535	1575	1628	1644	949
45°	1250	1276	1341	1414	1440	964
55°	959	998	1086	1175	1210	856
65°	648	703	816	919	955	643
75°	335	412	537	638	674	357
85°	69	135	190	214	222	86
90°	0	0	0	0	0	



TEST NUMBER: P311055

CATALOG NUMBER: 24FCZ2-65HE-UNV-L82765-CP125-W2A-U-5700K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	2007.4	2007.4	2007.4	2007.4	2007.4
2.5°	2009.5	2007.4	1997.3	2007.4	2005.4
5°	2003.4	2001.4	1991.3	2003.4	2003.4
7.5°	1989.3	1989.3	1979.2	1993.3	1995.3
10°	1969.1	1969.1	1963.0	1979.2	1979.2
12.5°	1944.8	1944.8	1944.8	1961.0	1963.0
15°	1914.5	1916.6	1918.6	1938.8	1942.8
17.5°	1878.2	1882.2	1888.3	1912.5	1916.6
20°	1839.8	1843.9	1854.0	1882.2	1888.3
22.5°	1791.3	1801.4	1815.6	1847.9	1854.0
25°	1746.9	1755.0	1775.2	1809.5	1819.6
27.5°	1692.4	1704.5	1730.8	1767.1	1781.2
30°	1637.9	1650.0	1682.3	1724.7	1736.8
32.5°	1579.3	1597.5	1631.8	1676.2	1690.4
35°	1518.7	1534.9	1575.3	1627.8	1643.9
37.5°	1452.1	1474.3	1518.7	1575.3	1595.5
40°	1387.4	1411.7	1462.2	1522.7	1547.0
42.5°	1322.8	1347.0	1403.6	1472.3	1496.5
45°	1250.1	1276.4	1341.0	1413.7	1439.9
47.5°	1177.4	1209.7	1280.4	1357.1	1385.4
50°	1102.7	1139.0	1215.8	1296.6	1328.9
52.5°	1036.0	1070.4	1151.1	1238.0	1268.3
55°	959.3	997.7	1086.5	1175.4	1209.7
57.5°	880.5	922.9	1017.9	1114.8	1149.1
60°	803.8	850.2	955.3	1052.2	1090.6
62.5°	729.1	775.5	884.6	985.5	1023.9
65°	648.3	702.8	815.9	918.9	955.3
67.5°	571.5	630.1	749.3	850.2	886.6
70°	496.8	553.4	680.6	779.5	815.9
72.5°	416.0	480.7	607.9	710.9	749.3
75°	335.2	412.0	537.2	638.2	674.5
77.5°	260.5	339.3	464.5	547.3	565.5
80°	191.9	272.6	381.7	440.3	462.5
82.5°	123.2	204.0	290.8	333.2	351.4
85°	68.7	135.3	189.8	214.1	222.2
87.5°	28.3	58.6	76.7	86.8	86.8
90°	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)