

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P581568

Luminaire Tested: **HC6R10D010-HM60525827-62RMDC**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P581568
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-13)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC6R10D010-HM60525827-62RMDC
Description: HALO COMMERCIAL 6" ROUND, RETROFIT FRAME, WITH 6" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1143.6 lumens
Efficiency: N/A
Efficacy: 115.5 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 0.96
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P581568

CATALOG NUMBER: HC6R10D010-HM60525827-62RMDC

Luminous Intensity Polar Plot





TEST NUMBER: P581568

CATALOG NUMBER: HC6R10D010-HM60525827-62RMDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	92	95	93	91	92	90	89	87		
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81		
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75		
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70		
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67	65		
7	83	74	68	64	82	73	67	63	72	67	63	71	66	63	70	65	62	61		
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	62	58	57		
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53		
10	72	62	56	52	71	61	56	52	60	55	52	60	55	52	59	55	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	53044
5°	54210
10°	57464
15°	64229
20°	67247
25°	56072
30°	39240
35°	26421
40°	13611
45°	4729
50°	2107
55°	688
60°	318
65°	285
70°	240
75°	148
80°	221
85°	0



TEST NUMBER: P581568

CATALOG NUMBER: HC6R10D010-HM60525827-62RMDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	95.5	8.3
10°-20°	318.9	27.9
20°-30°	414.4	36.2
30°-40°	244.8	21.4
40°-50°	58.4	5.1
50°-60°	8.6	0.8
60°-70°	2.2	0.2
70°-80°	0.8	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	828.7	72.5
0°-40°	1073.5	93.9
0°-60°	1140.5	99.7
0°-90°	1143.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1143.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	968	
5°	985	95
15°	1132	319
25°	927	414
35°	395	245
45°	61	58
55°	7	9
65°	2	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P581568

CATALOG NUMBER: HC6R10D010-HM60525827-62RMDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	967.6
2.5°	969.8
5°	985.1
7.5°	1004.6
10°	1032.3
12.5°	1075.7
15°	1131.7
17.5°	1169.4
20°	1152.7
22.5°	1068.5
25°	927.0
27.5°	765.1
30°	619.9
32.5°	501.6
35°	394.8
37.5°	290.4
40°	190.2
42.5°	103.8
45°	61.0
47.5°	37.7
50°	24.7
52.5°	14.5
55°	7.2
57.5°	3.6
60°	2.9
62.5°	2.9
65°	2.2
67.5°	1.5
70°	1.5
72.5°	0.7
75°	0.7
77.5°	0.7
80°	0.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)