

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P593253

Luminaire Tested: **HC635D010-HM63040950-61NDH**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P593253
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-2)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC635D010-HM63040950-61NDH
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" NARROW DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3602.6 lumens
Efficiency: N/A
Efficacy: 106.9 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.89
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 33.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P593253

CATALOG NUMBER: HC635D010-HM63040950-61NDH

Luminous Intensity Polar Plot





TEST NUMBER: P593253

CATALOG NUMBER: HC635D010-HM63040950-61NDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	113	111	108	106	111	109	106	104		105	103	101			101	99	98			97
2	108	103	99	96	106	101	98	94		98	95	92			95	93	90			92
3	102	96	91	87	100	95	90	86		92	88	85			90	86	84			87
4	97	90	84	80	95	88	83	79		86	82	78			84	81	78			82
5	92	84	78	74	91	83	77	73		81	76	73			79	75	72			78
6	88	79	73	68	86	78	72	68		76	71	68			75	71	67			74
7	83	74	68	64	82	73	67	63		72	67	63			71	66	63			70
8	79	70	64	59	78	69	63	59		68	63	59			67	62	59			66
9	75	66	60	56	74	65	59	56		64	59	55			63	59	55			62
10	72	62	56	52	71	62	56	52		61	56	52			60	55	52			59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	220536
5°	219601
10°	214403
15°	203526
20°	181409
25°	152809
30°	121747
35°	86859
40°	46709
45°	20010
50°	9100
55°	3326
60°	1634
65°	1284
70°	1202
75°	530
80°	789
85°	0



TEST NUMBER: P593253

CATALOG NUMBER: HC635D010-HM63040950-61NDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	376.7	10.5
10°-20°	994.0	27.6
20°-30°	1151.3	32.0
30°-40°	796.1	22.1
40°-50°	229.9	6.4
50°-60°	39.6	1.1
60°-70°	10.1	0.3
70°-80°	3.9	0.1
80°-90°	1.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2522.0	70.0
0°-40°	3318.1	92.1
0°-60°	3587.5	99.6
0°-90°	3602.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3602.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4023	
5°	3991	377
15°	3586	994
25°	2526	1151
35°	1298	796
45°	258	230
55°	35	40
65°	10	10
75°	2	4
85°	0	1
90°	0	



TEST NUMBER: P593253

CATALOG NUMBER: HC635D010-HM63040950-61NDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	4022.9
2.5°	4005.5
5°	3990.6
7.5°	3945.9
10°	3851.6
12.5°	3737.4
15°	3586.1
17.5°	3372.6
20°	3109.6
22.5°	2819.2
25°	2526.3
27.5°	2226.1
30°	1923.3
32.5°	1620.5
35°	1297.9
37.5°	962.9
40°	652.7
42.5°	412.0
45°	258.1
47.5°	166.3
50°	106.7
52.5°	64.5
55°	34.8
57.5°	19.8
60°	14.9
62.5°	12.4
65°	9.9
67.5°	7.5
70°	7.5
72.5°	5.0
75°	2.5
77.5°	2.5
80°	2.5
82.5°	2.5
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)