

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P582882

Luminaire Tested: **HC6R05D010-HM60525830-62RMDC**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P582882
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-13)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC6R05D010-HM60525830-62RMDC
Description: HALO COMMERCIAL 6" ROUND, RETROFIT FRAME, WITH 6" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 752.4 lumens
Efficiency: N/A
Efficacy: 125.4 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 0.96
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P582882

CATALOG NUMBER: HC6R05D010-HM60525830-62RMDC

Luminous Intensity Polar Plot





TEST NUMBER: P582882

CATALOG NUMBER: HC6R05D010-HM60525830-62RMDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	95	98	95	92		95	93	91		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	89	83	79	86	82	79		84	81	78		83
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62
10	72	62	56	52	71	61	56	52	60	55	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	34893
5°	35665
10°	37803
15°	42259
20°	44238
25°	36891
30°	25814
35°	17387
40°	8952
45°	3109
50°	1390
55°	449
60°	208
65°	195
70°	144
75°	106
80°	158
85°	0



TEST NUMBER: P582882

CATALOG NUMBER: HC6R05D010-HM60525830-62RMDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.8	8.3
10°-20°	209.8	27.9
20°-30°	272.6	36.2
30°-40°	161.0	21.4
40°-50°	38.4	5.1
50°-60°	5.7	0.8
60°-70°	1.4	0.2
70°-80°	0.6	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	545.2	72.5
0°-40°	706.2	93.9
0°-60°	750.3	99.7
0°-90°	752.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	752.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	636	
5°	648	63
15°	745	210
25°	610	273
35°	260	161
45°	40	38
55°	5	6
65°	2	1
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P582882

CATALOG NUMBER: HC6R05D010-HM60525830-62RMDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	636.5
2.5°	638.0
5°	648.1
7.5°	660.9
10°	679.1
12.5°	707.7
15°	744.6
17.5°	769.3
20°	758.3
22.5°	703.0
25°	609.9
27.5°	503.3
30°	407.8
32.5°	330.0
35°	259.8
37.5°	191.0
40°	125.1
42.5°	68.3
45°	40.1
47.5°	24.9
50°	16.3
52.5°	9.6
55°	4.7
57.5°	2.4
60°	1.9
62.5°	1.9
65°	1.5
67.5°	0.9
70°	0.9
72.5°	0.5
75°	0.5
77.5°	0.5
80°	0.5
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)