

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P583008

Luminaire Tested: **HC6R55D010-HM64560827-62RMDC**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P583008
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-13)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC6R55D010-HM64560827-62RMDC
Description: HALO COMMERCIAL 6" ROUND, RETROFIT FRAME, WITH 6" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 2700K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5330.2 lumens
Efficiency: N/A
Efficacy: 102.5 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 0.96
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 52
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P583008

CATALOG NUMBER: HC6R55D010-HM64560827-62RMDC

Luminous Intensity Polar Plot





TEST NUMBER: P583008

CATALOG NUMBER: HC6R55D010-HM64560827-62RMDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	92	95	93	91	92	90	89	87		
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81		
4	97	90	84	80	95	89	83	79	86	82	79	84	81	78	83	79	77	75		
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70		
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67	65		
7	83	74	68	64	82	73	67	63	72	67	63	71	66	63	70	65	62	61		
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	62	58	57		
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53		
10	72	62	56	52	71	61	56	52	60	55	52	60	55	52	59	55	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	247239
5°	252652
10°	267814
15°	299355
20°	313435
25°	261342
30°	182902
35°	123172
40°	63433
45°	22033
50°	9808
55°	3230
60°	1480
65°	1323
70°	1074
75°	720
80°	1073
85°	0



TEST NUMBER: P583008

CATALOG NUMBER: HC6R55D010-HM64560827-62RMDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	445.0	8.3
10°-20°	1486.2	27.9
20°-30°	1931.5	36.2
30°-40°	1140.9	21.4
40°-50°	272.2	5.1
50°-60°	40.1	0.8
60°-70°	10.0	0.2
70°-80°	4.0	0.1
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3862.6	72.5
0°-40°	5003.5	93.9
0°-60°	5315.8	99.7
0°-90°	5330.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5330.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4510	
5°	4591	445
15°	5275	1486
25°	4321	1931
35°	1840	1141
45°	284	272
55°	34	40
65°	10	10
75°	3	4
85°	0	0
90°	0	



TEST NUMBER: P583008

CATALOG NUMBER: HC6R55D010-HM64560827-62RMDC

CANDELA DISTRIBUTION (FULL):

0°	
0°	4510.0
2.5°	4520.1
5°	4591.2
7.5°	4682.6
10°	4811.1
12.5°	5014.1
15°	5274.6
17.5°	5450.6
20°	5372.7
22.5°	4980.3
25°	4320.6
27.5°	3566.0
30°	2889.4
32.5°	2337.8
35°	1840.5
37.5°	1353.4
40°	886.4
42.5°	483.8
45°	284.2
47.5°	175.9
50°	115.0
52.5°	67.7
55°	33.8
57.5°	16.9
60°	13.5
62.5°	13.5
65°	10.2
67.5°	6.7
70°	6.7
72.5°	3.4
75°	3.4
77.5°	3.4
80°	3.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)