

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P583108

Luminaire Tested: **HC655D010-HM64560935-61WDBB**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P583108
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-11)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC655D010-HM64560935-61WDBB
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" WIDE DISTRIBUTION, BLACK BAFFLE TRIM
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4487.0 lumens
Efficiency: N/A
Efficacy: 86.3 lumens/watt
Spacing Criteria (0/90/45): 1.32 / 1.32 / 1.14
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 52
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P583108

CATALOG NUMBER: HC655D010-HM64560935-61WDBB

Luminous Intensity Polar Plot





TEST NUMBER: P583108

CATALOG NUMBER: HC655D010-HM64560935-61WDBB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	97	95	94	92				92
2	107	101	97	93	104	100	95	92	96	93	90	93	91	88	90	88	86	85				85
3	100	93	88	83	98	92	87	83	89	85	81	87	83	80	84	81	79	77				77
4	95	86	80	75	93	85	79	75	83	78	74	81	77	73	79	75	72	71				71
5	89	80	73	68	87	79	73	68	77	72	67	75	70	67	73	69	66	65				65
6	84	74	67	62	82	73	67	62	71	66	62	70	65	61	69	64	61	59				59
7	79	68	62	57	77	68	61	57	66	61	57	65	60	56	64	59	56	54				54
8	74	64	57	52	73	63	57	52	62	56	52	61	56	52	60	55	52	50				50
9	70	59	53	48	69	59	53	48	58	52	48	57	52	48	56	51	48	46				46
10	66	56	49	45	65	55	49	45	54	48	45	53	48	44	53	48	44	43				43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	159357
5°	160532
10°	163329
15°	169802
20°	176923
25°	183234
30°	180781
35°	150630
40°	96595
45°	48230
50°	19138
55°	6499
60°	1864
65°	1323
70°	1074
75°	1419
80°	1073
85°	0



TEST NUMBER: P583108

CATALOG NUMBER: HC655D010-HM64560935-61WDBB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	278.9	6.2
10°-20°	848.6	18.9
20°-30°	1385.6	30.9
30°-40°	1358.3	30.3
40°-50°	520.8	11.6
50°-60°	76.4	1.7
60°-70°	11.3	0.3
70°-80°	5.8	0.1
80°-90°	1.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2513.1	56.0
0°-40°	3871.4	86.3
0°-60°	4468.6	99.6
0°-90°	4487.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4487.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2907	
5°	2917	279
15°	2992	849
25°	3029	1386
35°	2251	1358
45°	622	521
55°	68	76
65°	10	11
75°	7	6
85°	0	1
90°	0	



TEST NUMBER: P583108

CATALOG NUMBER: HC655D010-HM64560935-61WDBB

CANDELA DISTRIBUTION (FULL):

	0°
0°	2906.9
2.5°	2900.1
5°	2917.2
7.5°	2927.3
10°	2934.1
12.5°	2957.9
15°	2991.9
17.5°	3019.1
20°	3032.7
22.5°	3036.1
25°	3029.3
27.5°	2981.8
30°	2855.9
32.5°	2617.9
35°	2250.8
37.5°	1798.5
40°	1349.8
42.5°	962.1
45°	622.1
47.5°	380.8
50°	224.4
52.5°	129.2
55°	68.0
57.5°	30.6
60°	17.0
62.5°	13.6
65°	10.2
67.5°	10.2
70°	6.7
72.5°	6.7
75°	6.7
77.5°	3.4
80°	3.4
82.5°	3.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)