

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P593415

Luminaire Tested: **HC660D010-HM64560850-61NDH**

Issue Date: 9/16/2021

Test Information

Test Method: LM-41-14
Report Number: P593415
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2105-241-2)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 9/16/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HC660D010-HM64560850-61NDH
Description: HALO COMMERCIAL 6" ROUND, NEW CONSTRUCTION FRAME, WITH 6" NARROW DISTRIBUTION, HAZE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 5000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6016.5 lumens
Efficiency: N/A
Efficacy: 109.4 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.89
Luminous Opening: Circular (Dia: 0.5' x H: 0')
CIE Type: Direct


Input Watts (W): 55
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P593415

CATALOG NUMBER: HC660D010-HM64560850-61NDH

Luminous Intensity Polar Plot





TEST NUMBER: P593415

CATALOG NUMBER: HC660D010-HM64560850-61NDH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	109	106	104	105	103	101		101	99	98		97
2	108	103	99	96	106	101	98	94	98	95	92		95	93	90		92
3	102	96	91	87	100	95	90	86	92	88	85		90	86	84		87
4	97	90	84	80	95	88	83	79	86	82	78		84	81	78		82
5	92	84	78	74	91	83	77	73	81	76	73		79	75	72		78
6	88	79	73	68	86	78	72	68	76	71	68		75	71	67		74
7	83	74	68	64	82	73	67	63	72	67	63		71	66	63		70
8	79	70	64	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	56	64	59	55		63	59	55		62
10	72	62	56	52	71	62	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	368304
5°	366745
10°	358065
15°	339894
20°	302963
25°	255208
30°	203329
35°	145069
40°	78003
45°	33422
50°	15198
55°	5543
60°	2719
65°	2140
70°	1988
75°	868
80°	1294
85°	0



TEST NUMBER: P593415

CATALOG NUMBER: HC660D010-HM64560850-61NDH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	629.1	10.5
10°-20°	1660.1	27.6
20°-30°	1922.7	32.0
30°-40°	1329.5	22.1
40°-50°	383.9	6.4
50°-60°	66.1	1.1
60°-70°	16.8	0.3
70°-80°	6.5	0.1
80°-90°	1.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4211.9	70.0
0°-40°	5541.5	92.1
0°-60°	5991.5	99.6
0°-90°	6016.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6016.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6718	
5°	6664	629
15°	5989	1660
25°	4219	1923
35°	2168	1330
45°	431	384
55°	58	66
65°	16	17
75°	4	7
85°	0	2
90°	0	



TEST NUMBER: P593415

CATALOG NUMBER: HC660D010-HM64560850-61NDH

CANDELA DISTRIBUTION (FULL):

	0°
0°	6718.4
2.5°	6689.4
5°	6664.5
7.5°	6589.9
10°	6432.4
12.5°	6241.8
15°	5988.9
17.5°	5632.5
20°	5193.2
22.5°	4708.3
25°	4219.2
27.5°	3717.7
30°	3212.1
32.5°	2706.4
35°	2167.7
37.5°	1608.2
40°	1090.0
42.5°	688.0
45°	431.1
47.5°	277.7
50°	178.2
52.5°	107.8
55°	58.0
57.5°	33.2
60°	24.8
62.5°	20.7
65°	16.5
67.5°	12.4
70°	12.4
72.5°	8.3
75°	4.1
77.5°	4.1
80°	4.1
82.5°	4.1
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-HRDQ47P





— 0°-180°







(END OF REPORT)