

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584397

Luminaire Tested: **HCC8W35D010SL-HM82555830-81WDBB**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584397
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-11)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8W35D010SL-HM82555830-81WDBB
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, BLACK BAFFLE TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3905.9 lumens
Efficiency: N/A
Efficacy: 115.9 lumens/watt
Spacing Criteria (0/90/45): 1.32 / 1.32 / 1.13
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 33.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584397

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDBB

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P584397

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDBB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	109	107	104		110	107	105	102		103	101	99		99	98	96		96	95	93
2	106	100	95	92		104	98	94	91		95	92	89		92	89	87		89	87	85
3	99	92	86	81		97	90	85	81		88	83	79		85	81	78		83	80	77
4	93	84	78	73		91	83	77	72		81	76	71		79	74	71		77	73	70
5	87	77	71	66		85	76	70	65		74	69	65		73	68	64		71	67	63
6	82	71	64	59		80	70	64	59		69	63	59		67	62	58		66	61	58
7	77	66	59	54		75	65	59	54		64	58	54		63	57	53		61	57	53
8	72	61	54	49		71	61	54	49		59	53	49		58	53	49		57	52	49
9	68	57	50	45		67	56	50	45		55	49	45		54	49	45		53	48	45
10	64	53	46	42		63	53	46	42		52	46	42		51	45	42		50	45	41

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	73181
5°	72575
10°	71617
15°	72433
20°	78222
25°	85540
30°	84502
35°	70097
40°	41256
45°	26950
50°	20892
55°	13881
60°	6753
65°	2087
70°	703
75°	631
80°	462
85°	920



TEST NUMBER: P584397

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDBB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	222.0	5.7
10°-20°	651.8	16.7
20°-30°	1139.7	29.2
30°-40°	1108.6	28.4
40°-50°	504.1	12.9
50°-60°	233.7	6.0
60°-70°	39.2	1.0
70°-80°	4.8	0.1
80°-90°	1.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2013.6	51.6
0°-40°	3122.2	79.9
0°-60°	3860.1	98.8
0°-90°	3905.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3905.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2373	
5°	2345	222
15°	2269	652
25°	2514	1140
35°	1862	1109
45°	618	504
55°	258	234
65°	29	39
75°	5	5
85°	3	2
90°	0	



TEST NUMBER: P584397

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDBB

CANDELA DISTRIBUTION (FULL):

0°	
0°	2373.2
2.5°	2368.0
5°	2344.6
7.5°	2318.5
10°	2287.2
12.5°	2263.7
15°	2268.9
17.5°	2310.7
20°	2383.7
22.5°	2467.2
25°	2514.1
27.5°	2488.0
30°	2373.2
32.5°	2172.5
35°	1862.1
37.5°	1434.4
40°	1024.9
42.5°	764.1
45°	618.0
47.5°	521.6
50°	435.5
52.5°	346.8
55°	258.2
57.5°	177.3
60°	109.5
62.5°	60.0
65°	28.6
67.5°	13.1
70°	7.8
72.5°	5.3
75°	5.3
77.5°	2.6
80°	2.6
82.5°	2.6
85°	2.6
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)