

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584391

Luminaire Tested: **HCC8W35D010MB-HM82555830-81NDC**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584391
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-1)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8W35D010MB-HM82555830-81NDC
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" NARROW DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3872.0 lumens
Efficiency: N/A
Efficacy: 114.9 lumens/watt
Spacing Criteria (0/90/45): 0.22 / 0.22 / 0.27
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 33.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584391

CATALOG NUMBER: HCC8W35D010MB-HM82555830-81NDC

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P584391

CATALOG NUMBER: HCC8W35D010MB-HM82555830-81NDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	115	112	110	108	112	110	108	107		106	105	103			102	101	100			99
2	110	106	103	100	108	104	101	99		101	99	97			98	96	95			96
3	106	101	97	93	104	99	96	93		97	94	91			95	92	90			92
4	102	96	91	88	100	95	91	88		93	89	87			91	88	86			89
5	98	92	87	83	97	91	86	83		89	85	82			87	84	82			86
6	95	88	83	79	93	87	82	79		86	82	79			84	81	78			83
7	91	84	79	76	90	83	79	76		82	78	75			81	78	75			80
8	88	81	76	73	87	80	76	73		79	75	72			78	75	72			77
9	85	78	73	70	84	77	73	70		76	72	70			76	72	69			75
10	83	75	70	67	82	75	70	67		74	70	67			73	69	67			73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	728782
5°	467456
10°	211168
15°	127412
20°	97094
25°	78409
30°	57459
35°	20802
40°	7765
45°	3528
50°	1127
55°	285
60°	160
65°	190
70°	0
75°	0
80°	462
85°	920



TEST NUMBER: P584391

CATALOG NUMBER: HCC8W35D010MB-HM82555830-81NDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1151.8	29.7
10°-20°	1169.9	30.2
20°-30°	1047.2	27.0
30°-40°	421.8	10.9
40°-50°	69.2	1.8
50°-60°	6.3	0.2
60°-70°	2.2	0.1
70°-80°	1.7	0.0
80°-90°	2.5	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3368.9	87.0
0°-40°	3790.7	97.9
0°-60°	3866.2	99.9
0°-90°	3872.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3872.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	23634	
5°	15102	###
15°	3991	1170
25°	2304	1047
35°	553	422
45°	81	69
55°	5	6
65°	3	2
75°	0	2
85°	3	2
90°	0	



TEST NUMBER: P584391

CATALOG NUMBER: HCC8W35D010MB-HM82555830-81NDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	23633.9
0.5°	23560.9
1°	23255.9
1.5°	22765.8
2°	22022.8
2.5°	21144.3
3°	20044.2
3.5°	18837.2
4°	17643.3
4.5°	16306.0
5°	15101.6
5.5°	13790.4
6°	12726.7
6.5°	11618.8
7°	10748.1
7.5°	9827.9
8°	9087.5
8.5°	8344.5
9°	7786.8
9.5°	7171.5
10°	6744.0
12.5°	4973.9
15°	3991.1
17.5°	3409.7
20°	2958.8
22.5°	2599.1
25°	2304.5
27.5°	2009.9
30°	1613.7
32.5°	1037.6
35°	552.6
37.5°	305.0
40°	192.9
42.5°	127.7
45°	80.9
47.5°	49.5
50°	23.5
52.5°	7.8
55°	5.3
57.5°	2.6
60°	2.6
62.5°	2.6
65°	2.6

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P584391

CATALOG NUMBER: HCC8W35D010MB-HM82555830-81NDC

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	2.6
80°	2.6
82.5°	2.6
85°	2.6
87.5°	2.6
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



67.5°	2.6
70°	0.0

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)