

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584398

Luminaire Tested: **HCC8W35D010SL-HM82555830-81WDC**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584398
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-7)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8W35D010SL-HM82555830-81WDC
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3000K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4380.4 lumens
Efficiency: N/A
Efficacy: 130.0 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.05
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 33.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584398

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDC

Luminous Intensity Polar Plot





TEST NUMBER: P584398

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						
1	113	110	107	105	110	108	105	103	104	102	100	100	98	97	96	95	94	92						
2	106	101	96	93	104	99	95	92	96	92	90	93	90	88	90	88	86	84						
3	100	93	87	83	98	91	86	82	89	84	81	86	83	79	84	81	78	77						
4	94	86	79	75	92	84	79	74	82	77	73	80	76	72	78	75	71	70						
5	88	79	72	68	87	78	72	67	76	71	67	74	70	66	73	69	65	64						
6	83	73	66	62	82	72	66	61	71	65	61	69	64	61	68	64	60	59						
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	63	59	55	54						
8	74	63	57	52	73	63	56	52	62	56	52	60	55	51	59	55	51	50						
9	70	59	53	48	69	59	52	48	58	52	48	57	51	48	56	51	47	46						
10	66	55	49	45	65	55	49	45	54	48	44	53	48	44	52	48	44	43						

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	105096
5°	102266
10°	101492
15°	99980
20°	96950
25°	93335
30°	87187
35°	72149
40°	43563
45°	29340
50°	21142
55°	12059
60°	5304
65°	1904
70°	703
75°	310
80°	0
85°	0



TEST NUMBER: P584398

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	313.9	7.2
10°-20°	880.1	20.1
20°-30°	1255.5	28.7
30°-40°	1143.3	26.1
40°-50°	539.3	12.3
50°-60°	212.1	4.8
60°-70°	33.8	0.8
70°-80°	2.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2449.5	55.9
0°-40°	3592.8	82.0
0°-60°	4344.3	99.2
0°-90°	4380.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4380.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3408	
5°	3304	314
15°	3132	880
25°	2743	1256
35°	1917	1143
45°	673	539
55°	224	212
65°	26	34
75°	3	2
85°	0	0
90°	0	



TEST NUMBER: P584398

CATALOG NUMBER: HCC8W35D010SL-HM82555830-81WDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	3408.2
2.5°	3363.9
5°	3303.8
7.5°	3269.9
10°	3241.3
12.5°	3194.3
15°	3131.8
17.5°	3053.6
20°	2954.4
22.5°	2850.2
25°	2743.2
27.5°	2612.8
30°	2448.6
32.5°	2227.0
35°	1916.6
37.5°	1481.1
40°	1082.2
42.5°	831.9
45°	672.8
47.5°	552.8
50°	440.7
52.5°	331.1
55°	224.3
57.5°	140.8
60°	86.0
62.5°	52.1
65°	26.1
67.5°	13.1
70°	7.8
72.5°	2.6
75°	2.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)