

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584677

Luminaire Tested: **HCC8S45D010BZ-HM82555835-81MDC**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584677
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8S45D010BZ-HM82555835-81MDC
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" MEDIUM DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5508.8 lumens
Efficiency: N/A
Efficacy: 125.2 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.67
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 44
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584677

CATALOG NUMBER: HCC8S45D010BZ-HM82555835-81MDC

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P584677

CATALOG NUMBER: HCC8S45D010BZ-HM82555835-81MDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	114	111	109	107	112	109	107	105		105	104	102			102	100	99			98
2	109	105	101	98	107	103	100	97		100	97	95			97	95	93			94
3	104	98	94	90	102	97	93	90		94	91	88			92	89	87			90
4	100	93	88	84	98	92	87	83		90	86	82			88	84	82			86
5	95	88	82	78	94	87	82	78		85	81	77			83	80	77			82
6	91	83	78	74	90	82	77	74		81	76	73			79	76	73			78
7	87	79	73	70	86	78	73	69		77	72	69			76	72	69			75
8	84	75	70	66	82	74	69	66		73	69	65			72	68	65			71
9	80	71	66	62	79	71	66	62		70	65	62			69	65	62			68
10	77	68	63	59	76	68	63	59		67	62	59			66	62	59			65

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	329141
5°	314042
10°	271134
15°	207325
20°	158633
25°	125501
30°	94803
35°	50436
40°	19213
45°	9219
50°	3929
55°	1650
60°	629
65°	496
70°	307
75°	0
80°	0
85°	0



TEST NUMBER: P584677

CATALOG NUMBER: HCC8S45D010BZ-HM82555835-81MDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	921.0	16.7
10°-20°	1813.0	32.9
20°-30°	1688.5	30.7
30°-40°	871.3	15.8
40°-50°	177.5	3.2
50°-60°	30.4	0.6
60°-70°	5.9	0.1
70°-80°	1.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4422.5	80.3
0°-40°	5293.8	96.1
0°-60°	5501.6	99.9
0°-90°	5508.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5508.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10674	
5°	10145	921
15°	6494	1813
25°	3689	1689
35°	1340	871
45°	211	177
55°	31	30
65°	7	6
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P584677

CATALOG NUMBER: HCC8S45D010BZ-HM82555835-81MDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	10673.8
2.5°	10530.6
5°	10145.4
7.5°	9511.4
10°	8659.1
12.5°	7540.9
15°	6494.3
17.5°	5587.5
20°	4834.1
22.5°	4220.5
25°	3688.6
27.5°	3184.1
30°	2662.5
32.5°	2042.1
35°	1339.8
37.5°	777.2
40°	477.3
42.5°	313.7
45°	211.4
47.5°	132.9
50°	81.9
52.5°	47.7
55°	30.7
57.5°	13.6
60°	10.2
62.5°	6.8
65°	6.8
67.5°	3.4
70°	3.4
72.5°	3.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)