

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P584687

Luminaire Tested: **HCC8W45D010MB-HM82555835-81WDC**

Issue Date: 10/21/2021

Test Information

Test Method: LM-41-14
Report Number: P584687
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2109-368-7)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 10/21/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO COMMERCIAL
Catalog Number: HCC8W45D010MB-HM82555835-81WDC
Description: HALO COMMERCIAL 8" ROUND, NEW CONSTRUCTION FRAME, WITH 8" WIDE DISTRIBUTION, SPECULAR TRIM
Light Source: (1) HIGH LUMEN LED 80CRI / 3500K CCT
CYLINDER
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5726.9 lumens
Efficiency: N/A
Efficacy: 130.2 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.05
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 44
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P584687

CATALOG NUMBER: HCC8W45D010MB-HM82555835-81WDC

Luminous Intensity Polar Plot





TEST NUMBER: P584687

CATALOG NUMBER: HCC8W45D010MB-HM82555835-81WDC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96
2	106	101	96	93	104	99	95	92	96	92	90		93	90	88		90
3	100	93	87	83	98	91	86	82	89	84	81		86	83	79		84
4	94	86	79	75	92	84	79	74	82	77	73		80	76	72		78
5	88	79	72	68	87	78	72	67	76	71	67		74	70	66		73
6	83	73	66	62	82	72	66	61	71	65	61		69	64	61		68
7	78	68	61	57	77	67	61	56	66	60	56		65	60	56		63
8	74	63	57	52	73	63	56	52	62	56	52		60	55	51		59
9	70	59	53	48	69	59	52	48	58	52	48		57	51	48		56
10	66	55	49	45	65	55	49	45	54	48	44		53	48	44		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	137404
5°	133706
10°	132688
15°	130713
20°	126752
25°	122024
30°	113984
35°	94329
40°	56955
45°	38354
50°	27642
55°	15757
60°	6938
65°	2488
70°	920
75°	405
80°	0
85°	0



TEST NUMBER: P584687

CATALOG NUMBER: HCC8W45D010MB-HM82555835-81WDC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	410.4	7.2
10°-20°	1150.7	20.1
20°-30°	1641.5	28.7
30°-40°	1494.7	26.1
40°-50°	705.1	12.3
50°-60°	277.3	4.8
60°-70°	44.2	0.8
70°-80°	3.1	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3202.5	55.9
0°-40°	4697.2	82.0
0°-60°	5679.6	99.2
0°-90°	5726.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5726.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4456	
5°	4320	410
15°	4094	1151
25°	3586	1641
35°	2506	1495
45°	880	705
55°	293	277
65°	34	44
75°	3	3
85°	0	0
90°	0	



TEST NUMBER: P584687

CATALOG NUMBER: HCC8W45D010MB-HM82555835-81WDC

CANDELA DISTRIBUTION (FULL):

	0°
0°	4455.9
2.5°	4397.8
5°	4319.5
7.5°	4275.1
10°	4237.6
12.5°	4176.2
15°	4094.5
17.5°	3992.2
20°	3862.6
22.5°	3726.3
25°	3586.4
27.5°	3416.0
30°	3201.2
32.5°	2911.5
35°	2505.8
37.5°	1936.4
40°	1414.9
42.5°	1087.5
45°	879.5
47.5°	722.8
50°	576.2
52.5°	433.0
55°	293.1
57.5°	184.0
60°	112.5
62.5°	68.2
65°	34.1
67.5°	17.0
70°	10.2
72.5°	3.4
75°	3.4
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)