

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO

Report Number: P990559

Luminaire Tested: **ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K**

Issue Date: 5/13/2025

Tested By:

Approved By:



Cooper Lighting Solutions laboratories have been accredited by National Voluntary Laboratory Accreditation Program (NVLAP) that it adheres to the requirements of ISO/IEC 17025:2005 and appropriate IESNA test methods. This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST or any agency of the Federal Government. Results contained in this report are valid for luminaire sample tested, as supplied by requestor. Information related to the luminaire tested has been supplied by requestor and can affect the validity of the test results. Report shall not be reproduced except in full without approval of Cooper Lighting Solutions Lighting Laboratory. Test performed at address noted above.

**Test Information**

Test Method: LM-79-08  
 Report Number: P990559  
 Test Lab: Cooper Lighting Solutions  
 Issue Date: 5/13/2025  
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
 Product Line: HALO  
 Catalog Number: ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K  
 Description: 2IN ROUND ML FLEX ADJUSTABLE, SELECTABLE CCT, WITH 25D TIR, MATTE BLACK TRIM  
 Light Source: (1) STANDARD SELECTABLE LUMEN LED 90CRI / 3500K CCT  
 Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
 Luminaire Lumens: 342.6 lumens  
 Efficiency: N/A  
 Efficacy: 56.2 lumens/watt  
 Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.6  
 Luminous Opening: Circular (Dia: 0.17' x H: 0')  
 CIE Type: Direct

Input Watts (W): 6.1  
 Input Voltage (V): NR  
 Input Current (Ain): NR  
 Voltage Rise (V): NR  
 Power Factor: NR  
 Total Harmonic Distortion (THDi): NR  
 Frequency (hertz): 60  
 Stabilization Time: NR  
 Operation Time: NR  
 Ambient Temperature (°C): NR  
 Test Distance: 25 FT

| Measurement and Test Equipment |                       |                  |                      |
|--------------------------------|-----------------------|------------------|----------------------|
| Instrument                     | Identification Number | Calibration Date | Calibration Due Date |
| Photometer                     | GONIO 1 IN0055        | 4/22/2021        | 10/22/2021           |
| Power Meter                    | XITRON 2801 IN0197    | 12/1/2020        | 12/1/2021            |
| AC Power Source                | CHROMA 61505 IN0196   | 12/1/2020        | 12/1/2021            |
| DC Power Supply                | AGILENT E3634A IN0198 | 11/30/2020       | 11/30/2021           |
| Room Thermometer               | ONSET IN0143          | 12/1/2020        | 12/1/2021            |

TEST NUMBER: P990559  
CATALOG NUMBER: ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K

### Luminous Intensity Polar Plot



TEST NUMBER: P990559

CATALOG NUMBER: ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 111 | 108 | 106 | 111 | 109 | 106 | 104 | 104 | 103 | 101 |  | 101 | 99  | 98  |  | 97  |
| 2   | 108 | 103 | 99  | 96  | 106 | 101 | 98  | 94  | 98  | 95  | 92  |  | 95  | 93  | 90  |  | 92  |
| 3   | 103 | 96  | 91  | 87  | 101 | 95  | 90  | 86  | 92  | 88  | 85  |  | 90  | 86  | 84  |  | 87  |
| 4   | 97  | 90  | 85  | 80  | 96  | 89  | 84  | 80  | 87  | 82  | 79  |  | 85  | 81  | 78  |  | 83  |
| 5   | 93  | 85  | 79  | 75  | 91  | 84  | 78  | 74  | 82  | 77  | 74  |  | 80  | 76  | 73  |  | 79  |
| 6   | 88  | 80  | 74  | 70  | 87  | 79  | 73  | 69  | 77  | 73  | 69  |  | 76  | 72  | 68  |  | 75  |
| 7   | 84  | 75  | 70  | 65  | 83  | 75  | 69  | 65  | 73  | 68  | 65  |  | 72  | 68  | 65  |  | 71  |
| 8   | 81  | 71  | 66  | 62  | 79  | 71  | 65  | 62  | 70  | 65  | 61  |  | 69  | 64  | 61  |  | 68  |
| 9   | 77  | 68  | 62  | 58  | 76  | 67  | 62  | 58  | 67  | 62  | 58  |  | 66  | 61  | 58  |  | 65  |
| 10  | 74  | 65  | 59  | 55  | 73  | 64  | 59  | 55  | 64  | 59  | 55  |  | 63  | 58  | 55  |  | 62  |

**AVERAGE LUMINANCE (cd/sqm):**

|     |        |
|-----|--------|
|     | 0°     |
| 0°  | 338656 |
| 5°  | 313403 |
| 10° | 255706 |
| 15° | 193127 |
| 20° | 141709 |
| 25° | 100221 |
| 30° | 69276  |
| 35° | 47401  |
| 40° | 32267  |
| 45° | 22467  |
| 50° | 16503  |
| 55° | 12301  |
| 60° | 8782   |
| 65° | 6304   |
| 70° | 3895   |
| 75° | 3431   |
| 80° | 0      |
| 85° | 0      |

TEST NUMBER: P990559

CATALOG NUMBER: ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 56.5   | 16.5      |
| 10°-20°   | 105.0  | 30.7      |
| 20°-30°   | 85.3   | 24.9      |
| 30°-40°   | 50.2   | 14.7      |
| 40°-50°   | 25.7   | 7.5       |
| 50°-60°   | 13.1   | 3.8       |
| 60°-70°   | 5.2    | 1.5       |
| 70°-80°   | 1.5    | 0.4       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 246.8  | 72.0      |
| 0°-40°    | 297.0  | 86.7      |
| 0°-60°    | 335.8  | 98.0      |
| 0°-90°    | 342.6  | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 342.6  | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°  | Flux |
|-----|-----|------|
| 0°  | 686 |      |
| 5°  | 633 | 56   |
| 15° | 378 | 105  |
| 25° | 184 | 85   |
| 35° | 79  | 50   |
| 45° | 32  | 26   |
| 55° | 14  | 13   |
| 65° | 5   | 5    |
| 75° | 2   | 2    |
| 85° | 0   | 0    |
| 90° | 0   |      |

TEST NUMBER: P990559  
CATALOG NUMBER: ML2ALSFL9FS1E-TIR1D25NFL-TL2RDMB-400LM-3500K

**CANDELA DISTRIBUTION (FULL):**

| 0°    |       |
|-------|-------|
| 0°    | 686.4 |
| 2.5°  | 672.1 |
| 5°    | 632.8 |
| 7.5°  | 576.5 |
| 10°   | 510.4 |
| 12.5° | 442.4 |
| 15°   | 378.1 |
| 17.5° | 320.9 |
| 20°   | 269.9 |
| 22.5° | 224.3 |
| 25°   | 184.1 |
| 27.5° | 150.2 |
| 30°   | 121.6 |
| 32.5° | 98.3  |
| 35°   | 78.7  |
| 37.5° | 62.6  |
| 40°   | 50.1  |
| 42.5° | 40.2  |
| 45°   | 32.2  |
| 47.5° | 25.9  |
| 50°   | 21.5  |
| 52.5° | 17.9  |
| 55°   | 14.3  |
| 57.5° | 11.6  |
| 60°   | 8.9   |
| 62.5° | 6.3   |
| 65°   | 5.4   |
| 67.5° | 3.6   |
| 70°   | 2.7   |
| 72.5° | 1.8   |
| 75°   | 1.8   |
| 77.5° | 0.9   |
| 80°   | 0.0   |
| 82.5° | 0.0   |
| 85°   | 0.0   |
| 87.5° | 0.0   |
| 90°   | 0.0   |

(END OF REPORT)