

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: HALO

Report Number: P997218

Luminaire Tested: **SMX6SLSFSD2W-750LM-3500K**

Issue Date: 3/11/2025



Test Information

Test Method: LM-41-14
Report Number: P997218
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (A2410656A001)
Test Lab:
Issue Date: 3/11/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO
Catalog Number: SMX6SLSFSD2W-750LM-3500K
Description: 6IN SQAURE, 90CRI, DIMMING TO 10%, DAMP LOCATION
Light Source: SELECTABLE CCT 90CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 819.5 lumens
Efficiency: N/A
Efficacy: 106.4 lumens/watt
Spacing Criteria (0/90/45): 1.26 / 1.27 / 1.38
Luminous Opening: Rectangular (W 0.5' x L: 0.5' x H: 0')
CIE Type: Direct

Input Watts (W): 7.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	109	104	100	96	106	102	98	94	97	94	91	93	91	88	90	88	86	84		
2	99	90	84	78	96	89	82	77	85	80	75	82	77	73	79	75	72	69		
3	90	79	71	64	87	78	70	64	75	68	63	72	66	62	69	65	61	58		
4	82	70	61	54	80	69	60	54	66	59	53	64	58	53	62	56	52	50		
5	76	63	53	47	73	61	53	47	59	52	46	57	51	45	55	50	45	43		
6	70	56	47	41	68	55	47	41	53	46	40	52	45	40	50	44	39	37		
7	65	51	42	36	63	50	42	36	49	41	36	47	40	35	46	40	35	33		
8	60	46	38	32	59	46	38	32	44	37	32	43	36	31	42	36	31	29		
9	56	43	34	29	55	42	34	29	41	34	29	40	33	28	39	33	28	26		
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	26	24		

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	12185	12185	12185	12185
5°	12184	12179	12184	12179
10°	12145	12189	12145	12189
15°	12133	12151	12133	12151
20°	12096	12105	12096	12105
25°	12029	12057	12029	12057
30°	11947	11987	11947	11987
35°	11884	11900	11884	11900
40°	11781	11814	11781	11814
45°	11679	11691	11679	11691
50°	11528	11548	11528	11548
55°	11335	11357	11335	11357
60°	11065	11083	11065	11083
65°	10667	10697	10667	10697
70°	10083	10083	10083	10083
75°	9133	9149	9133	9149
80°	7686	7711	7686	7711
85°	5286	5483	5286	5483



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	26.8	3.3
10°-20°	76.8	9.4
20°-30°	116.8	14.2
30°-40°	141.5	17.3
40°-50°	147.8	18.0
50°-60°	134.8	16.4
60°-70°	103.4	12.6
70°-80°	58.1	7.1
80°-90°	13.5	1.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	220.4	26.9
0°-40°	361.9	44.2
0°-60°	644.5	78.6
0°-90°	819.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	819.5	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	283	283	283	283	283	
5°	282	282	282	282	282	27
15°	272	273	272	273	272	77
25°	253	254	253	254	253	117
35°	226	226	226	226	226	141
45°	192	192	192	192	192	148
55°	151	151	151	151	151	135
65°	105	105	105	105	105	103
75°	55	55	55	55	55	58
85°	11	11	11	11	11	13
90°	0	0	0	0	0	

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
0°	283.0	283.0	283.0	283.0	283.0	283.0	283.0	283.0	283.0	283.0	283.0
0.5°	283.0	282.9	282.8	283.3	283.5	283.3	282.8	282.9	283.0	282.9	282.8
1°	282.9	282.9	283.0	283.3	283.6	283.3	283.0	282.9	282.9	282.9	283.0
1.5°	283.2	282.7	283.0	283.2	283.5	283.2	283.0	282.7	283.2	282.7	283.0
2°	283.2	282.6	282.9	283.3	283.6	283.3	282.9	282.6	283.2	282.6	282.9
2.5°	282.8	282.6	282.7	283.1	282.9	283.1	282.7	282.6	282.8	282.6	282.7
3°	282.7	282.3	282.6	283.0	282.8	283.0	282.6	282.3	282.7	282.3	282.6
3.5°	282.7	282.2	282.6	282.8	282.6	282.8	282.6	282.2	282.7	282.2	282.6
4°	282.3	282.2	282.4	282.5	282.7	282.5	282.4	282.2	282.3	282.2	282.4
4.5°	282.3	281.8	282.2	282.1	282.4	282.1	282.2	281.8	282.3	281.8	282.2
5°	281.9	281.4	282.0	281.9	281.8	281.9	282.0	281.4	281.9	281.4	282.0
5.5°	282.0	281.4	281.6	281.6	282.0	281.6	281.6	281.4	282.0	281.4	281.6
6°	281.2	281.0	281.3	281.6	282.0	281.6	281.3	281.0	281.2	281.0	281.3
6.5°	281.1	280.7	280.9	281.0	281.3	281.0	280.9	280.7	281.1	280.7	280.9
7°	280.8	280.5	280.6	280.9	281.3	280.9	280.6	280.5	280.8	280.5	280.6
7.5°	280.4	280.1	280.4	280.3	280.6	280.3	280.4	280.1	280.4	280.1	280.4
8°	280.1	279.4	280.2	280.1	280.6	280.1	280.2	279.4	280.1	279.4	280.2
8.5°	279.5	279.3	279.5	279.6	280.0	279.6	279.5	279.3	279.5	279.3	279.5
9°	278.5	278.9	279.0	279.4	279.6	279.4	279.0	278.9	278.5	278.9	279.0
9.5°	278.3	278.6	278.5	279.1	279.0	279.1	278.5	278.6	278.3	278.6	278.5
10°	277.8	278.2	278.1	278.6	278.8	278.6	278.1	278.2	277.8	278.2	278.1
10.5°	277.3	277.4	277.8	278.0	278.2	278.0	277.8	277.4	277.3	277.4	277.8
11°	277.0	276.9	277.2	277.7	277.2	277.7	277.2	276.9	277.0	276.9	277.2
11.5°	276.5	276.4	276.9	276.7	277.0	276.7	276.9	276.4	276.5	276.4	276.9
12°	276.0	275.6	276.0	276.5	276.7	276.5	276.0	275.6	276.0	275.6	276.0
12.5°	275.4	275.3	275.6	275.8	275.9	275.8	275.6	275.3	275.4	275.3	275.6
13°	275.0	274.6	274.9	275.0	275.2	275.0	274.9	274.6	275.0	274.6	274.9
13.5°	274.3	273.9	274.5	274.2	274.4	274.2	274.5	273.9	274.3	273.9	274.5
14°	273.4	273.4	273.7	273.7	274.2	273.7	273.7	273.4	273.4	273.4	273.7
14.5°	273.0	272.7	273.1	273.1	273.4	273.1	273.1	272.7	273.0	272.7	273.1
15°	272.2	272.1	272.5	272.4	272.6	272.4	272.5	272.1	272.2	272.1	272.5
15.5°	271.5	271.3	271.4	271.6	272.0	271.6	271.4	271.3	271.5	271.3	271.4
16°	270.5	270.6	270.8	271.0	270.8	271.0	270.8	270.6	270.5	270.6	270.8
16.5°	270.0	269.7	270.0	270.2	270.3	270.2	270.0	269.7	270.0	269.7	270.0
17°	269.2	269.0	269.3	269.6	269.2	269.6	269.3	269.0	269.2	269.0	269.3
17.5°	268.3	268.0	268.3	268.4	268.6	268.4	268.3	268.0	268.3	268.0	268.3
18°	267.2	267.1	267.5	267.7	267.7	267.7	267.5	267.1	267.2	267.1	267.5
18.5°	266.6	266.6	266.5	266.7	267.2	266.7	266.5	266.6	266.6	266.6	266.5
19°	265.7	265.6	265.9	265.9	266.4	265.9	265.9	265.6	265.7	265.6	265.9
19.5°	264.7	264.3	265.0	264.8	264.9	264.8	265.0	264.3	264.7	264.3	265.0
20°	264.0	263.8	263.9	264.1	264.2	264.1	263.9	263.8	264.0	263.8	263.9
20.5°	263.0	262.5	262.8	263.0	263.3	263.0	262.8	262.5	263.0	262.5	262.8
21°	261.7	261.8	261.7	262.1	262.4	262.1	261.7	261.8	261.7	261.8	261.7

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
22.5°	259.1	258.3	258.4	259.3	259.1	259.3	258.4	258.3	259.1	258.3	258.4
23°	257.9	257.5	257.6	258.3	258.1	258.3	257.6	257.5	257.9	257.5	257.6
23.5°	256.8	256.3	256.6	257.1	257.0	257.1	256.6	256.3	256.8	256.3	256.6
24°	255.9	255.3	255.6	255.8	256.1	255.8	255.6	255.3	255.9	255.3	255.6
24.5°	254.6	254.2	254.3	254.5	254.8	254.5	254.3	254.2	254.6	254.2	254.3
25°	253.2	253.2	253.4	253.5	253.8	253.5	253.4	253.2	253.2	253.2	253.4
25.5°	252.2	252.0	252.3	252.5	252.4	252.5	252.3	252.0	252.2	252.0	252.3
26°	250.9	250.8	251.0	251.1	251.4	251.1	251.0	250.8	250.9	250.8	251.0
26.5°	249.9	249.5	249.9	249.9	250.0	249.9	249.9	249.5	249.9	249.5	249.9
27°	248.6	248.3	248.4	248.8	249.0	248.8	248.4	248.3	248.6	248.3	248.4
27.5°	247.5	247.0	247.2	247.5	247.7	247.5	247.2	247.0	247.5	247.0	247.2
28°	246.1	245.9	246.1	246.3	246.6	246.3	246.1	245.9	246.1	245.9	246.1
28.5°	244.9	244.4	244.9	245.0	245.4	245.0	244.9	244.4	244.9	244.4	244.9
29°	243.3	243.1	243.4	243.5	243.8	243.5	243.4	243.1	243.3	243.1	243.4
29.5°	242.0	241.8	242.2	242.2	242.5	242.2	242.2	241.8	242.0	241.8	242.2
30°	240.3	240.6	240.7	240.8	241.1	240.8	240.7	240.6	240.3	240.6	240.7
30.5°	239.3	239.0	239.4	239.5	240.1	239.5	239.4	239.0	239.3	239.0	239.4
31°	237.9	237.6	237.9	238.1	238.6	238.1	237.9	237.6	237.9	237.6	237.9
31.5°	236.5	236.1	236.5	236.7	237.1	236.7	236.5	236.1	236.5	236.1	236.5
32°	234.9	234.7	235.0	235.2	235.3	235.2	235.0	234.7	234.9	234.7	235.0
32.5°	233.7	233.1	233.8	233.8	234.0	233.8	233.8	233.1	233.7	233.1	233.8
33°	232.1	232.0	232.2	232.5	232.4	232.5	232.2	232.0	232.1	232.0	232.2
33.5°	230.8	230.2	230.9	230.9	230.8	230.9	230.9	230.2	230.8	230.2	230.9
34°	229.3	229.3	228.9	229.4	229.3	229.4	228.9	229.3	229.3	229.3	228.9
34.5°	227.4	227.5	227.6	227.8	228.0	227.8	227.6	227.5	227.4	227.5	227.6
35°	226.1	226.0	225.9	226.2	226.4	226.2	225.9	226.0	226.1	226.0	225.9
35.5°	224.3	224.5	224.4	224.9	224.6	224.9	224.4	224.5	224.3	224.5	224.4
36°	223.0	222.8	222.9	223.3	223.0	223.3	222.9	222.8	223.0	222.8	222.9
36.5°	221.0	221.0	221.3	221.6	221.4	221.6	221.3	221.0	221.0	221.0	221.3
37°	220.0	219.5	219.6	219.8	220.0	219.8	219.6	219.5	220.0	219.5	219.6
37.5°	217.6	217.8	218.3	218.6	218.5	218.6	218.3	217.8	217.6	217.8	218.3
38°	216.2	216.4	216.5	216.8	216.8	216.8	216.5	216.4	216.2	216.4	216.5
38.5°	214.4	214.5	214.7	215.2	215.1	215.2	214.7	214.5	214.4	214.5	214.7
39°	212.9	213.1	213.3	213.3	213.6	213.3	213.3	213.1	212.9	213.1	213.3
39.5°	211.3	211.2	211.6	211.7	211.7	211.7	211.6	211.2	211.3	211.2	211.6
40°	209.6	209.5	209.7	210.0	210.2	210.0	209.7	209.5	209.6	209.5	209.7
40.5°	207.9	207.7	207.9	208.3	208.4	208.3	207.9	207.7	207.9	207.7	207.9
41°	206.3	206.2	206.2	206.4	206.6	206.4	206.2	206.2	206.3	206.2	206.2
41.5°	204.4	204.2	204.5	204.7	204.9	204.7	204.5	204.2	204.4	204.2	204.5
42°	202.7	202.4	202.8	203.0	202.7	203.0	202.8	202.4	202.7	202.4	202.8
42.5°	201.0	200.6	201.0	201.3	201.1	201.3	201.0	200.6	201.0	200.6	201.0
43°	199.1	199.1	199.2	199.4	199.4	199.4	199.2	199.1	199.1	199.1	199.2
43.5°	197.3	197.1	197.2	197.5	197.6	197.5	197.2	197.1	197.3	197.1	197.2

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
45°	191.8	191.5	191.6	192.0	192.0	192.0	191.6	191.5	191.8	191.5	191.6
45.5°	189.8	189.4	189.7	190.0	190.0	190.0	189.7	189.4	189.8	189.4	189.7
46°	187.8	187.6	187.8	188.1	188.1	188.1	187.8	187.6	187.8	187.6	187.8
46.5°	185.9	185.6	185.8	186.0	186.0	186.0	185.8	185.6	185.9	185.6	185.8
47°	184.1	183.8	184.0	184.1	184.1	184.1	184.0	183.8	184.1	183.8	184.0
47.5°	182.2	181.8	182.1	182.3	182.3	182.3	182.1	181.8	182.2	181.8	182.1
48°	180.1	179.8	180.1	180.3	180.3	180.3	180.1	179.8	180.1	179.8	180.1
48.5°	178.2	177.9	178.1	178.2	178.2	178.2	178.1	177.9	178.2	177.9	178.1
49°	176.3	176.0	176.1	176.5	176.5	176.5	176.1	176.0	176.3	176.0	176.1
49.5°	174.2	173.9	174.1	174.2	174.2	174.2	174.1	173.9	174.2	173.9	174.1
50°	172.1	171.9	171.8	172.3	172.3	172.3	171.8	171.9	172.1	171.9	171.8
50.5°	170.1	169.8	169.8	170.2	170.2	170.2	169.8	169.8	170.1	169.8	169.8
51°	168.0	167.8	167.7	168.2	168.2	168.2	167.7	167.8	168.0	167.8	167.7
51.5°	165.9	165.7	165.8	166.0	166.0	166.0	165.8	165.7	165.9	165.7	165.8
52°	163.8	163.6	163.5	163.9	163.9	163.9	163.5	163.6	163.8	163.6	163.5
52.5°	161.5	161.4	161.6	161.8	161.8	161.8	161.6	161.4	161.5	161.4	161.6
53°	159.5	159.4	159.5	159.7	159.7	159.7	159.5	159.4	159.5	159.4	159.5
53.5°	157.6	157.2	157.5	157.3	157.3	157.3	157.5	157.2	157.6	157.2	157.5
54°	155.4	155.1	155.2	155.5	155.5	155.5	155.2	155.1	155.4	155.1	155.2
54.5°	153.2	152.9	153.0	153.4	153.4	153.4	153.0	152.9	153.2	152.9	153.0
55°	151.0	150.8	150.9	151.2	151.2	151.2	150.9	150.8	151.0	150.8	150.9
55.5°	148.9	148.6	148.7	148.8	148.8	148.8	148.7	148.6	148.9	148.6	148.7
56°	146.6	146.3	146.5	146.6	146.6	146.6	146.5	146.3	146.6	146.3	146.5
56.5°	144.4	144.1	144.3	144.4	144.4	144.4	144.3	144.1	144.4	144.1	144.3
57°	142.1	141.8	142.0	142.3	142.3	142.3	142.0	141.8	142.1	141.8	142.0
57.5°	139.8	139.6	139.8	140.1	140.1	140.1	139.8	139.6	139.8	139.6	139.8
58°	137.6	137.3	137.6	137.8	137.8	137.8	137.6	137.3	137.6	137.3	137.6
58.5°	135.4	135.2	135.3	135.4	135.4	135.4	135.3	135.2	135.4	135.2	135.3
59°	133.2	132.9	132.8	133.1	133.1	133.1	132.8	132.9	133.2	132.9	132.8
59.5°	130.8	130.6	130.5	130.8	130.8	130.8	130.5	130.6	130.8	130.6	130.5
60°	128.5	128.3	128.2	128.5	128.5	128.5	128.2	128.3	128.5	128.3	128.2
60.5°	126.2	125.9	125.9	126.2	126.2	126.2	125.9	125.9	126.2	125.9	125.9
61°	123.7	123.6	123.6	123.8	123.8	123.8	123.6	123.6	123.7	123.6	123.6
61.5°	121.3	121.2	121.3	121.5	121.5	121.5	121.3	121.2	121.3	121.2	121.3
62°	118.9	118.9	118.9	119.2	119.2	119.2	118.9	118.9	118.9	118.9	118.9
62.5°	116.6	116.6	116.6	116.9	116.9	116.9	116.6	116.6	116.6	116.6	116.6
63°	114.3	114.2	114.3	114.5	114.5	114.5	114.3	114.2	114.3	114.2	114.3
63.5°	111.8	111.8	111.9	112.0	112.0	112.0	111.9	111.8	111.8	111.8	111.9
64°	109.5	109.3	109.5	109.6	109.6	109.6	109.5	109.3	109.5	109.3	109.5
64.5°	107.0	107.0	107.1	107.1	107.1	107.1	107.1	107.0	107.0	107.0	107.1
65°	104.7	104.5	104.6	104.7	104.7	104.7	104.6	104.5	104.7	104.5	104.6
65.5°	102.2	102.1	102.2	102.3	102.3	102.3	102.2	102.1	102.2	102.1	102.2
66°	99.7	99.6	99.7	99.9	99.9	99.9	99.7	99.6	99.7	99.6	99.7

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
67.5°	92.5	92.2	92.3	92.5	92.6	92.5	92.3	92.2	92.5	92.2	92.3
68°	90.0	89.8	89.8	90.0	90.2	90.0	89.8	89.8	90.0	89.8	89.8
68.5°	87.5	87.4	87.5	87.6	87.6	87.6	87.5	87.4	87.5	87.4	87.5
69°	85.0	84.9	84.8	85.0	85.1	85.0	84.8	84.9	85.0	84.9	84.8
69.5°	82.5	82.3	82.4	82.6	82.6	82.6	82.4	82.3	82.5	82.3	82.4
70°	80.1	79.9	80.0	80.1	80.1	80.1	80.0	79.9	80.1	79.9	80.0
70.5°	77.5	77.3	77.4	77.6	77.6	77.6	77.4	77.3	77.5	77.3	77.4
71°	75.0	74.9	74.9	75.1	75.1	75.1	74.9	74.9	75.0	74.9	74.9
71.5°	72.4	72.3	72.4	72.6	72.5	72.6	72.4	72.3	72.4	72.3	72.4
72°	69.9	69.8	69.8	70.0	70.0	70.0	69.8	69.8	69.9	69.8	69.8
72.5°	67.4	67.3	67.4	67.6	67.5	67.6	67.4	67.3	67.4	67.3	67.4
73°	64.8	64.8	64.8	65.1	65.0	65.1	64.8	64.8	64.8	64.8	64.8
73.5°	62.4	62.3	62.3	62.5	62.5	62.5	62.3	62.3	62.4	62.3	62.3
74°	60.0	59.9	59.9	59.9	60.1	59.9	59.9	59.9	60.0	59.9	59.9
74.5°	57.4	57.4	57.4	57.5	57.5	57.5	57.4	57.4	57.4	57.4	57.4
75°	54.9	54.9	54.9	55.0	55.0	55.0	54.9	54.9	54.9	54.9	54.9
75.5°	52.4	52.4	52.4	52.5	52.5	52.5	52.4	52.4	52.4	52.4	52.4
76°	50.0	49.9	49.9	50.0	50.0	50.0	49.9	49.9	50.0	49.9	49.9
76.5°	47.5	47.4	47.5	47.6	47.5	47.6	47.5	47.4	47.5	47.4	47.5
77°	45.0	45.0	45.1	45.2	45.2	45.2	45.1	45.0	45.0	45.0	45.1
77.5°	42.7	42.6	42.7	42.8	42.8	42.8	42.7	42.6	42.7	42.6	42.7
78°	40.3	40.3	40.3	40.5	40.5	40.5	40.3	40.3	40.3	40.3	40.3
78.5°	38.0	38.0	37.9	38.1	38.1	38.1	37.9	38.0	38.0	38.0	37.9
79°	35.7	35.6	35.6	35.7	35.8	35.7	35.6	35.6	35.7	35.6	35.6
79.5°	33.3	33.3	33.3	33.4	33.4	33.4	33.3	33.3	33.3	33.3	33.3
80°	31.0	30.9	31.0	31.1	31.1	31.1	31.0	30.9	31.0	30.9	31.0
80.5°	28.7	28.7	28.7	28.9	28.8	28.9	28.7	28.7	28.7	28.7	28.7
81°	26.5	26.5	26.5	26.6	26.6	26.6	26.5	26.5	26.5	26.5	26.5
81.5°	24.3	24.2	24.3	24.4	24.4	24.4	24.3	24.2	24.3	24.2	24.3
82°	22.0	22.0	22.1	22.2	22.3	22.2	22.1	22.0	22.0	22.0	22.1
82.5°	19.9	19.9	20.0	20.2	20.3	20.2	20.0	19.9	19.9	19.9	20.0
83°	17.9	18.0	18.0	18.2	18.3	18.2	18.0	18.0	17.9	18.0	18.0
83.5°	16.0	16.0	16.1	16.2	16.3	16.2	16.1	16.0	16.0	16.0	16.1
84°	14.2	14.1	14.3	14.3	14.4	14.3	14.3	14.1	14.2	14.1	14.3
84.5°	12.4	12.4	12.4	12.6	12.7	12.6	12.4	12.4	12.4	12.4	12.4
85°	10.7	10.7	10.7	10.9	11.1	10.9	10.7	10.7	10.7	10.7	10.7
85.5°	9.0	9.0	9.2	9.3	9.4	9.3	9.2	9.0	9.0	9.0	9.2
86°	7.5	7.6	7.7	7.8	8.0	7.8	7.7	7.6	7.5	7.6	7.7
86.5°	6.1	6.1	6.3	6.4	6.6	6.4	6.3	6.1	6.1	6.1	6.3
87°	4.8	4.9	5.0	5.1	5.3	5.1	5.0	4.9	4.8	4.9	5.0
87.5°	3.7	3.8	3.9	4.0	4.2	4.0	3.9	3.8	3.7	3.8	3.9
88°	2.7	2.7	2.9	3.0	3.3	3.0	2.9	2.7	2.7	2.7	2.9
88.5°	1.8	1.9	2.0	2.2	2.4	2.2	2.0	1.9	1.8	1.9	2.0

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P997218
CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°	202.5°	225°
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
0°	283.0	283.0	283.0	283.0	283.0	283.0
0.5°	283.3	283.5	283.3	282.8	282.9	283.0
1°	283.3	283.6	283.3	283.0	282.9	282.9
1.5°	283.2	283.5	283.2	283.0	282.7	283.2
2°	283.3	283.6	283.3	282.9	282.6	283.2
2.5°	283.1	282.9	283.1	282.7	282.6	282.8
3°	283.0	282.8	283.0	282.6	282.3	282.7
3.5°	282.8	282.6	282.8	282.6	282.2	282.7
4°	282.5	282.7	282.5	282.4	282.2	282.3
4.5°	282.1	282.4	282.1	282.2	281.8	282.3
5°	281.9	281.8	281.9	282.0	281.4	281.9
5.5°	281.6	282.0	281.6	281.6	281.4	282.0
6°	281.6	282.0	281.6	281.3	281.0	281.2
6.5°	281.0	281.3	281.0	280.9	280.7	281.1
7°	280.9	281.3	280.9	280.6	280.5	280.8
7.5°	280.3	280.6	280.3	280.4	280.1	280.4
8°	280.1	280.6	280.1	280.2	279.4	280.1
8.5°	279.6	280.0	279.6	279.5	279.3	279.5
9°	279.4	279.6	279.4	279.0	278.9	278.5
9.5°	279.1	279.0	279.1	278.5	278.6	278.3
10°	278.6	278.8	278.6	278.1	278.2	277.8
10.5°	278.0	278.2	278.0	277.8	277.4	277.3
11°	277.7	277.2	277.7	277.2	276.9	277.0
11.5°	276.7	277.0	276.7	276.9	276.4	276.5
12°	276.5	276.7	276.5	276.0	275.6	276.0
12.5°	275.8	275.9	275.8	275.6	275.3	275.4
13°	275.0	275.2	275.0	274.9	274.6	275.0
13.5°	274.2	274.4	274.2	274.5	273.9	274.3
14°	273.7	274.2	273.7	273.7	273.4	273.4
14.5°	273.1	273.4	273.1	273.1	272.7	273.0
15°	272.4	272.6	272.4	272.5	272.1	272.2
15.5°	271.6	272.0	271.6	271.4	271.3	271.5
16°	271.0	270.8	271.0	270.8	270.6	270.5
16.5°	270.2	270.3	270.2	270.0	269.7	270.0
17°	269.6	269.2	269.6	269.3	269.0	269.2
17.5°	268.4	268.6	268.4	268.3	268.0	268.3
18°	267.7	267.7	267.7	267.5	267.1	267.2
18.5°	266.7	267.2	266.7	266.5	266.6	266.6
19°	265.9	266.4	265.9	265.9	265.6	265.7
19.5°	264.8	264.9	264.8	265.0	264.3	264.7
20°	264.1	264.2	264.1	263.9	263.8	264.0
20.5°	263.0	263.3	263.0	262.8	262.5	263.0
21°	262.1	262.4	262.1	261.7	261.8	261.7

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
22.5°	259.3	259.1	259.3	258.4	258.3	259.1
23°	258.3	258.1	258.3	257.6	257.5	257.9
23.5°	257.1	257.0	257.1	256.6	256.3	256.8
24°	255.8	256.1	255.8	255.6	255.3	255.9
24.5°	254.5	254.8	254.5	254.3	254.2	254.6
25°	253.5	253.8	253.5	253.4	253.2	253.2
25.5°	252.5	252.4	252.5	252.3	252.0	252.2
26°	251.1	251.4	251.1	251.0	250.8	250.9
26.5°	249.9	250.0	249.9	249.9	249.5	249.9
27°	248.8	249.0	248.8	248.4	248.3	248.6
27.5°	247.5	247.7	247.5	247.2	247.0	247.5
28°	246.3	246.6	246.3	246.1	245.9	246.1
28.5°	245.0	245.4	245.0	244.9	244.4	244.9
29°	243.5	243.8	243.5	243.4	243.1	243.3
29.5°	242.2	242.5	242.2	242.2	241.8	242.0
30°	240.8	241.1	240.8	240.7	240.6	240.3
30.5°	239.5	240.1	239.5	239.4	239.0	239.3
31°	238.1	238.6	238.1	237.9	237.6	237.9
31.5°	236.7	237.1	236.7	236.5	236.1	236.5
32°	235.2	235.3	235.2	235.0	234.7	234.9
32.5°	233.8	234.0	233.8	233.8	233.1	233.7
33°	232.5	232.4	232.5	232.2	232.0	232.1
33.5°	230.9	230.8	230.9	230.9	230.2	230.8
34°	229.4	229.3	229.4	228.9	229.3	229.3
34.5°	227.8	228.0	227.8	227.6	227.5	227.4
35°	226.2	226.4	226.2	225.9	226.0	226.1
35.5°	224.9	224.6	224.9	224.4	224.5	224.3
36°	223.3	223.0	223.3	222.9	222.8	223.0
36.5°	221.6	221.4	221.6	221.3	221.0	221.0
37°	219.8	220.0	219.8	219.6	219.5	220.0
37.5°	218.6	218.5	218.6	218.3	217.8	217.6
38°	216.8	216.8	216.8	216.5	216.4	216.2
38.5°	215.2	215.1	215.2	214.7	214.5	214.4
39°	213.3	213.6	213.3	213.3	213.1	212.9
39.5°	211.7	211.7	211.7	211.6	211.2	211.3
40°	210.0	210.2	210.0	209.7	209.5	209.6
40.5°	208.3	208.4	208.3	207.9	207.7	207.9
41°	206.4	206.6	206.4	206.2	206.2	206.3
41.5°	204.7	204.9	204.7	204.5	204.2	204.4
42°	203.0	202.7	203.0	202.8	202.4	202.7
42.5°	201.3	201.1	201.3	201.0	200.6	201.0
43°	199.4	199.4	199.4	199.2	199.1	199.1
43.5°	197.5	197.6	197.5	197.2	197.1	197.3

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
45°	192.0	192.0	192.0	191.6	191.5	191.8
45.5°	190.0	190.0	190.0	189.7	189.4	189.8
46°	188.1	188.1	188.1	187.8	187.6	187.8
46.5°	186.0	186.2	186.0	185.8	185.6	185.9
47°	184.1	184.2	184.1	184.0	183.8	184.1
47.5°	182.3	182.4	182.3	182.1	181.8	182.2
48°	180.3	180.5	180.3	180.1	179.8	180.1
48.5°	178.2	178.4	178.2	178.1	177.9	178.2
49°	176.5	176.3	176.5	176.1	176.0	176.3
49.5°	174.2	174.5	174.2	174.1	173.9	174.2
50°	172.3	172.4	172.3	171.8	171.9	172.1
50.5°	170.2	170.3	170.2	169.8	169.8	170.1
51°	168.2	168.2	168.2	167.7	167.8	168.0
51.5°	166.0	166.2	166.0	165.8	165.7	165.9
52°	163.9	164.2	163.9	163.5	163.6	163.8
52.5°	161.8	162.0	161.8	161.6	161.4	161.5
53°	159.7	159.8	159.7	159.5	159.4	159.5
53.5°	157.3	157.7	157.3	157.5	157.2	157.6
54°	155.5	155.6	155.5	155.2	155.1	155.4
54.5°	153.4	153.4	153.4	153.0	152.9	153.2
55°	151.2	151.3	151.2	150.9	150.8	151.0
55.5°	148.8	149.2	148.8	148.7	148.6	148.9
56°	146.6	146.8	146.6	146.5	146.3	146.6
56.5°	144.4	144.5	144.4	144.3	144.1	144.4
57°	142.3	142.3	142.3	142.0	141.8	142.1
57.5°	140.1	140.1	140.1	139.8	139.6	139.8
58°	137.8	137.8	137.8	137.6	137.3	137.6
58.5°	135.4	135.5	135.4	135.3	135.2	135.4
59°	133.1	133.3	133.1	132.8	132.9	133.2
59.5°	130.8	130.9	130.8	130.5	130.6	130.8
60°	128.5	128.7	128.5	128.2	128.3	128.5
60.5°	126.2	126.4	126.2	125.9	125.9	126.2
61°	123.8	124.0	123.8	123.6	123.6	123.7
61.5°	121.5	121.6	121.5	121.3	121.2	121.3
62°	119.2	119.3	119.2	118.9	118.9	118.9
62.5°	116.9	116.9	116.9	116.6	116.6	116.6
63°	114.5	114.5	114.5	114.3	114.2	114.3
63.5°	112.0	112.2	112.0	111.9	111.8	111.8
64°	109.6	109.9	109.6	109.5	109.3	109.5
64.5°	107.1	107.4	107.1	107.1	107.0	107.0
65°	104.7	105.0	104.7	104.6	104.5	104.7
65.5°	102.3	102.4	102.3	102.2	102.1	102.2
66°	99.9	100.0	99.9	99.7	99.6	99.7

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



TEST NUMBER: P997218

CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
67.5°	92.5	92.6	92.5	92.3	92.2	92.5
68°	90.0	90.2	90.0	89.8	89.8	90.0
68.5°	87.6	87.6	87.6	87.5	87.4	87.5
69°	85.0	85.1	85.0	84.8	84.9	85.0
69.5°	82.6	82.6	82.6	82.4	82.3	82.5
70°	80.1	80.1	80.1	80.0	79.9	80.1
70.5°	77.6	77.6	77.6	77.4	77.3	77.5
71°	75.1	75.1	75.1	74.9	74.9	75.0
71.5°	72.6	72.5	72.6	72.4	72.3	72.4
72°	70.0	70.0	70.0	69.8	69.8	69.9
72.5°	67.6	67.5	67.6	67.4	67.3	67.4
73°	65.1	65.0	65.1	64.8	64.8	64.8
73.5°	62.5	62.5	62.5	62.3	62.3	62.4
74°	59.9	60.1	59.9	59.9	59.9	60.0
74.5°	57.5	57.5	57.5	57.4	57.4	57.4
75°	55.0	55.0	55.0	54.9	54.9	54.9
75.5°	52.5	52.5	52.5	52.4	52.4	52.4
76°	50.0	50.0	50.0	49.9	49.9	50.0
76.5°	47.6	47.5	47.6	47.5	47.4	47.5
77°	45.2	45.2	45.2	45.1	45.0	45.0
77.5°	42.8	42.8	42.8	42.7	42.6	42.7
78°	40.5	40.5	40.5	40.3	40.3	40.3
78.5°	38.1	38.1	38.1	37.9	38.0	38.0
79°	35.7	35.8	35.7	35.6	35.6	35.7
79.5°	33.4	33.4	33.4	33.3	33.3	33.3
80°	31.1	31.1	31.1	31.0	30.9	31.0
80.5°	28.9	28.8	28.9	28.7	28.7	28.7
81°	26.6	26.6	26.6	26.5	26.5	26.5
81.5°	24.4	24.4	24.4	24.3	24.2	24.3
82°	22.2	22.3	22.2	22.1	22.0	22.0
82.5°	20.2	20.3	20.2	20.0	19.9	19.9
83°	18.2	18.3	18.2	18.0	18.0	17.9
83.5°	16.2	16.3	16.2	16.1	16.0	16.0
84°	14.3	14.4	14.3	14.3	14.1	14.2
84.5°	12.6	12.7	12.6	12.4	12.4	12.4
85°	10.9	11.1	10.9	10.7	10.7	10.7
85.5°	9.3	9.4	9.3	9.2	9.0	9.0
86°	7.8	8.0	7.8	7.7	7.6	7.5
86.5°	6.4	6.6	6.4	6.3	6.1	6.1
87°	5.1	5.3	5.1	5.0	4.9	4.8
87.5°	4.0	4.2	4.0	3.9	3.8	3.7
88°	3.0	3.3	3.0	2.9	2.7	2.7
88.5°	2.2	2.4	2.2	2.0	1.9	1.8

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



TEST NUMBER: P997218
CATALOG NUMBER: SMX6SLSFSD2W-750LM-3500K

CANDELA DISTRIBUTION (continued):

	247.5°	270°	292.5°	315°	337.5°	360°
90°	0.0	0.0	0.0	0.0	0.0	0.0

Classified

Scaled Data Report

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269



Report Generated By 670245859 / DESKTOP-T8S5UU9

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270° - · - 135°-315°

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report





21.5°	261.2	260.5	260.6	261.0	261.2	261.0	260.6	260.5	261.2	260.5	260.6
22°	260.1	259.4	259.9	260.3	260.0	260.3	259.9	259.4	260.1	259.4	259.9



44°	195.6	195.2	195.4	195.8	195.7	195.8	195.4	195.2	195.6	195.2	195.4
44.5°	193.5	193.3	193.5	193.8	193.9	193.8	193.5	193.3	193.5	193.3	193.5



66.5°	97.3	97.1	97.2	97.5	97.5	97.2	97.1	97.3	97.1	97.2
67°	94.9	94.7	94.8	94.9	94.9	94.8	94.7	94.9	94.7	94.8



89°	1.1	1.2	1.4	1.5	1.7	1.5	1.4	1.2	1.1	1.2	1.4
89.5°	0.6	0.7	0.8	1.0	1.2	1.0	0.8	0.7	0.6	0.7	0.8

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



21.5°	261.0	261.2	261.0	260.6	260.5	261.2
22°	260.3	260.0	260.3	259.9	259.4	260.1

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



44°	195.8	195.7	195.8	195.4	195.2	195.6
44.5°	193.8	193.9	193.8	193.5	193.3	193.5

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



66.5°	97.5	97.5	97.5	97.2	97.1	97.3
67°	94.9	95.1	94.9	94.8	94.7	94.9

Classified
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



89°	1.5	1.7	1.5	1.4	1.2	1.1
89.5°	1.0	1.2	1.0	0.8	0.7	0.6

Classified

Cooper Lighting Solutions Photometric Lab

1121 Highway 74 South

Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)