

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: HALO

Report Number: P188925

Luminaire Tested: **L80808FL9035P**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P188925
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P27060)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: HALO
Catalog Number: L80808FL9035P
Description: HALO TRACK L LED 08, 850 LM, FLOOD, WHITE

Light Source: EATON LED 3500K
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 992.2 lumens
Efficiency: N/A
Efficacy: 83.4 lumens/watt
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.62
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct


Input Watts (W): 11.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P188925

CATALOG NUMBER: L80808FL9035P

Luminous Intensity Polar Plot



TEST NUMBER: P188925

CATALOG NUMBER: L80808FL9035P

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100								
1	114	112	109	107	112	110	108	106	106	104	102	102	101	99	98	97	97	95								
2	109	105	102	99	107	103	100	97	100	98	95	97	95	93	95	93	91	90								
3	105	99	95	92	103	98	94	91	95	92	89	93	90	88	91	89	87	85								
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81								
5	97	90	85	81	95	89	84	80	87	83	80	85	82	79	84	81	78	77								
6	93	85	80	77	92	85	80	76	83	79	76	82	78	75	81	77	75	74								
7	89	81	76	73	88	81	76	73	80	75	72	79	75	72	78	74	72	70								
8	86	78	73	69	85	77	73	69	76	72	69	75	72	69	75	71	68	67								
9	83	75	70	66	82	74	70	66	73	69	66	73	69	66	72	68	66	65								
10	80	72	67	64	79	71	67	64	71	66	63	70	66	63	69	66	63	62								

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	445359
5°	441976
10°	408654
15°	350831
20°	264483
25°	124168
30°	58566
35°	30196
40°	16803
45°	9644
50°	6277
55°	4396
60°	3552
65°	3580
70°	3719
75°	2965
80°	2904
85°	0



TEST NUMBER: P188925

CATALOG NUMBER: L80808FL9035P

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	186.5	18.8
10°-20°	423.4	42.7
20°-30°	257.3	25.9
30°-40°	76.2	7.7
40°-50°	26.0	2.6
50°-60°	11.2	1.1
60°-70°	6.9	0.7
70°-80°	4.1	0.4
80°-90°	0.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	867.2	87.4
0°-40°	943.4	95.1
0°-60°	980.6	98.8
0°-90°	992.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	992.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2031	
5°	2008	187
15°	1545	423
25°	513	257
35°	113	76
45°	31	26
55°	12	11
65°	7	7
75°	4	4
85°	0	1
90°	0	



TEST NUMBER: P188925

CATALOG NUMBER: L80808FL9035P

CANDELA DISTRIBUTION (FULL):

0°	
0°	2031.0
1°	2024.1
2°	2019.5
3°	2018.3
4°	2016.0
5°	2007.9
6°	1994.1
7°	1970.0
8°	1935.5
9°	1889.4
10°	1835.3
11°	1781.3
12°	1723.7
13°	1666.2
14°	1607.5
15°	1545.4
16°	1482.1
17°	1414.2
18°	1340.5
19°	1249.6
20°	1133.4
21°	1002.2
22°	868.8
23°	742.2
24°	621.4
25°	513.2
26°	435.0
27°	376.3
28°	323.3
29°	275.0
30°	231.3
32.5°	159.9
35°	112.8
37.5°	80.5
40°	58.7
42.5°	42.6
45°	31.1
47.5°	24.2
50°	18.4
52.5°	15.0
55°	11.5
57.5°	10.4
60°	8.1
62.5°	8.1
65°	6.9



TEST NUMBER: P188925

CATALOG NUMBER: L80808FL9035P

CANDELA DISTRIBUTION (continued):

	0°
67.5°	5.8
70°	5.8
72.5°	4.6
75°	3.5
77.5°	3.5
80°	2.3
82.5°	1.2
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)