

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: INVUE

Report Number: G2-2108-353-8

Luminaire Tested: **LXS-VA1-AMB-U-SYM-C**

Test Date: 9/20/2021

Test Information

Test Method: LM-79-08
Report Number: G2-2108-353-8
Test Lab: COOPER LIGHTING SOLUTIONS
Test Date: 9/20/2021
Issue Date: 9/20/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: INVUE
Catalog Number: LXS-VA1-AMB-U-SYM-C
Description: LUXESCAPE OUTDOOR ARCHITECTURAL LUMINAIRE
NARROW BAND AMBER LEDS AND TYPE V OPTIC, CANTILEVER MOUNT
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1675.3 lumens
Efficiency: N/A
Efficacy: 25.5 lumens/watt
Luminous Opening: Circular (Dia: 1.67' x H: 0')
IES Classification: Type V - Short
BUG Rating: B1 - U0 - G1

Input Watts (W): 65.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT




REPORT NUMBER: G2-2108-353-8
 CATALOG NUMBER: LXS-VA1-AMB-U-SYM-C

Iso-Footcandle Lines of Horizontal Illumination

× Max cd


--- 1/2 Max cd



Based on 12 foot mounting height. Maximum calculated value = 0.6 fc
 Type V - Short - N/A

REPORT NUMBER: G2-2108-353-8
CATALOG NUMBER: LXS-VA1-AMB-U-SYM-C

Luminous Intensity Polar Plot



REPORT NUMBER: G2-2108-353-8

CATALOG NUMBER: LXS-VA1-AMB-U-SYM-C


FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	837.7	0.0	837.7
	% Fixture	50.0	0.0	50.0
Street Side	Lumens	837.7	0.0	837.7
	% Fixture	50.0	0.0	50.0
Total	Lumens	1675.3	0.0	1675.3
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	3.3	0.2
10°-20°	11.9	0.7
20°-30°	28.2	1.7
30°-40°	70.8	4.2
40°-50°	184.1	11.0
50°-60°	392.0	23.4
60°-70°	510.8	30.5
70°-80°	388.6	23.2
80°-90°	85.7	5.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	1675.3	100.0
0°-180°	1675.3	100.0

Coefficient of Utilization



REPORT NUMBER: G2-2108-353-8


CATALOG NUMBER: LXS-VA1-AMB-U-SYM-C

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	21.7	1.3			
FM	(30°-60°)	323.4	19.3			
FH	(60°-80°)	449.7	26.8			G0/660
FVH	(80°-90°)	42.9	2.6			G1/100
BL	(0°-30°)	21.7	1.3	B0/110		
BM	(30°-60°)	323.4	19.3	B1/1000		
BH	(60°-80°)	449.7	26.8	B1/500		G0/660
BVH	(80°-90°)	42.9	2.6			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B1-U0-G1

Type V Short



REPORT NUMBER: G2-2108-353-8

CATALOG NUMBER: LXS-VA1-AMB-U-SYM-C

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	32	32	32	32	32	32	32	32	32	32	32
2.5°	33	33	33	33	33	33	33	33	33	33	33
5°	34	34	34	34	34	34	34	34	34	34	34
7.5°	36	35	35	35	35	35	35	35	35	35	35
10°	38	38	37	37	37	37	37	37	37	37	37
12.5°	40	40	40	39	39	39	39	39	39	39	39
15°	42	42	41	41	41	41	41	41	41	41	41
17.5°	45	45	44	43	43	43	43	42	42	43	43
20°	49	49	48	47	48	48	47	46	46	47	47
22.5°	55	55	54	53	53	53	51	51	50	51	51
25°	63	63	61	59	59	59	57	56	55	56	56
27.5°	74	73	71	68	68	67	65	64	63	62	62
30°	87	86	84	81	79	78	76	75	73	71	71
32.5°	104	103	99	96	94	91	88	87	85	84	84
35°	121	120	117	114	112	107	103	102	101	100	100
37.5°	140	140	136	134	133	127	122	121	123	121	122
40°	163	163	159	159	158	154	148	149	150	147	147
42.5°	193	195	190	191	191	190	183	184	187	182	180
45°	233	234	229	230	232	233	227	228	231	224	221
47.5°	276	278	274	277	280	280	278	280	283	274	271
50°	329	330	328	331	336	344	338	342	342	333	331
52.5°	386	387	386	386	394	402	400	403	401	393	390
55°	431	432	435	435	445	452	453	455	452	445	442
57.5°	463	463	471	468	480	491	488	491	488	483	482
60°	487	485	497	494	506	515	515	521	515	512	513
62.5°	497	502	518	512	531	533	538	537	532	531	527
65°	500	507	514	509	528	542	534	535	530	533	534
67.5°	493	490	504	500	513	525	518	522	515	519	520
70°	457	465	480	473	490	492	492	494	486	488	494
72.5°	418	425	429	426	441	450	443	445	439	442	451
75°	366	365	371	369	379	386	377	380	376	379	389
77.5°	292	298	304	298	308	309	304	305	303	308	311
80°	215	226	226	224	228	232	225	227	222	226	226
82.5°	141	145	143	141	144	148	139	146	139	142	147
85°	64	64	58	58	58	58	53	56	56	55	60
87.5°	3	3	3	2	2	2	2	2	2	1	1
90°	0	0	0	0	0	0	0	0	0	0	0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



LM-79-08: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

INVUE

Report Number: SP1-2201-507-1

Luminaire Tested: ARB-B1-LED-D1-T2-AMB

Test Date: 01/21/2022


Test Information

Test Method: LM-79-08
 Report Number: SP1-2201-507-1
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1
 Measurement Geometry: 4π
 Issue Date: 01/21/2022
 Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
 Product Line: INVUE
 Catalog Number: **ARB-B1-LED-D1-T2-AMB**
 Description: INVUE ARBOR AMBER

TESTED IN SITU. ARBOR OUTDOOR ARCHITECTURAL POST TOP. NARROW BAND AMBER LEDS AND TYPE II OPTIC, GRAPHITE METALLIC PAINTED FINISH. EACH LED BOARD AT 500MA.

Spectral Parameters

CCT (K):	1838	CRI (Ra):	-25.2		
CIE u':	0.3190	R1:	-44.1	R9:	-415.1
CIE v':	0.5510	R2:	45.5	R10:	16.1
Duv:	0.0083	R3:	23.9	R11:	-105.6
CIE x:	0.5632	R4:	-72.5	R12:	-27.5
CIE y:	0.4323	R5:	-46.4	R13:	-25.8
CIE z:	0.0045	R6:	27.4	R14:	48.6
Peak Wavelength (nm):	591	R7:	-2.2		
Dominant Wavelength (nm):	588	R8:	-133.0		
Purity:	99.4				
Rf:	8				
Rg:	12.7				



Test Conditions


Stabilization Time: 164M
 Operation Time: 12H
 Room Temperature (°C) / RH%: 24.2/26%
 Sphere Temperature (°C): 24.6

REPORT NUMBER: SP1-2201-507-1
CATALOG NUMBER: ARB-B1-LED-D1-T2-AMB


Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	76INCH SPHERE IN0058	8/3/2021	2/3/2022
Power Meter	XITRON 2801 IN0071	11/29/2021	11/29/2022
AC Power Source	CHROMA 61603 IN0063	11/29/2021	11/29/2022
DC Power Source	AGILENT E3634A IN0208	11/29/2021	11/29/2022
Sphere Thermometer	ONSET IN0085	11/29/2021	11/29/2022
Room Thermometer	ONSET IN0046	11/29/2021	11/29/2022

REPORT NUMBER: SP1-2201-507-1

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



REPORT NUMBER: SP1-2201-507-1

Photopic Flux vs. Wavelength




#####

λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)
360	232	NR	490	102	NR	620	1285	NR	750	361	NR	880	1054	NR
365	141	NR	495	91	NR	625	794	NR	755	226	NR	885	743	NR
370	221	NR	500	109	NR	630	604	NR	760	303	NR	890	375	NR
375	314	NR	505	95	NR	635	625	NR	765	277	NR	895	132	NR
380	237	NR	510	92	NR	640	568	NR	770	149	NR	900	509	NR
385	296	NR	515	131	NR	645	573	NR	775	286	NR	905	284	NR
390	260	NR	520	132	NR	650	495	NR	780	359	NR	910	225	NR
395	190	NR	525	133	NR	655	464	NR	785	390	NR	915	726	NR
400	227	NR	530	175	NR	660	397	NR	790	276	NR	920	800	NR
405	169	NR	535	205	NR	665	409	NR	795	342	NR	925	345	NR
410	152	NR	540	294	NR	670	281	NR	800	177	NR	930	77	NR
415	171	NR	545	475	NR	675	262	NR	805	373	NR	935	233	NR
420	121	NR	550	833	NR	680	208	NR	810	500	NR	940	730	NR
425	135	NR	555	1466	NR	685	193	NR	815	602	NR	945	259	NR
430	90	NR	560	2623	NR	690	213	NR	820	681	NR	950	510	NR
435	92	NR	565	4872	NR	695	267	NR	825	615	NR	955	800	NR
440	87	NR	570	8896	NR	700	218	NR	830	529	NR	960	959	NR
445	129	NR	575	16191	NR	705	234	NR	835	526	NR	965	925	NR
450	75	NR	580	29728	NR	710	280	NR	840	531	NR	970	863	NR
455	88	NR	585	53245	NR	715	393	NR	845	627	NR	975	1444	NR
460	76	NR	590	78694	NR	720	370	NR	850	248	NR	980	1342	NR
465	74	NR	595	63659	NR	725	376	NR	855	262	NR	985	1396	NR
470	87	NR	600	31696	NR	730	324	NR	860	579	NR	990	2816	NR
475	37	NR	605	13208	NR	735	359	NR	865	439	NR	995	1223	NR
480	77	NR	610	5473	NR	740	294	NR	870	923	NR	1000	487	NR
485	97	NR	615	2571	NR	745	300	NR	875	874	NR			

REPORT NUMBER: SP1-2201-507-1

Scotopic Flux vs. Wavelength




Scotopic Lumens: 236

S/P: 0.29

λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)
360	232	NR	490	102	NR	620	1285	NR	750	361	NR	880	1054	NR
365	141	NR	495	91	NR	625	794	NR	755	226	NR	885	743	NR
370	221	NR	500	109	NR	630	604	NR	760	303	NR	890	375	NR
375	314	NR	505	95	NR	635	625	NR	765	277	NR	895	132	NR
380	237	NR	510	92	NR	640	568	NR	770	149	NR	900	509	NR
385	296	NR	515	131	NR	645	573	NR	775	286	NR	905	284	NR
390	260	NR	520	132	NR	650	495	NR	780	359	NR	910	225	NR
395	190	NR	525	133	NR	655	464	NR	785	390	NR	915	726	NR
400	227	NR	530	175	NR	660	397	NR	790	276	NR	920	800	NR
405	169	NR	535	205	NR	665	409	NR	795	342	NR	925	345	NR
410	152	NR	540	294	NR	670	281	NR	800	177	NR	930	77	NR
415	171	NR	545	475	NR	675	262	NR	805	373	NR	935	233	NR
420	121	NR	550	833	NR	680	208	NR	810	500	NR	940	730	NR
425	135	NR	555	1466	NR	685	193	NR	815	602	NR	945	259	NR
430	90	NR	560	2623	NR	690	213	NR	820	681	NR	950	510	NR
435	92	NR	565	4872	NR	695	267	NR	825	615	NR	955	800	NR
440	87	NR	570	8896	NR	700	218	NR	830	529	NR	960	959	NR
445	129	NR	575	16191	NR	705	234	NR	835	526	NR	965	925	NR
450	75	NR	580	29728	NR	710	280	NR	840	531	NR	970	863	NR
455	88	NR	585	53245	NR	715	393	NR	845	627	NR	975	1444	NR
460	76	NR	590	78694	NR	720	370	NR	850	248	NR	980	1342	NR
465	74	NR	595	63659	NR	725	376	NR	855	262	NR	985	1396	NR
470	87	NR	600	31696	NR	730	324	NR	860	579	NR	990	2816	NR
475	37	NR	605	13208	NR	735	359	NR	865	439	NR	995	1223	NR
480	77	NR	610	5473	NR	740	294	NR	870	923	NR	1000	487	NR
485	97	NR	615	2571	NR	745	300	NR	875	874	NR			

REPORT NUMBER: SP1-2201-507-1

Melanopic Flux vs. Wavelength



Melanopic Lumens: 31.6

S/P: 0.04

λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)	λ (nm)	Power (μW/nm)	Lumens (Φ/nm)
360	232	NR	490	102	NR	620	1285	NR	750	361	NR	880	1054	NR
365	141	NR	495	91	NR	625	794	NR	755	226	NR	885	743	NR
370	221	NR	500	109	NR	630	604	NR	760	303	NR	890	375	NR
375	314	NR	505	95	NR	635	625	NR	765	277	NR	895	132	NR
380	237	NR	510	92	NR	640	568	NR	770	149	NR	900	509	NR
385	296	NR	515	131	NR	645	573	NR	775	286	NR	905	284	NR
390	260	NR	520	132	NR	650	495	NR	780	359	NR	910	225	NR
395	190	NR	525	133	NR	655	464	NR	785	390	NR	915	726	NR
400	227	NR	530	175	NR	660	397	NR	790	276	NR	920	800	NR
405	169	NR	535	205	NR	665	409	NR	795	342	NR	925	345	NR
410	152	NR	540	294	NR	670	281	NR	800	177	NR	930	77	NR
415	171	NR	545	475	NR	675	262	NR	805	373	NR	935	233	NR
420	121	NR	550	833	NR	680	208	NR	810	500	NR	940	730	NR
425	135	NR	555	1466	NR	685	193	NR	815	602	NR	945	259	NR
430	90	NR	560	2623	NR	690	213	NR	820	681	NR	950	510	NR
435	92	NR	565	4872	NR	695	267	NR	825	615	NR	955	800	NR
440	87	NR	570	8896	NR	700	218	NR	830	529	NR	960	959	NR
445	129	NR	575	16191	NR	705	234	NR	835	526	NR	965	925	NR
450	75	NR	580	29728	NR	710	280	NR	840	531	NR	970	863	NR
455	88	NR	585	53245	NR	715	393	NR	845	627	NR	975	1444	NR
460	76	NR	590	78694	NR	720	370	NR	850	248	NR	980	1342	NR
465	74	NR	595	63659	NR	725	376	NR	855	262	NR	985	1396	NR
470	87	NR	600	31696	NR	730	324	NR	860	579	NR	990	2816	NR
475	37	NR	605	13208	NR	735	359	NR	865	439	NR	995	1223	NR
480	77	NR	610	5473	NR	740	294	NR	870	923	NR	1000	487	NR
485	97	NR	615	2571	NR	745	300	NR	875	874	NR			


REPORT NUMBER: SP1-2201-507-1

TM-30-18





Summary

$R_f = 8$
 $R_g = 12.7$
 CIE $R_a = -25.2$
 $R_g = -415.1$

Spectral Power Distribution Comparison



Color Vector Graphics




REPORT NUMBER: SP1-2201-507-1

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)




CES01 = 89	CES26 = 8	CES51 = 13	CES76 = 5
CES02 = 66	CES27 = 62	CES52 = 1	CES77 = 39
CES03 = 30	CES28 = 51	CES53 = 0	CES78 = 14
CES04 = 76	CES29 = 21	CES54 = 14	CES79 = 53
CES05 = 50	CES30 = 59	CES55 = 9	CES80 = 44
CES06 = 55	CES31 = 24	CES56 = 0	CES81 = 19
CES07 = 37	CES32 = 12	CES57 = 0	CES82 = 73
CES08 = 36	CES33 = 57	CES58 = 0	CES83 = 60
CES09 = 29	CES34 = 14	CES59 = 12	CES84 = 68
CES10 = 84	CES35 = 49	CES60 = 64	CES85 = 32
CES11 = 68	CES36 = 90	CES61 = 18	CES86 = 2
CES12 = 72	CES37 = 30	CES62 = 62	CES87 = 22
CES13 = 43	CES38 = 78	CES63 = 63	CES88 = 9
CES14 = 76	CES39 = 82	CES64 = 0	CES89 = 3
CES15 = 72	CES40 = 60	CES65 = 1	CES90 = 7
CES16 = 47	CES41 = 89	CES66 = 0	CES91 = 58
CES17 = 55	CES42 = 1	CES67 = 0	CES92 = 0
CES18 = 58	CES43 = 2	CES68 = 4	CES93 = 7
CES19 = 79	CES44 = 96	CES69 = 52	CES94 = 0
CES20 = 68	CES45 = 3	CES70 = 2	CES95 = 1
CES21 = 93	CES46 = 13	CES71 = 2	CES96 = 4
CES22 = 85	CES47 = 71	CES72 = 59	CES97 = 0
CES23 = 93	CES48 = 1	CES73 = 0	CES98 = 0
CES24 = 95	CES49 = 7	CES74 = 75	CES99 = 0
CES25 = 78	CES50 = 7	CES75 = 9	



REPORT NUMBER: SP1-2201-507-1

TM-30-18



Color Rendition by Hue-Angle Bin



REPORT NUMBER: SP1-2201-507-1

TM-30-18

Measure Comparisons



(END OF REPORT)