

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1304329

Luminaire Tested: P3RT05R309735DE010 E3CBUS1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1304329
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-88)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3RT05R309735DE010 E3CBUS1MW
Description: 3in Adjustable LED luminaire with, R30 optic, 3500K CCT AND, 97CRI , E3CBUS1MW TRIM
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 648.0 lumens
Efficiency: N/A
Efficacy: 90.0 lumens/watt
Spacing Criteria (0/90/45): 0.5 / 0.5 / 0.45
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 7.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1304329
CATALOG NUMBER: P3RT05R309735DE010 E3CBUS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P1304329
 CATALOG NUMBER: P3RT05R309735DE010 E3CBUS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | 99 | 99 | 100 |
| 1 | 115 | 113 | 111 | 110 | 113 | 111 | 109 | 108 | 107 | 106 | 105 | 103 | 103 | 102 | 100 | 99 | 99 | 97 | 97 | 97 | 97 |
| 2 | 112 | 108 | 105 | 103 | 110 | 107 | 104 | 102 | 104 | 101 | 100 | 101 | 99 | 98 | 98 | 97 | 96 | 96 | 96 | 96 | 94 |
| 3 | 108 | 104 | 101 | 98 | 107 | 103 | 100 | 97 | 100 | 98 | 96 | 98 | 96 | 94 | 96 | 94 | 93 | 92 | 92 | 92 | 92 |
| 4 | 105 | 100 | 97 | 94 | 104 | 99 | 96 | 93 | 97 | 94 | 92 | 95 | 93 | 91 | 94 | 92 | 90 | 89 | 89 | 89 | 89 |
| 5 | 102 | 97 | 93 | 90 | 101 | 96 | 93 | 90 | 95 | 91 | 89 | 93 | 90 | 88 | 92 | 89 | 88 | 87 | 87 | 87 | 87 |
| 6 | 100 | 94 | 90 | 87 | 99 | 93 | 90 | 87 | 92 | 89 | 86 | 91 | 88 | 86 | 90 | 87 | 85 | 84 | 84 | 84 | 84 |
| 7 | 97 | 91 | 87 | 84 | 96 | 91 | 87 | 84 | 90 | 86 | 84 | 89 | 86 | 83 | 88 | 85 | 83 | 82 | 82 | 82 | 82 |
| 8 | 95 | 89 | 85 | 82 | 94 | 88 | 84 | 82 | 87 | 84 | 82 | 86 | 83 | 81 | 86 | 83 | 81 | 80 | 80 | 80 | 80 |
| 9 | 92 | 86 | 82 | 80 | 92 | 86 | 82 | 80 | 85 | 82 | 79 | 84 | 81 | 79 | 84 | 81 | 79 | 78 | 78 | 78 | 78 |
| 10 | 90 | 84 | 80 | 78 | 90 | 84 | 80 | 78 | 83 | 80 | 77 | 82 | 79 | 77 | 82 | 79 | 77 | 76 | 76 | 76 | 76 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 581247 |
| 5° | 564758 |
| 10° | 477992 |
| 15° | 287902 |
| 20° | 103679 |
| 25° | 29131 |
| 30° | 7697 |
| 35° | 2971 |
| 40° | 1145 |
| 45° | 0 |
| 50° | 0 |
| 55° | 0 |
| 60° | 0 |
| 65° | 0 |
| 70° | 0 |
| 75° | 0 |
| 80° | 0 |
| 85° | 0 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 0 cd/sqm



TEST NUMBER: P1304329

CATALOG NUMBER: P3RT05R309735DE010 E3CBUS1MW

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 232.2 | 35.8 |
| 10°-20° | 337.5 | 52.1 |
| 20°-30° | 69.7 | 10.8 |
| 30°-40° | 8.1 | 1.3 |
| 40°-50° | 0.5 | 0.1 |
| 50°-60° | 0.0 | 0.0 |
| 60°-70° | 0.0 | 0.0 |
| 70°-80° | 0.0 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 639.3 | 98.7 |
| 0°-40° | 647.4 | 99.9 |
| 0°-60° | 648.0 | 100.0 |
| 0°-90° | 648.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 648.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 2651 | |
| 5° | 2566 | 232 |
| 15° | 1268 | 337 |
| 25° | 120 | 70 |
| 35° | 11 | 8 |
| 45° | 0 | 1 |
| 55° | 0 | 0 |
| 65° | 0 | 0 |
| 75° | 0 | 0 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P1304329
CATALOG NUMBER: P3RT05R309735DE010 E3CBUS1MW

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 2650.7 |
| 2.5° | 2629.5 |
| 5° | 2565.7 |
| 7.5° | 2425.0 |
| 10° | 2146.7 |
| 12.5° | 1746.9 |
| 15° | 1268.2 |
| 17.5° | 811.7 |
| 20° | 444.3 |
| 22.5° | 222.7 |
| 25° | 120.4 |
| 27.5° | 65.8 |
| 30° | 30.4 |
| 32.5° | 18.2 |
| 35° | 11.1 |
| 37.5° | 7.1 |
| 40° | 4.0 |
| 42.5° | 1.0 |
| 45° | 0.0 |
| 47.5° | 0.0 |
| 50° | 0.0 |
| 52.5° | 0.0 |
| 55° | 0.0 |
| 57.5° | 0.0 |
| 60° | 0.0 |
| 62.5° | 0.0 |
| 65° | 0.0 |
| 67.5° | 0.0 |
| 70° | 0.0 |
| 72.5° | 0.0 |
| 75° | 0.0 |
| 77.5° | 0.0 |
| 80° | 0.0 |
| 82.5° | 0.0 |
| 85° | 0.0 |
| 87.5° | 0.0 |
| 90° | 0.0 |

(END OF REPORT)