

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: IRiS

Report Number: P1304642

Luminaire Tested: P3RT17R309827DE010 E3CBUS1MW

Issue Date: 1/29/2026

Test Information

Test Method: LM-79-2019
Report Number: P1304642
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2510-583-88)
Test Lab: INNOVATION CENTER
Issue Date: 1/29/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: IRiS
Catalog Number: P3RT17R309827DE010 E3CBUS1MW
Description: 3in Adjustable LED luminaire with, R30 optic, 2700K CCT AND, 98CRI , E3CBUS1MW TRIM
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1521.0 lumens
Efficiency: N/A
Efficacy: 74.6 lumens/watt
Spacing Criteria (0/90/45): 0.5 / 0.5 / 0.45
Luminous Opening: Circular (Dia: 0.25' x H: 0')
CIE Type: Direct

Input Watts (W): 20.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1304642

CATALOG NUMBER: P3RT17R309827DE010 E3CBUS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P1304642

CATALOG NUMBER: P3RT17R309827DE010 E3CBUS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	99	99
1	115	113	111	110	113	111	109	108	107	106	105	103	103	102	100	99	99	97	96	96
2	112	108	105	103	110	107	104	102	104	101	100	101	99	98	98	97	96	94	93	93
3	108	104	101	98	107	103	100	97	100	98	96	98	96	94	96	94	93	92	91	91
4	105	100	97	94	104	99	96	93	97	94	92	95	93	91	94	92	90	89	88	88
5	102	97	93	90	101	96	93	90	95	91	89	93	90	88	92	89	88	87	86	86
6	100	94	90	87	99	93	90	87	92	89	86	91	88	86	90	87	85	84	83	83
7	97	91	87	84	96	91	87	84	90	86	84	89	86	83	88	85	83	82	81	81
8	95	89	85	82	94	88	84	82	87	84	82	86	83	81	86	83	81	80	79	79
9	92	86	82	80	92	86	82	80	85	82	79	84	81	79	84	81	79	78	77	77
10	90	84	80	78	90	84	80	78	83	80	77	82	79	77	82	79	77	76	75	75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1364342
5°	1325618
10°	1121957
15°	675759
20°	243364
25°	68399
30°	18053
35°	6987
40°	2719
45°	0
50°	0
55°	0
60°	0
65°	0
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 0 cd/sqm

TEST NUMBER: P1304642

CATALOG NUMBER: P3RT17R309827DE010 E3CBUS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	544.9	35.8
10°-20°	792.1	52.1
20°-30°	163.6	10.8
30°-40°	19.1	1.3
40°-50°	1.3	0.1
50°-60°	0.0	0.0
60°-70°	0.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1500.6	98.7
0°-40°	1519.7	99.9
0°-60°	1521.0	100.0
0°-90°	1521.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1521.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6222	
5°	6022	545
15°	2977	792
25°	283	164
35°	26	19
45°	0	1
55°	0	0
65°	0	0
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P1304642

CATALOG NUMBER: P3RT17R309827DE010 E3CBUS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	6221.9
2.5°	6172.0
5°	6022.3
7.5°	5692.1
10°	5038.8
12.5°	4100.4
15°	2976.7
17.5°	1905.3
20°	1042.9
22.5°	522.6
25°	282.7
27.5°	154.4
30°	71.3
32.5°	42.8
35°	26.1
37.5°	16.6
40°	9.5
42.5°	2.4
45°	0.0
47.5°	0.0
50°	0.0
52.5°	0.0
55°	0.0
57.5°	0.0
60°	0.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)